

Safety Data Sheets

CD-HF



Roadyard Bisbee FTS Structures

09/21/2018



Safety Data Sheet Index

Binder: Roadyard Bisbee FTS Structures - CD-HF

Product Name	CAS Number	Manufacturer	Version Date	Page
+32°F SuperTech Windshield Washer Fluid - +32°F SuperTech Windshield Washer Fluid		Splash Products, Inc.	08/23/2016	5
12 OZ NAPA MAC'S CARB, CHOKE & THROTTLE BODY CLEANER 8700 - 12 OZ NAPA MAC'S CARB, CHOKE & THROTTLE BODY CLEANER 8700		NAPA Balkamp Inc.	06/14/2016	13
ACE Water-Based APWA Marking Paint Brilliant White - ACE Water-Based APWA Marking Paint Brilliant White		ACE HARDWARE CORPORATION	05/01/2015	24
ACE Water-Based APWA Marking Paint Utility Yellow - ACE Water-Based APWA Marking Paint Utility Yellow		ACE HARDWARE CORPORATION	05/01/2015	38
C-Thru Glass Cleaner - C-Thru Glass Cleaner		Lawson Products, Inc.	05/12/2015	53
C1: Portland Cement Based Concrete Products - C1: Portland Cement Based Concrete Products		The QUIKRETE Companies	02/01/2018	63
C5: Portland Cement Based Concrete Products - C5: Portland Cement Based Concrete Products		The QUIKRETE Companies	07/01/2017	73
CRACK-PAC Injection Epoxy - CRACK-PAC Injection Epoxy		Simpson Strong-Tie Company, Inc.	09/01/2016	84
CW5037 Dirt Jet Pro Industrial Hand Towels - CW5037 Dirt Jet Pro Industrial Hand Towels		Lawson Products, Inc.	05/08/2015	95
Detergent Thickened Husky 302 D/T Bowl Cleaner - Detergent Thickened Husky 302 D/T Bowl Cleaner		Canberra Corporation	12/31/2014	99
DO IT BEST RUST COAT ENAMELS, 1244 ENAMEL - DO IT BEST RUST COAT ENAMELS, 1244 ENAMEL		PLASTI-KOTE INC	05/15/1996	103
FAST ORANGE SMOOTH LOTION 64 FL.OZ - FAST ORANGE SMOOTH LOTION 64 FL.OZ		ITW Permatex	03/23/2016	107
Forney Nozzle Gel - Forney Nozzle Gel		Forney Industries, Inc.	04/01/2014	114
Goo Gone- 4 oz. - Goo Gone		Goo Gone	11/28/2017	119
GREAT STUFF (12 OZ) FOAM INSULATION - GREAT STUFF (12 OZ) FOAM INSULATION		Dow Chemical Company	04/20/2012	124
Green Light Many Purpose Dust - Green Light Many Purpose Dust		Swiss Farms Products Inc	12/04/2015	129

Product Name	CAS Number	Manufacturer	Version Date	Page
Gunk Engine Cleaner & Degrease - Multi Surface - Gunk Engine Cleaner & Degrease - Multi Surface		RSC Chemical Solutions	05/10/2017	139
Hospital Surface Disinfectant Spray - Hospital Surface Disinfectant Spray		WAXIE SANITARY SUPPLY	01/13/2016	147
HUSKY 1240 FOAMING DISINFECTANT CLEANER - HUSKY 1240 FOAMING DISINFECTANT CLEANER		Canberra Corporation	02/01/2015	155
HUSKY 430 CREME CLEANSER - HUSKY 430 CRÈME CLEANSER		Canberra Corporation	01/19/2016	159
IC + SSPR 6PK GLOSS GLOSSY WHITE - IC + SSPR 6PK GLOSS GLOSSY WHITE		Rust-Oleum Corporation	08/25/2014	162
IC SSPR 6PK GLOSS BRIGHT GALVANIZING - IC SSPR 6PK GLOSS BRIGHT GALVANIZING		Rust-Oleum Corporation	03/13/2018	175
IC SSPR 6PK GLOSS MACHINE GRAY - IC SSPR 6PK GLOSS MACHINE GRAY		Rust-Oleum Corporation	12/02/2010	181
IC SSPR GLOSS FLUORESCENT PINK - IC SSPR GLOSS FLUORESCENT PINK		Rust-Oleum Corporation	08/25/2014	183
Invisible Glass by Stoner - Invisible Glass		STONER INCORPORATED	12/04/2017	194
Klean Strip Lacquer Thinner - Klean Strip Lacquer Thinner		W. M. Barr	06/26/2017	197
KRYLON Industrial QUIK-MARK Water-Based Inverted Marking Paint (APWA) Green - KRYLON Industrial QUIK-MARK Water-Based Inverted Marking Paint (APWA) Green		Krylon Products Group	12/26/2017	207
KRYLON QUIK-MARK Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Pink - KRYLON QUIK-MARK Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Pink		Krylon Products Group	12/01/2017	222
Lawson Expunge Graffiti And Vandal Mark Remover - Lawson Expunge Graffiti And Vandal Mark Remover		Lawson Products, Inc.	04/30/2018	236
Lawson Ready Orange Wipes - Lawson Ready Orange Wipes		Lawson Products, Inc.	06/06/2018	249
Lifeguard Disinfectant and Cleaner - Lifeguard Disinfectant and Cleaner		Lawson	09/17/2014	260
Lysol Brand Disinfectant Spray, All Scents (Aerosol) - Lysol Brand Disinfectant Spray, All Scents (Aerosol)		Reckitt Benckiser - Morris Corporate Center IV	04/23/2015	265
Marvel Air Tool Oil - Marvel Air Tool Oil		Marvel Oil Company	01/26/2017	277
NAPA De-Icer Jul 2016 - NAPA De-Icer		Niento	07/21/2016	285
OFF! DEEP WOODS FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P.		S.C. Johnson and Son, Limited	08/16/2017	300

Product Name	CAS Number	Manufacturer	Version Date	Page
ACT) - OFF! DEEP WOODS FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)				
PB Penetrating Catalyst (Aerosol) - PB Penetrating Catalyst		The Blaster Corporation	06/26/2017	318
Power Care Premium SAE 30 4-Cycle Engine Oil - Power Care Premium SAE 30 4-Cycle Engine Oil		Phillips 66 Spectrum Corporation	09/20/2016	325
Propane (odorized) - PROPANE		FERRELLGAS INC	02/12/2018	331
Quick & Clean Crawling Insect Killer II HIL0109454 - Quick & Clean Crawling Insect Killer II HIL0109454		Hillyard Industries, Inc.	01/04/2010	338
RedGard Waterproofing and Crack Prevention Membrane - RedGard Waterproofing And Crack Prevention Membrane		Custom Building Products	10/06/2017	339
ROHPER LSPR 6PK GLOSS CRYSTAL CLEAR - ROHPER LSPR 6PK GLOSS CRYSTAL CLEAR		Rust-Oleum Corporation	04/07/2016	350
SAKRETE ANCHOR CEMENT, 20# & 10#; CEMENT PATCHER, - Sakrete Anchor Cement		Sakrete of North America	01/31/2018	361
SMOKE ODOR NEUTRALIZER CANADA - SMOKE ODOR NEUTRALIZER CANADA		ZEP Inc.	08/10/2017	367
STRUST + SSPR 6PK FLAT BLACK - STRUST + SSPR 6PK FLAT BLACK		Rust-Oleum Corporation	02/15/2018	377
Type S Hydrated Lime - Type S Hydrated Lime		Lhoist North America	01/01/2018	383
White Inverted Tip Marking Paint - White Inverted Tip Marking Paint		Lawson Products, Inc.	02/08/2005	391
WINDOW CLEAN+ - WINDOW CLEAN+		Hillyard Industries	08/25/2016	399

Safety Data Sheet

Section 1: Identification

Product Identifier

Detergent

Product Name

Trade Name: +32°F SuperTech Windshield Washer Fluid

PN (Part number): 050630

Relevant identified uses of the substance or mixture and uses advised against

- Material for industrial applications
- Industrial and professional use
- Consumer end use

Details of the supplier of the safety data sheet

Manufacturer

SPLASH Products
51 Maryland Ave. E
St. Paul, MN 55117
Phone: (651) 489-8211

Emergency telephone number

1-800-535-5053

Section 2: Hazard(s) Identification

OSHA/HCS status

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

No Classification

GHS label elements

Hazard pictograms-No Pictograms

Signal word-No Signal Words

Hazard statements-No Hazard Statements

Precautionary statements

Prevention

- Wear protective gloves/protective clothing/eye protection/face protection.
- Take off contaminated clothing and wash before use
- Keep away from oxidizing materials and strong acids

Response

- IF SWALLOWED: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- IF ON SKIN (or hair): Wash with soap and water. Get medical attention if irritation develops. Cold water may be used.
- IF IN EYES: Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. Cold water may be used. Get medical attention if irritation persists.
- IF EXPOSED or CONCERNED:
Immediately call a POISON CENTER or a doctor/physician.

Storage

Store in a well-ventilated place.

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

Product is stable.

Section 3: Composition/Information on Ingredients

Substance/mixture:Mixture

Chemical name: None

Other means of identification: No

CAS number/other identifiers

Ingredient name	%	CAS number

No hazardous ingredients

Section 4: First Aid Measurements

Description of necessary first aid measures

Eye contact: Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 30 minutes. Cold water may be used. Get medical attention if irritation persists.

Inhalation: Bring accident victims out into the fresh air. Call a physician immediately in severe cases or if recovery is not rapid.

Skin contact: After contact with skin, wash immediately with plenty of water. Remove contaminated clothing and wash before reuse.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact

May cause irritation to eyes

Inhalation

May irritate lungs

Skin contact

None

Ingestion

None

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

None.

Specific treatments

N/A

Protection of first-aiders

N/A

See toxicological information (Section 11)

Section 5: Fire Fighting Measures

Extinguishing media

Suitable extinguishing media

SMALL FIRE: Use DRY chemical powder, CO₂ or appropriate foam.

LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Unsuitable extinguishing media

None known

Specific hazards arising from the chemical

Closed containers exposed to heat may explode.

Hazardous thermal decomposition products/Products of combustion

Products of combustion are carbon oxides (CO, CO₂).

Special protective actions for fire fighters

Do not release runoff from fire control methods to sewers or waterways.

Special protective equipment for fire-fighters

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode.

Section 6: Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Ventilate area of leak or spill. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

Environmental precautions

Methods and materials for containment and cleaning up:

Exposure to the spilled material may be severely irritating or toxic. Follow personal protective equipment recommendations found in Section 8 of this SDS. Personal protective equipment needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including: the material spilled, the quantity of the spill, the area in which the spill occurred, and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

Section 7: Handling and Storage

Precautions for safe handling

Protective measures, advice on general occupational hygiene and conditions for safe storage, including any incompatibilities:

Keep container tightly closed in a cool, well-ventilated place. Keep away from oxidizing materials and strong acids.

Section 8: Exposure Controls/Personal Protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits			
Windshield washer fluid		<u>ACGIH</u>		<u>OSHA</u>	
		<u>(TWA)</u>	<u>(STEL)</u>	<u>(TWA)</u>	<u>(STEL)</u>
		N/A	N/A	N/A	N/A

Appropriate engineering controls and Environmental exposure controls

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source,

preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Individual protection measures

Hygiene measures

None

Eye/face protection: Use chemical safety goggles.

Skin protection

Hand protection and Body protection: Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Other skin protection

Wash hands and other exposed areas with mild soap and water before eating or drinking.

Respiratory protection: No respiratory protection required under normal circumstances.

Respirator Type(s) (NIOSH Approved): If the exposure limit is exceeded and engineering controls are not feasible, a half face piece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full face piece particulate respirator (NIOSH type N100 filter) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, Glycerin, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full face piece positive-pressure, air-supplied respirator. **WARNING:** Air-purifying respirators do not protect workers in Oxygen-deficient atmospheres.

Section 9: Physical and Chemical Properties

Appearance

Physical state: Blue liquid

Odor: None

Odor threshold: Not determined

pH: 8.0

Specific Gravity: 1.000

Melting point: Not determined

Boiling point: Not determined

Flash point: >93°C

Evaporation rate (BuAc=1): Not determined

Flammability (solid, gas): No

Lower and upper explosive (flammable) limits: N/A

Vapor pressure: Not determined

Vapor density (Air=1): Not determined

Solubility: Soluble in water

Partition coefficient: n-octanol/water: Not Established

Auto-ignition temperature: Not Applicable

Decomposition temperature: Not Established

Viscosity: Not determined

VOC%: 0

Section 10: Stability and Reactivity

Reactivity

Stable under recommended storage conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Will not occur.

Conditions to avoid

None

Incompatible materials

Strong acids

Strong bases

Strong oxidizing agents

Strong reducing agents

Hazardous decomposition products

Will not occur.

Section 11: Toxicological Information

Information on toxicological effects**Acute toxicity**

Product/ingredient name	Test	Results
Windshield Washer Fluid	Acute toxicity, oral (male rat)	LD50 = 5,628 mg/kg (estimated)
	Acute toxicity, dermal	LD50 = 15,800 mg/kg (estimated)
	Acute toxicity, inhalation (rat)	LC50 = Not Determined

Summary Comments:**Sensitization**

Product/ingredient name	Test	Results	Basis
Windshield Washer Fluid		No evidence of sensitization effect	

Summary Comments:**Carcinogenicity**

Product/ingredient name	Test	Results	Basis
Windshield Washer Fluid		No known carcinogenic effects	

Summary Comments:**Specific target organ toxicity (single exposure)**

Product/ingredient name	Test	Results	Basis
Windshield Washer Fluid	STOT-one-time exposure-oral	Not Determined	
	STOT-one-time exposure-dermal	Not Determined	
	STOT-one-time exposure-inhalation	Not Determined	

Summary Comments:**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Test	Results	Basis
Windshield Washer Fluid		Not Determined	

Summary Comments:**Aspiration hazard**

Product/ingredient name	Test	Results	Basis
Windshield Washer Fluid	Human exposure studies	Not Determined	

Summary Comments:**Information on the likely routes of exposure**

None

Potential acute health effects

Eye contact: May be irritating to the eyes.

Inhalation: Not expected to be a hazard.

Skin contact: Not expected to be a hazard.

Ingestion: Not expected to be a hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Eye irritation.

Inhalation: None expected.

Skin contact: None expected.

Ingestion: None expected.

Potential chronic health effects (Windshield Washer Fluid)

Carcinogenicity: No known carcinogens.

Mutagenicity: No data available.

Teratogenicity: No data available.

Developmental effects: No data available.

Fertility effects: No data available.

Numerical measures of toxicity**Acute toxicity estimates**

No data available

Section 12: Ecological Information

Toxicity**Acute Fish toxicity: (Windshield Washer Fluid)**

LC50 - Oncorhynchus mykiss (rainbow trout) - No data available

LC50 – Lepomis macrochirus (Bluegill) - No data available

Acute toxicity for daphnia: (Windshield Washer Fluid)

EC50 - Daphnia magna (Water flea) - No data available

EC100 - Daphnia magna (Water flea) - No data available

Acute toxicity for algae: (Windshield Washer Fluid)

EC50 - Scenedesmus capricornutum (fresh water algae) - No data available

Acute bacterial toxicity: (Windshield Washer Fluid)

No data available.

Ecotoxicology Assessment: (Windshield Washer Fluid)

Material is not expected to be toxic to aquatic life.

Persistence and degradability**Biodegradability: (Windshield Washer Fluid)**

Not expected to bioaccumulate.

Stability in water: (Windshield Washer Fluid)

No data available.

Photodegradation: (Windshield Washer Fluid)

No data available

Volatility (Henry's Law constant): (Windshield Washer Fluid)Partition coefficient n-octanol/water (log K_{ow}) = No data available**Bioaccumulative potential****Bioaccumulation: (Windshield Washer Fluid)**

Bioaccumulation Cyprinus carpio (Carp) – No data available

Bioconcentration factor (BCF): No data available

Mobility in soil: (Windshield Washer Fluid)**Distribution among environmental compartments:**

No data available.

Other adverse effects:

Section 13: Disposal Considerations

Disposal methods

Dispose in accordance with applicable international, national and local laws, ordinances and statutes.

Section 14: Transport Information

UN Number: Not Regulated**UN Proper Shipping Name:****Transport hazard Class(es):****Packing Group:****Land Transport ADR/RID and GGVS/GGVE (Cross Border / Domestic)****Transport Hazard Class(es):** Not Regulated**Maritime Transport IMDG/GGVSea****Transport Hazard Class(es):** Not Regulated**Marine Pollutant:** No**Air Transport ICAO-TI and IATA-DGR****Transport Hazard Class(es):** Not Regulated

Section 15: Regulatory Information

Chemical Inventory Status-Part 1

Ingredient (CAS#)	TSCA	EC	Japan	Australia
Windshield Washer Fluid	Yes	Yes	Yes	Yes

Chemical Inventory Status-Part 2

Ingredient (CAS#)	Korea	Canada	Canada	Philippines
		DSL	NDSL	
Windshield Washer Fluid	Yes	Yes	No	Yes

Federal, State & International Regulations-Part 1

	SARA 302		SARA 313	
Ingredient (CAS#)	RQ	TPQ	List Chemical	Category
Windshield Washer Fluid	No	No	Yes	No

Federal, State & International Regulations-Part 2

	RCRA		TSCA
Ingredient (CAS#)	CERCLA	261.33	8(d)
Windshield Washer Fluid	No	No	No

Chemical Weapons Convention: No

TSCA 12b: No

CDTA: No

SARA 311/312:

Acute: No, Chronic: No, Fire: No, Pressure: No, Reactivity: No

Mixture/Liquid

Australian Hazchem Code: No information found

Poison Schedule: No information found

Section 16: Other Information

History

Date of issue: 08/23/16

Version: 2a.

Revised Sections(s): Changed environmental verbiage

Prepared by: Andrew Gioino, SPLASH PRODUCTS

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

SAFETY DATA SHEET

1. Identification

Product number 1000028769
Product identifier 12 OZ NAPA MAC'S CARB, CHOKE & THROTTLE BODY CLEANER 8700
Company information NAPA Balkamp
 2601 S. Holt Road
 Indianapolis, IN 46241 United States
Company phone General Assistance 1-317-244-7241
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 01
Recommended use CLEANER
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Health hazards Serious eye damage/eye irritation Category 2A
 Reproductive toxicity (the unborn child) Category 2
 Specific target organ toxicity, single exposure Category 3 narcotic effects
 Specific target organ toxicity, repeated exposure Category 2
OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.
 Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

Hazard(s) not otherwise classified (HNOC) Combustible.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methyl Acetate		79-20-9	40 - 60
Acetone		67-64-1	10 - 20
Carbon Dioxide		124-38-9	2.5 - 10
Toluene		108-88-3	2.5 - 10
Other components below reportable levels			20 - 40

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Combustible.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Environmental precautions

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3 5000 ppm
Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m3 200 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm
	TWA	5000 ppm
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Acetone (CAS 67-64-1)	TWA	590 mg/m3 250 ppm
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3 30000 ppm
	TWA	9000 mg/m3 5000 ppm
Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m3 250 ppm
	TWA	610 mg/m3 200 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m3 150 ppm
	TWA	375 mg/m3 100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Toluene (CAS 108-88-3) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Toluene (CAS 108-88-3) Skin designation applies.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas.
Form Aerosol.
Color Not available.

Odor Not available.

Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	105.93 °F (41.07 °C) estimated
Flash point	53.5 °F (11.9 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	2.3 % estimated
Flammability limit - upper (%)	12.9 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	95 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.939 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Nitrates. Aluminum.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity	Narcotic effects.

Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Methyl Acetate (CAS 79-20-9)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC100	Rabbit	98.4 mg/l, 4 Hours
Oral		
LD50	Rat	6482 mg/kg
Toluene (CAS 108-88-3)		
Acute		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
LC50	Mouse	6405 - 7436 ppm, 6 Hours
		5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours
		25.7 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Risk of cancer cannot be excluded with prolonged exposure.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not regulated.	
US. National Toxicology Program (NTP) Report on Carcinogens	
Not listed.	

Reproductive toxicity	Suspected of damaging the unborn child.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Respiratory system. Skin. Kidneys. Central nervous system. Eyes. Liver. May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not likely, due to the form of the product.
Chronic effects	May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
Methyl Acetate (CAS 79-20-9)			
Aquatic			
Algae	IC50	Algae	120.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	1026.7 mg/L, 48 Hours
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)	
Acetone	-0.24
Methyl Acetate	0.18
Toluene	2.73

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Listed.

Toluene (CAS 108-88-3)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - Yes

Pressure Hazard - No

Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Toluene	108-88-3	2.5 - 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Toluene (CAS 108-88-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)

6532

Toluene (CAS 108-88-3)

6594

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1)	35 %WV
Toluene (CAS 108-88-3)	35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	594

US state regulations**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Acetone (CAS 67-64-1)
Toluene (CAS 108-88-3)

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1)
Carbon Dioxide (CAS 124-38-9)
Methyl Acetate (CAS 79-20-9)
Toluene (CAS 108-88-3)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
Carbon Dioxide (CAS 124-38-9)
Methyl Acetate (CAS 79-20-9)
Toluene (CAS 108-88-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Carbon Dioxide (CAS 124-38-9)
Methyl Acetate (CAS 79-20-9)
Toluene (CAS 108-88-3)

US. Rhode Island RTK

Acetone (CAS 67-64-1)
Toluene (CAS 108-88-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Acetaldehyde (CAS 75-07-0)	Listed: April 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Methanol (CAS 67-56-1)	Listed: March 16, 2012
Toluene (CAS 108-88-3)	Listed: January 1, 1991

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 06-14-2016

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Product and Company Identification
Physical & Chemical Properties: Multiple Properties

SAFETY DATA SHEET

1262278

Section 1. Identification

Product name : ACE® Water-Based APWA Marking Paint
Brilliant White

Product code : 1262278

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Manufacturer : Mfd. for:
ACE HARDWARE CORPORATION
Oak Brook, IL 60521

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : Not available.

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300


Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION (Fertility) - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 35.4%

GHS label elements

Hazard pictograms



Signal word : Danger

Date of issue/Date of revision : 5/1/2015. **Date of previous issue** : No previous validation. **Version** : 1 1/14

Section 2. Hazards identification

Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes skin irritation. Suspected of damaging fertility or the unborn child. Suspected of causing cancer. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness and dizziness. May cause damage to organs through prolonged or repeated exposure.
<u>Precautionary statements</u>	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash hands thoroughly after handling.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Please refer to the SDS for additional information. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Date of issue/Date of revision	: 5/1/2015.	Date of previous issue	: No previous validation.	Version	: 1	2/14

Section 3. Composition/information on ingredients

Ingredient name	% by weight	CAS number
Propane	15.0	74-98-6
Toluene	11.8	108-88-3
Butane	7.0	106-97-8
Hexane	6.3	110-54-3
2-Methylpentane	2.9	107-83-5
Lt. Aliphatic Hydrocarbon Solvent	2.4	64742-89-8
Titanium Dioxide	2.4	13463-67-7
3-Methylpentane	1.1	96-14-0

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Section 4. First aid measures

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Date of issue/*Date of revision* : 5/1/2015. *Date of previous issue* : No previous validation. *Version* : 1 4/14

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Propane	NIOSH REL (United States, 10/2013). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
Toluene	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 4/2014). TWA: 20 ppm 8 hours.
Butane	NIOSH REL (United States, 10/2013). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 4/2014). STEL: 1000 ppm 15 minutes.
Hexane	ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 50 ppm 8 hours. NIOSH REL (United States, 10/2013). TWA: 50 ppm 10 hours. TWA: 180 mg/m ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 500 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
2-Methylpentane	ACGIH TLV (United States, 4/2014). TWA: 500 ppm 8 hours. TWA: 1760 mg/m ³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 3500 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 350 mg/m ³ 10 hours. CEIL: 510 ppm 15 minutes. CEIL: 1800 mg/m ³ 15 minutes. ACGIH TLV (United States, 4/2014). TWA: 10 mg/m ³ 8 hours.
Titanium Dioxide	OSHA PEL (United States, 2/2013). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 4/2014). TWA: 500 ppm 8 hours. TWA: 1760 mg/m ³ 8 hours. STEL: 1000 ppm 15 minutes.
3-Methylpentane	STEL: 1000 ppm 15 minutes.

Date of issue/Date of revision

: 5/1/2015.

Date of previous issue

: No previous validation.

Version : 1

6/14

Section 8. Exposure controls/personal protection

STEL: 3500 mg/m³ 15 minutes.
NIOSH REL (United States, 10/2013).
TWA: 100 ppm 10 hours.
TWA: 350 mg/m³ 10 hours.
CEIL: 510 ppm 15 minutes.
CEIL: 1800 mg/m³ 15 minutes.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 7

Date of issue/Date of revision : 5/1/2015. **Date of previous issue** : No previous validation. **Version** : 1 7/14

Section 9. Physical and chemical properties

Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
Evaporation rate	: 9.1 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: 0.9% Upper: 9.5%
Vapor pressure	: 13.5 kPa (101.325 mm Hg) [at 20°C]
Vapor density	: 1 [Air = 1]
Relative density	: 0.82
Solubility	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): <0.205 cm ² /s (<20.5 cSt) Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt)
<u>Aerosol product</u>	
Type of aerosol	: Spray
Heat of combustion	: 0.00002025 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame).
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
Hexane	LC50 Inhalation Gas.	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-

Irritation/Corrosion

Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Eyes - Severe irritant	Rabbit	-	870 Micrograms	-
	Skin - Mild irritant	Pig	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 250 microliters	-
	Skin - Moderate irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
Hexane	Eyes - Mild irritant	Rabbit	-	500 milligrams	-
Titanium Dioxide	Skin - Mild irritant	Human	-	10 milligrams	-
				72 hours 300 Micrograms Intermittent	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Propane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Toluene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Butane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Hexane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
2-Methylpentane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

Date of issue/Date of revision : 5/1/2015. Date of previous issue : No previous validation. Version : 1 9/14

Section 11. Toxicological information

Lt. Aliphatic Hydrocarbon Solvent	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
3-Methylpentane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Propane	Category 2	Not determined	Not determined
Toluene	Category 2	Not determined	Not determined
Butane	Category 2	Not determined	Not determined
Hexane	Category 2	Not determined	Not determined
2-Methylpentane	Category 2	Not determined	Not determined
Lt. Aliphatic Hydrocarbon Solvent	Category 2	Not determined	Not determined
3-Methylpentane	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
Propane	ASPIRATION HAZARD - Category 1
Toluene	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Hexane	ASPIRATION HAZARD - Category 1
2-Methylpentane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
3-Methylpentane	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

- Skin contact** : Adverse symptoms may include the following:
 irritation
 redness
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
 nausea or vomiting
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- General** : May cause damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	3469.1 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
Hexane Lt. Aliphatic Hydrocarbon Solvent	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute LC50 2500 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours

Date of issue/Date of revision : 5/1/2015. **Date of previous issue** : No previous validation. **Version** : 1 11/14

Section 12. Ecological information

Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low
Hexane	-	501.187	high
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high
Titanium Dioxide	-	352	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

Date of issue/Date of revision : 5/1/2015. Date of previous issue : No previous validation. Version : 1 12/14

Section 14. Transport information

Additional information	Special provisions LIMITED QUANTITY	Special provisions LIMITED QUANTITY	Special provisions (ERG#126)	Special provisions LIMITED QUANTITY	Emergency schedules (EmS) LIMITED QUANTITY, F-D, S-U

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations :

State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Section 16. Other information

[Notice to reader](#)

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

1262328

Section 1. Identification

Product name : ACE® Water-Based APWA Marking Paint
Utility Yellow

Product code : 1262328

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against
Not applicable.

Manufacturer : Mfd. for:
ACE HARDWARE CORPORATION
Oak Brook, IL 60521

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : Not available.

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300


Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION (Fertility) - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation and Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 40.4%

GHS label elements

Hazard pictograms



Signal word : Danger

Date of issue/Date of revision : 5/1/2015. **Date of previous issue** : No previous validation. **Version** : 1 1/15

Section 2. Hazards identification

Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes skin irritation. Suspected of damaging fertility or the unborn child. Suspected of causing cancer. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness and dizziness. May cause damage to organs through prolonged or repeated exposure.
<u>Precautionary statements</u>	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash hands thoroughly after handling.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.
Disposal	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Please refer to the SDS for additional information. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Date of issue/Date of revision	: 5/1/2015.	Date of previous issue	: No previous validation.	Version	: 1	2/15

Section 3. Composition/information on ingredients

Ingredient name	% by weight	CAS number
Toluene	15.1	108-88-3
Propane	15.0	74-98-6
Hexane	7.3	110-54-3
Lt. Aliphatic Hydrocarbon Solvent	4.7	64742-89-8
2-Methylpentane	3.4	107-83-5
3-Methylpentane	1.3	96-14-0
2,3-Dimethylbutane	1.1	79-29-8
Titanium Dioxide	1.0	13463-67-7
Ethylbenzene	0.1	100-41-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Section 4. First aid measures

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

Date of issue/Date of revision : 5/1/2015. **Date of previous issue** : No previous validation. **Version** : 1 4/15

Section 5. Fire-fighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Date of issue/Date of revision : 5/1/2015. **Date of previous issue** : No previous validation. **Version** : 1 5/15

Section 7. Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Toluene	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 4/2014). TWA: 20 ppm 8 hours.
Propane	NIOSH REL (United States, 10/2013). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
Hexane	ACGIH TLV (United States, 4/2014). Absorbed through skin. TWA: 50 ppm 8 hours. NIOSH REL (United States, 10/2013). TWA: 50 ppm 10 hours. TWA: 180 mg/m ³ 10 hours. OSHA PEL (United States, 2/2013). TWA: 500 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
2-Methylpentane	ACGIH TLV (United States, 4/2014). TWA: 500 ppm 8 hours. TWA: 1760 mg/m ³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 3500 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 350 mg/m ³ 10 hours. CEIL: 510 ppm 15 minutes. CEIL: 1800 mg/m ³ 15 minutes.
3-Methylpentane	ACGIH TLV (United States, 4/2014). TWA: 500 ppm 8 hours. TWA: 1760 mg/m ³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 3500 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours.

Date of issue/Date of revision

: 5/1/2015.

Date of previous issue

: No previous validation.

Version : 1

6/15

Section 8. Exposure controls/personal protection

2,3-Dimethylbutane	TWA: 350 mg/m³ 10 hours. CEIL: 510 ppm 15 minutes. CEIL: 1800 mg/m³ 15 minutes. ACGIH TLV (United States, 4/2014). TWA: 500 ppm 8 hours. TWA: 1760 mg/m³ 8 hours. STEL: 1000 ppm 15 minutes. STEL: 3500 mg/m³ 15 minutes. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 350 mg/m³ 10 hours. CEIL: 510 ppm 15 minutes. CEIL: 1800 mg/m³ 15 minutes. ACGIH TLV (United States, 4/2014). TWA: 10 mg/m³ 8 hours. OSHA PEL (United States, 2/2013). TWA: 15 mg/m³ 8 hours. Form: Total dust ACGIH TLV (United States, 4/2014). TWA: 20 ppm 8 hours. NIOSH REL (United States, 10/2013). TWA: 100 ppm 10 hours. TWA: 435 mg/m³ 10 hours. STEL: 125 ppm 15 minutes. STEL: 545 mg/m³ 15 minutes. OSHA PEL (United States, 2/2013). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours.
Titanium Dioxide	
Ethylbenzene	

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

- : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

- : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

- : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : 7
- Melting point** : Not available.
- Boiling point** : Not available.
- Flash point** : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 9.1 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 0.9%
Upper: 9.5%
- Vapor pressure** : 13.5 kPa (101.325 mm Hg) [at 20°C]
- Vapor density** : 1 [Air = 1]
- Relative density** : 0.84
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (room temperature): <0.205 cm²/s (<20.5 cSt)
Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)

Aerosol product

- Type of aerosol** : Spray
- Heat of combustion** : 0.00002014 kJ/g

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

Date of issue/Date of revision : 5/1/2015. *Date of previous issue* : No previous validation. *Version* : 1 8/15

Section 10. Stability and reactivity

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Hexane	LC50 Inhalation Gas.	Rat	48000 ppm	4 hours
	LD50 Oral	Rat	15840 mg/kg	-
Ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
				100 milligrams	
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
Hexane Titanium Dioxide	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
	Eyes - Mild irritant	Rabbit	-	10 milligrams	-
	Skin - Mild irritant	Human	-	72 hours 300 Micrograms	-
Ethylbenzene				Intermittent	
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Section 11. Toxicological information

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-
Titanium Dioxide	-	2B	-
Ethylbenzene	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Propane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Hexane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Lt. Aliphatic Hydrocarbon Solvent	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
2-Methylpentane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
3-Methylpentane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
2,3-Dimethylbutane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Ethylbenzene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 2	Not determined	Not determined
Propane	Category 2	Not determined	Not determined
Hexane	Category 2	Not determined	Not determined
Lt. Aliphatic Hydrocarbon Solvent	Category 2	Not determined	Not determined
2-Methylpentane	Category 2	Not determined	Not determined
3-Methylpentane	Category 2	Not determined	Not determined
2,3-Dimethylbutane	Category 2	Not determined	Not determined
Ethylbenzene	Category 2	Not determined	Not determined

Aspiration hazard

Section 11. Toxicological information

Name	Result
Toluene	ASPIRATION HAZARD - Category 1
Propane	ASPIRATION HAZARD - Category 1
Hexane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1
2-Methylpentane	ASPIRATION HAZARD - Category 1
3-Methylpentane	ASPIRATION HAZARD - Category 1
2,3-Dimethylbutane	ASPIRATION HAZARD - Category 1
Ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Date of issue/*Date of revision* : 5/1/2015. *Date of previous issue* : No previous validation. *Version* : 1 11/15

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	2510.9 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
Hexane Lt. Aliphatic Hydrocarbon Solvent Titanium Dioxide Ethylbenzene	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute LC50 2500 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 6530 µg/l Fresh water	Crustaceans - Artemia sp. - Nauplii	48 hours
	Acute EC50 2930 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily
Ethylbenzene	-	-	Readily

Bioaccumulative potential

Date of issue/Date of revision	: 5/1/2015.	Date of previous issue	: No previous validation.	Version : 1	12/15

Section 12. Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low
Hexane	-	501.187	high
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high
Titanium Dioxide	-	352	low

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	<u>Special provisions</u> LIMITED QUANTITY	<u>Special provisions</u> LIMITED QUANTITY	<u>Special provisions</u> (ERG#126)	<u>Special provisions</u> LIMITED QUANTITY	<u>Emergency schedules (EmS)</u> LIMITED QUANTITY, F-D, S-U

Date of issue/Date of revision : 5/1/2015. Date of previous issue : No previous validation. Version : 1 13/15

Section 14. Transport information

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

Section 15. Regulatory information

U.S. Federal regulations :
State regulations

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Notice to reader

Date of issue/Date of revision : 5/1/2015. **Date of previous issue** : No previous validation. **Version** : 1 14/15

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.



SAFETY DATA SHEET

1. Identification

Product number 19951
Product identifier **C-Thru Glass Cleaner**
Company information Lawson Products, Inc.
8770 W. Bryn Mawr Ave.
Chicago, IL 60631 United States
Company phone 773-304-5050
Emergency telephone US 888-426-4851
Version # 01
Recommended use Cleaner
Recommended restrictions None known.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Gases under pressure Liquefied gas
Health hazards Not classified.
Environmental hazards Not classified.
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
Precautionary statement
Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
Response Wash hands after handling.
Storage Protect from sunlight. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC) None known.
Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Isopropyl Alcohol		67-63-0	2.5 - 10
2-Propanol, 1-propoxy-		1569-01-3	1 - 2.5
Butane		106-97-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Anhydrous Ammonia		7664-41-7	0.1 - 1
Other components below reportable levels			90 - 100

SDS US

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

**Conditions for safe storage,
including any incompatibilities**

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Anhydrous Ammonia (CAS 7664-41-7)	PEL	35 mg/m3
		50 ppm
Isopropyl Alcohol (CAS 67-63-0)	PEL	980 mg/m3
		400 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Anhydrous Ammonia (CAS 7664-41-7)	STEL	35 ppm
	TWA	25 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Anhydrous Ammonia (CAS 7664-41-7)	STEL	27 mg/m3
		35 ppm
	TWA	18 mg/m3
		25 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	1225 mg/m3
		500 ppm
	TWA	980 mg/m3
		400 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

SDS US

Other	Wear suitable protective clothing.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol. Liquefied gas.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	212 °F (100 °C) estimated
Flash point	-6.5 °F (-21.4 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	23.01 psig @70F estimated
Vapor density	Not available.
Relative density	0.973 g/cm3 estimated
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.

Other information

Density	0.97 g/cm3 estimated
Flammability class	Flammable IB estimated
Heat of combustion	2.34 kJ/g estimated
Heat of combustion (NFPA 30B)	2.23 kJ/g estimated
Percent volatile	98.04 % estimated
Specific gravity	0.973 estimated
VOC (Weight %)	5.91 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.

SDS US

Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Expected to be a low ingestion hazard.
Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2-Propanol, 1-propoxy- (CAS 1569-01-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg 3775 mg/kg, 24 Hours 4.29 ml/kg, 24 Hours
<i>Inhalation</i>		
LC50	Rat	> 1725 ppm, 6 Hours
<i>Oral</i>		
LD50	Mouse	260 mg/kg
	Rat	2490 mg/kg 2.83 ml/kg
Anhydrous Ammonia (CAS 7664-41-7)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	4230 ppm, If <1L: Consumer Commodity Hours
	Rat	7939 mg/m3 4000 ppm, If <1L: Consumer Commodity Hours
<i>Oral</i>		
LD50	Rat	350 mg/kg
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l
Isopropyl Alcohol (CAS 67-63-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	16.4 ml/kg, 24 Hours

SDS US

Components	Species	Test Results
<i>Inhalation</i> LC50	Rat	> 10000 ppm, 6 Hours
<i>Oral</i> LD50	Rat	5.84 g/kg
Propane (CAS 74-98-6)		
Acute <i>Inhalation</i> LC50	Mouse	1237 mg/l, 120 Minutes 52 %, 120 Minutes
	Rat	1355 mg/l 658 mg/l/4h

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Anhydrous Ammonia (CAS 7664-41-7)		
Aquatic Fish	LC50	Chinook salmon (<i>Oncorhynchus tshawytscha</i>) 0.43 - 0.47 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)		
Aquatic Algae	IC50	Algae 1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 13299 mg/L, 48 Hours
Fish	LC50	Bluegill (<i>Lepomis macrochirus</i>) > 1400 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

2-Propanol, 1-propoxy-	0.621
Butane	2.89

SDS US

Partition coefficient n-octanol / water (log Kow)

Isopropyl Alcohol	0.05
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information**DOT**

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1

SDS US

Subsidiary risk	-
Label(s)	None
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
DOT	



IATA; IMDG



15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Anhydrous Ammonia (CAS 7664-41-7) Listed.

SARA 304 Emergency release notification

Anhydrous Ammonia (CAS 7664-41-7) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Chemical name	CAS number	Reportable quantity	Threshold planning quantity	Threshold planning quantity, lower value	Threshold planning quantity, upper value

Anhydrous Ammonia	7664-41-7	100	500 lbs		

SARA 311/312 Hazardous chemical No

SDS US

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Anhydrous Ammonia	7664-41-7	0.1 - 1

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Anhydrous Ammonia (CAS 7664-41-7)

Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.**US state regulations****US. Massachusetts RTK - Substance List**

Anhydrous Ammonia (CAS 7664-41-7)

Butane (CAS 106-97-8)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Anhydrous Ammonia (CAS 7664-41-7)

Butane (CAS 106-97-8)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Anhydrous Ammonia (CAS 7664-41-7)

Butane (CAS 106-97-8)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Anhydrous Ammonia (CAS 7664-41-7)

Butane (CAS 106-97-8)

Isopropyl Alcohol (CAS 67-63-0)

Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 05-12-2015

SDS US

Version #

01

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Information

Composition / Information on Ingredients: Component Summary

Fire-fighting measures: Specific methods

GHS: Classification



CEMENT & CONCRETE PRODUCTS™

C1: Portland Cement Based Concrete Products

SAFETY DATA SHEET

(Complies with OSHA 29 CFR 1910.1200)

SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE® Companies
5 Concourse Parkway, Suite 1900
Atlanta, GA 30328

Emergency Telephone Number
INFOTRAC (800) 535-5053
Information Telephone Number
(800) 282-5828

SDS C1

Revision: Feb-18

QUIKRETE® Product Name	Item #(s)
Fence Post Mix	1005
Fiber-Reinforced Concrete Mix	1006
Crack Resistant Concrete Mix	1006-80
Pro-Finish Crack Resistant Concrete Mix	1006-68
QUIKRETE 5000 Concrete Mix	1007
QUIKRETE 6000 Concrete Mix	1007
Pro-Finish QUIKRETE 5000	1007-85
Lightweight Concrete Mix	1008
Basic Concrete Mix	1015
Maximum Yield Concrete Mix	1100-80
Concrete Mix	1101-10, -20, -40, -60, -80, -90
Green Concrete Mix	1101-63, -73
B-Crete	1101-81
Red-E-Crete Concrete mix	1101-91, -87; 1141-62, -63, -92, -93, Bulk NR810035
Countertop Mix	1106-80
Form & Pour Concrete Mix	1120-80/NR810065
Form & Pour Concrete Mix MS	1120-80/NR810065
All-Star Concrete Mix	1121
Rip Rap	1129
Rip Rap Scrim	1134-80
Handicrete Concrete Mix	1141-59, -60, -80
RiteMix Concrete	1171-60
Fiber Reinforced Deck Mix	1251-80, -81
All-Star Crack Resistant Concrete Mix	1470-03
All-Star 5000 Concrete Mix	1470-01
FlowCrete 5000 (Mix 801)	8080026/NR80026
Mix 801 Concrete Mix	NR81001

Product Use: Portland cement-based, aggregated products for general construction

SDS C1

QUIKRETE Companies, LLC

2/7/2018



CEMENT & CONCRETE PRODUCTS™

See most current revision of this document at www.QUIKRETE.com.

SECTION II - HAZARD IDENTIFICATION

Hazard-determining components of labeling: Silica, Portland cement

2.1 Classification of the substance or mixture

Carcinogen – Category 1A

Skin Corrosion – Category 1B

Eye Damage – Category 1

Skin Sensitization – Category 1B

Specific Target Organ Toxicity Repeat Exposure – Category 1

Specific Target Organ Toxicity: Single Exposure – Category 3

2.2a Signal word DANGER!

2.2b Hazard Statements

May cause cancer through chronic inhalation

Causes severe skin burns and serious eye damage

May cause an allergic skin reaction

Causes damage to lungs through prolonged or repeated inhalation

May cause respiratory irritation

Harmful if swallowed.

2.2c Pictograms



2.2d Precautionary statements

Do not handle until all safety precautions have been read and understood.

Wear impervious gloves, such as nitrile. Wear eye protection, and protective clothing.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Use only in a well-ventilated area. Wear a NIOSH approved respirator (mask) such as N95 in poorly ventilated areas, when used for extended periods, when use is frequent, or when permissible exposure limits may be exceeded.

Do not breathe dust.

If swallowed: Rinse mouth. Do NOT induce vomiting.

SDS C1

QUIKRETE Companies, LLC

2/7/2018

**CEMENT & CONCRETE PRODUCTS™**

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If on skin (or hair): Remove immediately all contaminated clothing and wash before re-use. Rinse skin or hair with water.

If significant skin irritation or rash occurs: get medical advice or attention.

Immediately seek medical advice or attention if symptoms are significant or persist.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/containers in accordance with all regulations.

2.3 Additional Information

The Portland cement in this product can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. Burns from Portland cement may not cause immediate pain or discomfort. You cannot rely on pain to alert you to cement burns. Portland cement can cause dermatitis or sensitization. Therefore precautions must be taken to prevent all contact with Portland cement. Cement burns can become worse even after contact has ended. If there is contact with this product, immediately remove all product from body and thoroughly rinse with water. If you experience or suspect a cement burn or inflammation you should immediately see a health care professional.

Skin burns and irritation may be caused by brief exposure, though often are caused by extended exposure of 15 minutes, an hour, or longer. Interaction of Portland cement with water or sweat releases a caustic solution which produces the burns or irritation. Any extended exposure should be treated as though a burn has occurred until determined otherwise.

Skin contact with Portland cement can also cause inflammation of the skin, referred to as dermatitis. Signs and symptoms of dermatitis can include itching, redness, swelling, blisters, scaling, and other changes in the normal condition of the skin. Signs and symptoms of burns include the above and whitening, yellowing, blackening, peeling or cracking of skin.

The Portland cement in this product may cause allergic contact dermatitis in sensitized individuals. This overreaction of the immune system can lead to severe inflammation. Sensitization may result from a single exposure to the low levels of Cr (VI) in Portland cement or repeated exposures over months or years. Sensitization is long lasting and, after sensitization, even very small quantities can trigger the dermatitis. Sensitization is uncommon. Individuals who experience skin problems, including seemingly minor ones, are advised to seek medical attention.

2.3a HNOX – Hazards not otherwise classified: Not applicable

2.3b Unknown Acute Toxicity: None



CEMENT & CONCRETE PRODUCTS™

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

<u>Hazardous Components</u>	<u>CAS No.</u>	<u>% by Weight</u>
Sand, Silica, Quartz	14808-60-7	60-100*
Portland Cement	65997 15 1	10-30*
Fly Ash	68131-74-8	5-10*

*The concentrations ranges are provided due to batch-to-batch variability.
None of the constituents of this material are of unknown toxicity.

SECTION IV – FIRST AID MEASURES

4.1 Description of the first-aid measures**General information:**

After inhalation: Remove person to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration. In case of unconsciousness, place patient stably in side position for transportation.

After skin contact: Wash skin with cool water and pH-neutral soap or a mild detergent. If significant skin irritation or rash occurs: get medical advice or attention.

After eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing: Do not induce vomiting. If conscious, have the victim drink plenty of water and call a physician immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms/effects, acute and delayed

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated inhalation. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: Skin burns and irritation may be caused by brief exposure, though often are caused by extended exposure of 15 minutes, an hour, or longer.

Eye Contact: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

4.3 Indication of immediate medical attention and special treatment needed:

Immediately seek medical advice or attention if symptoms are significant or persist.

SECTION V - FIRE FIGHTING MEASURES

5.1 Flammability of the Product: Non-flammable and non-combustible

5.2 Suitable extinguishing agents: Treat for surrounding material

5.3 Special hazards arising from the substance or mixture: None

SDS C1

QUIKRETE Companies, LLC

2/7/2018



CEMENT & CONCRETE PRODUCTS™

5.3a Products of Combustion: None**5.3b Explosion Hazards in Presence of Various Substances:** Non-explosive in presence of shocks

SECTION VI – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Wear personal protective equipment (See section VIII). Keep unprotected persons away.**6.2 Methods and material for containment and cleaning up:**

Do not allow to enter sewers/ surface or ground water. Dispose of unwanted materials and containers properly in accordance with all regulations.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

7.1 Handling**Precautions for safe handling:** Ensure good ventilation/exhaustion at the workplace. DO NOT BREATHE DUST. In dusty environments, the use of an OSHA, MSHA or NIOSH approved respirator and tight fitting goggles is recommended. Wear appropriate PPE (See section 8). Do not mix with other chemical products, except as indicated by the manufacturer. Do not get in eyes, on skin or clothing. Good housekeeping is important to prevent accumulation of dust.**7.2 Storage****Requirements to be met by storerooms and receptacles:** No special requirements.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:** Keep out of the reach of children. Keep container tightly closed and prevent exposure to humidity. Do not allow water to contact the product until time of use to preserve product utility.

SECTION VIII – EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION

8.1 Components with limit values that require monitoring at the workplace:

Hazardous Components	CAS No.	PEL (OSHA) mg/M ³	TLV (ACGIH) mg/M ³
Silica Sand, crystalline	14808-60-7	0.1	0.025 (resp)
Portland Cement	65997-15-1	5 (resp) 15 (total)	10 (resp)
Fly Ash	68131-74-8	N/A	N/A

8.2 Exposure Controls

Use ventilation adequate to keep exposures below recommended exposure limits.



CEMENT & CONCRETE PRODUCTS™

8.3 General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

8.3a Personal protective equipment**Protection of hands:**

Wear gloves of adequate length to offer appropriate skin protection from splashes. Nitrile, Butyl and PVC gloves have been found to offer adequate protection for incidental contact. You cannot rely on pain to alert you to cement burns. Portland cement can cause dermatitis or sensitization.

Eye protection:

Wear approved eye protection (properly fitted dust- or splash-proof chemical safety glasses).

Respiratory protection:

Wear a NIOSH approved respirator (mask) such as N95 in poorly ventilated areas, when used for extended periods, when use is frequent, or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional, following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

General Information

Appearance	Form: Granular Solid Color: Gray to gray-brown colored Odor: None
pH-value at 20°C (68 °F):	13 (10%)
Boiling point/Boiling range:	Not applicable
Flash point:	Not applicable
Auto igniting:	Product is not self-igniting
Vapor pressure at 21°C (70°F)	Not available
Density at 25°C (77 °F):	2.6 to 3.15

Solubility in / Miscibility with

Water:	Insoluble
VOC content:	0 g/L VOC

SECTION X – STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal storage conditions. Keep in dry storage.

CEMENT & CONCRETE PRODUCTS™**10.3 Possibility of hazardous reaction**

No dangerous reaction known under conditions of normal use.

10.4 Thermal decomposition / conditions to be avoided

No decomposition if used according to specifications.

10.5 Incompatible materials

Contact of silica with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, or oxygen difluoride may cause fires

10.6 Hazardous Decomposition or By-products

Silica will dissolve in Hydrofluoric Acid and produce a corrosive gas – silicon tetrafluoride.

SECTION XI – TOXICOLOGICAL INFORMATION

11.1 Exposure Routes: Skin contact, skin adsorption, eye contact, inhalation, or ingestion.

11.2 Symptoms related to physical/chemical/toxicological characteristics:

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: Causes severe skin burns. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact. Product becomes extremely alkaline when exposed to moisture, and can cause alkali burns and affect the mucous membranes.

Eye Contact: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Ingestion: Harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

11.3 Delayed, immediate and chronic effects of short-term and long-term exposure**Short Term**

Skin Corrosion/Irritation: Causes severe skin burns.

Serious Eye Damage/Irritation: Causes severe eye damage.

Respiratory Sensitization: Not available

Skin Sensitization: May cause an allergic skin reaction.

Specific Target Organ Toxicity-Single Exposure: (Category 3) May cause respiratory irritation.

Aspiration Hazard: Not available

Long Term

Carcinogenicity: May cause cancer through chronic inhalation.

Germ Cell Mutagenicity: Not available

Reproductive Toxicity: Not available

**CEMENT & CONCRETE PRODUCTS™**

Specific Target Organ Toxicity- Repeated Exposure: (Category 1) Causes damage to lungs through prolonged/repeated exposure

Synergistic/Antagonistic Effects: Not available.

SECTION XII – ECOLOGICAL INFORMATION

12.1 Ecotoxicity

May cause long-term adverse effects to the aquatic environment. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or un-neutralized

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential:

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Other Adverse Effects

No further relevant information available.

SECTION XIII – DISPOSAL CONSIDERATIONS

13.1 Waste Disposal Method

The packaging and material may be land filled; however, material should be covered to minimize generation of airborne dust. This product is not classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302). Disposal must be made in accordance with local, state and federal regulations.

13.2 Other disposal considerations**Uncleaned packaging**

Recommendation: Disposal must be made in accordance with local, state and federal regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

SECTION XIV – TRANSPORT INFORMATION

	DOT (U.S.)	TDG (Canada)
UN-Number	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated
Transport Hazard Class(es)	Not Regulated	Not Regulated
Packing Group (if applicable)	Not Regulated	Not Regulated



CEMENT & CONCRETE PRODUCTS™

14.1 Environmental hazards:

Not Available

14.2 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code

Not available

14.3 Special precautions for user

Do not handle until all safety precautions have been read and understood.

SECTION XV – OTHER REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations/Legislations specific for the chemical**Canada**

WHMIS Classification: Considered to be a hazardous material under the Hazardous Products Act as defined by the Hazardous Products Regulations and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the HPR.

15.2 US Federal Information**SARA 302/311/312/313 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302, 311, 312 or 313.

RCRA: Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et seq.

CERCLA: Crystalline silica (quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR §302.

Emergency Planning and Community Right to Know Act (SARA Title III): Crystalline silica (quartz) is not an extremely hazardous substance under Section 302 and is not a toxic chemical subject to the requirements of Section 313.

FDA: Silica is included in the list of substances that may be included in coatings used in food contact surfaces, 21 CFR §175.300(b)(3)(xxvi).

NTP: Respirable crystalline silica, primarily quartz dusts occurring in industrial and occupational settings, is classified as Known to be a Human Carcinogen.

OSHA Carcinogen: Crystalline silica (quartz) is not listed.

**CEMENT & CONCRETE PRODUCTS™**

15.3 State Right to Know Laws

California Prop. 65 Components



WARNING: This product can expose you to chemicals including crystalline silica which is known to the State of California to cause cancer and hexavalent chromium compounds which are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Inhalation Reference Exposure Level (REL): California established a chronic REL of 3 µg for silica (crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

Massachusetts Toxic Use Reduction Act: Silica, crystalline (respirable size, <10 microns) is "toxic" for purposes of the Massachusetts Toxic Use Reduction Act.

15.4 Global Inventories

DSL All components of this product are on the Canadian DSL list.

TSCA No.: Crystalline silica (quartz) appears on the EPA TSCA inventory under the CAS No. 14808-60-7. All constituents are listed in the TSCA inventory.

SECTION XVI – OTHER INFORMATION

Last Updated: February 7, 2018

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by

The QUIKRETE Companies, LLC

End of SDS



CEMENT & CONCRETE PRODUCTS™

C5: Portland Cement Based Concrete Products

SAFETY DATA SHEET

(Complies with OSHA 29 CFR 1910.1200)

SECTION I: PRODUCT IDENTIFICATION

The QUIKRETE® Companies
5 Concourse Parkway, Suite 1900
Atlanta, GA 30328

Emergency Telephone Number
INFOTRAC (800) 535-5053
Information Telephone Number
(800) 282-5828

Revision: Jul-17
SDS C5

QUIKRETE® Product Name	Item #(s)
HPC® FastSet Stucco Mix	1139-55
Fiber Reinforced Scratch & Brown Base Coat Stucco	1139-78
Scratch & Brown Base Coat	1139-80
Pumpable Base Coat Stucco	1139-86
Pumpable Base Coat Stucco, Concentrated	1139-90
Scratch & Brown Base Coat White with waterstop	1139-89
Parging Mix	1155-30
Exterior Stucco	1209
QUIKRETE® One Coat Fiberglass-Reinforced Stucco	1200
Finish Coat Stucco	1201
Base Coat Stucco	1202-11, -80, -82
Foam Coating	1219
QUIKRETE® One Coat Fiberglass-Reinforced Stucco Concentrated	1216
Quikwall® Surface Bonding Cement - Unsanded	1220
BlocBond	1225-51
Aquablend	1225-60
Aqualight	1225-62
Quikwall® Surface Bonding Cement	1230, 1231
BBond MS	1234
Heavy-Duty Masonry Coating	1301, 1312, 2401
Pool Plaster	1319
Pool Finish	1800
Pebble Finish	1806
Wall Float	153-50, -76
All-Star Base Coat Stucco	
All-Star Finish Coat Stucco	
Red-E-Crete Stucco	

SDS C5

QUIKRETE Companies, LLC

7/10/2017



CEMENT & CONCRETE PRODUCTS™

MIX 403 ONE COAT STUCCO FRS

SR/NR 43001

Product Use: Portland cement-based Plasters and CoatingsSee most current revision of this document at www.QUIKRETE.com.

SECTION II - HAZARD IDENTIFICATION

Hazard-determining components of labeling: Silica, Portland cement**2.1 Classification of the substance or mixture**

Carcinogen – Category 1A

Skin Corrosion – Category 1B

Skin Sensitization – Category 1B

Specific Target Organ Toxicity Repeat Exposure – Category 1

Specific Target Organ Toxicity: Single Exposure – Category 3

2.2a Signal word DANGER!**2.2b Hazard Statements**

May cause cancer through chronic inhalation

Causes severe skin burns and serious eye damage

May cause an allergic skin reaction

Causes damage to lungs through prolonged or repeated inhalation

May cause respiratory irritation

2.2c Pictograms**2.2d Precautionary statements**

Do not handle until all safety precautions have been read and understood.

Wear impervious gloves, such as nitrile. Wear eye protection, and protective clothing.

Do not eat, drink or smoke when using this product.

Wash thoroughly after handling.

Use only in a well-ventilated area.

Do not breathe dust.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

SDS C5

QUIKRETE Companies, LLC

7/10/2017

**CEMENT & CONCRETE PRODUCTS™**

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If on skin (or hair): Remove immediately all contaminated clothing and wash before re-use. Rinse skin or hair with water.

If significant skin irritation or rash occurs: get medical advice or attention.

Immediately seek medical advice or attention if symptoms are significant or persist.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/containers in accordance with all regulations.

2.3 Additional Information

The Portland cement in this product can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. Burns from Portland cement may not cause immediate pain or discomfort. You cannot rely on pain to alert you to cement burns. Therefore precautions must be taken to prevent all contact with Portland cement. Cement burns can become worse even after contact has ended. If there is contact with this product, immediately remove all product from body and thoroughly rinse with water. If you experience or suspect a cement burn or inflammation you should immediately see a health care professional.

Skin burns and irritation may be caused by brief exposure, though often are caused by extended exposure of 15 minutes, an hour, or longer. Interaction of Portland cement with water or sweat releases a caustic solution which produces the burns or irritation. Any extended exposure should be treated as though a burn has occurred until determined otherwise.

Skin contact with Portland cement can also cause inflammation of the skin, referred to as dermatitis. Signs and symptoms of dermatitis can include itching, redness, swelling, blisters, scaling, and other changes in the normal condition of the skin. Signs and symptoms of burns include the above and whitening, yellowing, blackening, peeling or cracking of skin.

The Portland cement in this product may cause allergic contact dermatitis in sensitized individuals. This overreaction of the immune system can lead to severe inflammation. Sensitization may result from a single exposure to the low levels of Cr(VI) in Portland cement or repeated exposures over months or years. Sensitization is long lasting and, after sensitization, even very small quantities can trigger the dermatitis. Sensitization is uncommon. Individuals who experience skin problems, including seemingly minor ones, are advised to seek medical attention.

2.3a HNOX – Hazards not otherwise classified: Not applicable

2.3b Unknown Acute Toxicity: None



CEMENT & CONCRETE PRODUCTS™

Class E – Corrosive Material

SECTION III - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	CAS No.	% by Weight
Sand, Silica, Quartz	14808-60-7	40-70*
Portland Cement	65997 15 1	10-30*
Lime	01305-62-0	5-10*

*The concentrations ranges are provided due to batch-to-batch variability.
None of the constituents of this material are of unknown toxicity.

SECTION IV – FIRST AID MEASURES

4.1 Description of the first-aid measures

General information:

After inhalation: Remove person to fresh air. If breathing is difficult, administer oxygen. If not breathing, give artificial respiration. In case of unconsciousness, place patient stably in side position for transportation.

After skin contact: Wash skin with cool water and pH-neutral soap or a mild detergent. If significant skin irritation or rash occurs: get medical advice or attention.

After eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

After swallowing: Do not induce vomiting. If conscious, have the victim drink plenty of water and call a physician immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms/effects, acute and delayed

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated inhalation. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: The Portland cement in this product can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns.

Burns from Portland cement may not cause immediate pain or discomfort. You cannot rely on pain to alert you to cement burns. Therefore precautions must be taken to prevent all contact with Portland cement. Cement burns can become worse even after contact has ended. If there is contact with this product, immediately remove all product from body and thoroughly rinse with water. If you experience or suspect a cement burn or inflammation you should immediately see a health care professional.



CEMENT & CONCRETE PRODUCTS™

Skin burns and irritation may be caused by brief exposure, though often are caused by extended exposure of 15 minutes, an hour, or longer. Interaction of Portland cement with water or sweat releases a caustic solution which produces the burns or irritation. Any extended exposure should be treated as though a burn has occurred until determined otherwise.

Skin contact with Portland cement can also cause inflammation of the skin, referred to as dermatitis. Signs and symptoms of dermatitis can include itching, redness, swelling, blisters, scaling, and other changes in the normal condition of the skin. Signs and symptoms of burns include the above and whitening, yellowing, blackening, peeling or cracking of skin.

The Portland cement in this product may cause allergic contact dermatitis in sensitized individuals. This overreaction of the immune system can lead to severe inflammation. Sensitization may result from a single exposure to the low levels of Cr(VI) in Portland cement or repeated exposures over months or years. Sensitization is long lasting and, after sensitization, even very small quantities can trigger the dermatitis. Sensitization is uncommon. Individuals who experience skin problems, including seemingly minor ones, are advised to seek medical attention.

Eye Contact: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

4.3 Indication of immediate medical attention and special treatment needed:
Immediately seek medical advice or attention if symptoms are significant or persist.

SECTION V - FIRE FIGHTING MEASURES

5.1 Flammability of the Product: Non-flammable and non-combustible

5.2 Suitable extinguishing agents: Treat for surrounding material

5.3 Special hazards arising from the substance or mixture: None

5.3a Products of Combustion: None

5.3b Explosion Hazards in Presence of Various Substances: Non-explosive in presence of shocks

SECTION VI – ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures: Wear personal protective equipment (See section VIII). Keep unprotected persons away.

6.2 Methods and material for containment and cleaning up:

SDS C5

QUIKRETE Companies, LLC

7/10/2017



CEMENT & CONCRETE PRODUCTS™

Do not allow to enter sewers/ surface or ground water. Dispose of unwanted materials and containers properly in accordance with all regulations.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND STORAGE

7.1 Handling

Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace. DO NOT BREATHE DUST. In dusty environments, the use of an OSHA, MSHA or NIOSH approved respirator and tight fitting goggles is recommended. Wear appropriate PPE (See section 8). Do not mix with other chemical products, except as indicated by the manufacturer. Do not get in eyes, on skin or clothing. Good housekeeping is important to prevent accumulation of dust.

7.2 Storage

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep out of the reach of children. Keep container tightly closed and prevent exposure to humidity. Do not allow water to contact the product until time of use to preserve product utility.

SECTION VIII – EXPOSURE CONTROL MEASURES / PERSONAL PROTECTION

8.1 Components with limit values that require monitoring at the workplace:

Hazardous Components	CAS No.	PEL (OSHA) mg/M ³	TLV (ACGIH) mg/M ³
Silica Sand, crystalline	14808-60-7	0.1	0.025 (resp)
Portland Cement	65997-15-1	5 (resp) 15 (total)	10 (resp)
Lime	01305-62-0	5	5

8.2 Exposure Controls

Use ventilation adequate to keep exposures below recommended exposure limits.

8.3 General protective and hygienic measures

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

8.3a Personal protective equipment

Protection of hands:

Wear gloves of adequate length to offer appropriate skin protection from splashes. Nitrile, Butyl and PVC gloves have been found to offer adequate protection for incidental contact. Precautions must be observed because burns occur with little warning -- little heat is sensed.



CEMENT & CONCRETE PRODUCTS™

Eye protection:

Wear approved eye protection (properly fitted dust- or splash-proof chemical safety glasses).

Respiratory protection:

A NIOSH-approved dust mask or filtering face piece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional, following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

SECTION IX - PHYSICAL/CHEMICAL CHARACTERISTICS

General Information**Appearance**

Form: Granular Solid
 Color: Gray to gray-brown colored
 Odor: None

pH-value at 20°C (68 °F): 13 (10%)

Boiling point/Boiling range: Not applicable

Flash point: Not applicable

Auto igniting: Product is not self-igniting

Vapor pressure at 21°C (70°F) Not available

Density at 25°C (77 °F): 2.6 to 3.15

Solubility in / Miscibility with

Water: Insoluble

VOC content: 0 g/L VOC

SECTION X – STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal storage conditions. Keep in dry storage.

10.3 Possibility of hazardous reaction

No dangerous reaction known under conditions of normal use.

10.4 Thermal decomposition / conditions to be avoided

No decomposition if used according to specifications.

10.5 Incompatible materials

Contact of silica with powerful oxidizing agents such as fluorine, chlorine trifluoride, manganese trioxide, or oxygen difluoride may cause fires

10.6 Hazardous Decomposition or By-products

SDS C5

QUIKRETE Companies, LLC

7/10/2017



CEMENT & CONCRETE PRODUCTS™

Silica will dissolve in Hydrofluoric Acid and produce a corrosive gas – silicon tetrafluoride.

SECTION XI – TOXICOLOGICAL INFORMATION

11.1 Exposure Routes: Skin contact, skin adsorption, eye contact, inhalation, or ingestion.

11.2 Symptoms related to physical/chemical/toxicological characteristics:

Inhalation: May cause respiratory tract irritation. Causes damage to organs through prolonged or repeated exposure. This product contains crystalline silica. Prolonged or repeated inhalation of respirable silica from this product can cause silicosis.

Skin contact: Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis. May cause sensitization by skin contact. Product becomes extremely alkaline when exposed to moisture, and can cause alkali burns and affect the mucous membranes.

Eye Contact: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Ingestion: Harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

11.3 Delayed, immediate and chronic effects of short-term and long-term exposure

Short Term

Skin Corrosion/Irritation: Causes severe skin burns.

Serious Eye Damage/Irritation: Causes severe eye damage.

Respiratory Sensitization: Not available

Skin Sensitization: May cause an allergic skin reaction.

Specific Target Organ Toxicity-Single Exposure: (Category 3) May cause respiratory irritation.

Aspiration Hazard: Not available

Long Term

Carcinogenicity: May cause cancer through chronic inhalation.

Germ Cell Mutagenicity: Not available

Reproductive Toxicity: Not available

Specific Target Organ Toxicity- Repeated Exposure: (Category 1) Causes damage to lungs through prolonged/repeated exposure

Synergistic/Antagonistic Effects: Not available.

SECTION XII – ECOLOGICAL INFORMATION

12.1 Ecotoxicity

SDS C5

QUIKRETE Companies, LLC

7/10/2017



CEMENT & CONCRETE PRODUCTS™

May cause long-term adverse effects to the aquatic environment. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or un-neutralized

12.2 Persistence and degradability

No further relevant information available.

12.3 Bioaccumulative potential:

No further relevant information available.

12.4 Mobility in soil

No further relevant information available.

12.5 Other Adverse Effects

No further relevant information available.

SECTION XIII – DISPOSAL CONSIDERATIONS

13.1 Waste Disposal Method

The packaging and material may be land filled; however, material should be covered to minimize generation of airborne dust. This product is not classified as a hazardous waste under the authority of the RCRA (40CFR 261) or CERCLA (40CFR 117&302). Disposal must be made in accordance with local, state and federal regulations.

13.2 Other disposal considerations**Uncleaned packaging**

Recommendation: Disposal must be made in accordance with local, state and federal regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

SECTION XIV – TRANSPORT INFORMATION

	DOT (U.S.)	TDG (Canada)
UN-Number	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated
Transport Hazard Class(es)	Not Regulated	Not Regulated
Packing Group (if applicable)	Not Regulated	Not Regulated

14.1 Environmental hazards:

Not Available

14.2 Transport in bulk according to Annex II of Marpol 73/78 and the IBC Code

Not available



CEMENT & CONCRETE PRODUCTS™

14.3 Special precautions for user

Do not handle until all safety precautions have been read and understood.

SECTION XV – OTHER REGULATORY INFORMATION

15.1 Safety, Health and Environmental Regulations/Legislations specific for the chemical**Canada**

WHMIS Classification: Considered to be a hazardous material under the Hazardous Products Act as defined by the Controlled Products Regulations and subject to the requirements of Health Canada's Workplace Hazardous Material Information (WHMIS). This document complies with the WHMIS requirements of the Hazardous Products Act (HPA) and the CPR.

15.2 US Federal Information**SARA 302/311/312/313 Components**

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302, 311, 312 or 313.

RCRA: Crystalline silica (quartz) is not classified as a hazardous waste under the Resource Conservation and Recovery Act, or its regulations, 40 CFR §261 et seq.

CERCLA: Crystalline silica (quartz) is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR §302.

Emergency Planning and Community Right to Know Act (SARA Title III): Crystalline silica (quartz) is not an extremely hazardous substance under Section 302 and is not a toxic chemical subject to the requirements of Section 313.

FDA: Silica is included in the list of substances that may be included in coatings used in food contact surfaces, 21 CFR §175.300(b)(3)(xxvi).

NTP: Respirable crystalline silica, primarily quartz dusts occurring in industrial and occupational settings, is classified as Known to be a Human Carcinogen.

OSHA Carcinogen: Crystalline silica (quartz) is not listed.

15.3 State Right to Know Laws**California Prop. 65 Components**



CEMENT & CONCRETE PRODUCTS™



WARNING: This product can expose you to chemicals including crystalline silica which is known to the State of California to cause cancer and Portland cement which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Inhalation Reference Exposure Level (REL): California established a chronic REL of 3 µg for silica (crystalline, respirable). A chronic REL is an airborne level of a substance at or below which no adverse health effects are anticipated in individuals indefinitely exposed to the substance at that level.

Massachusetts Toxic Use Reduction Act: Silica, crystalline (respirable size, <10 microns) is “toxic” for purposes of the Massachusetts Toxic Use Reduction Act.

15.4 Global Inventories

DSL All components of this product are on the Canadian DSL list.

TSCA No.: Crystalline silica (quartz) appears on the EPA TSCA inventory under the CAS No. 14808-60-7. All constituents are listed in the TSCA inventory.

SECTION XVI – OTHER INFORMATION

Last Updated: July 10, 2017

NOTE: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by

The QUIKRETE Companies, LLC

End of SDS

CRACK-PAC® Injection Epoxy

SAFETY DATA SHEET

SIMPSON
Strong-Tie

1. Identification

Product Identification

Product Identifier: CRACK-PAC®
Recommended Use: Crack-Pac® is a two component, low viscosity injection epoxy.
Use Restrictions: To ensure proper installation use according to package directions, complete application instructions can be found in Simpson Strong-Tie catalogs or online at strongtie.com.

Company Identification

Company: Simpson Strong-Tie Company Inc.
Address: 5956 W. Las Positas Blvd.
Pleasanton, CA 94588, USA
Phone: 1-800-999-5099
Website: www.strongtie.com
Emergency: 1-800-535-5053 (US/Canada)
1-352-323-3500 (International)

For most current SDS, please visit our website at www.strongtie.com/sds

2. Hazard Identification

General Information

CRACK-PAC® Injection Epoxy is an adhesive for use to repair concrete cracks of 1/64" to 1/4" wide. Its viscosity and low surface tension allow it to repair fine to medium cracks in dry, damp, or wet conditions. Crack-Pac® is a two part (8A:1B) system, with the resin (Component A) contained in a cartridge and the hardener (Component B) in a nozzle. The two parts of this product have been individually assessed according to the Globally Harmonized System (GHS). The mixed product can be assumed to carry the hazards of each component until the product has fully hardened. The final cured product will be blue (which will fade to light amber over time) in color and can be considered nonhazardous. This Safety Data Sheet covers the hazards and responses for the safe use of this product.

Resin (Blue Side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Skin Corrosion/Irritation	Category 2	H315: Causes skin irritation
	Serious Eye Damage/Irritation	Category 2	H319: Causes serious eye irritation
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	Chronic Aquatic Hazard	Category 2	H411: Toxic to aquatic life with long lasting effects

Main Symptoms: Irritation of eyes and skin. Symptoms include redness, itching, burning, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin.

GHS Label Elements



Contains: Bisphenol-A Based Epoxy Resin, Castor Oil Glycidyl Ether

Signal Word: **WARNING!**

Hazard Statements:

H315:	Causes skin irritation.
H319:	Causes serious eye irritation.
H317:	May cause an allergic skin reaction.
H411:	Toxic to aquatic life with long lasting effects.

Precautionary Statements:

Prevention:	P102: Keep out of reach of children.
	P103: Read label before use.
	P202: Do not handle until all safety precautions have been read and understood.
	P261: Avoid breathing mist or vapor.
	P264: Wash thoroughly after handling.
	P272: Contaminated work clothing should not be allowed out of the workplace.

CRACK-PAC® Injection Epoxy

SAFETY DATA SHEET

SIMPSON
Strong-Tie

Response:	P273:	Avoid release to the environment.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352:	IF ON SKIN: Wash with plenty of water.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
	P363:	Wash contaminated clothing before reuse.
Storage:	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
	P391:	Collect Spillage.
	P403:	Store in a well-ventilated place.
	P405:	Store locked up.
Disposal:	P411:	Store between 45-90°F (7-32°C).
	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.


Hardener (Clear Side) GHS Classification

Classification according to HazCom2012 (GHS)

Physical Hazards:	Not Classified.		
Health Hazards:	Acute Toxicity, Oral	Category 4	H302: Harmful if swallowed
	Acute Toxicity, Dermal	Category 4	H312: Harmful in contact with skin
	Acute Toxicity, Inhalation	Category 4	H332: Harmful if inhaled
	Skin Corrosion/Irritation	Category 1	H314: Causes severe skin burns
	Serious Eye Damage/Irritation	Category 1	H318: Causes serious eye damage
	Sensitization, Skin	Category 1	H317: May cause an allergic skin reaction
Environmental Hazards:	STOT, Single Exposure	Category 1	EU H071: Corrosive to the respiratory tract
	Acute Aquatic Hazard	Category 3	H402: Harmful to aquatic life
	Chronic Aquatic Hazard	Category 3	H412: Harmful to aquatic life with long lasting effects

Main Symptoms: Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. May cause rash/allergic reaction to the skin. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. May cause shortness of breath, discomfort in chest, or coughing.

GHS Label Elements



Contains:	Benzene-1,3-Dimethanamine, Diethylenetriamine	
Signal Word:	DANGER!	
Hazard Statements:	H302:	Harmful if swallowed.
	H312:	Harmful in contact with skin.
	H332:	Harmful if inhaled.
	H314:	Causes severe skin burns and eye damage.
	H318:	Causes serious eye damage.
	H317:	May cause an allergic skin reaction.
	EU H071:	Corrosive to the respiratory tract.
	H402:	Harmful to aquatic life.
	H412:	Harmful to aquatic life with long lasting effects.
Precautionary Statements:		
Prevention:	P102:	Keep out of reach of children.
	P103:	Read label before use.
	P202:	Do not handle until all safety precautions have been read and understood.
	P260:	Do not breathe mist or vapor.

Response:	P264:	Wash thoroughly after handling.
	P270:	Do not eat, drink or smoke when using this product.
	P271:	Use only outdoors or in a well-ventilated area.
	P272:	Contaminated work clothing must not be allowed out of the workplace.
	P273:	Avoid release to the environment.
	P280:	Wear protective gloves/protective clothing/eye protection/face protection.
	P301+P330+P331:	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P310:	Immediately call a poison center/doctor.
	P303+P361+P353:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P333+P313:	If skin irritation or rash occurs: Get medical advice/attention.
Storage:	P363:	Wash contaminated clothing before re-use.
	P304+P340:	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313:	If eye irritation persists: Get medical advice/attention.
Disposal:	P391:	Collect Spillage.
	P403+P233:	Store in a well-ventilated place. Keep container tightly closed.
	P405:	Store locked up.
	P411:	Store between 45-90°F (7-32°C).
	P501:	Dispose of contents/container in accordance with local/regional regulations.

Supplemental Label Information: None known.

Hazards Not Otherwise Classified (HNOC)

None known.

3. Composition Information

General Information

This product is a mixture. Hazardous ingredients for each component are listed below. May include other nonhazardous ingredients. May include other trace ingredients, see Section 15.

List of abbreviations and symbols:

Classification: Global Harmonized System Classifications

The full text for H-phrases is displayed in section 16. All concentrations are in percent by weight unless otherwise noted.

Resin (Blue Side)

Chemical Name	Weight %	CAS Number	EC Number
Bisphenol-A Based Epoxy Resin	50-80	25068-38-6	500-033-5
Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, Aquatic Chronic 2: H411			
Castor Oil Glycidyl Ether	10-20	74398-71-3	616-085-8
Classifications: Skin Irrit. 2: H315, Skin Sens. 1: H317			
Oxirane, 2-[(4-nonylphenoxy)methyl]-, branched	10-20	147094-54-0	---
Classifications: Skin Irrit. 2: H315, Eye Irrit. 2: H319, Skin Sens. 1: H317, STOT SE 3: H335			
Naphtha (petroleum), aromatic-containing	1-5	68603-08-7	271-635-0
Classifications: Asp. Tox. 1: H304			

Hardener (Clear Side)

Chemical Name	Weight %	CAS Number	EC Number
Benzene-1,3-Dimethanamine	70-90	1477-55-0	216-032-5
Classifications: Acute Tox. 4: H302+H332, Skin Corr. 1: H314, Eye Corr. 1: H318, Skin Sens. 1: H317, Aquatic 3: H402+H412			
Diethylenetriamine	10-30	111-40-0	203-865-4
Classifications: Acute Tox. 4: H302+H312, Skin Corr. 1: H314, Skin Sens. 1: H317			

4. First-Aid Measures

General Information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

Routes of Exposure

Eye Contact:	Immediately flush eyes with plenty of cool water for at least 15 minutes while holding the eyes open. Remove contact lenses if present and easy to do. If redness, burning, blurred vision, or swelling persists, consult a physician immediately.
Skin Contact:	Remove contaminated clothing, immediately wash affected area with soap and water. Do not apply greases or ointments. If skin irritation persists, consult a physician.
Ingestion:	Rinse mouth immediately. Give large amounts of milk or water, if person is conscious. Only induce vomiting at the instruction of medical personnel. Consult a physician immediately.
Inhalation:	Remove patient to fresh air. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give oxygen or artificial respiration if needed. If breathing has stopped, assist ventilation with a mechanical device. If patient continues to experience difficulty breathing, consult a physician.

Most Important Symptoms

Damage to the eyes and skin. Symptoms include burns, redness, itching, tearing, swelling, and blurred vision. Permanent eye damage, including blindness, may result. May cause rash/allergic reaction to the skin. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. May cause shortness of breath, discomfort in chest, or coughing. May cause damage to mucous membranes in nose, throat, lungs and bronchial system. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure.

5. Fire-Fighting Measures

Suitable Extinguishing Media:	Extinguish with foam, carbon dioxide, dry powder, or water fog.
Additional Information:	Do not use a solid water stream as it may scatter and spread fire.
Hazards during Fire-Fighting:	Hazardous decomposition products may occur when materials polymerize at temperatures above 500 °F (260°C). Do not allow run-off from fire-fighting to enter drains or water courses.
Fire-Fighting Procedures:	Use standard fire-fighting procedures and consider the hazards of other involved materials. In case of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn. Move containers from fire area if you can do so without risk. Cool containers with flooding quantities of water until well after fire is out. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

6. Accidental Release Measures

Personal Precautions

Non-emergency personnel: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not inhale vapors or mists. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Emergency personnel: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protection.

Clean-Up Methods

Small spills (uncured):	Wipe up with absorbent material (e.g. cloth, fleece). Place in leak-proof containers. Seal tightly for proper disposal. Clean surface thoroughly to remove residual contamination. If desired, approved solvents, such as ketones (MEK, acetone, etc.), lacquer thinner, or adhesive remover can be used. Do NOT use solvents to clean adhesives from skin. Take appropriate precautions when handling flammable solvents. Solvents may damage surfaces to which they are applied.
Large spills (uncured):	Stop the flow of material, if this is without risk. Dike far ahead of spill to contain material. Use a non-combustible material like vermiculite, sand or earth to soak up the product. Place in leak-proof containers. Seal tightly for proper disposal. Following product recovery, flush area with water.
Cured Material:	Chip or grind off surface. If you are grinding or cutting cured product, ensure good work practice and use of personal protective equipment as needed to control exposure to respirable dust.

Environmental Precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so.

7. Handling and Storage

Handling

Mechanical ventilation or local exhaust ventilation is recommended. Keep away from open flames, hot surfaces and sources of ignition.

CRACK-PAC® Injection Epoxy

SAFETY DATA SHEET

SIMPSON
Strong-Tie

Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Do not breathe mist or vapor. Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Storage

Store in a closed container away from incompatible materials. Keep in original container. Keep container tightly closed. Store in a dry place out of direct sunlight. Store between 45-90°F (7-32°C). Keep away from heat and sources of ignition. Store in a well-ventilated place. Store locked up. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Personal Protective Equipment

General Protection: Wear appropriate personal protective equipment.
Eye Protection: Wear chemical splash goggles or safety glasses with side shield.
Hand Protection: Wear chemical-resistant gloves such as: Nitrile, neoprene, butyl.
Skin and Body Protection: Wear long sleeve shirt/long pants and other clothing as required to minimize contact.
Respirator Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
General Hygiene: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Engineering Controls

When using indoors good general ventilation should be used. Ventilation rates should be matched to conditions. Ready access to running water is required. Provide eyewash station and emergency shower.

Limits

Component	OSHA (PEL)	ACGIH (TLV)	NIOSH Pocket Guide
Benzene-1,3-Dimethanamine (CAS 1477-55-0)	N/E	0.1 mg/m ³ (ceiling, skin)	0.1 mg/m ³ (ceiling, skin)
Diethylenetriamine (CAS 111-40-0)	4 mg/m ³	4 mg/m ³ (TWA)	4 mg/m ³ (TWA)

9. Physical and Chemical Properties

Property	Resin	Hardener
Physical State:	Liquid	Liquid
Color:	Blue	Clear
Odor:	Strong Acrid	Ammonia
pH:	No data	12
Flammability limit – lower %:	No data	No data
Flammability limit – upper %:	No data	No data
Vapor Pressure:	No data	No data
Vapor Density:	No data	No data
Solubility:	Insoluble in water	Slightly soluble in water
Freezing/Melting Point:	No data	No data
Boiling Point:	No data	No data
Flash Point:	>250 °F (121.1 °C) Open Cup	230 °F (110 °C) Closed Cup
Evaporation Rate:	No data	No data
Decomposition Temperature:	No data	No data
Specific Gravity:	No data	No data
VOC (after cure):	7 g/L	7 g/L
Kow:	No data	No data
Viscosity:	No data	No data
Corrosiveness:	Non-corrosive	Corrosive

10. Stability and Reactivity

Resin (Blue Side)

Reactivity: This product is stable and non-reactive under normal conditions.

CRACK-PAC® Injection Epoxy

SAFETY DATA SHEET

Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Oxidizing agents, acids, organic bases, and amines.
Hazardous Reactions:	Hazardous polymerization does not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

Hardener (Clear Side)

Reactivity:	This product is stable and non-reactive under normal conditions.
Chemical Stability:	Stable under normal storage conditions.
Condition to Avoid:	High heat and open flame.
Substances to Avoid:	Strong oxidizing agents. Strong acids. Epoxy resins.
Hazardous Reactions:	Hazardous polymerization does not occur.
Decomposition Products:	Carbon dioxide, carbon monoxide, oxides of nitrogen, and other organic compounds.

11. Toxicological Information

Likely Routes of Exposure

Ingestion:	Harmful if swallowed. Corrosive material; may cause severe irritation or burns to the gastrointestinal tract or respiratory tract.
Inhalation:	Harmful if inhaled. Corrosive to the respiratory tract.
Skin contact:	Harmful in contact with skin. Causes severe skin burns. May cause an allergic skin reaction.
Eye contact:	Causes serious eye damage.
Symptoms:	Burns, redness, itching, tearing, swelling, and blurred vision. Rash/dermatitis. May cause severe irritation or burns to the gastrointestinal tract and respiratory system. May cause shortness of breath, discomfort in chest, or coughing.

Information on Toxicological Effects

Acute Effects

Toxicity:	Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

Component	Estimate
CRACK-PAC® Resin Toxicity Estimate	
Acute, Oral, LD50	> 9000
Acute, Dermal, LD50	2000
CRACK-PAC® Hardener Toxicity Estimate	
Acute, Oral, LD50	995
Acute, Dermal, LD50	1756
Acute, Inhalation, LC50	3.90

Component	Species	Test Result
Bisphenol-A Based Epoxy Resin (CAS 25068-38-6)		
Acute, Oral, LD50	Rat	11400 mg/kg
Acute, Dermal, LD50	Rabbit	2000 mg/kg
Castor Oil Glycidyl Ether (CAS 74398-71-3)		
Acute, Oral, LD50	Rat	> 5000 mg/kg
Acute, Dermal, LD50	Rabbit	> 2000 mg/kg
Benzene-1,3-Dimethanamine (CAS 1477-55-0)		
Acute, Oral, LD50	Rat	980 mg/kg
Acute, Dermal, LD50	Rabbit	2000 mg/kg
Acute, Inhalation, LC50	Rat	700 ppm, 1 hour
Diethylenetriamine (CAS 111-40-0)		
Acute, Oral, LD50	Rat	1080 mg/kg
Acute, Dermal, LD50	Rabbit	1090 mg/kg

Skin corrosion/irritation:	Causes severe skin irritation and burns.
Eye damage/eye irritation:	Causes serious eye irritation and damage.
Respiratory sensitization:	No data available.
Skin sensitization:	May cause an allergic skin reaction.
Aspiration hazard:	No data available.

CRACK-PAC® Injection Epoxy

SAFETY DATA SHEET



Specific target organ toxicity
Single exposure: Corrosive to the respiratory tract.

Chronic Effects

Germ cell mutagenicity: No data available.
Carcinogenicity: This product is not considered a carcinogen by IARC, NTP, ACGIH, or OSHA.
Reproductive toxicity: No data available.
Specific target organ toxicity
Repeated exposure: No data available.

Further Information

Toxicological, ecotoxicological, physical, and chemical properties may not have been fully investigated. Hazard data above is estimated based on best available information. Some workers with pre-existing medical conditions such as: asthma, allergies, or impaired pulmonary and/or liver functions, or who may be particularly susceptible to this material, may be affected by exposure to this material.

12. Ecological Information

General Information

Information given is based on data on the components and the ecotoxicology of similar products. CRACK-PAC Resin is classified as toxic to aquatic life with long lasting effects. CRACK-PAC Hardener is classified as harmful to aquatic life, with long lasting effects. Avoid release to the environment.

Supporting Data

Component	Species	Test Result
Bisphenol-A Based Epoxy Resin (CAS 25068-38-6)		
Aquatic , Fish, LC50	Salmo gairdneri	1.3 mg/l, 96 hours
Aquatic , Crustacea, EC50	Daphnia magna	2.1 mg/l, 48 hours
Aquatic , Algae, EC50	Algae	> 11 mg/l, 72 hours
Benzene-1,3-Dimethanamine (CAS 1477-55-0)		
Aquatic , Fish, LC50	Red killfish	87.6 mg/l, 96 hours
Aquatic , Crustacea, EC50	Daphnia magna	15.2 mg/l, 48 hours
Aquatic , Algae, EC50	Green algae	32.1 mg/l, 72 hours
Diethylenetriamine (CAS 111-40-0)		
Aquatic , Fish, LC50	Poecilia reticulata	1014 mg/l, 96 hours

Persistence and degradability: This product is not expected to be readily biodegradable.
Bioaccumulative potential: No data available for this product.

Chemical	Log Kow	BCF	Bioaccumulation Potential
Bisphenol-A Based Epoxy Resin (CAS 25068-38-6)	2.64-3.78	3-31	low

Mobility in soil: No data available.

Further Information

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. Disposal Consideration

Waste Disposal of Substance: Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.
Container Disposal: Empty containers or liners may retain some product residues; follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
Disposal of Cured Product: Chip or grind off surface. Solid material does not need special disposal consideration.

CRACK-PAC® Injection Epoxy

SAFETY DATA SHEET



14. Transportation Information

	Resin (Blue Side)	Hardener (Clear Side)
UN number:	UN3082	UN2735
UN proper shipping name:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A-Epichlorohydrin), 9, III, Marine Pollutant	AMINES, LIQUID, CORROSIVE, N.O.S. (Benzene-1,3-dimethanamine(MXDA)), 8, II
Precautions:	Marine Pollutant	Corrosive
Required Labels:	9	8
ERG Code (IATA):	9L	8L
EmS (IMDG):	F-A, S-F	F-A, S-B

Additional Information

Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: This substance/mixture is not intended to be transported in bulk.

This information does not cover all specific regulatory or operational requirements of this product. The classifications for transportation may vary by container volume or different regional or national regulations.

15. Regulatory Information

United States

Federal Regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4):

Acetic Acid (CAS 64-19-7)	LISTED
Alcohol Ethoxylate (CAS 78330-21-9)	LISTED
Phosphoric Acid (CAS 7664-38-2)	LISTED
Napthalene (CAS 91-20-3)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA):

Hazard Categories:	Immediate	Delayed	Fire	Pressure	Reactivity
Resin	Yes	Yes	No	No	No
Hardener	Yes	Yes	No	No	No

SARA 302 Extremely hazardous substance: No
SARA 311/312 Hazardous chemical: Yes

SARA 313 (TRI reporting):

Chemical	CAS Number	% In Blend (approx.)
Napthalene	91-20-3	< 0.1

US. California Proposition 65: WARNING: This product contains a chemical listed by the State of California as known to cause cancer, birth defects, or reproductive harm.

Carcinogen / Reproductive Toxin / Mutagen Information					
Component	% In Blend (approx.)	IARC Monographs	NTP	ACGIH	Other
Napthalene (91-20-3)	< 0.1	2B	ANTICIPATED	---	CA65 (Carcinogenic)
IARC: 1- Carcinogenic 2- Possibly carcinogenic 3- Not classifiable as to carcinogenicity 4- Probably not carcinogenic NTP: Known to be human carcinogen or Reasonably anticipated to be a human carcinogen ACGIH - A1 - Confirmed carcinogen A2 - Suspected carcinogen A3 - Animal carcinogen A4 - Not classified A5 - Not suspected CA65 - California Prop 65					

CRACK-PAC® Injection Epoxy

SAFETY DATA SHEET

US State Right-To-Know Lists

Chemical	Massachusetts RTK	New Jersey Work and Community RTK Act	Pennsylvania Worker and Community RTK Law	Rhode Island RTK
Benzene-1,3-Dimethaneamine (CAS 1477-55-0)	Listed	Listed	Listed	
Diethylenetriamine (CAS 111-40-0)	Listed	Listed	Listed	Listed

Canada

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

International

The product is classified in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

REACH Registered Substances			
Chemical	CAS Number	EC Number	Index Number
BPA Based Epoxy Resin	25068-38-6	500-033-5	603-074-00-8
Diethylenetriamine	111-40-0	203-865-4	612-058-00-X

This product is not subject to or not applicable for any of the following International Regulations; **Stockholm Convention, Rotterdam Convention, Kyoto Protocol, Montreal Protocol, Basel Convention.**

International Inventories

Australia	One or more components of this product are not listed on the Australian Inventory of Chemical Substances (AICS).
Canada	All components of this product are included on the Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).
China	One or more components of this product are not listed on the Inventory of Existing Chemical Substances in China (IECSC).
Europe	One or more components of this product are not included on the European Inventory of Existing Commercial Chemical Substances (EINECS) or are not exempt from listing.
Japan	One or more components in this product are not listed on the Inventory of Existing and New Chemical Substances (ENCS).
Korea	One or more components of this product are not included on the Existing Chemicals List (ECL).
New Zealand	One or more components of this product are not included on the New Zealand Inventory.
Philippines	One or more components in this product are not listed in the Philippine Inventory of Chemicals and Chemical Substances (PICCS).
United States & Puerto Rico	All components of this product are listed on the Toxic Substances Control Act (TSCA) Inventory or are not required to be listed.


16. Other Information

Date Prepared or Revised: September 2016
Supersedes: September 2014

Contact Simpson Strong-Tie Environmental Health and Safety at EHS@strongtie.com

Additional Resin (Blue Side) Classifications

NFPA Ratings



HMIS Rating

HEALTH	2	PHYSICAL	0
FLAMMABILITY	1	PPE	B


CRACK-PAC® Injection Epoxy

SAFETY DATA SHEET

SIMPSON
Strong-Tie

Additional Hardener (Clear Side) Classifications

NFPA Ratings



HMIS Rating

HEALTH	3	PHYSICAL	0
FLAMMABILITY	1	PPE	B

Abbreviations

ACGIH:	American Conference of Governmental Industrial Hygienists
CAS No.:	Chemical Abstract Service Registry Number
CERCLA:	Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
HPR:	Hazardous Product Regulations (Canada)
DOT:	Department of Transportation (U.S.)
EPA:	Environmental Protection Agency (U.S.)
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals
HEPA:	High-Efficiency Particulate Air
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods code
NIOSH:	National Institute of Occupational Safety and Health (U.S.)
NFPA:	National Fire Protection Association (US)
NTP:	National Toxicology Program (US)
OSHA:	Occupational Safety and Health Administration (U.S.)
PEL:	Permissible Exposure Limit
SARA:	Superfund Amendments and Reauthorization Act (U.S. EPA)
SDS:	Safety Data Sheet
STEL:	Short Term Exposure Limit (15 minute Time Weighted Average)
STOT:	Specific Target Organ Toxicity (GHS Classification)
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act (U.S.)
TWA:	Time Weighted Average (exposure for 8-hour workday)
VOC:	Volatile Organic Compounds
WHMIS:	Canadian Workplace Hazardous Materials Information System

Full Text of H – Phrases Under Section 3

H302:	Harmful if swallowed.
H304:	May be fatal if swallowed and enters airways.
H312:	Harmful in contact with skin.
H314:	Causes severe skin burns and eye damage.
H315:	Causes skin irritation.
H317:	May cause an allergic skin reaction.
H318:	Causes serious eye damage.
H319:	Causes serious eye irritation.
H332:	Harmful if inhaled.
H335:	May cause respiratory irritation.
H402:	Harmful to aquatic life.
H411:	Toxic to aquatic life with long lasting effects.
H412:	Harmful to aquatic life with long lasting effects.

CRACK-PAC® *Injection Epoxy*

SAFETY DATA SHEET



Disclaimer

This Safety Data Sheet (SDS) is prepared by Simpson Strong-Tie Co. in compliance with the requirements of OSHA 29 CFR Part 1910.1200. The information it contains is offered in good faith as accurate as of the date of this SDS. This SDS is provided solely for the purpose of conveying health, safety, and environmental information. No warranty, expressed or implied, is given. Health and Safety precautions may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations.

© 2016 Simpson Strong-Tie Company Inc.

Internal

FOR INTERNAL USE ONLY

CRACK-PAC Resin:	CRACK-PAC Hardener:
XCOM3B – 90% Cartridge	XCOM3B – 10% Cartridge
	XCORR – 10% Cartridge



Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code/Name: CW5037 Dirt Jet Pro Industrial Hand Towels

Intended Use: Hand cleanser solution absorbed into towel

Distributor: Lawson Products, Inc.

8770 W. Bryn Mawr Ave., Suite 900

Chicago, IL 60631 773-304-5050 Emergency Phone# 888-426-4851

2. HAZARD IDENTIFICATION



Signal Word: Danger

Classification:

Flammable liquid: Category 3

Skin irritation: Category 2

Eye irritation: Category 2

Skin sensitization: Category 1

Aspiration toxicant: Category 1

Hazard Statements:

Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary Statements:

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed.

Take precautionary measures against static discharge. Store in a well ventilated place. Keep cool.

Avoid breathing fume/vapors. Wash hands thoroughly after handling.

IF SWALLOWED: Immediately call a Poison Center or Physician. Do not induce vomiting.

IF ON SKIN (or hair) Remove immediately all contaminated clothing. Rinse skin with water.

If skin irritation occurs: Get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical attention.

In case of fire: Use water fog, foam, dry chemical or carbon dioxide (CO₂) for extinction.

Collect spillage. Dispose of contents and container in accordance with local regulations.

3. COMPONENTS

Significant Ingredients	CAS #	Weight %	Physical Haz
Orange Terpenes	68647-72-3	< 10	Flam Liq 3,



Safety Data Sheet

Ethoxylated Nonyl Phenol	9016-45-9	< 5	None
Lanolin	8006-54-0	< 1	None
Water	7732-18-5	> 90	None

This cleanser contains other ingredients that do not affect the product's final classification because of their minimal concentration. See product label for full ingredient information.

4. FIRST AID MEASURES

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical attention.

IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

If skin irritation occurs: Get medical attention.

IF SWALLOWED: Immediately call a Poison Center or Physician. Do not induce vomiting.

IF INHALED: Remove to fresh air; apply artificial respiration if necessary. Get medical attention.

5. FIRE-FIGHTING MEASURES

General Hazard

Flammable materials can form combustible mixtures at temperatures at or above the flash point. Empty containers can contain residues that can cause fires or explosions when exposed to heat, flames, or sparks.

Fire-Fighting

Keep fire exposed containers cool with water spray. Separate unburning product from fire. Use carbon dioxide, foam, or dry chemical extinguishing media to put out fires.

Unusual Decomposition Products Under Fire Conditions

None

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Remove greatly contaminated clothing, including shoes and wash thoroughly after contact.

Launder contaminated clothing before reuse.

Environmental Precautions

Due to package size and form, solution egress is not expected.

If towels are spilled from containers, eliminate all sources of ignition and ensure adequate ventilation.

Wipe up all liquid residues. Dispose in accordance with all applicable regulations.

7. HANDLING AND STORAGE

Safe Handling and Storage

Do not handle, store, or dispense near open flames or ignition sources.

Exposure to extreme conditions may have an adverse affect on this product.

Do not reuse containers.

Incompatible Products

Avoid strong oxidizing and reducing agents.



8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Ventilation

Local exhaust is usually sufficient. General exhaust is preferred.

Personal Protection

Use solvent resistant gloves to avoid prolonged contact.

Work Place Exposure Guide Lines

Orange Terpenes has a recommended TWA of 30 ppm.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	212 °F
Specific Gravity (water =1):	1.0
Vapor Pressure (mm Hg):	< 1
Melting Point:	Not Applicable
Vapor Density (Air =1):	> 5
Evaporation Rate (butyl Acetate=1):	< 0.2
Solubility in Water:	Rinsable
Reactivity in Water:	NIL
Appearance and Odor:	White liquid with citrus odor absorbed into towel
Flash Point:	129 °F
Flammable Limits (volume percent in air):	LEL: Not Established UEL: Not Established
Autoignition Temperature: approximately	Not Established

10. STABILITY AND REACTIVITY

Stability: ☐ Unstable ☒ Stable

Conditions to avoid: None

Incompatibility (Materials to avoid): Strong oxidizing and reducing agents.

Hazardous Decomposition Products: Combustion may produce oxides of carbon.

Hazardous Polymerization: ☐ May Occur ☒ Will Not Occur

Conditions to Avoid: Not Applicable

11. TOXICOLOGICAL INFORMATION

	Skin	Eye	Asp
Orange Terpenes	Skin Ir Cat 2, Skin Sen Cat 1	--	Asp Tox 1
Ethoxylated Nonyl Phenol	--	Eye Dam Cat 1	--
Lanolin	has no GHS classification		
Water	has no GHS classification		

Ethoxylated Nonyl Phenol has a Oral Ld50 960 – 3980 mg/kg and an Inhalation LC 50 1.15 mg/l

Symptoms Related to the Toxicological Characteristics

Eye irritation. Skin irritation. May include stinging, tearing, redness, swelling, and blurred vision.

Allergic skin reaction. May be fatal if swallowed and entered air ways.



Safety Data Sheet

This product is considered an aspiration hazard based on one component's physical/chemical properties.
This product is not expected to cause cancer. This product may cause an allergic skin reaction.
No data is available to indicate that any ingredient is mutagenic or genotoxic.
This product is not expected to cause reproductive or developmental effects.
Repeated exposure to low viscosity materials may defat the skin resulting in possible irritation and dermatitis.
Exposure to vapors or aerosol concentrations above the recommended exposure level is irritating to the eyes and respiratory tract, and may cause headaches, dizziness, anesthesia, and even unconsciousness.

12. ECOLOGICAL INFORMATION

This product is damaging to the environment.
It is toxic to aquatic life with long lasting effects.
This product contains a Volatile Organic Compound: So part of it will evaporate upon release.
Please refer to Section 6 for accidental release information.

13. DISPOSAL CONSIDERATIONS

Dry towels can be disposed with other solid waste.
Unused product can be incinerated directly in appropriate equipment.

14. TRANSPORT INFORMATION

The DOT does not regulate this product for ground shipments.

This product is not packaged in approved packaging for Air or International transport.

15. REGULATORY INFORMATION

This product's label design and content follows the cosmetic labeling requirements of the Food and Drug Administration.

All components of this product are on the U.S. EPA TSCA Inventory List.

16. OTHER INFORMATION

This document was revised 08 May 2015

INFORMATION GIVEN HEREIN IS OFFERED IN GOOD FAITH AS ACCURATE, BUT WITHOUT GUARANTEE. CONDITIONS OF USE AND SUITABILITY OF THE PRODUCT FOR PARTICULAR USES ARE BEYOND OUR CONTROL; ALL RISKS OF USE OF THE PRODUCT ARE THEREFORE ASSUMED BY THE USER AND WE EXPRESSLY DISCLAIM ALL WARRANTIES OF EVERY KIND AND NATURE, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE IN RESPECT TO THE USE OR SUITABILITY OF THE PRODUCT. APPROPRIATE WARNINGS AND SAFE HANDLING PROCEDURES SHOULD BE PROVIDED TO HANDLERS AND USERS.



CANBERRA CORPORATION SAFETY DATA SHEET

1. Identification

Product Identifier: DETERGENT THICKENED HUSKY 302 D/T BOWL CLEANER

Application or recommended use: Disinfectant toilet bowl cleaner

Restrictions on use: Do not use in any fashion not specified on the product label.

Manufacturer / supplier: Canberra Corporation

3610 N. Holland-Sylvania Rd.

Toledo, Ohio 43615 USA

Telephone: 419-841-6616 **Emergency phone:** 800-832-8992 **National Poison Center:** 800-222-1222

2. Hazards Identification

GHS Classification: Classification of this mixture in accordance with paragraph (d) of §1910.1200.

Skin Corrosion/Irritation - Category 1B

Eye Damage/Irritation - Category 1

Corrosive to Metals - 1

Label Elements:



Symbol:

Signal word:

DANGER

Hazard statements:

Causes severe skin burns and serious eye damage.

May be corrosive to metals.

Precautionary statements: Do not breathe mist/vapors/spray.

Wash hands, face and any skin contact thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep only in original container.

Absorb spillage to prevent material damage.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

See 4. First-Aid Measures for specific treatment.

Store locked up in corrosive resistant container.

Dispose of contents/container to an approved disposal facility.

Other Hazards: Harmful if swallowed.

3. Composition / Information on Ingredients

Chemical characterization: Hydrochloric acid solution, blended with detergents, germicides and auxiliary agents.

Hazardous ingredients: The exact percentage of composition has been withheld as a trade secret.

9.5 - 10% *Hydrochloric acid (Muriatic acid)

CAS 7647-01-0, EINECS/ELINCS 231-595-7

0.9 - 2.5% Ethanol, 2,2'-iminobis-,n-soya alkyl derivs.,

CAS 73246-96-5, EINECS/ELINCS Not Available

Other ingredients (> 1%):

> 85% Water

CAS 7732-18-5, EINECS/ELINCS 231-791-2

4. First-Aid Measures

Symptoms: Causes irritation or burning sensation. Causes severe skin burns and serious eye damage.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

Inhalation: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth to an unconscious person. If respiratory irritation, dizziness, or unconsciousness occurs, seek immediate medical assistance.

Skin Contact: Remove contaminated clothing and wash before reuse. Wash contaminated area with soap and water for 15-20 minutes. Call a poison control center or doctor for treatment advice.

Eye Contact: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Version: 001 **Date issued:** 31. 12. 2014

Revision Date: N/A

Page 1 of 4

4. First-Aid Measures (cont.)

Ingestion: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to a person who is unconscious or convulsing. If vomiting occurs, keep head below hips to reduce risk of aspiration. Probable mucosal damage may contraindicate the use of gastric lavage.

Note to Physician: Treat exposed patients symptomatically.

5. Fire-Fighting Measures

Suitable Extinguishing Media: Not applicable. Product is not a fire hazard.

Unsuitable Extinguishing Media: High pressure water jet.

Specific hazards in case of fire: Hydrogen chloride gas may be generated at high temperatures.

Special Fire Fighting Precautions: Fire fighters should wear appropriate protective equipment, including self-contained breathing apparatus and impervious clothing.

6. Accidental Release Measures

Emergency Procedures: Depending on the extent of release, consider the need for emergency responders with adequate personal protective equipment for clean up, need for evacuation or restriction of access to spill area.

Personal Precautions: Provide adequate ventilation. Do not eat, drink or smoke during clean up. If necessary, use self-contained respirator, or filtered mask. Wear protective clothing, eye protection and impervious gloves (e.g. neoprene). Wash thoroughly after clean up.

Environmental Precautions: Prevent spills from entering storm sewers/drains or contact with soil.

Clean up Methods: Small spills may be wiped up and rinsed with water. For larger spills, neutralize with sodium carbonate and absorb on fire retardant material (e.g. sand). Pick up absorbent and dispose of at an appropriate waste disposal facility.

7. Handling and Storage

Precautions for Safe Handling: Read label before use. Never use with chlorine products. Can react to give chlorine gas. If this occurs, flush toilet to remove chemicals and leave area. Do not return for half hour. Ventilate if possible. Never use or mix with other cleaners or chemicals. Do not use on any surface that can be damaged by acid materials. Do not breathe mist/vapors. Wash hands, face and any skin contact thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, protective clothing, eye protection, face protection. Use product only according to label directions. If unsure about safe use, contact your supervisor immediately. Use only in a well-ventilated area.

Conditions for Safe Storage: Keep out of reach of children. Do not contaminate water, food or feed by storage and disposal. Store locked up in tightly closed, original, corrosive resistant container in a cool (10° - 30°C), dry, well-ventilated area.

Incompatibility: Chlorine bleach, alkali. Do not mix with anything but water.

8. Exposure Controls / Personal Protection

Components with occupational exposure limits:

Component	Reference	TWA	PEL
Hydrochloric acid	ACGIH	2 ppm (C)	
	OSHA		5 ppm (C)

Engineering Controls: Proper ventilation in accordance with good industrial hygiene should be provided.

Personal Protective Equipment

Respiratory: Respiratory protection is not necessary under normal conditions of use. If necessary to prevent exposure above occupational limits, use an approved cartridge style respirator.

Gloves: Use water impervious gloves (latex or neoprene rubber). No breakthrough time has been established.

Eye Protection: Chemical resistant goggles and face protection.

Other: Protective clothing (long sleeves, pants), eyewash, safety shower are always advisable when working with chemicals.

9. Physical and Chemical Properties

Physical State -	Liquid	Auto-ignition temperature -	Not applicable
Color -	Green	Flash Point -	None
Odor -	Floral, acidic	Flammability -	Not applicable
Odor Threshold -	No data available	Flammability Limits -	Not applicable
Boiling Point -	212°F	Partition coefficient -	Not applicable
Decomposition temperature -	No data available	Solubility (Water) -	Complete
Freezing Point -	0°F	Vapor Density -	No data available
pH (Neat) -	< 1	Vapor Pressure -	No data available
Relative Density -	1.045	Viscosity -	Slightly viscous
Evaporation Rate -	Similar to water	% VOC -	< 0.5 (Excluding LVP material)

10. Stability and Reactivity

Reactivity: No specific reactivity test data is available. Under normal conditions of storage and use, hazardous reactions are not expected.

Incompatible materials: Mixing with bleach, alkali, or oxidizers may generate toxic gases.

Chemical stability: This product is stable at ambient temperatures and pressures.

Conditions to avoid: Temperatures above 50°C or below 10°C.

Hazardous decomposition products: Hydrogen chloride

11. Toxicological Information

Acute Toxicity: Toxicity data is not available for this mixture. Data below are estimates based on summation methods.

Test	Results	Classification (A.0.4.1(c))	Basis (A.1.3.6.1)
Oral	> 2000mg/kg	Not applicable	Ingredient literature (Additive formula)
Dermal	> 2000mg/kg	Not applicable	Ingredient literature (Additive formula)
Inhalation	> 20 mg/L	Not applicable	Ingredient literature (Additive formula)
Eye Damage/Irritation	Corrosion	Category 1	Ingredient literature
Skin Damage/Irritation	Corrosion	Category 1B	Ingredient literature

Summary: Skin and eye contact are most likely routes of exposure. Exposure causes skin burns and serious eye damage.

Subchronic/Chronic Toxicity:

Test	Results	Classification	Basis
Skin Sensitization	Not a sensitizer	Not applicable	Ingredient literature.

Summary: Repeated or prolonged contact causes skin burns and eye damage.

Carcinogens - Ingredients are not listed on the NTP Report on Carcinogens, *IARC Monographs or by OSHA

*IARC does list "strong inorganic acid mists" as carcinogenic, but under normal conditions, no exposure to acid mists occurs. Acid solutions are not listed.

Other data - No other toxicological information is available for this mixture.

12. Ecological Information

This material has not been tested for acute environmental effects.

Persistence and degradability: Material is not persistent. All organic components > 1% are readily biodegradable.

Bio-accumulative potential: No evidence to suggest bio-accumulation will occur.

Mobility: Accidental spillage may lead to penetration of soil and groundwater. However, due to degradability, no evidence suggests this would cause adverse ecological effects. Material will lower pH of affected area.

13. Disposal Considerations

RCRA Class - D002. Do not contaminate water, food or feed by disposal. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray, or mixture of rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label directions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA Regional Office for guidance. **Container Disposal:** Non-refillable container. Do not reuse or refill this container. Offer for recycling if available. Triple rinse container promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate, or if allowed by state and local authorities, burn. If burned, stay out of smoke. If container is one gallon or less, wrap empty container in plastic bag and discard in trash.

14. Transport Information

Proper Shipping Name: UN1789 Hydrochloric acid solution

RQ - 5000 Lbs. (Hydrochloric Acid)

Shipping emergency phone: 800-424-9300

Transport hazard class: 8

Hazard Label: Corrosive (When shipped as a Limited Quantity, labeling is not required.)

Packing Group: II

Emergency Guide No.: 154

Marine Pollutant: No

15. Regulatory Information

Inventory status: All components are listed on TSCA(US), EINECS/ELINCS(EU), DSL(Canada), AICS(Australia), ENCS(Japan).

FIFRA: This product is a U.S. EPA Registered pesticide, EPA Reg. No. 8155-6, and is subject to certain labeling requirements under Federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide products. The hazard information required on the pesticide label is reproduced here.

15. Regulatory Information (cont.)

DANGER: Corrosive. Causes irreversible eye damage and skin burns. May be fatal if swallowed. Do not breathe vapor or fumes. Do not get in eyes, on skin or on clothing. Wear protective eyewear (safety goggles or face shield), protective clothing and rubber gloves when handling. Use with adequate ventilation. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum or using tobacco. Remove and wash contaminated clothing before reuse.

Chemical Hazards: **Never use with chlorine products.** Can react to give chlorine gas. If this occurs, flush toilet to remove chemicals and leave area. Do not return for half an hour. Ventilate if possible. Never use or mix with other cleaners or chemicals. Clean up any spills or drips immediately. Do not use on any surface that can be damaged by acidic materials. Many surfaces are not resistant to acid. **Do not use on PVD finished surfaces.** The pesticide label also includes other important information, including directions for use.

OSHA Hazard Communication Standard: This product meets the §1910.1200 definition of a "Hazardous Chemical".

Superfund Amendments and Reauthorization Act of 1986 Title III (EPCRA) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes	Delayed (Chronic) Health Hazard	No
Fire Hazard	No	Reactive Hazard	No
Sudden Release of Pressure Hazard	No		

Superfund Amendments and Reauthorization Act of 1986 Title III (EPCRA) Section 313

*Chemicals marked with an asterisk in "**3. Composition/Information on Ingredients**" are subject to reporting requirements for Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40CFR Part 372.

Pennsylvania/New Jersey/Massachusetts Right to Know

See "**3. Composition/Information on Ingredients**" for hazardous and top five ingredients over 1% (w/w).

California Proposition 65: This product does not contain a listed substance known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

16. Other information

Date issued: 31. 12. 2014

F302-001 Revision: N/A

Disclaimer: No representation or warranty, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, is made with respect to information concerning the product referred to in this document. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, it is impossible to foresee every health effect or exposure risk incurred by the use of this product. All chemicals present some degree of hazard and should be used with caution. The information and recommendations contained herein are presented in good faith. The user should review this information in conjunction with their knowledge of the application intended to determine the suitability of this product for such purpose. In no event will the supplier be responsible for any damages of any nature whatsoever, resulting from the use, reliance upon, or the misuse of this information. Furthermore, it is the direct responsibility of the user to comply with all applicable regulations governing the use and disposal of this material. **Prepared by:** R&D, Canberra Corporation

A PLASTI-KOTE CO INC -- DO IT BEST RUST COAT ENAMELS, 1244 ENAMEL -- 8010-00N087340

===== Product Identification =====

Product ID:DO IT BEST RUST COAT ENAMELS, 1244 ENAMEL
MSDS Date:05/15/1996
FSC:8010
NIIN:00N087340
MSDS Number: CHJVL
=== Responsible Party ===
Company Name:A PLASTI-KOTE CO INC
Address:1000 LAKE RD
City:MEDINA
State:OH
ZIP:44256
Country:US
Info Phone Num:216-725-4511
Emergency Phone Num:216-725-4511
CAGE:07708

=== Contractor Identification ===

Company Name:TEMPO PRODUCTS CO A PLASTI-KOTE CO INC
Address:1000 LAKE ROAD
Box:City:MEDINA
State:OH
ZIP:44256
Country:US
Phone:330-725-4511
CAGE:07708

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA 313) (CERCLA). VP:186 @ 20C. EVAP RATE:SLOWER
THAN ETHER. FL PT:0F,-18C.

CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 32-40%
OSHA PEL:1000 PPM
ACGIH TLV:750 PPM;1000 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ETHYL ALCOHOL; (ETHANOL). VP:40 @ 20C. EVAP RATE:SLOWER
THAN ETHER. FL PT:0F,-18C.

CAS:64-17-5
RTECS #:KQ6300000
Fraction by Wt: 5-10%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM

Ingred Name:PROPIONIC ACID, 3-ETHOXY-, ETHYL ESTER;
(ETHYL-3-ETHOXYPROPIONATE). VP:0.67 @20C. EVAP RATE:SLOWER/ETHER.
FL PT:0F,-18C.

CAS:763-69-9
RTECS #:UF3325000
Fraction by Wt: 5-10%
OSHA PEL:N/K
ACGIH TLV:50 PPM (MFR)

Ingred Name:ISOPROPYL ALCOHOL (SARA 313). VP:33 @ 20C. EVAP RATE:SLOWER
THAN ETHER. FL PT:0F,-18C.

CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 0-5%
OSHA PEL:400 PPM
ACGIH TLV:400 PPM;500 STEL

Ingred Name:2-BUTANONE; (METHYL ETHYL KETONE) (MEK) (SARA 313)
(CERCLA). VP:70 @ 20C. EVAP RATE:SLOWER THAN ETHER. FL PT:0F,-18C.
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 0-5%
OSHA PEL:200 PPM
ACGIH TLV:200 PPM;300 STEL
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:XYLENE (SARA 313) (CERCLA). VP:5.1 @ 20C. EVAP RATE:SLOWER
THAN ETHER. FL PT:0F,-18C.
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5-10%
OSHA PEL:100 PPM
ACGIH TLV:100 PPM;150 STEL
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:HYDROCARBON PROPELLANT; (PROPANE-ISOBUTANE MIXTURE). EVAP
RATE:FASTER THAN ETHER. FL PT:-100F,-73C.
CAS:68476-86-8
Fraction by Wt: 23%
OSHA PEL:1000 PPM (MFR)
ACGIH TLV:N/K

Ingred Name:OTHER PROT EQUIP:OF AN INDUSTRIAL HYGIENIST.
RTECS #:9999999ZZ

Ingred Name:RESP PROT:(TC23C/EQUIV), OR LEAVE AREA.
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:INHAL:EXCESSIVE INHAL OF VAPS
CAN CAUSE NASAL & RESP IRRIT, DIZZ, WEAK, FATG, NAUS, HDCH, POSS
UNCON & EVEN ASPHY. EYE CONT:CAN CAUSE SEV IRRIT, REDNESS, TEARING,
BLURRED VISION. INGEST:CAN CAUS E GI IRRIT, NAUS, VOMIT, DIARR.
SKIN CONT:CAN CAUSE IRRIT FOR SOME PERSONS. CHRONIC:REPORTS HAVE
ASSOC (EFTS OF OVEREXP)
Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:HLTH HAZ:RPTD & PRLNG OCCUP OVEREXP TO SOLVS
W/PERM BRAIN & NERV SYS DMG. SEV OVEREXP IN LAB ANIMALS HAS ALSO
CAUSED LIVER ABNORMS & DMG TO KIDNEYS, LUNGS & SPLEEN, HEART &
ADRENALS. INTENTIONAL MISUS E BY DELIB CONC & INHALING CONTENTS
MAYBE HARMFUL/FATAL.
Medical Cond Aggravated by Exposure:CAN CAUSE RESPIRATORY &/OR SKIN
REACTION.

===== First Aid Measures =====

First Aid:INHAL:REMOVE INDIVIDUAL TO FRESH AIR. IF BRTHG IS DFCLT,
ADMIN OXYG. IF BRTHG IS STOPPED, GIVE ARTF RESP & SEEK MED HELP.
EYES:FLUSH W/WATER FOR AT LST 15 MINS WHILE HOLDING EYELIDS OPEN.
INGEST:DO NO T INDUCE VOMIT (ASPIR OF MATL INTO LUNGS CAN CAUSE
PNEUMONIC, WHICH CAN BE FATAL). KEEP PERSON WARM, QUIET & GET MED
ATTN/POIS CTL CTR. SKIN:WASH W/SOAP & WATER/VARIOUS HAND CLEANERS &
WASH CLOTHING.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:-100F,-73C

Lower Limits:1%

Extinguishing Media:ALCOHOL FOAM, CO*2, DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH APPRVD SCBA & FULL PROT EQUIP .

WATER SPRAY MAY BE INEFT. WATER MAY BE USED TO COOL CLSD CNTNRS TO
PVNT PRESS BUILD UP & POSS AUTOIGNIT/(SUPDAT)

Unusual Fire/Explosion Hazard:FLAMMABILITY CLASS:OSHA IA. EXTREMELY
FLAMM. LEVEL 3 AEROSOL. CLSD CNTNRS MAY EXPLODE &/OR AUTOIGNITE
WHEN EXPOS TO EXTREME HEAT. VAPS ARE HVR/AIR & MAY(SUPDAT)

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES, VENTILATE
AREA, ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER
ABSORBENT MATERIAL & TRANSFER TO A CLOSED CONTAINER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT PUNCTURE OR INCINERATE. DO NOT
STORE IN AREAS ABOVE 120F, OR IN DIRECT SUNLIGHT, OR NEAR HEAT OR
OPEN FLAMES.

Other Precautions:STORE LARGE QUANTITIES IN BUILDING PROTECTED FOR
STORAGE OF FLAMMABLE LIQUIDS. AS WITH ALL CHEMICALS MINIMIZE
PERSONAL CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR CASUAL/OCCAS USE-TO AVOID BRTHG VAPS/SPRAY
MIST, OPEN WINDOWS & DOORS/USE OTHER MEANS TO ENSURE FRESH AIR
ENTRY DURING APPLICATION & DRYING. IF YOU EXPER EYE WATERING,
HDCH/DIZZ, INCR FRESH AIR, W EAR NIOSH APPRVD RESP PROT (ING 9)

Ventilation:FOR REGULAR/CONTINUOUS USE-PROVIDE SUFFICIENT MECH (GEN)
&/OR LOC EXHST VENT TO MAINTAIN EXPOS BELOW TLV'S IN INGS.

Protective Gloves:CHEMICAL RESISTANT GLOVES (NEOPRENE).

Eye Protection:ANSI APPROVED CHEM WORKERS GOGGS .

Other Protective Equipment:ANSI APPRVD EYE WASH FOUNTAIN & DELUGE
SHOWER . WHERE SPECIAL/UNUSUAL CNDTNS EXIST, SEEK EXPERT ASSISTANCE
(ING 8)

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING WASHROOM.

Supplemental Safety and Health

FIRE FIGHT PROC:EXPLO WHEN EXPOS TO EXTREME HEAT. IF WATER IS USED, FOG
NOZZ ARE PREF. EXPLO HAZ:TRAVEL ALONG GROUND/MAY BE MOVED BY VENT &
IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPKS, HEATERS, SMOKIN G,
ELEC MOTORS/OTHER LOCATIONS DIST FROM MATL HNDLG POINT. FL
PT:0F(-18C) TCC (PROPELLANT = -100F).

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:>133F,>56C

Melt/Freeze Pt:M.P/F.P Text:1500F,816C

Vapor Pres:SEE INGS

Vapor Density:HVR/AIR

Spec Gravity:<1 (H*20=1)

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT TO MODERATE

Appearance and Odor:TYPICAL SOLVENT PAINT.

Percent Volatiles by Volume:80-90

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT W/STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:HEAT, SPARKS & OPEN FLAME.

Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, CARBON

DIOXIDE/CARBON MONOXIDE, VARIOUS HYDROCARBONS, NITROGEN COMPOUNDS,

ETC, WHEN HEATED.

===== Disposal Considerations =====

Waste Disposal Methods: MATERIAL COLLECTED ON ABSORBENT MATERIAL MAY BE
DEPOSITED IN A POSTED TOXIC SUBSTANCE LANDFILL I/A/W LOCAL, STATE &
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.



SAFETY DATA SHEET

Revision Date 23-Mar-2016

Version 2

1. IDENTIFICATION

Product identifier

Product Name FAST ORANGE SMOOTH LOTION 64 FL.OZ

Other means of identification

Product Code 23217

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Hand Cleaner or Soap - Heavy Duty

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufactured and Distributed by:

ITW Permatex
6875 Parkland Blvd.
Solon, OH 44139 USA

May Also Be Distributed by:

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994

Company Phone Number 1-87-Permatex
(877) 376-2839

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Label elements

Emergency Overview

The product contains no substances which at their given concentration, are considered to be hazardous to health

Appearance White

Physical state Lotion

Odor Citrus

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Repeated or prolonged skin contact may cause allergic reactions with susceptible persons

Unknown acute toxicity

6.4155 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
WATER	7732-18-5	60 - 100	*
ETHOXYLATED C11-C16 ALCOHOL	127036-24-2	1 - 5	*
D-LIMONENE	5989-27-5	0.1-1.0	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	None under normal use conditions.
Inhalation	None under normal use conditions.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms	See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

None in particular.

Explosion data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions, protective equipment and emergency procedures**

Personal precautions Avoid contact with eyes.

Environmental precautions

Environmental precautions Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with eyes.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep from freezing.

Incompatible materials None known

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure Guidelines****Appropriate engineering controls**

Engineering Controls Eyewash stations

Individual protection measures, such as personal protective equipment

Eye/face protection No special technical protective measures are necessary.

Skin and body protection None under normal use conditions.

Respiratory protection None under normal use conditions.

General Hygiene Considerations Avoid contact with eyes.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state Lotion

Appearance	White
Odor	Citrus
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	6.0-8.0	
Melting point / freezing point	No information available	
Boiling point / boiling range	> 100 °C / >212 °F	
Flash point	> 95 °C / > 203 °F	
Evaporation rate	< 1	Butyl acetate = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	>1	Air = 1
Relative density	0.96	
Water solubility	Soluble in water	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	<1
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Keep from freezing.

Incompatible materials

None known

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	None under normal use conditions.

Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact

None under normal use conditions. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

Ingestion

Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
WATER 7732-18-5	> 90 mL/kg (Rat)	-	-
D-LIMONENE 5989-27-5	= 4400 mg/kg (Rat)	> 5 g/kg (Rabbit)	-

Information on toxicological effects**Symptoms**

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Sensitization**

No information available.

Germ cell mutagenicity

No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
D-LIMONENE 5989-27-5	-	Group 3	-	X

IARC (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 405680 mg/kg

ATEmix (dermal) 461460 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

6.4372 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
D-LIMONENE 5989-27-5	-	35: 96 h Oncorhynchus mykiss mg/L LC50 0.619 - 0.796: 96 h Pimephales promelas mg/L LC50 flow-through	-

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods**Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
D-LIMONENE 5989-27-5	Toxic

14. TRANSPORT INFORMATION

DOT

Proper shipping name: Not regulated

IATA

Proper shipping name: Not regulated

IMDG

Proper shipping name: Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Not Listed.
IECSC	Complies
KECL	Not Listed.
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
LANOLIN 8006-54-0	-	-	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 1	Flammability 1	Instability 0	-
<u>HMIS</u>	Health hazards 1	Flammability 1	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 23-Mar-2016

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Safety Data Sheet

Part 1: Identification of the Substance/Mixture and of the Company

Product Name: Forney Nozzle Gel

Forney SKUs: 37031

Product Use Description: Protects against weld spatter build up on M.I.G. gun nozzles and welding components.

Trade Name: Forney Nozzle Gel

Manufacturers Name:

Forney Industries, Inc.

2057 Vermont Drive

Fort Collins, CO 80525

Phone: 1-800-521-6038

Email: customerservice@forneyind.com

Emergency Response Phone: 1-800-535-5053

International Emergency Response Phone: 352-323-3500

Part 2: Hazards Identification

Emergency Overview

No Hazardous ingredients as defined by OSHA 29 CFR 1910.1200 or Canadian Hazardous Products Act (Bill C70) . Appearance: gel; blue in color

Toxicological Data on Ingredients: Petrolatum, white LD50: Not Available LC50: Not Available.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion

Eye contact

Can cause mild eye irritation.

Skin contact

May cause mild skin irritation.

Ingestion

No not ingest. This material is inert and non-toxic.

Inhalation

Inhalation is unlikely at ambient temperatures and is not expected to present an inhalation hazard. Caution should be taken to prevent aerosolization or misting of this product.

Potential Acute Health Effects:

CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: Not available. Repeated or prolonged exposure is not known to aggravate medical condition.

Part 3: Composition / Information on Ingredients

Hazardous Components	CAS No.	% by weight
Petrolatum, white	8009-03-8	<=100%

Part 4: First Aid Measures

Eyes

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin

Wash with soap and water. Cover the irritated skin with an emollient. Get medical attention if irritation develops.

Ingestion

Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Part 5: Fire Fighting Measures

Flammability of the Product: May be combustible at high temperature.

Auto-Ignition Temperature: Not available.

Flash Point: CLOSED CUP: 185°C (365°F).

Flammable Limits: Not available.

Products of Combustion: Not available.

Fire Hazards in Presence of Various Substances: Slight flammable to flammable in presence of heat.

Explosion Hazards in Presence of Various Substances: Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions: SMALL FIRE: Use DRY chemical powder or CO2. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.

Special Remarks on Fire Hazards: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Special Remarks on Explosion Hazards: None

Part 6: Accidental Release Measures

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Use tools to put the spilled solid in a disposal container. Finish cleaning by spreading water on the contaminated surface and dispose of according to local and regional authority requirements.

Methods for cleaning up

Keep in suitable, closed containers for disposal. Use shovel to put the material into disposal container.

Other Information

Comply with all applicable federal, state and local regulations.

Part 7: Handling and Storage

Precautions

Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material.

Storage

Keep container tightly closed. Store in a cool, dry, ventilated area.

Part 8: Exposure Controls / Personal Protection

Engineering Controls:

Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

Personal Protection

Safety glasses. Lab coat, dust respirator. Be sure to use an approved/certified respirator or equivalent. Gloves

Personal Protection in Case of Large Spill

Wear appropriate chemical impervious clothing and boots whenever there is potential for skin contact with product. Launder clothing before reuse. Splash goggles. Full suit. Dust Respirator. Gloves.

Exposure Limits

Not Available

Part 9: Physical and Chemical Properties

Physical State :	Semi-solid
Odor and Appearance:	Blue; odorless
Specific Gravity (H2O=1):	0.82 - 0.865 @ 25°C.
pH:	Not Available
Boiling Point:	Not Available
Melting Point:	38°C (100.4°F)
Vapor Pressure:	Not applicable
Vapor Density:	Not Available
Volatility:	Not Available
Odor Threshold:	Not Available
Solubility:	Soluble in diethyl ether. Insoluble in cold water, hot water.
VOC's	0%

Part 10: Stability and Reactivity

Stability

Stable

Conditions to avoid

Excessive heat, incompatible materials.

Incompatible products

Oxidizing agents

Polymerization

Will not occur.

Part 11. Toxicological Information

Routes of Entry: Ingestion

Toxicity to Animals: LD50: Not Available. LC50: Not Available.

Chronic Effect on Humans: Not Available.

Other Toxic Effects on Humans: slight hazardous in case of skin contact (irritant), of ingestion, of inhalation.

Part 12. Ecological Information

Environmental Effects: This product has not been tested for environmental effects.

Important Environmental Characteristics: Not Available.

Aquatic Toxicity: Not Available.

Part 13. Disposal Considerations

Waste disposal methods

If containers are to be disposed of follow local, state and federal laws for proper disposal.

Part 14. Transport Information

DOT HM-181 Shipping Information

Proper Shipping Name: None

Hazardous Class or Division: None

UN Number: None

Packaging Group: None

Label(s) Required: None

U. S. Department of Transportation (DOT)

Highway/Rail (Bulk): Not regulated

Highway/Rail (Non-Bulk): Not regulated

International Information

Vessel (IMDG): Not regulated

Part 15. Regulatory Information

Federal and State Regulations: TSCA 8(b) Inventory: Petrolatum, white. Components of this material comply with US TSCA requirements.

Other Regulations: EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

WHMIS: (Canada): Not controlled under WHMIS.

HMIS (U.S.A.)

Health Hazard: 1

Fire Hazard: 1

Reactivity: 0

Personal Protection: E

National Fire Protection Association (U.S.A.):

Health: 2

Flammability: 1

Reactivity: 0

Specific Hazard:

Part 15 Continued:**CERCLA/SARA- Section 302 Extremely Hazardous Substances and TPQs (in pounds):**

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

CERCLA/SARA-Section 311/312 (Title III Hazard Categories)

Acute Health: No

Chronic Health: No

Fire Hazard: No

Pressure Hazard: No

Reactive Hazard: No

CERCLA/SARA-Section 313 and 40 CFR 372:

This material does not contain any chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372.

California Proposition 65: This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm.

Part 16. Other Information

Forney Industries, Inc.

2057 Vermont Drive

Fort Collins, CO 80525

Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date of the Safety Data sheet was prepared. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices as specified on the label copy.

SAFETY DATA SHEET

Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

**GOO
GONE.**

Product: Goo Gone- 2028, 2030, 2030A, 2050, 2053, 2082, 2086, 2087, 2089, 2090, 2092, 2035CLIP, 2095CLIP, 2129, 2139B, 2166D, 2221D

Revision Date: 28-Nov-2017

SECTION 1 – IDENTIFICATION

Product Identifier

Product Name: Goo Gone

Product Code: 2028, 2030, 2030A, 2050, 2053, 2082, 2086, 2087, 2089, 2090, 2092, 2035CLIP, 2095CLIP, 2129, 2139B, 2166D, 2221D

Recommended Use of the Chemical and Restrictions for Use

Recommended Use: Cleaner

Restrictions for Use: Use only as directed.

Details of the Supplier

Manufacturer: Goo Gone
755 Tri-State Parkway
Gurnee, IL 60031
855-364-8135

Emergency Phone Number

24-Hour Number: 1-800-535-5053

International: 1-352-323-3500

SECTION 2 – HAZARDS IDENTIFICATION

Classification

Hazard Class	Category
Flammable Liquid	4
Skin Sensitization	1
Aspiration Hazard	1

Label Elements

Hazard Symbols(s):



Signal Word(s): Danger

Hazard Statement(s): Combustible liquid. May cause an allergic skin reaction. May be fatal if swallowed and enters airways.

Precautionary Statement(s): Keep away from flames and hot surfaces. No smoking. Avoid breathing fume/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

Other Hazards

None known

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Wt %
Petroleum distillates, hydrotreated light	64742-47-8	60-100
D-Limonene	5989-27-5	1-5
Orange, sweet, extract	8028-48-6	0.5-1.5

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SAFETY DATA SHEET

Conforms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

**GOO
GONE.**

Product: Goo Gone- 2028, 2030, 2030A, 2050, 2053, 2082, 2086, 2087, 2089, 2090, 2092, 2035CLIP, 2095CLIP, 2129, 2139B, 2166D, 2221D

Revision Date: 28-Nov-2017

SECTION 4 – FIRST AID MEASURES

First Aid Measures

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Eye Contact: Rinse immediately with water for at least 15 minutes. Remove contact lenses, if worn. If irritation persists, seek medical attention immediately.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

Skin: In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash with soap and water. If irritation persists, seek medical attention.

Most Important Symptoms and Effects (Acute and Delayed)

Inhalation: May cause respiratory track irritation.

Eye Contact: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Skin: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause sensitization by skin contact.

Indication of any Immediate Medical Attention and Special Treatment Needed

Note to Physician: Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

Extinguishing Media

Suitable: Treat for surrounding material.

Unsuitable: None known.

Specific Hazards Arising from Chemical

Products of combustion include but are not limited to: oxides of carbon.

Protective Equipment and Precautions for Firefighters

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Personal Precautions: Use personal protective equipment as required.

Environmental Precautions: See Section 12 for ecological information.

Methods and Material for Containment and Cleaning Up

Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). For cleaning up scoop up material and place in a disposal container. Provide ventilation.

SECTION 7 – HANDLING AND STORAGE

Precautions for Safe Handling

Handling: Keep away from sources of ignition. No smoking. Avoid contact with skin and eyes. Avoid breathing fume/mist/vapors/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

General Hygiene Advice: Launder contaminated clothing before use. Wash hands before eating, drinking, or smoking.

SAFETY DATA SHEET

Conforms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

**GOO
GONE.**

Product: Goo Gone- 2028, 2030, 2030A, 2050, 2053, 2082, 2086, 2087, 2089, 2090, 2092, 2035CLIP, 2095CLIP, 2129, 2139B, 2166D, 2221D

Revision Date: 28-Nov-2017

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions: Keep container closed when not in use. Store in a dry, cool, and well-ventilated area. Keep out of reach of children.

Incompatible Materials: None known.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Exposure Guidelines:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light (64742-47-8)	200 mg/m ³	100 ppm	Not available
D-Limonene (5989-27-5)	Not available	Not available	Not available
Orange, sweet, extract (8028-48-6)	Not available	Not available	Not available

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Individual Protection Measures

Respiratory Protection: None required under normal use conditions. In case of insufficient ventilation, wear suitable respiratory equipment.

Skin and Body Protection: Wear suitable protective clothing.

Eye/Face Protection: Safety glasses or goggles are recommended when using product.

General Work/Hygienic Practices: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow clear liquid

Odor: Citrus

Odor threshold: Not determined

pH: Not determined

Melting point/freezing point: Not determined

Initial boiling point and boiling range: Not determined

Flash point: 85°C (185°F) TCC

Evaporation rate: Not determined

Flammability (solid, gas): Flammable

Upper/lower flammability or explosive limits: Not determined

Vapor pressure: Not determined

Vapor density: Not determined

Relative density: 0.80

Solubility(ies): Not determined

Partition coefficient (n-octanol/water): Not determined

Auto-ignition temperature: Not determined

Decomposition temperature: Not determined

Viscosity: Not determined

SECTION 10 – STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions.

Chemical stability: Stable under recommended storage conditions.

SAFETY DATA SHEET

Conforms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

**GOO
GONE.**

Product: Goo Gone- 2028, 2030, 2030A, 2050, 2053, 2082, 2086, 2087, 2089, 2090, 2092, 2035CLIP, 2095CLIP, 2129, 2139B, 2166D, 2221D

Revision Date: 28-Nov-2017

Possibility of hazardous reactions: None under normal use.

Conditions to avoid: Heat. Incompatible materials. Sources of ignition.

Incompatible materials: None known.

Hazardous decomposition products: May include and are not limited to: oxides of carbon.

SECTION 11 - TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Likely Routes of Exposure: Inhalation, skin contact, eye contact, ingestion

Information Related to Physical, Chemical, and Toxicological Effects

See section 4 of this SDS.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-term Exposure

Carcinogenicity: NTP: No IARC: No OSHA: No

Numerical Measures of Toxicity

Product	
ATE (oral)	>2000 mg/kg, rat
ATE (dermal)	>2000 mg/kg, rabbit
ATE (inhalation)	Not available

Component Information:

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates, hydrotreated light (64742-47-8)	>5000 mg/kg, rat	>2000 mg/kg, rabbit	>5.2 mg/l/4h, rat
D-Limonene (5989-27-5)	4400 mg/kg, rat	>5000 mg/kg, rabbit	Not available
Orange, sweet, extract (8028-48-6)	>5000 mg/kg, rat	>5000 mg/kg, rabbit	Not available

SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: Not established

Persistence and degradability: Not established

Bioaccumulative potential: Not established

Mobility in soil: No additional information available

Other adverse effects: No additional information available.

SECTION 13 – DISPOSAL CONSIDERATIONS

See section 8 of this SDS for exposure controls and personal protection.

Dispose of the product and container in accordance with all applicable local, state, and federal regulations.

SECTION 14 – TRANSPORT INFORMATION

Note: Classification changes based on quantity, packaging, and method of shipment. See current shipping paper for most up to date shipping information.

DOT (Ground): Not Regulated- See 49 CFR 173.150(f)(2) as the product is not bulk packaged.

IATA (Air): Not Regulated

IMDG (Vessel): Not Regulated

SECTION 15 – REGULATORY INFORMATION

All ingredients in this product are listed or are excluded from listing on the US Toxic Substances Act (TSCA) Chemical Substance Inventory.

SAFETY DATA SHEET

Confirms to OSHA Hazard Communication Standard (CFR 29 1910.1200) HazCom 2012

**GOO
GONE.**

Product: Goo Gone- 2028, 2030, 2030A, 2050, 2053, 2082, 2086, 2087, 2089, 2090, 2092, 2035CLIP, 2095CLIP, 2129, 2139B, 2166D, 2221D

Revision Date: 28-Nov-2017

This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration (OSHA) applicable to this Safety Data Sheet differ from the requirements of the CPSC and as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

SECTION 16 – OTHER INFORMATION

Issue Date: 23-Aug-2017

Revision Date: 28-Nov-2017

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designed and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Material Safety Data Sheet

[Home] [Manufacturer] [Part Number] [NSN] [Help]

SECTION I - Material Identity

Item Name..... GREAT STUFF (12 OZ) FOAM INSULATION
Part Number/Trade Name..... GREAT STUFF (12 OZ) FOAM INSULATION
National Stock Number..... 8030011922492
CAGE Code..... 54577
Part Number Indicator..... A
MSDS Number..... 192148
HAZ Code..... C

SECTION II - Manufacturer's Information

Manufacturer Name..... DOW CHEMICAL COMPANY
City..... MIDLAND
State..... MI
Country..... US
Zip Code..... 48674
Emergency Phone..... 800-424-9300
Information Phone..... 800-366-4740

MSDS Preparer's Information

Date MSDS Prepared/Revised..... 12APR20
Active Indicator..... N

Alternate Vendors

SECTION III - Physical/Chemical Characteristics

Hazard Storage Compatibility Code..... NR
NRC License Number..... NR
Net Propellant Weight (Ammo)..... NR
Appearance/Odor..... OFF WHITE, STICKY MATERIAL WITH A MILD ODOR
Boiling Point..... NR
Melting Point..... NR
Vapor Pressure..... 4210
Specific Gravity..... 1.1
Decomposition Temperature..... NR
Evaporation Rate..... NR
Solubility in Water..... NR
Percent Volatiles by Volume..... NR
Chemical pH..... NR

Corrosion Rate..... NR
Container Type..... F
Container Pressure Code..... 1
Temperature Code..... 4
Product State Code..... L

SECTION IV - Fire and Explosion Hazard Data

Flash Point..... 400
Flash Point Method..... PMCC
Lower Explosion Limit..... NA
Upper Explosion Limit..... NA
Extinguishing Media..... CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER
FOG OR FINE SPRAY. ALCOHOL RESISTANT FOAMS
(ATC TYPE) ARE PREFERRED IF AVAILABLE.
GENERAL PURPOSE SYNTHETIC FOAMS (INCLUDING
AFFF) OR PROTEIN FOAMS MAY FUNCTION, BUT
MUCH LESS EFFECTIVE. DO NOT USE DIRECT
WATER STREAM. MAY SPREAD FIRE.
Special Fire Fighting Procedures..... KEEP PEOPLE AWAY. ISOLATE FIRE AREA AND
DENY UNNECESSARY ENTRY. STAY UPWIND. KEEP
OUT OF LOW AREAS WHERE GASES (FUMES) CAN
ACCUMULATE. WATER IS NOT RECOMMENDED BUT
MAY BE APPLIED IN VERY LARGE QUANTITIES AS
A FINE SPRAY WHEN OTHER EXTINGUISHING
AGENTS ARE NOT AVAILABLE. CONTAIN FIRE
WATER RUN-OFF IF POSSIBLE. DO NOT USE
DIRECT WATER STREAM. MAY SPREAD FIRE.
FIGHT FIRE FROM PROTECTED LOCATION OR SAFE
DISTANCE. CONSIDER USE OF UNMANNED HOSE
HOLDER OR MONITOR NOZZLES. USE WATER SPRAY
TO COOL FIRE.
Unusual Fire/Explosion Hazards..... WEAR POSITIVE-PRESSURE SCBA AND PROTECTIVE
FIRE FIGHTING CLOTHING (INCLUDES FIRE
FIGHTING HELMET, COAT, PANTS, BOOTS, AND
GLOVES). AVOID CONTACT WITH THIS MATERIAL
DURING FIRE FIGHTING OPERATIONS. IF
CONTACT IS LIKELY, CHANGE TO FULL CHEMICAL
RESISTANT CLOTHING WITH SCBA.

SECTION V - Reactivity Data

Stability..... YES
Stability Conditions to Avoid..... AVOID TEMPERATURES ABOVE 105F/41C AND
BELOW 75F/24C. CAN REACT WITH ITSELF AT
TEMPERATURES ABOVE 320F/160C.
Materials to Avoid..... AVOID CONTACT WITH ACIDS, WATER, ALCOHOLS,
AMINES, AMMONIA, BASES, MOIST AIR, AND
STRONG OXIDIZERS. AVOID CONTACT WITH
METALS SUCH AS ALUMINUM, BRASS, COPPER,
GALVANIZED METALS, TIN, ZINC.
Hazardous Decomposition Products..... GASES ARE RELEASED DURING DECOMPOSITION
Hazardous Polymerization..... NO

SECTION VI - Health Hazard Data

Route of Entry: Skin..... YES
Route of Entry: Ingestion..... YES
Route of Entry: Inhalation..... YES
Health Hazards - Acute and Chronic..... [EYE] MAY CAUSE MODERATE IRRITATION. MAY CAUSE VERY SLIGHT TRANSIENT CORNEAL INJURY. [SKIN] PROLONGED OR REPEATED EXPOSURE MAY CAUSE SLIGHT SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION IN SUSCEPTIBLE INDIVIDUALS. [INGEST] SINGLE DOSE ORAL TOXICITY IS CONSIDERED TO BE LOW. NO HAZARDS ANTICIPATED FROM SWALLOWING SMALL AMOUNTS INCIDENTAL TO NORMAL HANDLING OPERATIONS. [INHAL] VAPORS ARE MINIMAL DUE TO LOW VAPOR PRESSURE. EXCESSIVE EXPOSURE MAY CAUSE IRRITATION TO UPPER RESPIRATORY TRACT/LUNGS.
Symptoms of Overexposure..... SEE ABOVE
Medical Cond. Aggravated by Exposure.... NR
Emergency/First Aid Procedures..... [EYE] IRRIGATE WITH FLOWING WATER IMMEDIATELY AND CONTINUOUSLY FOR 15 MIN. CONSULT MED PERSONNEL. [SKIN] REMOVE MATERIAL FROM SKIN IMMEDIATELY BY WASHING WITH SOAP AND PLENTY OF WATER. REMOVE CONTAMINATED CLOTHING AND SHOES WHILE WASHING. SEEK MED ATTENTION. [INGEST] SEEK MED ATTENTION. DO NOT INDUCE VOMITING UNLESS DIRECTED TO DO SO BY MEDICAL PERSONNEL. [INHAL] REMOVE TO FRESH AIR. GIVE OXYGEN OR CPR AS NEEDED. CALL A PHYSICIAN OR TRANSPORT TO A MEDICAL FACILITY.

SECTION VII - Precautions for Safe Handling and Use

Steps if Material Released/Spilled..... AVOID CONTACT. BARRICADE AREA. CLEAR NON EMERGENCY PERSONNEL FROM AREA. KEEP UPWIND OF SPILL. VENTILATE AREA OF LEAK OR SPILL. THE AREA MUST BE EVACUATED AND REENTERED BY PERSONS EQUIPPED FOR DECONTAMINATION. USE APPROPRIATE SAFETY EQUIPMENT. VENTILATE AREA. USE FOAM TO SUPPRESS VAPORS.
Waste Disposal Method..... DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. ALL DISPOSAL METHODS MUST BE IN COMPLIANCE WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.
Handling and Storage Precautions..... STORE IN A DRY PLACE BETWEEN 32F AND 90F (0-32C). KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL ABUSE. AVOID DIRECT SUNLIGHT. DO NOT INCINERATE AEROSOL CAN.
Other Precautions..... AVOID CONTACT OF THIS PRODUCT WITH WATER AT ALL TIMES DURING HANDLING AND STORAGE.

USE ONLY WITH ADEQUATE VENTILATION. KEEP EQUIPMENT CLEAN. USE DISPOSABLE CONTAINERS AND TOOLS WHERE POSSIBLE. DO NOT EAT, DRINK, OR SMOKE IN WORKING AREA. REFER TO EXPOSURE CONTROLS/PERSONAL PROTECTION SECTION.

SECTION VIII - Control Measures

Respiratory Protection..... WHEN NEEDED USE POSITIVE PRESSURE AIR SUPPLYING RESPIRATOR
Ventilation..... USE ONLY WITH ADEQUATE VENTILATION. PROVIDE GENERAL AND OR LOCAL EXHAUST VENTILATION TO CONTROL AIRBORNE LEVELS
Protective Gloves..... IMPERVIOUS
Eye Protection..... CHEMICAL SAFETY GOGGLES
Other Protective Equipment..... BOOTS, APRON OR FULL BODY SUIT.
Work Hygenic Practices..... WASH SKIN WITH SOAP AND WATER AND LAUNDER CLOTHING BEFORE REUSE
Supplemental Health/Safety Data..... NR

SECTION IX - Label Data

Protect Eye..... NO
Protect Skin..... NO
Protect Respiratory..... NO
Chronic Indicator..... UNKNOWN
Contact Code..... UNKNOWN
Fire Code..... UNKNOWN
Health Code..... UNKNOWN
React Code..... UNKNOWN

SECTION X - Transportation Data

Container Quantity..... 12
Unit of Measure..... OZN

SECTION XI - Site Specific/Reporting Information

Volatile Organic Compounds (P/G)..... 1.3193
Volatile Organic Compounds (G/L)..... 158.1034

SECTION XII - Ingredients/Identity Information

Ingredient #..... 01
Ingredient Name..... ISOCYANIC ACID, POLYMETHYLENEPOLYPHENYLENE ESTER (5-10%)
CAS Number..... 9016879
Proprietary..... NO
Percent..... 10

Ingredient #..... 02
Ingredient Name..... BENZENE, 1,1'-METHYLENEBIS[4-ISOCYANATO-
(40-50%)
CAS Number..... 101688
Proprietary..... NO
Percent..... 50
Ingredient #..... 03
Ingredient Name..... PROPANE, 2-METHYL- (10-30%)
CAS Number..... 75285
Proprietary..... NO
Percent..... 30
Ingredient #..... 04
Ingredient Name..... PROPANE (10-30%)
CAS Number..... 74986
Proprietary..... NO
Percent..... 30
Ingredient #..... 05
Ingredient Name..... *PREPOLYMER OF MDI AND POLYETHER POLYOL
(40-70%)
CAS Number..... 59075671
Proprietary..... NO
Percent..... 70

NOTICE: For additional information, contact BIOENVIRONMENTAL

HMMS Intranet - 24 Feb 2005 19:42 - web_msd.display - Visit the Official HMMS Website at www.hmms.com

Latest revision date: 12/04/2015
Version: 1.3

United States Safety Data Sheet

Swiss Farms Products Inc.
3993 Howard Hughes Parkway
Las Vegas, Nevada 89169-6754
United States

24 h. EMERGENCY TELEPHONE NUMBER
CHEMTREC (U.S.) 1-800-424-9300
CHEMTREC (International) 1-703-527-3887
Non-Emergency Calls
1-937-644-0011

Green Light Many Purpose Dust

Section 1. Identification

GHS product identifier : Green Light Many Purpose Dust
Product type : Pesticide
SDS # : 320000004551
EPA Registration Number: : 85827-8

Relevant identified uses of the substance or mixture and uses advised against

Use only in accordance with label directions.

Section 2. Hazards identification

This product is regulated by the Environmental Protection Agency (EPA) for label precautionary text see Section 15.

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

Classification of the substance or mixture : Not classified.

GHS label elements

Signal word : None

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention : Not applicable.

*Report
version.Re
port*

Version: version

Date of issue/Date of revision: Validity date***.

Date of previous issue: 10/08/2015

Response	:	Not applicable.
Storage	:	Not applicable.
Disposal	:	Not applicable.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Not available.
Other means of identification	:	Not available.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
Inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
Skin contact	:	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
Ingestion	:	Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact	:	No known significant effects or critical hazards.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	:	No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact	:	No specific data.

Report
version.Re
port

Version: version

Date of issue/Date of revision: Validity date***.

Date of previous issue: 10/08/2015

Inhalation	:	No specific data.
Skin contact	:	No specific data.
Ingestion	:	No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	:	No specific treatment.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	:	None known.
Specific hazards arising from the chemical	:	No specific fire or explosion hazard.
Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Report
version.Re
port

Version: version

Date of issue/Date of revision: Validity date***.

Date of previous issue: 10/08/2015

- Environmental precautions** :
- Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Spill** :
- Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** :
- Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** :
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** :
- Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Occupational exposure limits

None.

- Appropriate engineering controls** :
- Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- Environmental exposure controls** :
- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** :
- Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end

Report
version.Re
port

Version: version

Date of issue/Date of revision: Validity date***.

Date of previous issue: 10/08/2015

Eye/face protection	of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
	: Protective eyewear is not required, but may be used in situations where contact is expected.
<u>Skin protection</u>	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	: Wear long-sleeved shirt, long pants, shoes with socks., Remove and wash contaminated clothing before reuse.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Appearance

Physical state	: solid [Fine powder]
Color	: White to off-white
Odor	: Faint odor.
Odor threshold	: Not available.
pH	: Not available.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: Not available.
	: Upper: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: Not available.
Solubility	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.

Report
version.Re
port

Version: version

Date of issue/Date of revision: Validity date***.

Date of previous issue: 10/08/2015

Viscosity : **Dynamic:** Not available.
Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.
Chemical stability : The product is stable.
Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid : No specific data.
Incompatible materials : No specific data.
Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
	LD50 Oral	Rat	> 5,000 mg/kg	-
	LC50 Inhalation	Rat	> 5 mg/l	4 h
	LD50 Dermal	Rat	> 5,000 mg/kg	-

Conclusion/Summary : No known significant effects or critical hazards.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
	Eyes - Redness of the conjunctivae	Rabbit	1.0		-
	Skin - Erythema/Es char	Rabbit	1.0		-

Conclusion/Summary

Skin : Slight
Eyes : Minimal
Respiratory : May cause respiratory irritation

Sensitization

Product/ingredient name	Route of exposure	Species	Result

Report
 version.Re
 port

Version: version

Date of issue/Date of revision: Validity date***.

Date of previous issue: 10/08/2015

	Skin	Guinea pig	Not sensitizing

Conclusion/Summary

Skin : Not sensitizing
Respiratory : Not available.

Mutagenicity

Conclusion/Summary : No known significant effects or critical hazards.

Carcinogenicity

Conclusion/Summary : No known significant effects or critical hazards.

Reproductive toxicity

Conclusion/Summary : No known significant effects or critical hazards.

Teratogenicity

Conclusion/Summary : No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential chronic health effects

Conclusion/Summary : No known significant effects or critical hazards.

General : No known significant effects or critical hazards.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Teratogenicity : No known significant effects or critical hazards.
Developmental effects : No known significant effects or critical hazards.
Fertility effects : No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity

Conclusion/Summary : Not available.

Report
version.Re
port

Version: version

Date of issue/Date of revision: Validity date***.

Date of previous issue: 10/08/2015

Persistence and degradability

Conclusion/Summary : No known significant effects or critical hazards.

Mobility in soil

Soil/water partition coefficient (KOC) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

<u>Regulatory information</u>	<u>UN no.</u>	<u>Proper shipping name</u>	<u>Class</u>	<u>PG*</u>	<u>Note</u>
DOT		Not Regulated			
IATA (C)	3077	Environmentally hazardous substance, solid, n.o.s. (deltamethrin (ISO))	9	(, III)	
IATA (P)	3077	Environmentally hazardous substance, solid, n.o.s. (deltamethrin (ISO))	9	(, III)	
IMDG	3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.	9	(, III)	

PG* : Packing group

Section 15. Regulatory information

Precautionary statements

Report
version.Re
port

Version: version **Date of issue/Date of revision:** Validity date***. **Date of previous issue:** 10/08/2015

Signal word : CAUTION!
Emergency Overview : Keep out of reach of children.
 Harmful if absorbed through the skin.
 Avoid contact with skin, eyes or clothing.
 Wash thoroughly with soap and water after handling and before eating,
 drinking, chewing gum, or using tobacco.

U.S. Federal regulations : **United States inventory (TSCA 8b):**
 Not determined.

State regulations

California Prop. 65
 Not available.


International lists

National inventory

Australia : Not determined.
Canada : Not determined.
China : Not determined.
Europe : Not determined.
Japan : Not determined.
Malaysia : Not determined.
New Zealand : Not determined.
Philippines : Not determined.
Republic of Korea : Not determined.
Taiwan : Not determined.

Section 16. Other information

National Fire Protection Association (U.S.A.):



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.
 Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity

Report
 version.Re
 port
Version: version **Date of issue/Date of revision:** Validity date***. **Date of previous issue:** 10/08/2015

hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
Not classified.	

History

Date of issue/Date of revision : Validity date***.
Version : 1.3

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Report
version.Re
port
Version: *version* **Date of issue/Date of revision:** *Validity date***.* **Date of previous issue:** *10/08/2015*

1. Identification

Product identifier	Gunk Engine Cleaner & Degrease - Multi Surface		
Other means of identification			
SDS number	EBT32		
Part No.	EBT32, EBT32ES, EBT-1G		
Tariff code	3402.20.5100		
Recommended use	Cleaner Degreaser		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer			
Company name	RSC Chemical Solutions		
Address	600 Radiator Road Indian Trail, NC 28079 United States		
Telephone	Customer Service:	(704) 821-7643	
	Technical:	(704) 684-1811	
Website	www.rscbrands.com		
E-mail	sds@rscbrands.com		
Emergency phone number	Emergency Telephone:	(303) 623-5716	
	Emergency Contact:	RMPDC (877-740-5015)	

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear eye protection/face protection. Wear protective gloves.
Response	If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

2.65% of the mixture consists of component(s) of unknown acute oral toxicity. 3.77% of the mixture consists of component(s) of unknown acute dermal toxicity. 5.95% of the mixture consists of component(s) of unknown acute inhalation toxicity. 9% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 9% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
2-(2-butoxyéthoxy) Éthanol		112-34-5	5 - < 10
Alcohols, C12-16, Ethoxylated (>1 <2.5 Mol Eo)		68551-12-2	1 - < 3
Alcohols, C9-11, ethoxylated		68439-46-3	1 - < 3
Sodium Carbonate (soda Ash)		497-19-8	< 0.3
Tetrasodium Ethylenediaminetetraacetate		64-02-8	< 0.3
Soda, Caustic		1310-73-2	< 0.1
Sodium Chloride		7647-14-5	< 0.1
Other components below reportable levels			90 - 100

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures**Inhalation**

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures**Suitable extinguishing media**

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Do not get this material in contact with eyes. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Soda, Caustic (CAS 1310-73-2)	PEL	2 mg/m3

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)	TWA	10 ppm	Inhalable fraction and vapor.
Soda, Caustic (CAS 1310-73-2)	Ceiling	2 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Soda, Caustic (CAS 1310-73-2)	Ceiling	2 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear safety glasses with side shields (or goggles) or a face shield.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded. Dust mask.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance	Clear. Liquid
Physical state	Liquid.
Form	Liquid.
Color	Light yellow.
Odor	Citrus
Odor threshold	Not available.
pH	8.3
Melting point/freezing point	-90.58 °F (-68.1 °C) estimated / 32 °F (0 °C)
Initial boiling point and boiling range	446.72 °F (230.4 °C) estimated
Flash point	No Flash Point
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	0.002 hPa estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	442 °F (227.78 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	8.42 lbs/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	95.09 % estimated
Specific gravity	1.01
VOC	6 % estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.

Skin contact	Causes skin irritation. May cause an allergic skin reaction.	
Eye contact	Causes serious eye damage.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.	
Information on toxicological effects		
Acute toxicity	Not known.	
Components	Species	Test Results
2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	2700 mg/kg
Oral		
LD50	Rat	4500 mg/kg
Sodium Carbonate (soda Ash) (CAS 497-19-8)		
<u>Acute</u>		
Oral		
LD50	Rat	4090 mg/kg
Sodium Chloride (CAS 7647-14-5)		
<u>Acute</u>		
Oral		
LD50	Rat	3000 mg/kg
* Estimates for product may be based on additional component data not shown.		
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	Not classifiable as to carcinogenicity to humans.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Not listed.		
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful.	
12. Ecological information		
Ecotoxicity	Harmful to aquatic life with long lasting effects.	

Components	Species		Test Results
2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	1300 mg/l, 96 hours
Alcohols, C9-11, ethoxylated (CAS 68439-46-3)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	2.9 - 8.5 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	6 - 12 mg/l, 96 hours
Soda, Caustic (CAS 1310-73-2)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	34.59 - 47.13 mg/l, 48 hours
Fish	LC50	Western mosquitofish (Gambusia affinis)	125 mg/l, 96 hours
Sodium Carbonate (soda Ash) (CAS 497-19-8)			
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	156.6 - 298.9 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	300 mg/l, 96 hours
Sodium Chloride (CAS 7647-14-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	340.7 - 469.2 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	6020 - 7070 mg/l, 96 hours
Tetrasodium Ethylenediaminetetraacetate (CAS 64-02-8)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	472 - 500 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-(2-butoxyéthoxy) Éthanol 0.56

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC Code

Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5) Listed.

Soda, Caustic (CAS 1310-73-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
2-(2-butoxyéthoxy) Éthanol	112-34-5	5 - < 10

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

2-(2-butoxyéthoxy) Éthanol (CAS 112-34-5)

Soda, Caustic (CAS 1310-73-2)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-28-2015
Revision date	05-10-2017
Version #	04
HMIS® ratings	Health: 3 Flammability: 0 Physical hazard: 0

NFPA ratings	Health: 3 Flammability: 0 Instability: 0

NFPA ratings



Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information	This document has undergone significant changes and should be reviewed in its entirety.

SAFETY DATA SHEET



This Safety Data Sheet (SDS) complies with the requirements of the U.S. Federal Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200, as updated in 2012) and equivalent state Standards. It has also been developed in accordance with the United Nations Globally Harmonized System of Classification of Chemicals (GHS) and the Canadian Workplace Hazardous Materials Information System (WHMIS). Refer to Section 16 of this document for the definition of terms and abbreviations.

SECTION 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

- ITEM NUMBER(S): 170041
- ZEP NUMBER: A00224
- PRODUCT NAME: **Hospital Surface Disinfectant Spray**

1.2 RELEVANT IDENTIFIED USES OF THE MIXTURE

- RECOMMENDED USE: Cleaning and disinfecting of surfaces.
- IDENTIFIED USERS: For sale to, use and storage by service persons only.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

- MANUFACTURER/
SUPPLIER: WAXIE Sanitary Supply
- ADDRESS: 9353 Waxie Way; San Diego, CA 92123-1036
- BUSINESS PHONE: 1-800-995-4466
- EMERGENCY PHONE: 1-800-255-3924 (CHEMTEL; 24 hours)

1.4 OTHER PERTINENT INFORMATION

- This product is sold and used in relatively small volumes. This SDS has been developed to address safety concerns affecting small volume handling situations and those involving warehouses and workplaces where large numbers of these items are stored or distributed.

SECTION 2: HAZARD IDENTIFICATION

2.1 EMERGENCY OVERVIEW

Appearance	Aerosol containing a liquefied gas
Color	Colorless, light yellow
Odor	Pleasant

2.2 GHS CLASSIFICATION

OSHA/HCS Status

Classification of the Substance or Mixture: Flammable Aerosol (Category 2); Gases under pressure (Liquefied gas); Eye irritation (Category 2A)

2.3 LABEL ELEMENTS (suggested)

Hazard Pictograms:



Signal Word:

Danger.

Hazard Statements:

Flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation.

SECTION 2: HAZARD IDENTIFICATION (Continued)

Precautionary Statements

Prevention:	Keep out of reach of children. Read label before use. Keep away from heat, hot surfaces, sparks, open flames. Do not spray on an open flame or other ignition source. No smoking. Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear eye protection/ face protection.
Response:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:	Dispose of contents/container in accordance with local regulation.

2.4 OTHER PERTINENT HAZARDS NOT OTHERWISE CLASSIFIED

- Carcinogenicity:**

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1 SUBSTANCES/MIXTURES

- Hazardous Components:**

CHEMICAL	CAS NUMBER	% (v/v)
Ethanol	67-15-5	>= 30 - < 50
Butane	106-97-8	>= 10 - < 20
Propane	74-98-6	>= 1 - < 5
Propan-2-ol	67-63-0	>= 1 - < 5
Sodium nitrite	7632-00-0	>= 0.1 - < 1

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES

General advice:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled:	If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact:	If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes.
In case of eye contact:	Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing.
If swallowed:	Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control

center. Take victim immediately to hospital.

SECTION 5: FIREFIGHTING MEASURES

5.1 DESCRIPTION OF FIREFIGHTING MEASURES

Suitable extinguishing media:	Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical Water spray jet
Unsuitable extinguishing media:	High volume water jet
Specific hazards during firefighting:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products:	Carbon dioxide (CO ₂). Carbon monoxide. Smoke.
Specific extinguishing methods:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Personal precautions, protective equipment and emergency procedures:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING AND STORAGE

Advice on safe handling:	Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Do not breathe vapors or spray mist. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national regulations. Always replace cap after use.
Conditions for safe storage:	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Keep in a dry, cool and well-ventilated place.
Materials to avoid:	Oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

AIRBORNE EXPOSURE LIMITS:

COMPONENT	ACGIH TLV	OSHA PEL	NIOSH REL	OTHER
Ethanol	STEL = 1000 ppm	TWA = 1000 ppm	TWA = 1000 ppm	NE
Propan-2-ol	TWA= 200 ppm; STEL = 400 ppm	TWA = 400 ppm	TWA= 400 ppm; STEL = 500 ppm	NE
Propane	Minimal Oxygen Content (19.5% at Sea Level)	TWA = 1000 ppm	TWA = 1000 ppm	NE
Butane	STEL = 1000 ppm	NE	TWA = 800 ppm	NE

BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS: The following BEIs have been established for components of this product.

- Propan-2-ol: Acetone in Urine; End of Shift at End of Work Week; 40 mg/L

8.2 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Respiratory protection:	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Hand protection:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection:	Safety glasses Ensure that eyewash stations and safety showers are close to the workstation location.
Skin and body protection:	Impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures:	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Aerosol containing a liquefied gas.
Color:	Clear, light yellow.
Odor:	Characteristic.
Odor Threshold:	No data available.
pH:	10-11
Melting point/freezing point:	No data available.
Boiling point:	No data available.
Flash point:	Not applicable.
Evaporation rate:	No data available.
Flammability (solid, gas):	Flammable aerosol.
Upper explosion limit:	No data available.
Lower explosion limit:	No data available.
Vapor pressure:	No data available.
Relative vapor density:	No data available.
Density:	0.895 g/cm ³
Solubility(ies)/Water solubility	Soluble.
Solubility in other solvents	Not determined.
Partition coefficient: n-octanol/water:	No data available.
Auto-ignition temperature:	No data available.
Thermal decomposition:	No data available.
Viscosity - Viscosity, kinematic:	No data available.
Heat of combustion:	24.20 kJ/g

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY, STABILITY, AND CONDITIONS TO AVOID

Reactivity:	Stable.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	Vapors may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid:	Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials:	Oxidizing agents; reducing agents.
Hazardous decomposition products:	Carbon monoxide; carbon dioxide (CO ₂) Nitrogen Oxides (NO _x).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON ACUTE EFFECTS

PRODUCT

Acute oral toxicity	Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute oral toxicity	Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

COMPONENTS

Ethanol

Acute oral toxicity:	LD50 rat: 6,060 mg/kg
Acute inhalation toxicity:	LC50 rat: 124.7mg/l Exposure time 4 h

Propan-2-ol

Acute oral toxicity	LD50, Oral, Rat: 4, 396 mg/kg Method: Calculation Method

Propane

Acute inhalation toxicity	LC50 mouse: 1,237 mg/l Exposure time: 2 h LC50 rat: 658 mg/l Exposure time: 4 h LC50 rat: 1,355 mg/l

Butane

Acute inhalation toxicity	LC50 mouse: 1,237 mg/l Exposure time: 2 h LC50 rat: 1,355 mg/l

11.2 INFORMATION ON OTHER HEALTH EFFECTS

PRODUCT

Skin corrosion/Irritation:	Remarks: May cause skin irritation in susceptible persons.
Serious eye damage/eye irritation:	Remarks: Irritating to eyes.
Respiratory or skin sensitization:	No data available.

COMPONENTS

Germ cell mutagenicity:	No data available.
Carcinogenicity:	No data available.
Reproductive toxicity:	No data available.
STOT - single exposure:	No data available.
STOT - repeated exposure:	No data available.
Aspiration toxicity:	No data available.

FURTHER INFORMATION

No data available.

SECTION 12: ECOLOGICAL INFORMATION

12.1 TOXICITY INFORMATION

Ecotoxicity:	No data available.	
Persistence and degradability:	No data available.	
Bioaccumulative potential – PRODUCT:	Partition coefficient: n-octanol/water	No data available
Bioaccumulative potential – BUTANE:	Partition coefficient: n-octanol/water	Pow: 2.89
Mobility in soil:	No data available.	
Other adverse effects:	No data available.	

12.2 OTHER PRODUCT INFORMATION

REGULATION:	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks :	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information:	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

SECTION 13: DISPOSAL CONSIDERATION

13.1 WASTE TREATMENT METHODS

- Dispose of in accordance with local, State and Federal regulations.
- Dispose of unused product properly. Do not re-use empty containers.

13.2 DISPOSAL CONSIDERATIONS

- EPA RCRA WASTE CODE: D001.

SECTION 14: TRANSPORT INFORMATION

14.1 DANGEROUS GOODS BASIC DESCRIPTION AND OTHER TRANSPORT INFORMATION

- **DEPARTMENT OF TRANSPORTATION HAZARDOUS MATERIALS SHIPPING REGULATIONS:**

ORM-D, CONSUMER COMMODITY

- **CANADIAN TRANSPORTATION INFORMATION:** This product is regulated by Transport Canada as dangerous goods under Canadian transportation standards. Use the following information:

UN 1950, Aerosols, Flammable, 2.1 (Limited Quantity)

- **IATA DESIGNATION:** This product is regulated as dangerous goods by the International Air Transport Association. Use the following information:

UN 1950, Aerosols, Flammable, 2.1 (Limited Quantity)

- **IMDG DESIGNATION:** This product is regulated as dangerous goods by the International Maritime Organization. Use the following information:

UN 1950, Aerosols, Flammable, 2.1 (Limited Quantity)

SECTION 15: REGULATORY INFORMATION

15.1 UNITED STATES REGULATIONS

- **EPCRA - Emergency Planning and Community Right-to-Know Act**
- **CERCLA Reportable Quantity:** Some items listed are below limits and are not subject to GHS reporting requirements for this formulation.

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetone	67-64-1	5000	*
Sodium Nitrite	7632-00-0	100	*

*Calculated RQ exceeds reasonably attainable upper limit.

- **SARA 304 Extremely Hazardous Substances Reportable Quantity:** This material does not contain any components with a section 304 EHS RQ.
- **Other Important Regulations:**
 - SARA 311/312 Hazards:** Fire Hazard; Sudden Release of Pressure Hazard; Acute Health Hazard
 - SARA 302:** SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.
 - SARA 313:** SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
 - California Prop 65:** Product contains amounts of the chemical known to the State of California to cause cancer.
biphenyl-2-ol – 90-43-7

15.2 OTHER REGULATIONS

TSCA
DSL

On TSCA Inventory.

AICS
NZIoC
PICCS
IECSC

This product contains one or several components that are not on the Canadian DSL nor NDSL.
Not in compliance with the inventory.
Not in compliance with the inventory.
Not in compliance with the inventory.
Not in compliance with the inventory.

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16: OTHER INFORMATION

16.1 INDICATION OF CHANGE

- **DATE OF REVISION:** January 13, 2016
- **SUPERCEDES:** April 29, 2015
- **CHANGE INDICATED:** Format alterations.

16.2 KEY LITERATURE REFERENCES AND SOURCES FOR DATA

- SAFETY DATA SHEET FOR MANUFACTURER PRODUCT.

16.3 HAZARDOUS MATERIALS CLASSIFICATION SYSTEM

Health	2
Flammability	3
Physical Hazard	2
Protective Equipment	B/C

HMIS Personal Protective Equipment Rating: Occupational Use situations: B - Safety glasses and gloves. If splashes or sprays can occur: C- Add body protection.

SECTION 16: OTHER INFORMATION (Continued)

16.4 PERSONAL PROTECTION SYMBOLS

Hand Protection



Eye/Face Protection



Body Protection

(When splashes/sprays may occur)



16.5 NFPA INFORMATION

NFPA Rating



NFPA Classification

Flammable Aerosol

16.6 DISCLAIMER

WAXIE Sanitary Supply makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of their own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by WAXIE Sanitary Supply as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does WAXIE Sanitary Supply assume any liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. WAXIE Sanitary Supply does not recommend blending this product with any other chemicals. All information, recommendations and data contained herein concerning this product are based upon information available at the time of writing from recognized technical sources.

16.7 ABBREVIATIONS AND ACRONYMS

ALL SECTIONS: OSHA: U.S. Federal Occupational Safety and Health Administration. WHMIS: Canadian Workplace Hazardous Materials Standard. GHS: Globally Harmonized System of Classification of Chemical Substances. REACH: European Union regulation, Registration, Evaluation, Authorization and Restriction of Chemical substances.

SECTION 2: CAS Number: Chemical Abstract Service Number, which is used by the American chemical Society to uniquely identify a chemical.

SECTION 5: NFPA: National Fire Protection Association. NFPA FLAMMABILITY CLASSIFICATION: The NFPA uses the flash point (F.P.) and boiling point (BP) to classify flammable or combustible liquids. Class IA: F.P. below 73°F and BP below 100°F. Class IB: F.P. below 73°F and BP at or above 100°F. Class IC: F.P. at or above 73°F and BP at or above 100°F. Class II: F.P. at or above 100°F and below 140°F. Class IIIA: F.P. at or above 140°F and below 200°F. Class IIIB: F.P. at or above 200°F. NFPA HAZARDOUS MATERIALS RATING: This is a rating system used to summarize physical and health hazards to firefighters. 0 = No Significant Hazard. 1 = Slight Hazard. 2 = Moderate Hazard. 3 = Severe Hazard. 4 = Extreme Hazard.

SECTION 8: NE: Not established. ACGIH: American Conference of Government Industrial Hygienists; TWA: Time-Weighted Average (over an 8-hour work day); STEL: Short-Term Exposure Limit (15 minute average, no more than 4-times daily and each exposure separated by one-hour minimally); C: Ceiling Limit (concentration not to be exceeded in a work environment). PEL: Permissible Exposure Limit. NIOSH: National Institute of Occupational Safety and Health; REL: Recommended Exposure Limit; IDLH: Immediately Dangerous to Life and Health Concentrations. *Note*: In July 1992, a court ruling vacated the more protective PELs set by OSHA in 1989. Because OSHA may enforce the more protective levels under the "general duty clause", both the current and vacated levels are presented in this document. ppm: Parts per Million. mg/m³: Milligrams per cubic meter. mppt: Millions of Particles per Cubic Foot. BEI: Biological Exposure Limit. EL: Exposure Limit (United Kingdom). Federal Republic of Germany (DFG) Maximum Concentration Values in the Workplace (MAKs)

SECTION 9: pH: Scale (0 to 14) used to rate the acidity or alkalinity of aqueous solutions. For example, a pH value of 0 indicates a strongly acidic solution, pH of 7 indicates a neutral solution, and a pH value of 14 indicates an extremely basic solution. FLASH POINT: Temperature at which a liquid generates enough flammable vapors so that ignition may occur. AUTOIGNITION TEMPERATURE: Temperature at which spontaneous ignition occurs.

SECTION 9 (Continued): LOWER EXPLOSIVE LIMIT (LEL): The minimal concentration of flammable vapors in air which will sustain ignition. UPPER EXPLOSIVE LIMIT (UEL): The maximum concentration of flammable vapors in air which will sustain ignition. ≈: Approximately symbol. VOC: Volatile Organic Compound.

SECTION 11: CARCINOGENICITY STATUS: NTP: National Toxicology Program. IARC: International Agency for Research on Cancer. REPRODUCTIVE TOXICITY INFORMATION: Mutagen: Substance capable of causing chromosomal damage to cells. Embryotoxin: Substance capable of damaging the developing embryo in an overexposed female. Teratogen: Substance capable of damaging the developing fetus in an overexposed female. Reproductive toxin: Substance capable of adversely affecting male or female reproductive organs or functions. TOXICOLOGY DATA: LD_{xx} or LC_{xx}: The Lethal Dose or Lethal Concentration of a substance which will be fatal to a given percentage (xx) of exposed test animals by the designate route of administration. This value is used to access the toxicity of chemical substances to humans. TD_{xx} or TC_{xx}: The Toxic Dose or Toxic Concentration of a substance which will cause an adverse effect to a given percentage (xx) of exposed test animals by the designate route of administration.

SECTION 12: EC50: Effect Concentration (on 50% of study group); BOD: Biological Oxygen Demand. N/LOEC: No/Lowest Observable Effect Concentration.

SECTION 13: RCRA: Resource Conservation and Recovery Act. The regulations promulgated under this act under Act are found in 40 CFR, Sections 260 ff, and define the requirements of hazardous waste generation, transport, treatment, storage, and disposal. EPA RCRA Waste Codes: Defined in 40 CFR Section 261.

SECTION 15: CERCLA: Comprehensive Environmental Response Compensation and Liability Act (a.k.a. "Superfund") and SARA: (Superfund Amendment and Reauthorization Act). The regulations promulgated under this Act are located under 40 CFR 300 ff. and provide "community right-to-know" requirements. TSCA: Toxic Substances Control Act: Rules regulating the manufacture and sale of chemicals found in 40 CFR 700-766. DSL/NDSL: Canadian Domestic Substances and Non-Domestic Substances Lists.

SECTION 16: HAZARDOUS MATERIALS IDENTIFICATION SYSTEM RATING: This is a rating system used by industry to summarize physical and health hazards to chemical users and was originally developed by the National Paint and Coating Association. 0 = No Significant Hazard. 1 = Slight Hazard. 2 = Moderate Hazard. 3 = Severe Hazard. 4 = Extreme Hazard.



CANBERRA CORPORATION SAFETY DATA SHEET

1. Identification

Product Identifier: HUSKY 1240 FOAMING DISINFECTANT CLEANER

Application or recommended use: Hard surface disinfectant/cleaner

Restrictions on use: Do not use in any fashion not specified on the product label.

Manufacturer / supplier: Canberra Corporation

3610 N. Holland-Sylvania Rd.

Toledo, Ohio 43615 USA

Telephone: 419-841-6616 **Emergency phone:** 866-836-8855

2. Hazards Identification

GHS Classification: Classification of this mixture in accordance with paragraph (d) of §1910.1200.

Flammable Aerosols - Category 1

Eye Damage/Irritation - Category 2A

Label Elements:



Symbol:

Signal word:

DANGER

Hazard statements: Extremely flammable aerosol. Causes serious eye irritation.

Precautionary statements: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Wash thoroughly after handling. Wear eye/face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

See 4. First-Aid Measures for specific treatment.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container to an approved disposal facility.

Other Hazards: None known.

3. Composition / Information on Ingredients

Chemical characterization: Mixture of water, emulsifiers, solvents and auxiliary agents.

Hazardous ingredients: The exact percentage of composition has been withheld as a trade secret.

2 - 10% 2-Butoxyethanol CAS 111-76-2

1 - 2.5% Butane CAS 106-97-8

1 - 2.5% EDTA-Tetrasodium CAS 64-02-8

4. First-aid measures

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact: Rinse with water. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed: Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment needed: Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

5. Fire-fighting measures

Suitable extinguishing media: Water.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, and rubber boots.

Fire-fighting equipment/instructions: Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods: Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes. **General fire hazards:** Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them.

Methods and materials for containment and cleaning up: Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Environmental precautions: Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3 (50 ppm)

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3 (5 ppm)
Butane (CAS 106-97-8)	TWA	1900 mg/m3 (800 ppm)

Exposure guidelines

US - California OELs: Skin designation

US - Tennessee OELs: Skin designation

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol: Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol: Skin designation applies.

Appropriate engineering controls: Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment:

Eye/face protection: Wear safety glasses with side shields (or goggles).

Hand protection: Wear appropriate chemical resistant gloves.

Other: Wear suitable protective clothing.

Respiratory protection: If permissible levels are exceeded use organic vapor cartridge or an air-supplied respirator.

General hygiene considerations: When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance****Physical state:** Gas.**Color:** Not available.**Odor threshold:** Not available.**Melting point/freezing point:** Not available.**Flash point:** -156.0 °F (-104.4 °C) Propellant estimated.**Evaporation rate:** Not available.**Upper/lower flammability or explosive limits****Flammability limit – lower (%):** Not available.**Explosive limit - lower (%):** Not available.**Vapor pressure:** 55 - 75 psig @70F estimated**Relative density:** Not available.**Solubility (water):** Not available.**Auto-ignition temperature:** Not available.**Viscosity:** Not available.**Form:** Aerosol.**Odor:** Not available.**pH:** Not available.**Initial boiling point/boiling range:** 212 °F (100 °C) estimated.**Flammability:** Not available.**Flammability limit – upper (%):** Not available.**Explosive limit - upper (%):** Not available.**Vapor density:** Not available.**Specific gravity:** 0.979 estimated**Partition coefficient (n-octanol/water):** Not available.**Decomposition temperature:** Not available.**10. Stability and reactivity****Reactivity:** Reacts violently with strong acids. This product may react with oxidizing agents.**Chemical stability:** Material is stable under normal conditions.**Possibility of hazardous reactions:** Hazardous polymerization does not occur.**Conditions to avoid:** Do not mix with other chemicals. Contact with incompatible materials.**Incompatible materials:** Acids. Oxidizing agents.**Hazardous decomposition products:** No hazardous decomposition products are known.**11. Toxicological information****Information on likely routes of exposure:****Ingestion:** Expected to be a low ingestion hazard.**Inhalation:** Prolonged inhalation may be harmful.**Skin contact:** 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.**Eye contact:** Causes serious eye irritation.**Symptoms related to the physical, chemical and toxicological characteristics:** Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.**Information on toxicological effects:****Symptoms related to the physical, chemical and toxicological characteristics:** Headache. Irritation of nose and throat.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. Skin irritation.

Acute toxicity: Harmful if inhaled. Harmful if swallowed.**Skin corrosion/irritation:** Prolonged skin contact may cause temporary irritation.**Serious eye damage/eye irritation:** Causes serious eye irritation.**Respiratory sensitization:** Not available.**Skin sensitization:** This product is not expected to cause skin sensitization.**Carcinogenicity:** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):** Not listed.**Reproductive toxicity:** This product is not expected to cause reproductive or developmental effects.**Specific target organ toxicity - single exposure:** Not classified.**Specific target organ toxicity - repeated exposure:** Not classified.**Aspiration hazard:** Not likely, due to the form of the product.**Chronic effects:** Prolonged inhalation may be harmful. May be harmful if absorbed through skin. 2-Butoxyethanol may be absorbed through the skin in toxic amounts if contact is repeated or prolonged. Effects have not been observed in humans.**12. Ecological information****Ecotoxicity:** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.**Persistence and degradability:** No data is available on the degradability of this product.**Bioaccumulative potential:** No data available.**Partition coefficient n-octanol/water (log Kow):** 2-Butoxyethanol 0.83 Butane 2.89**Mobility in soil:** No data available.**Other adverse effects:** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Waste from residues/unused products: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT **UN number:** UN1950 **UN proper shipping name:** Aerosols, non-flammable **Class:** 2.2
Subsidiary risk: N/A **Label(s):** 2.2 **Packing group:** Not applicable.
Special precautions for user: Read safety instructions, SDS and emergency procedures before handling.
Packaging exceptions: This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity.

15. Regulatory information**US federal regulations**

FIFRA: This product is a U.S. EPA Registered pesticide, EPA Reg. No. 706-65-8155, and is subject to certain labeling requirements under Federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide products.

OSHA: This product is a "Hazardous Chemical" under the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA: All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

SARA 304 Emergency release notification: Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA): Hazard categories

Immediate Hazard – Yes Delayed Hazard – No

Fire Hazard – Yes Pressure Hazard – No

Reactivity Hazard – No

SARA 311/312 Hazardous chemical: No

SARA 313 (TRI reporting): Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Butane (CAS 106-97-8)

Safe Drinking Water Act (SDWA): Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

US. New Jersey Worker and Community Right-to-Know Act

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2) Butane (CAS 106-97-8)

US. Rhode Island RTK

Butane (CAS 106-97-8)

US. California Proposition 65: California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

16. Other information, including date of preparation or last revision

Date issued: 01. 02. 2015

HSK-1240 Revision: N/A

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. We cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.



CANBERRA CORPORATION SAFETY DATA SHEET

1. Identification

Product Identifier: HUSKY 430 CRÈME CLEANSER

Application or recommended use: Scouring cleanser

Restrictions on use: Do not use in any fashion not specified on the product label.

Manufacturer / supplier: Canberra Corporation

3610 N. Holland-Sylvania Rd.

Toledo, Ohio 43615 USA

Telephone: 419-841-6616 **Emergency phone:** 800-832-8992 **National Poison Center:** 800-222-1222

2. Hazards Identification

GHS Classification: Classification of this mixture in accordance with paragraph (d) of §1910.1200.

Acute Toxicity (Oral) - Category 4

Skin Corrosion/Irritation - Category 2

Eye Damage/Irritation - Category 1

Label Elements:



Symbol:

Signal word:

DANGER

Hazard statements:

Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

Precautionary statements: Wash hands, face and any skin contact thoroughly after handling.

Wear protective gloves/eye protection/face protection.

Do not eat, drink or smoke when using this product.

IF SWALLOWED: Rinse mouth. Call a poison center/doctor if you feel unwell.

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

See 4. First-Aid Measures for specific treatment.

Dispose of contents/container to an approved disposal facility.

Other Hazards: None known

3. Composition / Information on Ingredients

Chemical characterization: Mixture of water, silica, detergents, and auxiliary agents.

Hazardous ingredients: The exact percentage of composition has been withheld as a trade secret.

35 - 40% Silica

CAS 14808-60-7, EINECS/ELINCS 238-874-4

5 - 10% C₉₋₁₁ Alcohol ethoxylate

CAS 68439-46-3, EINECS/ELINCS N/A

1 - 5% Sulfonic acid,

CAS 27176-87-0, EINECS/ELINCS 248-289-4

Other ingredients (> 1%):

> 50% Water

CAS 7732-18-5, EINECS/ELINCS 231-791-2

4. First-Aid Measures

Symptoms: Burning or irritation of affected areas. Causes skin irritation and serious eye damage. Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

Inhalation: Move person to fresh air. If respiratory irritation or dizziness occurs, seek immediate medical assistance.

Skin Contact: Remove contaminated clothing and wash before reuse. Wash contaminated area with soap and water for 15-20 minutes. If skin irritation occurs, get medical advice/attention.

Eye Contact: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Ingestion: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to a person who is unconscious or convulsing. If vomiting occurs, keep head below hips to reduce risk of aspiration.

Note to Physician: Treat exposed patients symptomatically.

5. Fire-Fighting Measures

Suitable Extinguishing Media: Not applicable. Product is not a fire hazard.

Unsuitable Extinguishing Media: High pressure water jet. **Specific hazards in case of fire:** None known.

Special Fire Fighting Precautions: Fire fighters should wear appropriate protective equipment, including self-contained breathing apparatus and impervious clothing.

6. Accidental Release Measures

Emergency Procedures: Depending on the extent of release, consider the need for restriction of access to spill area.

Personal Precautions: Do not eat, drink or smoke during clean up. Wear protective clothing, eye protection and impervious gloves (e.g. neoprene). Wash thoroughly after clean up.

Environmental Precautions: Prevent spills from entering storm sewers/drains or contact with soil.

Clean up Methods: Small spills may be wiped up and rinsed with water. For larger spills, contain spill with inert material (sand, clay). Transfer material to labeled containers for recovery or proper disposal. After removal, flush area with water.

7. Handling and Storage

Precautions for Safe Handling: Read label before use. Avoid contact with skin or eyes. Wear protective gloves, eye protection, face protection. Use product only according to label directions. If unsure about safe use, contact your supervisor. Do not eat, drink or smoke while using this product. Wash hands, face and any skin contact thoroughly after handling.

Conditions for Safe Storage: Do not contaminate water, food or feed by storage and disposal. Store in tightly closed, original container in a cool (10° - 30°C), dry area. Keep in an area inaccessible to children. **Incompatibility:** None known.

8. Exposure Controls / Personal Protection

Components with occupational exposure limits:

Component	Reference	TWA	PEL
Silica	ACGIH(TLV)	0.025 mg/m ³	
	OSHA		0.1 mg/m ³
	NIOSH(REL)	0.05 mg/m ³	

Engineering Controls: Proper ventilation in accordance with good industrial hygiene should be provided.

Personal Protective Equipment

Respiratory: Respiratory protection is not necessary under normal conditions of use. If necessary to prevent exposure above occupational limits, use an approved cartridge style respirator.

Gloves: Use water impervious gloves (latex or neoprene rubber). No breakthrough time has been established.

Eye Protection: Chemical resistant goggles or face protection.

Other: Protective clothing (long sleeves, pants), eyewash, safety shower are always advisable when working with chemicals.

9. Physical and Chemical Properties

Physical State - Slurry

Color - White

Odor - Mint

Odor Threshold - Not available

Boiling Point - 212°F

Decomposition temperature - No data available

Freezing Point - 32°F

pH (Neat) - 1.0 - 2.5

Relative Density - 1.20 - 1.30

Evaporation Rate - Similar to water

Auto-ignition temperature - Not applicable

Flash Point - None

Flammability - Not applicable

Flammability Limits - Not applicable

Partition coefficient - Not applicable

Solubility (Water) - Complete

Vapor Density - Not available

Vapor Pressure - Not available

Viscosity - Viscous slurry

% VOC - < 1 (Excluding exempt material)

10. Stability and Reactivity

Reactivity: No specific reactivity test data is available for this mixture. Under normal conditions of storage and use, hazardous reactions are not expected.

Incompatible materials: None known.

Chemical stability: This product is stable at ambient temperatures and pressures.

Conditions to avoid: Temperatures above 50°C or below 10°C.

Hazardous decomposition products: None known.

11. Toxicological Information

Acute Toxicity: Toxicity data is not available for this mixture. Data below are estimates based on summation methods.

Test	Results	Classification (A.0.4.1(c))	Basis (A.1.3.6.1)
Oral	> 1075mg/kg	Category 4	Ingredient literature (Additive formula)
Dermal	> 2000mg/kg	Not applicable	Ingredient literature (Additive formula)
Inhalation	> 20 mg/L	Not applicable	Ingredient literature (Additive formula)
Eye Damage/Irritation	Corrosion	Category 1	Ingredient literature
Skin Damage/Irritation	Irritation	Category 2	Ingredient literature

Summary: Skin and eye contact are most likely routes of exposure. Exposure causes skin irritation and serious eye damage.

11. Toxicological Information (cont.)**Subchronic/Chronic Toxicity:**

Test	Results	Classification	Basis
Skin Sensitization	Not a sensitizer	Not applicable	Ingredient literature.

Summary: Repeated or prolonged contact causes skin irritation and serious eye damage.

Carcinogens - Silica CAS# 14808-60-7 is listed by both IARC and NTP as a human carcinogen when present in the form of respirable quartz. Husky 430 Creme Cleanser, as delivered, does not contain respirable quartz.

Other data - No other toxicological information is available for this mixture.

12. Ecological Information

This material has not been tested for acute environmental effects.

Persistence and degradability: Material is not persistent. All organic components > 1% are readily biodegradable.

Bio-accumulative potential: No evidence to suggest bio-accumulation will occur.

Mobility: Accidental spillage may lead to penetration of soil and groundwater.

13. Disposal Considerations

Do not contaminate water, food or feed by disposal. If these materials cannot be disposed of by use according to label directions, contact your State Environmental Control Agency, or the hazardous waste representative at the nearest EPA Regional Office for guidance. Rinse container promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill. If container is one gallon or less, wrap empty container in plastic bag and discard in trash.

14. Transport Information

Proper Shipping Name: Not regulated **RQ** - Not Applicable
Shipping emergency phone: 800-424-9300
Transport hazard class: Not Applicable **Hazard Label:** Not Applicable
Packing Group: Not Applicable **Emergency Guide No.:** Not Applicable **Marine Pollutant:** No

15. Regulatory Information

Inventory status: All components are listed on TSCA(US), EINECS/ELINCS(EU), DSL(Canada), AICS(Australia).

OSHA Hazard Communication Standard: This product meets the §1910.1200 definition of a "Hazardous Chemical".

Superfund Amendments and Reauthorization Act of 1986 Title III (EPCRA) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes
Delayed (Chronic) Health Hazard	Yes
Fire Hazard	No
Reactive Hazard	No
Sudden Release of Pressure Hazard	No

Superfund Amendments and Reauthorization Act of 1986 Title III (EPCRA) Section 313

*Chemicals marked with an asterisk in "3. Composition/Information on Ingredients" are subject to reporting requirements for Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40CFR Part 372.

Pennsylvania/New Jersey/Massachusetts Right to Know

See "3. Composition/Information on Ingredients" for hazardous and top five ingredients over 1% (w/w).

California Proposition 65: This product contains a listed substance known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute: Silica CAS# 14808-60-7. In its current form however, no respirable quartz is present.

16. Other information

Date issued: 31. 12. 2014 F430-001
Revision: 19. 01. 2016 Version 002 Revised Physical and Chemical Properties, pH

Disclaimer: No representation or warranty, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, is made with respect to information concerning the product referred to in this document. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, it is impossible to foresee every health effect or exposure risk incurred by the use of this product. All chemicals present some degree of hazard and should be used with caution. The information and recommendations contained herein are presented in good faith. The user should review this information in conjunction with their knowledge of the application intended to determine the suitability of this product for such purpose. In no event will the supplier be responsible for any damages of any nature whatsoever, resulting from the use, reliance upon, or the misuse of this information. Furthermore, it is the direct responsibility of the user to comply with all applicable regulations governing the use and disposal of this material. **Prepared by:** R&D, Canberra Corporation

Common Name: IC +SSPR 6PK GLOSS GLOSSY WHITE, 1692830
Manufacturer: RUST-OLEUM
MSDS Revision Date: 8/25/2014
MSDS Format: GHS-US

Grainger Item Number(s): 6KP31
Manufacturer Model Number(s):

DATE PRINTED: 8/25/2014

SAFETY DATA SHEET

RUST-OLEUM CORPORATION

TRUSTED QUALITY SINCE 1921

WWW.RUSTOLEUM.COM

1. IDENTIFICATION



PRODUCT NAME: IC +SSPR 6PK GLOSS GLOSSY WHITE

PRODUCT IDENTIFIER: 1692830

PRODUCT USE/CLASS: TOPCOAT/AEROSOLS

SUPPLIER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

MANUFACTURER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

PREPARER: REGULATORY DEPARTMENT

EMERGENCY TELEPHONE:
24 HOUR HOTLINE: 847-367-7700

REVISION DATE: 8/25/2014

SUPERCEDES DATE: NEW SDS

2. HAZARD IDENTIFICATION



EMERGENCY OVERVIEW:
HARMFUL IF SWALLOWED. EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. CONTENTS UNDER PRESSURE. HARMFUL IF INHALED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE EYE, SKIN, OR RESPIRATORY TRACT IRRITATION. KEEP OUT OF REACH OF CHILDREN. HARMFUL IF INHALED. CAUSES EYE IRRITATION. USE VENTILATION NECESSARY TO KEEP EXPOSURES BELOW RECOMMENDED EXPOSURE LIMITS, IF ANY. VAPOR HARMFUL. CAUSES EYE, SKIN, NOSE, AND THROAT IRRITATION.

CLASSIFICATION:

SYMBOL(S) OF PRODUCT:

EXCLAMATION MARK

FLAME

HEALTH HAZARD

SIGNAL WORD: DANGER

GHS HAZARD STATEMENTS:

FLAMMABLE AEROSOL, CATEGORY 1:

H222: EXTREMELY FLAMMABLE AEROSOL.

FLAMMABLE LIQUID, CATEGORY 1:

H224: EXTREMELY FLAMMABLE LIQUID AND VAPOUR.

ACUTE TOXICITY, ORAL, CATEGORY 5:

H303: MAY BE HARMFUL IF SWALLOWED.

ACUTE TOXICITY, DERMAL, CATEGORY 5:

H313: MAY BE HARMFUL IN CONTACT WITH SKIN.

SKIN IRRITATION, CATEGORY 2:

H315: CAUSES SKIN IRRITATION.

EYE IRRITATION, CATEGORY 2:

H319: CAUSES SERIOUS EYE IRRITATION.

ACUTE TOXICITY, INHALATION, CATEGORY 4:

H332: HARMFUL IF INHALED.

STOT, SINGLE EXPOSURE, CATEGORY 3, RTI:

H335: MAY CAUSE RESPIRATORY IRRITATION.

STOT, SINGLE EXPOSURE, CATEGORY 3, NE:

H336: MAY CAUSE DROWSINESS OR DIZZINESS.

ASPIRATION HAZARD, CATEGORY 2:

H305: MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS.

EYE IRRITATION, CATEGORY 2B:

H320: CAUSES EYE IRRITATION.

FLAMMABLE AEROSOL, CATEGORY 1:

H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED

GHS PRECAUTIONARY STATEMENTS:

P211: DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

P220: KEEP/STORE AWAY FROM CLOTHING/.../COMBUSTIBLE MATERIALS.

P235: KEEP COOL.

P251:

PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE.

P375: FIGHT FIRE REMOTELY DUE TO THE RISK OF EXPLOSION.

P102: KEEP OUT OF REACH OF CHILDREN.

P103: READ LABEL BEFORE USE.

P202:

DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

P234: KEEP ONLY IN ORIGINAL CONTAINER.

P260: DO NOT BREATHE DUST/FUME/GAS/MIST/VAPOURS/SPRAY.

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPOURS/SPRAY.

P262: DO NOT GET IN EYES, ON SKIN, OR ON CLOTHING.

P264: WASH ... THOROUGHLY AFTER HANDLING.

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT.

P271: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P273: AVOID RELEASE TO THE ENVIRONMENT.

P280:
WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

P281: USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED.

P285: IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION.

P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

P351: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES.

P374: FIGHT FIRE WITH NORMAL PRECAUTIONS FROM A REASONABLE DISTANCE.

P402: STORE IN A DRY PLACE.

P210: KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

P410+P412:
PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING
50 DEG. C/ 122 DEG. F.

P240: GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT.

P241: USE EXPLOSION-PROOF ELECTRICAL/VENTILATING/LIGHTING/.../ EQUIPMENT.

P242: USE ONLY NON-SPARKING TOOLS.

P243: TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.

P303+P361+P353:
IF ON SKIN (OR HAIR):
REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN
WITH WATER/SHOWER.

P370+P378:
IN CASE OF FIRE: USE ... FOR EXTINCTION.

P403+P235: STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

P501: DISPOSE OF CONTENTS/CONTAINER TO ...

P321: SPECIFIC TREATMENT (SEE ... ON THIS LABEL).

P352: WASH WITH PLENTY OF SOAP AND WATER.

P362: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

P332+P313:

IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ATTENTION.

P305+P351+P338:

IF IN EYES:

RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

P337+P313:

IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

P304+P340:

IF INHALED:

REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING.

P405: STORE LOCKED UP.

P403+P233:

STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P302+P350:

IF ON SKIN: GENTLY WASH WITH PLENTY OF SOAP AND WATER.

3. COMPOSITION / INFORMATION ON INGREDIENTS



HAZARDOUS SUBSTANCES:

CHEMICAL NAME	CAS-NO.	WT.% RANGE	GHS SYMBOLS	GHS STATEMENTS
LIQUEFIED PETROLEUM GAS	68476-86-8	25-50		
ACETONE	67-64-1	10-25	GHS02	H225
TITANIUM DIOXIDE	13463-67-7	10-25		
XYLENE	1330-20-7	2.5-10	GHS02	H226
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	64742-49-0	2.5-10		
ETHYLBENZENE	100-41-4	1.0-2.5	GHS02-GHS07	H225-332
SOLVENT NAPHTHA, LIGHT AROMATIC	64742-95-6	1.0-2.5		
PROPYLENE GLYCOL MONOBUTYL ETHER	5131-66-8	1.0-2.5	GHS02-GHS07	H226-302
1,2,4-TRIMETHYLBENZENE	95-63-6	1.0-2.5	GHS02	H226

THE TEXT FOR GHS HAZARD STATEMENTS SHOWN ABOVE (IF ANY) IS GIVEN IN THE "16. OTHER INFORMATION" SECTION.

4. FIRST-AID MEASURES



FIRST AID - EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. DO NOT ALLOW RUBBING OF EYES OR KEEPING EYES CLOSED.

FIRST AID - SKIN CONTACT:

WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY. REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT USE MOUTH-TO-MOUTH RESUSCITATION.

FIRST AID - INGESTION:

ASPIRATION HAZARD:

DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION. IF SWALLOWED, GET MEDICAL ATTENTION.

5. FIRE-FIGHTING MEASURES



EXTINGUISHING MEDIA:

ALCOHOL FILM FORMING FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR!

WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT DUE TO BUILDUP OF STEAM. NO UNUSUAL FIRE OR EXPLOSION HAZARDS NOTED.

SPECIAL FIREFIGHTING PROCEDURES:

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE. FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION OR EXPLOSION. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. CONTAINERS MAY EXPLODE WHEN HEATED.

6. ACCIDENTAL RELEASE MEASURES



STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. ISOLATE THE HAZARD AREA AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL. VENTILATE AREA, ISOLATE SPILLED MATERIAL, AND REMOVE WITH INERT ABSORBENT. DISPOSE OF CONTAMINATED ABSORBENT, CONTAINER, AND UNUSED CONTENTS IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

7. HANDLING AND STORAGE



HANDLING:

WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. USE ONLY IN A WELL-VENTILATED AREA. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING FUMES, VAPORS, OR MIST. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. USE ONLY WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

STORAGE:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F. PRODUCT SHOULD BE STORED IN TIGHTLY SEALED CONTAINERS AND PROTECTED FROM HEAT, MOISTURE, AND FOREIGN MATERIALS. STORE IN A DRY, WELL VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND SOURCES OF IGNITION. AVOID EXCESS HEAT.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



CHEMICAL NAME	CAS-NO.	WEIGHT % LESS THAN
LIQUEFIED PETROLEUM GAS	68476-86-8	30.0
ACETONE	67-64-1	25.0
TITANIUM DIOXIDE	13463-67-7	15.0
XYLENE	1330-20-7	10.0
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	64742-49-0	10.0
ETHYLBENZENE	100-41-4	5.0
SOLVENT NAPHTHA, LIGHT AROMATIC	64742-95-6	5.0
PROPYLENE GLYCOL MONOBUTYL ETHER	5131-66-8	5.0
1,2,4-TRIMETHYLBENZENE	95-63-6	5.0

CHEMICAL NAME	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
LIQUEFIED PETROLEUM GAS	N.E.	N.E.	N.E.	N.E.
ACETONE	500 PPM	750 PPM	1000 PPM	N.E.
TITANIUM DIOXIDE	10 MG/M3	N.E.	15 MG/M3 [TOTAL DUST]	N.E.
XYLENE	100 PPM	150 PPM	100 PPM	N.E.
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	200 MG/M3	N.E.	N.E.	N.E.
ETHYLBENZENE	20 PPM	125 PPM	100 PPM	N.E.

SOLVENT NAPHTHA, LIGHT AROMATIC	N.E.	N.E.	N.E.	N.E.
PROPYLENE GLYCOL MONOBUTYL ETHER	N.E.	N.E.	N.E.	N.E.
1,2,4-TRIMETHYLBENZENE	25 PPM	N.E.	N.E.	N.E.

PERSONAL PROTECTION:

ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. PROVIDE GENERAL DILUTION OF LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS.

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

SKIN PROTECTION:

USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION. USE GLOVES TO PREVENT PROLONGED SKIN CONTACT.

EYE PROTECTION:

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION. REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER GUIDANCE REGARDING TYPES OF PERSONAL PROTECTIVE EQUIPMENT AND THEIR APPLICATIONS.

HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING. REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND LAUNDER BEFORE REUSE.

9. PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE: AEROSOLIZED MIST

PHYSICAL STATE: LIQUID

ODOR: SOLVENT LIKE

ODOR THRESHOLD: N.E.

RELATIVE DENSITY: 0.817

PH: N.A.

FREEZE POINT, DEG. C: N.D.

VISCOSITY: N.D.

SOLUBILITY IN WATER: SLIGHT

PARTITION COEFFICIENT, N-OCTANOL/WATER: NO INFORMATION

DECOMPOSITION TEMP., DEG. C: NO INFORMATION

BOILING RANGE, DEG. C: -34 - 662

EXPLOSIVE LIMITS, VOL%: 0.7 - 13.0

FLAMMABILITY: SUPPORTS COMBUSTION

FLASH POINT, DEG. C: -105

EVAPORATION RATE: FASTER THAN ETHER

AUTO-IGNITION TEMP., DEG. C: NO INFORMATION

VAPOR DENSITY: HEAVIER THAN AIR

VAPOR PRESSURE: N.D.

(SEE "OTHER INFORMATION" SECTION FOR ABBREVIATION LEGEND)

10. STABILITY AND REACTIVITY



CONDITIONS TO AVOID:

AVOID TEMPERATURES ABOVE 120 DEG. F. AVOID ALL POSSIBLE SOURCES OF IGNITION. AVOID CONTACT WITH STRONG ACID AND STRONG BASES.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION:

BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE. WHEN HEATED TO DECOMPOSITION, IT EMITS ACRID SMOKE AND IRRITATING FUMES. CONTAINS SOLVENTS WHICH MAY FORM CARBON MONOXIDE, CARBON DIOXIDE, AND FORMALDEHYDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

11. TOXICOLOGICAL INFORMATION



EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES SERIOUS EYE IRRITATION

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:

SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. MAY CAUSE SKIN IRRITATION. ALLERGIC REACTIONS ARE POSSIBLE.

EFFECTS OF OVEREXPOSURE - INHALATION:

HARMFUL IF INHALED. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. AVOID BREATHING FUMES, SPRAY, VAPORS, OR MIST. HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS. PROLONGED OR EXCESSIVE INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION.

EFFECTS OF OVEREXPOSURE - INGESTION:

ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:

IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL AS REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE. CONTAINS TITANIUM DIOXIDE. TITANIUM DIOXIDE IS LISTED AS A GROUP 2B-"POSSIBLY CARCINOGENIC TO HUMANS" BY IARC. NO SIGNIFICANT EXPOSURE TO TITANIUM DIOXIDE IS THOUGHT TO OCCUR DURING THE USE OF PRODUCTS IN WHICH TITANIUM DIOXIDE IS BOUND TO OTHER MATERIALS, SUCH AS IN PAINTS DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF TITANIUM DIOXIDE IN THE FORMULA. (REF: IARC MONOGRAPH, VOL. 93, 2010)MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. HIGH CONCENTRATIONS MAY LEAD TO CENTRAL NERVOUS SYSTEM EFFECTS (DROWSINESS, DIZZINESS, NAUSEA, HEADACHES, PARALYSIS, AND BLURRED VISION) AND/OR DAMAGE.

PRIMARY ROUTE(S) OF ENTRY:

EYE CONTACT, INGESTION, INHALATION, SKIN ABSORPTION, SKIN CONTACT

ACUTE TOXICITY VALUES:

THE ACUTE EFFECTS OF THIS PRODUCT HAVE NOT BEEN TESTED. DATA ON INDIVIDUAL COMPONENTS ARE TABULATED BELOW:

CAS-NO.	CHEMICAL NAME	ORAL LD50	DERMAL LD50	VAPOR LC50
13463-67-7	TITANIUM DIOXIDE	>10000 MG/KG RAT	N.I.	N.I.
1330-20-7	XYLENE	4300 MG/KG RAT	N.I.	47635 MG/L RAT
64742-49-0	NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	>5000 MG/KG RAT	>3160 MG/KG RABBIT	N.I.
100-41-4	ETHYLBENZENE	3500 MG/KG RAT	15354 MG/KG RABBIT	17.2 MG/L RAT
64742-95-6	SOLVENT NAPHTHA, LIGHT AROMATIC	N.I.	>2000 MG/KG RABBIT	N.I.
5131-66-8	PROPYLENE GLYCOL MONOBUTYL ETHER	1900 MG/KG RAT	N.I.	N.I.
95-63-6	1, 2, 4-TRIMETHYLBENZENE	3280 MG/KG RAT	>3160 MG/KG RABBIT	N.I.

N.I. - NO INFORMATION

12. ECOLOGICAL INFORMATION



ECOLOGICAL INFORMATION:

PRODUCT IS A MIXTURE OF LISTED COMPONENTS. PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

13. DISPOSAL INFORMATION



DISPOSAL INFORMATION:

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE, AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER WATERWAYS, WASTEWATER, SOIL, STORM DRAINS OR SEWER SYSTEMS.

14. TRANSPORT INFORMATION



	DOMESTIC (USDOT)	INTERNATIONAL (IMDG)	AIR (IATA)	TDG (CANADA)
UN NUMBER	N.A.	1950	1950	N.A.
PROPER SHIPPING NAME	PAINT PRODUCTS IN LIMITED QUANTITIES	AEROSOLS	AEROSOLS	PAINT PRODUCTS IN LIMITED QUANTITIES
HAZARD CLASS	N.A.	2.1	2.1	N.A.
PACKING GROUP	N.A.	N.A.	N.A.	N.A.
LIMITED QUANTITY	YES	YES	YES	YES

15. REGULATORY INFORMATION



U.S. FEDERAL REGULATIONS:

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES' PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:
FIRE HAZARD, PRESSURE HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

SARA SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS-NO.
XYLENE	1330-20-7
ETHYLBENZENE	100-41-4
1,2,4-TRIMETHYLBENZENE	95-63-6

TOXIC SUBSTANCES CONTROL ACT:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:
NO TSCA COMPONENTS EXIST IN THIS PRODUCT.

INVENTORY INFORMATION:

COUNTRY	VALUE
USA (TSCA)	NO INFORMATION

CANADA (DSL)	NO INFORMATION
MEXICO(INSQ)	NO INFORMATION
EUROPE (EINECS)	NO INFORMATION
JAPAN (ENCS)	NO INFORMATION
PHILIPPINES (PICCS)	NO INFORMATION
CHINA (IECSC)	NO INFORMATION
AUSTRALIA (AICS)	NO INFORMATION
KOREA (KECI)	NO INFORMATION
NEW ZEALAND (NZIOC)	NO INFORMATION

NO INFORMATION

CALIFORNIA PROPOSITION 65:

WARNING:

THIS PRODUCTS CONTAINS A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

CHEMICAL NAME	CAS-NO.
TITANIUM DIOXIDE	13463-67-7
ETHYLBENZENE	100-41-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS:

WARNING:

THIS PRODUCT CONTAINS A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NO PROPOSITION 65 REPRODUCTIVE TOXINS EXIST IN THIS PRODUCT.

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS:

THIS SDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

16. OTHER INFORMATION



HMIS RATINGS:

HEALTH	2*
FLAMMABILITY	4
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

CANADIAN WHMIS CLASS:

B2
D2A

NFPA RATINGS:

HEALTH	2
FLAMMABILITY	4
INSTABILITY	0

VOLATILE ORGANIC COMPOUNDS, G/L: 515

MSDS REVISION DATE: 8/25/2014

REASON FOR REVISION: NO INFORMATION

LEGEND:

N.A. - NOT APPLICABLE

N.E. - NOT ESTABLISHED

N.D. - NOT DETERMINED

TEXT FOR GHS HAZARD STATEMENTS SHOWN IN SECTION 3 DESCRIBING EACH INGREDIENT:

H225: HIGHLY FLAMMABLE LIQUID AND VAPOUR.

H226: FLAMMABLE LIQUID AND VAPOUR.

H302: HARMFUL IF SWALLOWED.

H332: HARMFUL IF INHALED.

ICONS FOR GHS PICTOGRAMS SHOWN IN SECTION 3 DESCRIBING EACH INGREDIENT:

GHS02: FLAME

GHS07: EXCLAMATION MARK

RUST-OLEUM CORPORATION BELIEVES, TO THE BEST OF ITS KNOWLEDGE, INFORMATION AND BELIEF, THE INFORMATION CONTAINED HEREIN TO BE ACCURATE AND RELIABLE AS OF THE DATE OF THIS SAFETY DATA SHEET. HOWEVER, BECAUSE THE CONDITIONS OF HANDLING, USE, AND STORAGE OF THESE MATERIALS ARE BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY OR LIABILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE INCURRED BY THE USE OF THESE MATERIALS. RUST-OLEUM CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OR RELIABILITY OF THE DATA OR RESULTS OBTAINED FROM THEIR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. THE INFORMATION AND RECOMMENDATIONS IN THIS MATERIAL SAFETY DATA SHEET ARE OFFERED FOR THE USERS' CONSIDERATION AND EXAMINATION. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE FINAL SUITABILITY OF THIS INFORMATION AND TO COMPLY WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

Safety Data Sheet



1. Identification

Product Name:	IC SSPR 6PK GLOSS BRIGHT GALVANIZING	Revision Date:	3/13/2018
Product Identifier:	244305	Supersedes Date:	12/13/2016
Product Use/Class:	Top Coat/ Aerosol		
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
	Rust-Oleum Consumer Brands Canada (RCBC) 200 Confederation Parkway Concord, ON L4K 4T8 Canada		
Preparer:	Regulatory Department		
Emergency Telephone:	24 Hour Hotline: 847-367-7700		

2. Hazard Identification

Classification

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

24% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Flammable Aerosol, category 1	H222	Extremely flammable aerosol.
Compressed Gas	H280	Contains gas under pressure; may explode if heated.
Germ Cell Mutagenicity, category 1B	H340	May cause genetic defects.
Carcinogenicity, category 1B	H350	May cause cancer.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.

Acute Toxicity, Oral, category 4

H302

Harmful if swallowed.

GHS LABEL PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P201	Obtain special instructions before use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local, regional and national regulations.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P314	Get medical advice/attention if you feel unwell.
P330	Rinse mouth.
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

GHS SDS PRECAUTIONARY STATEMENTS

P270	Do not eat, drink or smoke when using this product.

3. Composition / Information On Ingredients**HAZARDOUS SUBSTANCES**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Zinc	7440-66-6	38	GHS07	H302
n-Butyl Acetate	123-86-4	19	GHS02-GHS07	H226-336
Propane	74-98-6	10	GHS04	H280
Hydrotreated Light Distillate	64742-47-8	10	GHS08	H304

Aluminum Flake	7429-90-5	5.8	GHS02	H228-261
n-Butane	106-97-8	4.8	GHS04	H280
Stoddard Solvent	8052-41-3	3.0	GHS08	H304-372
Xylenes (o-, m-, p- isomers)	1330-20-7	1.5	GHS02-GHS07	H226-315-319-332
Zinc Oxide	1314-13-2	1.4	Not Available	Not Available
Solvent Naphtha, Light Aromatic	64742-95-6	1.2	GHS07-GHS08	H304-332-340-350
Ethylbenzene	100-41-4	0.4	GHS02-GHS07-GHS08	H225-304-332-351-373

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLASH POINT IS LESS THAN 20°F. EXTREMELY FLAMMABLE LIQUID AND VAPOR! Water spray may be ineffective. Closed containers may explode when exposed to extreme heat due to buildup of steam. Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Isolate from heat, electrical equipment, sparks and open flame. Perforation of the pressurized container may cause bursting of the can. No unusual fire or explosion hazards noted. Keep containers tightly closed.

SPECIAL FIREFIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Evacuate area and fight fire from a safe distance. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

Special Fire and Explosion Hazard (Combustible Dust): No Information

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Contents under pressure. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of flammable aerosols. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials. Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep away from heat, sparks, flame and sources of ignition. Avoid excess heat.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Zinc	7440-66-6	40.0	N.E.	N.E.	N.E.	N.E.
n-Butyl Acetate	123-86-4	20.0	50 ppm	150 ppm	150 ppm	N.E.
Propane	74-98-6	15.0	N.E.	N.E.	1000 ppm	N.E.
Hydrotreated Light Distillate	64742-47-8	15.0	N.E.	N.E.	N.E.	N.E.
Aluminum Flake	7429-90-5	10.0	1 mg/m3	N.E.	15 mg/m3	N.E.
n-Butane	106-97-8	5.0	N.E.	1000 ppm	N.E.	N.E.
Stoddard Solvent	8052-41-3	5.0	100 ppm	N.E.	500 ppm	N.E.
Xylenes (o-, m-, p- isomers)	1330-20-7	5.0	100 ppm	150 ppm	100 ppm	N.E.
Zinc Oxide	1314-13-2	5.0	2 mg/m3	10 mg/m3	5 mg/m3	N.E.
Solvent Naphtha, Light Aromatic	64742-95-6	5.0	N.E.	N.E.	N.E.	N.E.
Ethylbenzene	100-41-4	1.0	20 ppm	N.E.	100 ppm	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use explosion-proof ventilation equipment. Provide general dilution of local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance:	Aerosolized Mist	Physical State:	Liquid
Odor:	Solvent Like	Odor Threshold:	N.E.
Relative Density:	1.212	pH:	N.A.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Slight	Partition Coefficient, n-octanol/ water:	N.D.
Decomposition Temp., °C:	N.D.	Explosive Limits, vol%:	0.8 - 9.5
Boiling Range, °C:	-37 - 204	Flash Point, °C:	-96
Flammability:	Supports Combustion	Auto-ignition Temp., °C:	N.D.
Evaporation Rate:	Faster than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Flammable hydrogen gas will evolve when product comes in contact with water or damp air. Heat will be generated. The amount of heat generated will depend upon the volume of material in contact. Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes Serious Eye Irritation

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation. Allergic reactions are possible.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. IARC lists Ethylbenzene as a possible human carcinogen (group 2B). May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
7440-66-6	Zinc	630 mg/kg Rat	N.E.	N.E.
123-86-4	n-Butyl Acetate	10768 mg/kg Rat	>17600 mg/kg Rabbit	> 21 mg/L Rat
64742-47-8	Hydrotreated Light Distillate	>5000 mg/kg Rat	>2000 mg/kg Rabbit	>5000 mg/L Rat
106-97-8	n-Butane	N.E.	N.E.	658 mg/L Rat
1330-20-7	Xylenes (o-, m-, p- isomers)	3500 mg/kg Rat	>4350 mg/kg Rabbit	29.08 mg/L Rat
1314-13-2	Zinc Oxide	>5000 mg/kg Rat	N.E.	N.E.
64742-95-6	Solvent Naphtha, Light Aromatic	8400 mg/kg Rat	>2000 mg/kg Rabbit	N.E.
100-41-4	Ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.4 mg/L Rat

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Do not incinerate closed containers. This product as supplied is a USEPA defined ignitable hazardous waste. Dispose of unusable product as a hazardous waste (D001) in accordance with local, state, and federal regulation.

14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
UN Number:	N.A.	1950	1950	N.A.
Proper Shipping Name:	Paint Products in Limited Quantities	Aerosols	Aerosols	Paint Products in Limited Quantities
Hazard Class:	N.A.	2.1	2.1	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	Yes	Yes	Yes	Yes

15. Regulatory Information

U.S. Federal Regulations:**CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

No Information

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Zinc	7440-66-6
Aluminum Flake	7429-90-5
Xylenes (o-, m-, p- isomers)	1330-20-7
Zinc Oxide	1314-13-2
Ethylbenzene	100-41-4

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Information**HMIS RATINGS**

Health: 2* Flammability: 4 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 4 Instability: 0

VOLATILE ORGANIC COMPOUNDS, g/L: 613

SDS REVISION DATE: 3/13/2018

REASON FOR REVISION: Regulatory Formula Source Changed
Product Composition Changed
Substance and/or Product Properties Changed in Section(s):
01 - Identification
02 - Hazard Identification
15 - Regulatory Information
16 - Other Information
Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

MSDS C2209

ITEM: 6YH30 - Spray Paint, Machinery Gray, 12 oz.

DELIVERY: 6298938119

HU NUMBER: U555318921

MATERIAL SAFETY DATA SHEET (MSDS)

This MSDS should be attached or kept with the respective product with which it is associated.

MATERIAL SAFETY DATA SHEET - C2209

Associated Grainger Items
6YH30

MATERIAL SAFETY DATA SHEET

24 HOUR ASSISTANCE:
1-847-367-7700
RUST-OLEUM CORP.

WWW.RUSTOLEUM.COM

-----SECTION 1 - CHEMICAL PRODUCT / COMPANY INFORMATION -----

PRODUCT NAME: IC SSPR 6PK GLOSS MACHINE GRAY

IDENTIFICATION NUMBER: 202214

PRODUCT USE/CLASS: TOPCOAT/AEROSOL

SUPPLIER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USAMANUFACTURER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

PREPARER: REGULATORY DEPARTMENT

REVISION DATE: 12/02/2010

-----SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS -----

CHEMICAL NAME	CAS NUMBER	WEIGHT	ACGIH	ACGIH	OSHA	OSHA
% LESS THAN	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING		
ACETONE	67-64-1	35.0	500 PPM	750 PPM	1000 PPM	N.E.
LIQUEFIED PETROLEUM GAS	68476-86-8	30.0	N.E.	N.E.	N.E.	N.E.
NAPHTHA	8032-32-4	10.0	N.E.	N.E.	N.E.	N.E.
XYLENE	1330-20-7	10.0	100 PPM	150 PPM	100 PPM	N.E.
TITANIUM DIOXIDE	13463-67-7	5.0	10	15 MG/M3 (TOTAL DUST)	N.E.	N.E.
MINERAL SPIRITS	64742-88-7	5.0	100 PPM	N.E.	100 PPM	N.E.
ETHYLBENZENE	100-41-4	5.0	100 PPM	125 PPM	100 PPM	N.E.
CARBON BLACK	1333-86-4	1.0	3.5	N.E.	3.5 MG/M3	N.E.

-----SECTION 3 - HAZARDS IDENTIFICATION -----

EMERGENCY OVERVIEW:
CONTENTS UNDER PRESSURE. HARMFUL IF INHALED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. HARMFUL IF SWALLOWED. EXTREMELY FLAMMABLE LIQUID AND VAPOR.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES EYE IRRITATION.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:
PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION.EFFECTS OF OVEREXPOSURE - INHALATION:
HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. HARMFUL IF INHALED.EFFECTS OF OVEREXPOSURE - INGESTION:
ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. SUBSTANCE MAY BE HARMFUL IF SWALLOWED.EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:
CONTAINS TITANIUM DIOXIDE. TITANIUM DIOXIDE IS LISTED AS A GROUP 2B-"POSSIBLY CARCINOGENIC TO HUMANS" BY IARC. SIGNIFICANT EXPOSURE IS NOT ANTICIPATED DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF TITANIUM DIOXIDE IN THE FORMULA.

IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL 6YH30

CONTAINS CARBON BLACK. CHRONIC INFLAMMATION, LUNG FIBROSIS, AND LUNG TUMORS HAVE BEEN OBSERVED IN SOME RATS EXPERIMENTALLY EXPOSED FOR LONG PERIODS OF TIME TO EXCESSIVE CONCENTRATIONS OF CARBON BLACK AND SEVERAL INSOLUBLE FINE DUST PARTICLES. TUMORS HAVE NOT BEEN OBSERVED IN OTHER ANIMAL SPECIES (I.E., MOUSE AND HAMSTER) UNDER SIMILAR CIRCUMSTANCES AND STUDY CONDITIONS. EPIDEMIOLOGICAL STUDIES OF NORTH AMERICAN WORKERS SHOW NO EVIDENCE OF CLINICALLY SIGNIFICANT ADVERSE HEALTH EFFECTS DUE TO

OCCUPATIONAL EXPOSURE TO CARBON BLACK.

CARBON BLACK IS LISTED AS A GROUP 2B-"POSSIBLY CARCINOGENIC TO HUMANS" BY IARC AND IS PROPOSED TO BE LISTED AS A4-"NOT CLASSIFIED AS A HUMAN CARCINOGEN" BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS. SIGNIFICANT EXPOSURE IS NOT ANTICIPATED DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF CARBON BLACK IN THE FORMULA.

PRIMARY ROUTE(S) OF ENTRY:
SKIN CONTACT, SKIN ABSORPTION, INHALATION, INGESTION, EYE CONTACT

-----SECTION 4 - FIRST AID MEASURES -----

FIRST AID - EYE CONTACT:
IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. DO NOT ALLOW RUBBING OF EYES OR KEEPING EYES CLOSED.FIRST AID - SKIN CONTACT:
WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.FIRST AID - INHALATION:
IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

FIRST AID - INGESTION:

ASPIRATION HAZARD:
DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

-----SECTION 5 - FIRE FIGHTING MEASURES -----

FLASH POINT: -156 F (SETAFLASH)

EXTINGUISHING MEDIA:
FILM FORMING FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOGUNUSUAL FIRE AND EXPLOSION HAZARDS:
WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK.

FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR!

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN.

SPECIAL FIREFIGHTING PROCEDURES:
EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

-----SECTION 6 - ACCIDENTAL RELEASE MEASURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:
CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

-----SECTION 7 - HANDLING AND STORAGE -----

HANDLING:
WASH THOROUGHLY AFTER HANDLING. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING VAPOR OR MIST. USE ONLY IN A WELL-VENTILATED AREA. WASH HANDS BEFORE EATING.STORAGE:
KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F.

-----SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION -----

ENGINEERING CONTROLS:
PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT.RESPIRATORY PROTECTION:
A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE. EXPOSURE LEVELS ARE NOT KNOWN, OR IN ANY OTHER CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

SKIN PROTECTION:
USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THE

MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION.

EYE PROTECTION:
USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:
REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.

HYGIENIC PRACTICES:
WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING.

-----SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -----

VAPOR DENSITY: HEAVIER THAN AIR

ODOR: SOLVENT LIKE

APPEARANCE: AEROSOLIZED MIST

EVAPORATION RATE: FASTER THAN ETHER

SOLUBILITY IN H₂O: SLIGHT

FREEZE POINT: ND

SPECIFIC GRAVITY: 0.756

pH: NE

PHYSICAL STATE: LIQUID

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

-----SECTION 10 - STABILITY AND REACTIVITY -----

CONDITIONS TO AVOID:
AVOID TEMPERATURES ABOVE 120 DEG. F. AVOID ALL POSSIBLE SOURCES OF IGNITION.

INCOMPATIBILITY:
INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION:
WHEN HEATED TO DECOMPOSITION, IT EMITS ACRID SMOKE AND IRRITATING FUMES. BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

-----SECTION 11 - TOXICOLOGICAL INFORMATION -----

CHEMICAL NAME	LD50	LC50
ACETONE	5800 MG/KG (RAT)	50100 MG/M3 (RAT, 8HR)
LIQUEFIED PETROLEUM GAS	N.E.	N.E.
NAPHTHA	>5000 MG/KG (RAT, ORAL) N.E.	
XYLENE	4300 MG/KG (RAT, ORAL)	5000 PPM (RAT, INHALATION, 4HR)
TITANIUM DIOXIDE	>7500 MG/KG (RAT, ORAL) N.E.	
MINERAL SPIRITS	>5000 MG/KG (RAT, ORAL)	>1400 PPM (RAT, INHALATION, 4HR)
ETHYLBENZENE	3500 MG/KG (RAT, ORAL)	N.E.
CARBON BLACK	>8000 MG/KG (RAT, ORAL) N.E.	

-----SECTION 12 - ECOLOGICAL INFORMATION -----

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

-----SECTION 13 - DISPOSAL INFORMATION -----

DISPOSAL INFORMATION:
DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

-----SECTION 14 - TRANSPORTATION INFORMATION -----

DOMESTIC (USDOT) INTERNATIONAL (IMDG) AIR (IATA)

PROPER SHIPPING NAME	CONSUMER COMMODITY	AEROSOLS	AEROSOLS
HAZARD CLASS	ORM-D	2.1	2.1
UN NUMBER	N.A.	UN1950	UN1950
PACKING GROUP	N.A.	N.A.	N.A.
LIMITED QUANTITY	NO	YES	YES

-----SECTION 15 - REGULATORY INFORMATION -----

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:
IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD, PRESSURIZED GAS HAZARD

SARA SECTION 313:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS NUMBER
XYLENE	1330-20-7
ETHYLBENZENE	100-41-4

TOXIC SUBSTANCES CONTROL ACT:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:
THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT.

CHEMICAL NAME	CAS NUMBER
MODIFIED ALKYD	PROPRIETARY

PENNSYLVANIA RIGHT-TO-KNOW:
THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%.

CHEMICAL NAME	CAS NUMBER
MODIFIED ALKYD	PROPRIETARY

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS:
THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS:
ABS
D2A
D2B

-----SECTION 16 - OTHER INFORMATION -----

NFPA RATINGS:
HEALTH 2
FLAMMABILITY 4
INSTABILITY 0

VOLATILE ORGANIC COMPOUNDS, G/L: 515

REASON FOR REVISION: REGULATORY UPDATE

LEGEND:
N.A. - NOT APPLICABLE
N.E. - NOT ESTABLISHED
N.D. - NOT DETERMINED

RUST-OLEUM CORPORATION BELIEVES, TO THE BEST OF ITS KNOWLEDGE, INFORMATION AND BELIEF, THE INFORMATION CONTAINED HEREIN TO BE ACCURATE AND RELIABLE AS OF THE DATE OF THIS MATERIAL SAFETY DATA SHEET. HOWEVER, BECAUSE THE CONDITIONS OF HANDLING, USE, AND STORAGE OF THESE MATERIALS ARE BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY OR LIABILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE INCURRED BY THE USE OF THESE MATERIALS. RUST-OLEUM CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OR RELIABILITY OF THE DATA OR RESULTS OBTAINED FROM THEIR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. THE INFORMATION AND RECOMMENDATIONS IN THIS MATERIAL SAFETY DATA SHEET ARE OFFERED FOR THE USERS' CONSIDERATION AND EXAMINATION. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE FINAL SUITABILITY OF THIS INFORMATION AND TO COMPLY WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.

☐ Close this window

MSDS

Common Name: IC SSPR GLOSS FLUORESCENT PINK, 1659830**Manufacturer:** RUST-OLEUM**MSDS Revision Date:** 8/25/2014**MSDS Format:** GHS-US**Grainger Item Number(s):** 6KP08**Manufacturer Model Number(s):**

MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

- [1. IDENTIFICATION](#)
- [2. HAZARD IDENTIFICATION](#)
- [3. COMPOSITION/INFORMATION ON INGREDIENTS](#)
- [4. FIRST-AID MEASURES](#)
- [5. FIRE-FIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL INFORMATION](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION](#)

DATE PRINTED: 8/25/2014

SAFETY DATA SHEET

RUST-OLEUM CORPORATION

TRUSTED QUALITY SINCE 1921

WWW.RUSTOLEUM.COM

1. IDENTIFICATION



PRODUCT NAME: IC SSPR GLOSS FLUORESCENT PINK

PRODUCT IDENTIFIER: 1659830

PRODUCT USE/CLASS: AEROSOL

REVISION DATE: 8/25/2014

SUPERCEDES DATE: NEW SDS

SUPPLIER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY

VERNON HILLS IL 60061
USA

MANUFACTURER:
RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS IL 60061
USA

PREPARER: REGULATORY DEPARTMENT

EMERGENCY TELEPHONE:
24 HOUR HOTLINE: 84 -36 - 00

2. HAZARD IDENTIFICATION



EMERGENCY OVERVIEW:

HARMFUL IF SWALLOWED. EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. CONTENTS UNDER PRESSURE. HARMFUL IF INHALED. MAY AFFECT THE NERVOUS SYSTEM CAUSING DIZZINESS HEADACHE OR NAUSEA. MAY CAUSE EYE SKIN OR RESPIRATORY TRACT IRRITATION. KEEP OUT OF REACH OF CHILDREN. HARMFUL IF INHALED. CAUSES EYE IRRITATION. USE VENTILATION NECESSARY TO KEEP EXPOSURES BELOW RECOMMENDED EXPOSURE LIMITS IF ANY. VAPOR HARMFUL. CAUSES EYE SKIN NOSE AND THROAT IRRITATION.

CLASSIFICATION:

SYMBOLS OF PRODUCT:
EXCLAMATION MARK
FLAME
HEALTH HAZARD

SIGNAL WORD: DANGER

GHS HAZARD STATEMENTS:

FLAMMABLE AEROSOL CATEGORY 1:
H222: EXTREMELY FLAMMABLE AEROSOL.

FLAMMABLE LIQUID CATEGORY 1:
H224: EXTREMELY FLAMMABLE LIQUID AND VAPOUR.

ACUTE TOXICITY ORAL CATEGORY 5:
H303: MAY BE HARMFUL IF SWALLOWED.

ACUTE TOXICITY DERMAL CATEGORY 5:
H313: MAY BE HARMFUL IN CONTACT WITH SKIN.

SKIN IRRITATION CATEGORY 2:
H315: CAUSES SKIN IRRITATION.

EYE IRRITATION CATEGORY 2:
H319: CAUSES SERIOUS EYE IRRITATION.

ACUTE TOXICITY INHALATION CATEGORY 4:
H332: HARMFUL IF INHALED.

STOT SINGLE EXPOSURE CATEGORY 3 RTI:
H335: MAY CAUSE RESPIRATORY IRRITATION.

STOT SINGLE EXPOSURE CATEGORY 3 NE:
H336: MAY CAUSE DROWSINESS OR DIZZINESS.

ASPIRATION HAZARD CATEGORY 2:
H305: MAY BE HARMFUL IF SWALLOWED AND ENTERS AIRWAYS.

EYE IRRITATION CATEGORY 2 :

H320: CAUSES EYE IRRITATION.

FLAMMA LE AEROSOL CATEGORY 1:

H280: CONTAINS GAS UNDER PRESSURE MAY EXPLODE IF HEATED

GHS PRECAUTIONARY STATEMENTS:

P211: DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

P220: KEEP/STORE AWAY FROM CLOTHING/.../COMBUSTIBLE MATERIALS.

P235: KEEP COOL.

P251:

PRESSURIZED CONTAINER: DO NOT PIERCE OR TURN EVEN AFTER USE.

P305: FIGHT FIRE REMOTELY DUE TO THE RISK OF EXPLOSION.

P102: KEEP OUT OF REACH OF CHILDREN.

P103: READ LABEL BEFORE USE.

P202:

DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

P234: KEEP ONLY IN ORIGINAL CONTAINER.

P260: DO NOT BREATHE DUST/FUME/GAS/MIST/VAPOURS/SPRAY.

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPOURS/SPRAY.

P262: DO NOT GET IN EYES ON SKIN OR ON CLOTHING.

P264: WASH ... THOROUGHLY AFTER HANDLING.

P200: DO NOT EAT DRINK OR SMOKE WHEN USING THIS PRODUCT.

P201: USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

P203: AVOID RELEASE TO THE ENVIRONMENT.

P280:

WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

P281: USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED.

P285: IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION.

P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

P351: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES.

P304: FIGHT FIRE WITH NORMAL PRECAUTIONS FROM A REASONABLE DISTANCE.

P402: STORE IN A DRY PLACE.

P210: KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES. - NO SMOKING.

P410 P412:

PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING
50 DEG. C / 122 DEG. F.

P240: GROUND/ UNDO CONTAINER AND RECEIVING EQUIPMENT.

P241: USE EXPLOSION-PROOF ELECTRICAL/VENTILATING/LIGHTING/ .../ EQUIPMENT.

P242: USE ONLY NON-SPARKING TOOLS.

P243: TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE.

P303 P361 P353:
 IF ON SKIN OR HAIR :
 REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH
 WATER/SHOWER.

P308 P313:
 IN CASE OF FIRE: USE ... FOR EXTINCTION.

P403 P235: STORE IN A WELL-VENTILATED PLACE. KEEP COOL.

P501: DISPOSE OF CONTENTS/CONTAINER TO ...

P321: SPECIFIC TREATMENT SEE ... ON THIS LABEL.

P352: WASH WITH PLENTY OF SOAP AND WATER.

P362: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE.

P332 P313:
 IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ATTENTION.

P305 P351 P338:
 IF IN EYES:
 RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES IF
 PRESENT AND EASY TO DO. CONTINUE RINSING.

P333 P313:
 IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

P304 P340:
 IF INHALED:
 REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR
 BREATHING.

P405: STORE LOCKED UP.

P403 P233:
 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P302 P350:
 IF ON SKIN: GENTLY WASH WITH PLENTY OF SOAP AND WATER.

3. COMPOSITION/INFORMATION ON INGREDIENTS



HAZARDOUS SUBSTANCES:

CHEMICAL NAME	CAS-NO.	WT. RANGE	GHS SYMBOLS	GHS STATEMENTS
LIQUEFIED PETROLEUM GAS	684 6-86-8	10-25		
NAPHTHA HYDROTREATED HEAVY	64 42-48-9	10-25		
ARIUM SULFATE	2 -43-	10-25		
MINERAL SPIRITS	64 42-88-	10-25	GHS06	H331
LIMESTONE	131 -65-3	2.5-10		
ACETONE	6 -64-1	2.5-10	GHS02	H225
HYDROTREATED LIGHT DISTILLATE	64 42-4 -8	2.5-10	GHS06	H331
CRYSTALLINE SILICA	14808-60-	0.1-1.0	GHS0	H302

THE TEXT FOR GHS HAZARD STATEMENTS SHOWN ABOVE IF ANY IS GIVEN IN THE "16. OTHER INFORMATION" SECTION.

4. FIRST-AID MEASURES



FIRST AID - EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. DO NOT ALLOW RUNNING OF EYES OR KEEPING EYES CLOSED.

FIRST AID - SKIN CONTACT:

WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY IN BREATHING LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED GET MEDICAL ASSISTANCE IMMEDIATELY. REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT USE MOUTH-TO-MOUTH RESUSCITATION.

FIRST AID - INGESTION:

ASPIRATION HAZARD:

DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION. IF SWALLOWED GET MEDICAL ATTENTION.

5. FIRE-FIGHTING MEASURES



EXTINGUISHING MEDIA:

ALCOHOL FILM FORMING FOAM CARBON DIOXIDE DRY CHEMICAL DRY SAND WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

FLASH POINT IS LESS THAN 20 DEG. F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR

WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT ELECTRICAL EQUIPMENT SPARKS AND OPEN FLAME. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE ERUPTION OF THE CAN. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT DUE TO BUILDUP OF STEAM. NO UNUSUAL FIRE OR EXPLOSION HAZARDS NOTED.

SPECIAL FIREFIGHTING PROCEDURES:

EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE. FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION OR EXPLOSION. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. CONTAINERS MAY EXPLODE WHEN HEATED.

6. ACCIDENTAL RELEASE MEASURES



STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. REMOVE ALL SOURCES OF IGNITION VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL STATE PROVINCIAL AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. ISOLATE THE HAZARD AREA AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL. VENTILATE AREA ISOLATE SPILLED MATERIAL AND REMOVE WITH INERT ABSORBENT. DISPOSE OF CONTAMINATED

A SOURCE CONTAINER AND UNUSED CONTENTS IN ACCORDANCE WITH LOCAL STATE AND FEDERAL REGULATIONS.

7. HANDLING AND STORAGE



HANDLING:

WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. USE ONLY IN A WELL-VENTILATED AREA. FOLLOW ALL MSDS/LOCAL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING FUMES VAPORS OR MIST. REMOVE CONTAMINATED CLOTHING AND LAUNDRER BEFORE REUSE. USE ONLY WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES SKIN AND CLOTHING.

STORAGE:

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT ELECTRICAL EQUIPMENT SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F. PRODUCT SHOULD BE STORED IN TIGHTLY SEALED CONTAINERS AND PROTECTED FROM HEAT MOISTURE AND FOREIGN MATERIALS. STORE IN A DRY WELL VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT SPARKS FLAME AND SOURCES OF IGNITION. AVOID EXCESS HEAT.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION



CHEMICAL NAME	CAS-NO.	WEIGHT	LESS THAN
LIQUEFIED PETROLEUM GAS	684 6-86-8	30.0	
NAPHTHA HYDROTREATED HEAVY	64 42-48-9	25.0	
ARIUM SULFATE	2 -43-	20.0	
MINERAL SPIRITS	64 42-88-	15.0	
LIMESTONE	131 -65-3	10.0	
ACETONE	6 -64-1	5.0	
HYDROTREATED LIGHT DISTILLATE	64 42-4 -8	5.0	
CRYSTALLINE SILICA	14808-60-	1.0	

CHEMICAL NAME	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
LIQUEFIED PETROLEUM GAS	N.E.	N.E.	N.E.	N.E.
NAPHTHA HYDROTREATED HEAVY	400 PPM	N.E.	400 PPM	N.E.
ARIUM SULFATE	10 MG/M3	N.E.	15 MG/M3 ☐TOTAL DUST☐	N.E.
MINERAL SPIRITS	100 PPM	N.E.	100 PPM	N.E.
LIMESTONE	N.E.	N.E.	15 MG/M3 ☐TOTAL DUST☐	N.E.
ACETONE	500 PPM	50 PPM	1000 PPM	N.E.
HYDROTREATED LIGHT DISTILLATE	200 MG/M3	N.E.	N.E.	N.E.

CRYSTALLINE SILICA 0.025 N.E. 0.1 MG/M3 N.E.
 MG/M3 ☐RESPIRABLE
 ☐RESPIRABLE

PERSONAL PROTECTION:

ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES LOCAL EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE FLOSION-PROOF VENTILATION EQUIPMENT. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. PROVIDE GENERAL DILUTION OF LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS.

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

SKIN PROTECTION:

USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION. USE GLOVES TO PREVENT PROLONGED SKIN CONTACT.

EYE PROTECTION:

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION. REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER GUIDANCE REGARDING TYPES OF PERSONAL PROTECTIVE EQUIPMENT AND THEIR APPLICATIONS.

HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING DRINKING OR SMOKING. REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND LAUNDRY BEFORE REUSE.

9. PHYSICAL AND CHEMICAL PROPERTIES



APPEARANCE: AEROSOLIZED MIST

PHYSICAL STATE: LIQUID

ODOR: SOLVENT LIKE

ODOR THRESHOLD: ND

RELATIVE DENSITY: 0.864

PH: NE

FREEZE POINT DEG. C: ND

VISCOSITY: N.D.

SOLUBILITY IN WATER: SLIGHT

PARTITION COEFFICIENT N-OCTANOL/WATER: NO INFORMATION

DECOMPOSITION TEMP. DEG. C: NO INFORMATION

OILING RANGE DEG. C: -34 - 415

EXPLOSIVE LIMITS VOL : 1.0 - 13.1

FLAMMABILITY: DOES NOT SUPPORT COMBUSTION

FLASH POINT DEG. C: 93

EVAPORATION RATE: FASTER THAN ETHER

AUTO-IGNITION TEMP. DEG. C: NO INFORMATION

VAPOR DENSITY: HEAVIER THAN AIR

VAPOR PRESSURE: ND

SEE "OTHER INFORMATION" SECTION FOR A REVISION LEGEND

10. STABILITY AND REACTIVITY



CONDITIONS TO AVOID:

AVOID TEMPERATURES ABOVE 120 DEG. F. AVOID ALL POSSIBLE SOURCES OF IGNITION. AVOID CONTACT WITH STRONG ACID AND STRONG BASES.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS STRONG ACIDS AND STRONG ALKALIES.

Hazardous Decomposition:

May open flame carbon monoxide and carbon dioxide. When heated to decomposition it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide carbon dioxide and formaldehyde.

Hazardous Polymerization: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

Stability: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

11. TOXICOLOGICAL INFORMATION



EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES SERIOUS EYE IRRITATION

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:

SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. MAY CAUSE SKIN IRRITATION. ALLERGIC REACTIONS ARE POSSIBLE.

EFFECTS OF OVEREXPOSURE - INHALATION:

HARMFUL IF INHALED. HIGH GAS VAPOR MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. AVOID BREATHING FUMES SPRAY VAPORS OR MIST. HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES NOSE THROAT AND LUNGS. PROLONGED OR EXCESSIVE INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION.

EFFECTS OF OVEREXPOSURE - INGESTION:

ASPIRATION HARMFUL IF SWALLOWED CAN ENTER LUNGS AND CAUSE DAMAGE. HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:

MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER E.G. NARCOSIS INVOLVING A LOSS OF COORDINATION WEAKNESS FATIGUE MENTAL CONFUSION AND BLURRED VISION AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. HIGH CONCENTRATIONS MAY LEAD TO CENTRAL NERVOUS SYSTEM EFFECTS DROWSINESS DIZZINESS NAUSEA HEADACHES PARALYSIS AND BLURRED VISION AND/OR DAMAGE.

PRIMARY ROUTES OF ENTRY:

EYE CONTACT INGESTION INHALATION SKIN ABSORPTION SKIN CONTACT

ACUTE TOXICITY VALUES:

THE ACUTE EFFECTS OF THIS PRODUCT HAVE NOT BEEN TESTED. DATA ON INDIVIDUAL COMPONENTS ARE TABULATED BELOW:

CAS-NO.	CHEMICAL NAME	ORAL LD50	DERMAL LD50	VAPOR LC50
64-42-48-9	NAPHTHA HYDROTREATED HEAVY	5000 MG/KG RAT	3160 MG/KG RAT	N.I.
64-42-88-	MINERAL SPIRITS	5000 MG/KG RAT	3000 MG/KG RAT	5.28 MG/L RAT
64-42-4-8	HYDROTREATED LIGHT DISTILLATE	5000 MG/KG RAT	2000 MG/KG RAT	5.2 MG/L RAT
14808-60-	CRYSTALLINE SILICA	500 MG/KG RAT	N.I.	N.I.

N.I. - NO INFORMATION

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:

PRODUCT IS A Mixture OF LISTED COMPONENTS. PRODUCT IS A Mixture OF LISTED COMPONENTS.

13. DISPOSAL INFORMATION

DISPOSAL INFORMATION:

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER WATERWAYS WASTEWATER SOIL STORM DRAINS OR SEWER SYSTEMS.

14. TRANSPORT INFORMATION

	DOMESTIC USDOT	INTERNATIONAL IMDG	AIR IATA	TDG CANADA
UN NUMBER	N.A.	1950	1950	N.A.
PROPER SHIPPING NAME	PAINT PRODUCTS IN LIMITED QUANTITIES	AEROSOLS	AEROSOLS	PAINT PRODUCTS IN LIMITED QUANTITIES
HAZARD CLASS	N.A.	2.1	2.1	N.A.
PACKING GROUP	N.A.	N.A.	N.A.	N.A.
LIMITED QUANTITY	YES	YES	YES	YES

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA HAZARD CATEGORIES

PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 SARA TITLE III AND IS CONSIDERED UNDER APPLICABLE DEFINITIONS TO MEET THE FOLLOWING CATEGORIES:
FIRE HAZARD PRESSURE HAZARD ACUTE HEALTH HAZARD CHRONIC HEALTH HAZARD

SARA SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 312:
NO SARA 313 COMPONENTS EXIST IN THIS PRODUCT.

TOXIC SUBSTANCES CONTROL ACT:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12 IF EXPORTED FROM THE UNITED STATES:
NO TSCA COMPONENTS EXIST IN THIS PRODUCT.

INVENTORY INFORMATION:

COUNTRY	VALUE
USA TSCA	NO INFORMATION
CANADA DSL	NO INFORMATION
MEXICO INSQ	NO INFORMATION
EUROPE EINECS	NO INFORMATION
JAPAN ENCS	NO INFORMATION
PHILIPPINES PICCS	NO INFORMATION
CHINA IECSC	NO INFORMATION
AUSTRALIA AICS	NO INFORMATION
KOREA KECI	NO INFORMATION
NEW ZEALAND NZ IOCL	NO INFORMATION

NO INFORMATION

CALIFORNIA PROPOSITION 65:

WARNING:

THIS PRODUCT CONTAINS A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

CHEMICAL NAME	CAS-NO.
CRYSTALLINE SILICA	14808-60-

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS:

WARNING:

THIS PRODUCT CONTAINS A SUBSTANCE KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

NO PROPOSITION 65 REPRODUCTIVE TOXINS EXIST IN THIS PRODUCT.

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS:

THIS SDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

16. OTHER INFORMATION

HMIS RATINGS:

HEALTH 2□
 FLAMMABILITY 4
 PHYSICAL HAZARD 0
 PERSONAL PROTECTION

CANADIAN WHMIS CLASS:

A 5
 D2A

NFPA RATINGS:

HEALTH 2
 FLAMMABILITY 4
 INSTABILITY 0

VOLATILE ORGANIC COMPOUNDS G/L: 553

MSDS REVISION DATE: 8/25/2014

REASON FOR REVISION: NO INFORMATION

LEGEND:

N.A. - NOT APPLICABLE
 N.E. - NOT ESTABLISHED
 N.D. - NOT DETERMINED

TEXT FOR GHS HAZARD STATEMENTS SHOWN IN SECTION 3 DESCRIBING EACH INGREDIENT:

H225: HIGHLY FLAMMABLE LIQUID AND VAPOUR.
 H302: HARMFUL IF SWALLOWED.
 H331: TOXIC IF INHALED.

ICONS FOR GHS PICTOGRAMS SHOWN IN SECTION 3 DESCRIBING EACH INGREDIENT:

GHS02: FLAME
 GHS06: SKULLS AND CROSS BONES
 GHS08: HEALTH HAZARD

RUST-OLEUM CORPORATION BELIEVES TO THE BEST OF ITS KNOWLEDGE INFORMATION AND BELIEVES THE INFORMATION CONTAINED HEREIN TO BE ACCURATE AND RELIABLE AS OF THE DATE OF THIS SAFETY DATA SHEET. HOWEVER BECAUSE THE CONDITIONS OF HANDLING USE AND STORAGE OF THESE MATERIALS ARE BEYOND OUR CONTROL WE ASSUME NO RESPONSIBILITY OR LIABILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE INCURRED BY THE USE OF THESE MATERIALS. RUST-OLEUM CORPORATION MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OR RELIABILITY OF THE DATA OR RESULTS OBTAINED FROM THEIR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. THE INFORMATION AND RECOMMENDATIONS IN THIS MATERIAL SAFETY DATA SHEET ARE OFFERED FOR THE USER'S CONSIDERATION AND EVALUATION. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE FINAL SUITABILITY OF THIS INFORMATION AND TO COMPLY WITH ALL APPLICABLE INTERNATIONAL FEDERAL STATE AND LOCAL LAWS AND REGULATIONS.

Safety Data Sheet

92166 Invisible Glass®

Stoner

Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated
1070 Robert Fulton Hwy.
Quarryville, PA 17566
1-800-227-5538

Product Name: Invisible Glass®
Product Code: 92166
Product Use: Glass Cleaner
24-hour emergency phone: 1-800-424-9300 [CHEMTREC]

2. HAZARD IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification

Flammable Liquid Category 2
Serious Eye Damage/Eye Irritation Category 2A

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapour.
Causes serious eye irritation.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating and lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
P264 - Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
P370+P378 - In case of fire: Use proper media to extinguish.

Storage

Keep container tightly closed.
Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT

CAS

Percent

Water

7732-18-5

80 - 100

Proprietary hydrocarbon blend

Mixture

1-20

HMIS® III* HAZARDOUS WARNINGS:

Health: 2

Flammability: 3

Physical: 0

Personal Protective Equipment: See Section 8

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes:	Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.
Skin Contact:	In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. Seek medical attention if symptoms persist. Wash clothing before reuse.
Ingestion:	Contact a physician, medical facility, or poison control center immediately.
Inhalation:	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Continue your efforts until help arrives or the victim starts to breathe on his own. Do not leave victim alone. Seek immediate medical attention. Keep the victim warm and quiet.

NOTES TO PHYSICIAN:

No additional first aid information available. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); liver; kidney; blood forming system;

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	Product is water based material, containing minor amounts of flammable ingredients. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point.
Fire Fighting Instructions:	Use alcohol foam, water fog, dry chemical, or CO ₂ . Fire fighters should wear normal protective equipment and positive-pressure self-contained breathing apparatus. Although this product has a flash point below 200 F, it is an aqueous solution and does not sustain combustion. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Ventilate contaminated area. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling:	Do not use near ignition sources. If ventilation is not sufficient, wear proper respiratory equipment. Avoid prolonged or repeated contact with skin. Avoid prolonged or repeated breathing of vapor. Do not store containers in excessive heat or direct sunlight. Protect container against physical damage. Use with adequate ventilation. Do not use near ignition sources. Protect container against physical damage.
Storage:	Keep container tightly closed when not in use. Store in a cool, dry, well ventilated area away from all sources of ignition. Empty container may contain residues which are hazardous.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects). Local exhaust should be used in areas where exposure limits may be exceeded.
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.
Skin Protection:	The use of chemically resistant gloves is recommended if there is any possibility of prolonged or repeated liquid contact with skin.
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.

<u>COMPONENT</u>	<u>CAS #</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Water	7732-18-5	Not established	Not established	Not established
Proprietary hydrocarbon blend	Mixture	20 ppm	50 ppm	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Bulk trigger bottle	Lower Flammability Limit (%):	2.1
Appearance:	Clear Colorless	Upper Flammability Limit (%):	13
Odor:	Mild Alcohol	Vapor Pressure (PSIG @ 70°F):	No data available
Odor Threshold:	Sharp	Vapor Density [air = 1]:	> 1.0
pH:	Not applicable	Relative Density (H ₂ O=1):	0.98
Melting/Freezing Point (°F):	No data available	Solubility in Water:	Complete; 100%
Boiling Point (°F):	No data available	Partial Coefficient: n-octanol/water:	No data available
Flash Point (°F PMCC):	None	Autoignition Temperature (°F):	869
Evaporation Rate:	Not determined	Decomposition Temperature (°F):	No data available
Flammability (solid, gas):	No data available	Viscosity, dynamic (cSt):	No data available
Percent VOCs (%):	1-20		

10. STABILITY AND REACTION

Chemical Stability: Stable.
Conditions to Avoid: Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Acids. Strong oxidizing agents. Acetaldehyde. Chlorine. Ethylene oxide. Isocyanates. Strong alkalis.
Decomposition Products: Burning can produce the following combustion products: Carbon dioxide and carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Inhalation Toxicity: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Reproductive & Developmental Toxicity: No data available.

IARC Carcinogen Designation: No data available

Ingredient	CAS #
Proprietary hydrocarbon blend	Mixture

Toxicological Data

DERMAL LD50 Rabbit 220 mg/kg
ORAL LD50 GUINEA PIG 1200 mg/kg
ORAL LD50 Rat 250 mg/kg
INHALATION LC50 Rat 2900 MG/M3
INHALATION LC50 Mouse 700 ppm
INHALATION LC50 Mouse 3380 MG/M3

12. ECOLOGICAL INFORMATION

Ecological Toxicity: No data available

Mobility: No data available This material (or one of its components), dissolves in water. If it enters the soil, it will be highly mobile and may contaminate ground water.

Degradability: No data available.

Ingredient	CAS #
Proprietary hydrocarbon blend	Mixture

Toxicological Data

Aquatic LC50 (96h) MINNOW = 72860 mg/L
Aquatic LC50 (48h) Daphnia > 100 mg/L
Aquatic LC50 (96h) Algae 6500 - 13000 mg/L

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1993	Flammable Liquids, n.o.s.(contains ISOPROPANOL)†	3	II
IATA	UN1993	Flammable Liquids, n.o.s.(contains ISOPROPANOL)†	3	II
IMDG	UN1993	Flammable Liquids, n.o.s. (contains ISOPROPANOL)†	3	II

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:

COMPONENT	CAS #	% BY WEIGHT	Regulatory Body
No components listed in this section.			SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 12/04/17

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.

SAFETY DATA SHEET

Klean Strip Lacquer Thinner

Page: 1

Revision: 06/26/2017
Supersedes Revision: 05/24/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean Strip Lacquer Thinner
Company Name: W. M. Barr
2105 Channel Avenue
Memphis, TN 38113
Phone Number: (901)775-0100
Web site address: www.wmbarr.com
Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346
Information: W.M. Barr Customer Service (800)398-3892
Intended Use: Paint, stain, and varnish thinning.
Product Code: GML170, QML170, CML170, DML170, GML170P, PA12782, QML170W, GML170W, GML170HDWS, PML1701

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2
Acute Toxicity: Oral, Category 3
Acute Toxicity: Skin, Category 3
Acute Toxicity: Inhalation, Category 3
Serious Eye Damage/Eye Irritation, Category 2
Toxic To Reproduction, Category 2
Specific Target Organ Toxicity (single exposure), Category 1
Specific Target Organ Toxicity (repeated exposure), Category 2
Aspiration Toxicity, Category 1



GHS Signal Word:

Danger

GHS Hazard Phrases:

H225: Highly flammable liquid and vapor.
H301: Toxic if swallowed.
H304: May be fatal if swallowed and enters airways.
H311: Toxic in contact with skin.
H319: Causes serious eye irritation.
H331: Toxic if inhaled.
H361: Suspected of damaging fertility or the unborn child.
H370: Causes damage to organs.
H373: May cause damage to organs through prolonged or repeated exposure.

GHS Precaution Phrases:

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe gas/mist/vapors/spray.
P264: Wash hands thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P281: Use personal protective equipment as required.
P235: Keep cool.

SAFETY DATA SHEET

Klean Strip Lacquer Thinner

Page: 2

Revision: 06/26/2017

Supersedes Revision: 05/24/2017

GHS Response Phrases:


P301+310: IF SWALLOWED: Immediately P311: Call a POISON CENTER or doctor/physician.
P302+352: IF ON SKIN: Wash with plenty of soap and water.
P303+361+353: IF ON SKIN (or hair): P361: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+311: IF exposed: P311: Call a POISON CENTER or doctor/physician.
P308+313: IF exposed or concerned: Get medical attention/advice.
P314: Get medical attention/advice if you feel unwell.
P321: Specific treatment see label.
P330: Rinse mouth.
P331: Do NOT induce vomiting.
P337+313: If eye irritation persists, get medical advice/attention.
P363: Wash contaminated clothing before reuse.
P370+378: In case of fire, use dry chemical powder to extinguish.
P403+233: Store container tightly closed in well-ventilated place.
P405: Store locked up.
P501: Dispose of contents/container according to local, state and federal regulations.

GHS Storage and Disposal Phrases:

Hazard Rating System:

HEALTH	*	2
FLAMMABILITY		3
PHYSICAL		0
PPE		X

HMIS:



OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Inhalation Acute Exposure Effects:

Vapor harmful. May cause dizziness; headache; watering of eyes; irritation of respiratory tract; weakness; drowsiness; nausea; numbness in fingers, arms and legs; depression of central nervous system; loss of appetite; fatigue; hallucinations; light headedness; visual disturbances; giddiness and intoxication; sleepiness; cough and dyspnea; cold, clammy extremities; diarrhea; vomiting; dilation of pupils; spotted vision. Severe overexposure may cause convulsions; unconsciousness; coma; and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

Skin Contact Acute Exposure Effects:

May be absorbed through the skin. May cause irritation; numbness in the fingers and arms; drying of skin; and dermatitis. May cause increased severity of symptoms listed under inhalation.

Eye Contact Acute Exposure Effects:

This material is an eye irritant. May cause irritation; burns; conjunctivitis of eyes; and corneal ulcerations of the eye. Vapors may irritate eyes.

Ingestion Acute Exposure Effects:

Poison. Cannot be made non-poisonous. May be fatal or cause blindness. May cause dizziness; headache; nausea; vomiting; burning sensation in mouth, throat, and stomach; loss of coordination; depression of the central nervous system; narcosis; stupor; gastrointestinal irritation; liver, kidney, and heart damage; diarrhea; loss of appetite; coma and death. May produce symptoms listed under inhalation.

SAFETY DATA SHEET

Klean Strip Lacquer Thinner

Page: 3

Revision: 06/26/2017

Supersedes Revision: 05/24/2017

Chronic Exposure Effects:

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Prolonged or repeated contact may cause dermatitis. Prolonged skin contact may result in absorption of a harmful amount of this material. May cause conjunctivitis; gastric disturbances; insomnia; dizziness; headache; weakness; fatigue; nausea; heart palpitations; skin irritation; numbness in hands and feet; permanent central nervous system changes; some loss of memory; pancreatic damage; giddiness; visual impairment or blindness; kidney or liver damage; and death. May cause symptoms listed under inhalation.

Target Organs: Central Nervous System, Liver, Kidney, Heart, Stomach, Respiratory System

Primary Routes of Entry: Inhalation, Ingestion, Skin Absorption

Medical Conditions Generally Aggravated By Exposure: Diseases of the skin, eyes, liver, kidneys, central nervous system and respiratory system.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	25.0 -35.0 %
67-64-1	Acetone {2-Propanone}	20.0 -30.0 %
NA	Petroleum Hydrocarbon Mixture (Alkanes and Cycloalkanes)	20.0 -30.0 %
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	<15.0 %
108-88-3	Toluene {Benzene, Methyl-; Toluol}	< 5.0 %
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	< 5.0 %

Additional Chemical Information

Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

Skin:

Immediately begin washing the skin thoroughly with large amounts of water and mild soap, if available, while removing contaminated clothing. Seek medical attention if irritation persists.

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush the eyes for at least 15 minutes, then seek immediate medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do not induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.

In Case of Inhalation:

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

SAFETY DATA SHEET

Klean Strip Lacquer Thinner

Page: 4

Revision: 06/26/2017

Supersedes Revision: 05/24/2017

In Case of Skin Contact:	IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
In Case of Eye Contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
In Case of Ingestion:	If swallowed, do NOT induce vomiting. Call a physician, hospital emergency room, or poison control center immediately. Never give anything by mouth to an unconscious person.
Signs and Symptoms Of Exposure:	See Potential Health Effects.
Note to Physician:	Poison. This product contains methanol. Methanol is metabolized to formaldehyde and formic acid. These metabolites may cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used as an antidote. Methanol is effectively removed by hemodialysis. Call your local poison control center for further information.

5. FIRE FIGHTING MEASURES

	NFPA Class IB
Flash Pt:	0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: 1 UEL: 7
Autoignition Pt:	No data.
Suitable Extinguishing Media:	Use carbon dioxide, dry powder, or foam.
Unsuitable Extinguishing Media:	Do not use a solid water stream, as this may spread the fire.
Fire Fighting Instructions:	Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.
Flammable Properties and Hazards:	No data available.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	Vapors may cause flash fire or ignite explosively. Clean up: Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. Use non-sparking tools. Use proper bonding and grounding methods for all equipment and processes. Keep out of waterways and bodies of water. Be cautious of vapors collecting in small enclosed spaces, sewers, low lying areas, confined spaces, etc. Small spills: Take up with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. Large spills: Dike far ahead of spill for later disposal. Waste Disposal: Dispose in accordance with applicable local, state and federal regulations.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.
Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty.
Dispose of empty container according to all regulations. Do not reuse this container.

Do not use this product near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Do not use in small enclosed spaces, such as basements and bathrooms. Vapors can accumulate and explode if ignited.

Do not spread this product over large surface areas because fire and health safety risks will increase dramatically.

Precautions To Be Taken in Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	PEL: 200 ppm	TLV: 200 ppm STEL: 250 ppm	No data.
67-64-1	Acetone {2-Propanone}	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.
NA	Petroleum Hydrocarbon Mixture (Alkanes and Cycloalkanes)	No data.	TLV: 1500 mg/m3	No data.
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	PEL: 400 ppm	TLV: 400 ppm	No data.
108-88-3	Toluene {Benzene, Methyl-; Toluol}	PEL: 200 ppm STEL: 500 ppm/(10min) CEIL: 300 ppm	TLV: 50 ppm	No data.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	PEL: 50 ppm	TLV: 20 ppm	No data.

Respiratory Equipment (Specify Type):

For OSHA controlled work place and other regular users. Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV.

For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Eye Protection:

Protect eyes with chemical splash goggles.

Protective Gloves:

Wear gloves with as much resistance to the chemical ingredients as possible. Glove materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for additional information. Gloves contaminated with product should be discarded and not reused.

Other Protective Clothing:

Various application methods can dictate use of additional protective safety equipment,

SAFETY DATA SHEET

Klean Strip Lacquer Thinner

Page: 6

Revision: 06/26/2017

Supersedes Revision: 05/24/2017

Engineering Controls (Ventilation etc.):

such as impermeable aprons, etc., to minimize exposure.

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - Stop - ventilation is inadequate. Leave area immediately.

Work/Hygienic/Maintenance Practices:

Do not use in small enclosed spaces, such as basements and bathrooms.

A source of clean water should be available in the work area for flushing eyes and skin.

Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use.

Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States:	[] Gas [X] Liquid [] Solid
Appearance and Odor:	Water White / Free and Clear
Melting Point:	No data.
Boiling Point:	133.00 F
Autoignition Pt:	No data.
Flash Pt:	0.00 F Method Used: Setaflash Closed Cup (Rapid Setaflash)
Explosive Limits:	LEL: 1 UEL: 7
Specific Gravity (Water = 1):	0.7742 - 0.7942
Density:	6.518 LB/GL
Vapor Pressure (vs. Air or mm Hg):	115 MM HG at 68.0 F
Vapor Density (vs. Air = 1):	> 1
Evaporation Rate:	> 1
Solubility in Water:	Slight
Viscosity:	Water thin
Percent Volatile:	100.0 % by weight.
VOC / Volume:	600.0000 G/L

10. STABILITY AND REACTIVITY

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	No data available.
Incompatibility - Materials To Avoid:	Incompatible with strong oxidizing agents, strong caustics, hydrogen peroxide, and nitrates.
Hazardous Decomposition or Byproducts:	Decomposition may produce carbon monoxide; carbon dioxide
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not been tested as a whole. Information below will be for individual ingredients. Refer to section 2 for acute and chronic effects.

CAS# 67-64-1:

Standard Draize Test, Eyes, Species: Rabbit, 20.00 MG, Severe.

Result:

Behavioral: Change in motor activity (specific assay).

Behavioral: Alteration of classical conditioning.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 141-78-6:

Standard Draize Test, Eyes, Human, 400.0 PPM.

Result:

Liver: Hepatitis (hepatocellular necrosis), zonal.

- Journal of Industrial Hygiene and Toxicology, Vol/p/yr: 25,282, 1943

CAS# 108-88-3:

Reproductive Effects:, TCLO, Inhalation, Rat, 800.0 MG/M3, 6 H, female 14-20 day(s) after conception.

Result:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Effects on Newborn: Behavioral.

- Brazilian Journal of Medical and Biological Research., Vol/p/yr: 23,533, 1990

Standard Draize Test, Eyes, Species: Rabbit, 2.000 MG, 24 H, Severe.

Result:

Effects on Embryo or Fetus: Other effects to embryo.

Specific Developmental Abnormalities: Eye, ear.

- Prehled Prumyslove Toxikologie, Marhold, J., Organické Latky, Prague Czechoslovakia, Vol/p/yr: -,29, 1986

CAS# 111-76-2:

Acute toxicity, LC50, Inhalation, Rat, 450.0 PPM, 4 H.

Result:

Behavioral: Ataxia.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 68,405, 1983

Acute toxicity, LD50, Skin, Species: Rabbit, 220.0 MG/KG.

Result:

Effects on Embryo or Fetus: Extra embryonic structures (e.g., placenta, umbilical cord).

Effects on Embryo or Fetus: Other effects to embryo.

Specific Developmental Abnormalities: Musculoskeletal system.

- Dow Chemical Company Reports., Dow Chemical USA, Health and Environment Research, Toxicology Research Lab, Midland, MI 48640, Vol/p/yr: MSD-46,

SAFETY DATA SHEET

Klean Strip Lacquer Thinner

Page: 8

Revision: 06/26/2017
Supersedes Revision: 05/24/2017

Chronic Toxicological Effects:

Acute toxicity, LD50, Oral, Rat, 250.0 mg/kg.
Result:
Lungs, Thorax, or Respiration: Changes in pulmonary vascular resistance.

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, Severe.
Result:

Effects on Newborn: Apgar score (human only).

Effects on Newborn: Other neonatal measures or effects.

Effects on Newborn: Drug dependency.

- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

Carcinogenicity/Other Information:

IARC 3: Not Classifiable as to Carcinogenicity in Humans
ACGIH A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans
ACGIH A4 - Not Classifiable as a Human Carcinogen

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.
67-64-1	Acetone {2-Propanone}	n.a.	n.a.	A4	n.a.
NA	Petroleum Hydrocarbon Mixture (Alkanes and Cycloalkanes)	n.a.	n.a.	n.a.	n.a.
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	n.a.	n.a.	n.a.	n.a.
108-88-3	Toluene {Benzene, Methyl-, Toluol}	n.a.	3	A4	n.a.
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	n.a.	3	A3	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information:

This product has not been tested as a whole. Information below will be for individual ingredients.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Dispose of in accordance with all applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Paint Related Material

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1263

Packing Group: II



Additional Transport Information:

The shipper/supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

SAFETY DATA SHEET

Klean Strip Lacquer Thinner

Page: 9

Revision: 06/26/2017
Supersedes Revision: 05/24/2017

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes
67-64-1	Acetone {2-Propanone}	No	Yes 5000 LB	No
NA	Petroleum Hydrocarbon Mixture (Alkanes and Cycloalkanes)	No	No	No
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	No	Yes 5000 LB	No
108-88-3	Toluene {Benzene, Methyl-; Toluol}	No	Yes 1000 LB	Yes
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	No	No	Yes-Cat. N230

This material meets the EPA ☒ Yes ☐ No Acute (immediate) Health Hazard
'Hazard Categories' defined ☒ Yes ☐ No Chronic (delayed) Health Hazard
for SARA Title III Sections ☒ Yes ☐ No Fire Hazard
311/312 as indicated: ☐ Yes ☒ No Sudden Release of Pressure Hazard
☐ Yes ☒ No Reactive Hazard

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	CAA HAP,ODC: HAP; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: Yes: RDTox.
67-64-1	Acetone {2-Propanone}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
NA	Petroleum Hydrocarbon Mixture (Alkanes and Cycloalkanes)	CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA PROP.65: Yes
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No
108-88-3	Toluene {Benzene, Methyl-; Toluol}	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 8A CAIR; CA PROP.65: Yes: RDTox(F)
111-76-2	Ethanol, 2-Butoxy- {Ethylene glycol n-butyl ether, (a glycol ether)}	CAA HAP,ODC: Yes - Cat.; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No

Regulatory Information: This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

16. OTHER INFORMATION

Revision Date: 06/26/2017
Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About No data available.

This Product:

Company Policy or Disclaimer: The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability

SAFETY DATA SHEET
Klean Strip Lacquer Thinner

Page: 10

Revision: 06/26/2017

Supersedes Revision: 05/24/2017

and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

SAFETY DATA SHEET

A03904004

Section 1. Identification

Product name : KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (APWA) Green

Product code : A03904004

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Manufacturer : Krylon Products Group
101 Prospect Avenue NW
Cleveland, OH 44115

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 247-3266

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
CARCINOGENICITY - Category 2
TOXIC TO REPRODUCTION (Unborn child) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 25.9%
Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 35.8%
Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 21.4%

GHS label elements

Hazard pictograms



Signal word : Danger

Date of issue/Date of revision : 12/26/2017 **Date of previous issue** : 12/22/2017

Version : 8.02

1/15

A03904004 KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (APWA) Green

Section 2. Hazards identification

Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Causes skin irritation. Suspected of damaging the unborn child. Suspected of causing cancer. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Wash hands thoroughly after handling. Pressurized container: Do not pierce or burn, even after use.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.
CAS number/other identifiers	

Ingredient name	% by weight	CAS number
Toluene	9.95	108-88-3
Propane	9.52	74-98-6
Light Aliphatic Hydrocarbon	9	64742-47-8
Butane	4.48	106-97-8
Calcium Carbonate	1.57	1317-65-3
Lt. Aliphatic Hydrocarbon Solvent	1.3	64742-89-8
Titanium Dioxide	0.32	13463-67-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Date of issue/Date of revision	: 12/26/2017	Date of previous issue	: 12/22/2017	Version	: 8.02	2/15
A03904004	KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (APWA) Green					

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 4. First aid measures

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put

Section 6. Accidental release measures

on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Section 8. Exposure controls/personal protection

Ingredient name	Exposure limits
Toluene	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 3/2016). TWA: 20 ppm 8 hours.
Propane	NIOSH REL (United States, 10/2016). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours. OSHA PEL (United States, 6/2016). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
Light Aliphatic Hydrocarbon	OSHA PEL (United States, 6/2016). TWA: 100 ppm 8 hours. TWA: 400 mg/m ³ 8 hours.
Butane	NIOSH REL (United States, 10/2016). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2016). STEL: 1000 ppm 15 minutes.
Calcium Carbonate	NIOSH REL (United States, 10/2016). TWA: 5 mg/m ³ 10 hours. Form: Respirable fraction TWA: 10 mg/m ³ 10 hours. Form: Total OSHA PEL (United States, 6/2016). TWA: 5 mg/m ³ 8 hours. Form: Respirable fraction TWA: 15 mg/m ³ 8 hours. Form: Total dust
Lt. Aliphatic Hydrocarbon Solvent Titanium Dioxide	None. ACGIH TLV (United States, 3/2016). TWA: 10 mg/m ³ 8 hours. OSHA PEL (United States, 6/2016). TWA: 15 mg/m ³ 8 hours. Form: Total dust

Occupational exposure limits (Canada)

Ingredient name	Exposure limits
toluene	CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m ³ 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 20 ppm 8 hours. CA Québec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 188 mg/m ³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.

Section 8. Exposure controls/personal protection

Propane	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 1000 ppm 8 hours. CA Québec Provincial (Canada, 1/2014). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m ³ 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 1000 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.
Solvent naphtha (petroleum), medium aliph.	CA Québec Provincial (Canada, 1/2014). TWAEV: 400 ppm 8 hours. TWAEV: 1590 mg/m ³ 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 525 mg/m ³ 8 hours.
Butane	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 600 ppm 8 hours. STEL: 750 ppm 15 minutes. CA Québec Provincial (Canada, 1/2014). TWAEV: 800 ppm 8 hours. TWAEV: 1900 mg/m ³ 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 800 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.

Occupational exposure limits (Mexico)

Ingredient name	Exposure limits
toluene	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Propane	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Butane	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.

Appropriate engineering controls

- : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Section 8. Exposure controls/personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state	: Liquid.
Color	: Not available.
Odor	: Not available.
Odor threshold	: Not available.
pH	: 7
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
Evaporation rate	: 2 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: 0.9% Upper: 9.5%
Vapor pressure	: 101.3 kPa (760 mm Hg) [at 20°C]
Vapor density	: 1 [Air = 1]
Relative density	: 0.86
Solubility	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): <0.205 cm ² /s (<20.5 cSt)
Molecular weight	: Not applicable.

Section 9. Physical and chemical properties

Aerosol product

Type of aerosol : Spray
Heat of combustion : 13.726 kJ/g

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
				100 milligrams	
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Section 11. Toxicological information

Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Propane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Light Aliphatic Hydrocarbon	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Butane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Calcium Carbonate	Category 3	Not applicable.	Respiratory tract irritation
Lt. Aliphatic Hydrocarbon Solvent	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 2	Not determined	Not determined
Propane	Category 2	Not determined	Not determined
Light Aliphatic Hydrocarbon	Category 2	Not determined	Not determined
Butane	Category 2	Not determined	Not determined
Lt. Aliphatic Hydrocarbon Solvent	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1
Propane	ASPIRATION HAZARD - Category 1
Light Aliphatic Hydrocarbon	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.

Skin contact : Causes skin irritation.

Ingestion : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	4737.1 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
Lt. Aliphatic Hydrocarbon Solvent	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS

Date of issue/Date of revision : 12/26/2017 Date of previous issue : 12/22/2017 Version : 8.02 12/15
A03904004 KRYLON® Industrial QUIK-MARK™ Water-Based Inverted Marking Paint (APWA)
Green

Section 14. Transport information

Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	- ERG No. 126	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). ERG No. 126	- ERG No. 126	-	Emergency schedules F-D, S-U

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Proper shipping name : Not available.
Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		2
Physical hazards		0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A	Calculation method
CARCINOGENICITY - Category 2	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

History

Date of printing : 12/26/2017

Date of issue/Date of revision : 12/26/2017

Date of previous issue : 12/22/2017

Version : 8.02

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

SAFETY DATA SHEET

A03405004

Section 1. Identification

Product name : KRYLON® QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent)
Fluorescent Pink

Product code : A03405004

Other means of identification : Not available.

Product type : Aerosol.

Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Manufacturer : Krylon Products Group
101 Prospect Avenue NW
Cleveland, OH 44115

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : (800) 247-3266

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
TOXIC TO REPRODUCTION (Unborn child) - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
ASPIRATION HAZARD - Category 1

Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 23.2%
Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 32.9%
Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 18.7%

GHS label elements

Hazard pictograms



Signal word : Danger

Section 2. Hazards identification

Hazard statements	: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Suspected of damaging the unborn child. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Do not breathe dust or mist. Pressurized container: Do not pierce or burn, even after use.
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.
Storage	: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Please refer to the SDS for additional information. Keep out of reach of children. Keep upright in a cool, dry place. Do not discard empty can in trash compactor.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Toluene	9.77	108-88-3
Propane	9.52	74-98-6
Light Aliphatic Hydrocarbon	8	64742-47-8
Butane	4.48	106-97-8
Lt. Aliphatic Hydrocarbon Solvent	1.17	64742-89-8

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Section 4. First aid measures

- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

- Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Section 6. Accidental release measures

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	Exposure limits
Toluene	OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m ³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m ³ 15 minutes. ACGIH TLV (United States, 3/2016). TWA: 20 ppm 8 hours.

Section 8. Exposure controls/personal protection

Propane	NIOSH REL (United States, 10/2016). TWA: 1000 ppm 10 hours. TWA: 1800 mg/m ³ 10 hours.
Light Aliphatic Hydrocarbon	OSHA PEL (United States, 6/2016). TWA: 1000 ppm 8 hours. TWA: 1800 mg/m ³ 8 hours.
Butane	OSHA PEL (United States, 6/2016). TWA: 100 ppm 8 hours. TWA: 400 mg/m ³ 8 hours.
Lt. Aliphatic Hydrocarbon Solvent	NIOSH REL (United States, 10/2016). TWA: 800 ppm 10 hours. TWA: 1900 mg/m ³ 10 hours. ACGIH TLV (United States, 3/2016). STEL: 1000 ppm 15 minutes. None.

Occupational exposure limits (Canada)

Ingredient name	Exposure limits
toluene	CA Alberta Provincial (Canada, 4/2009). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m ³ 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 20 ppm 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 20 ppm 8 hours. CA Québec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 188 mg/m ³ 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.
Propane	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 1000 ppm 8 hours. CA Québec Provincial (Canada, 1/2014). TWAEV: 1000 ppm 8 hours. TWAEV: 1800 mg/m ³ 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 1000 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.
Solvent naphtha (petroleum), medium aliph.	CA Québec Provincial (Canada, 1/2014). TWAEV: 400 ppm 8 hours. TWAEV: 1590 mg/m ³ 8 hours. CA Ontario Provincial (Canada, 7/2015). TWA: 525 mg/m ³ 8 hours.
Butane	CA Alberta Provincial (Canada, 4/2009). 8 hrs OEL: 1000 ppm 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 600 ppm 8 hours. STEL: 750 ppm 15 minutes.

Section 8. Exposure controls/personal protection

CA Québec Provincial (Canada, 1/2014).
TWA_{EV}: 800 ppm 8 hours.
TWA_{EV}: 1900 mg/m³ 8 hours.
CA Ontario Provincial (Canada, 7/2015).
TWA: 800 ppm 8 hours.
CA Saskatchewan Provincial (Canada, 7/2013).
STEL: 1250 ppm 15 minutes.
TWA: 1000 ppm 8 hours.

Occupational exposure limits (Mexico)

Ingredient name	Exposure limits
toluene	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Propane	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.
Butane	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 1000 ppm 8 hours.

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.
Color : Not available.
Odor : Not available.
Odor threshold : Not available.
pH : 7
Melting point : Not available.
Boiling point : Not available.
Flash point : Closed cup: -29°C (-20.2°F) [Pensky-Martens Closed Cup]
Evaporation rate : 2 (butyl acetate = 1)
Flammability (solid, gas) : Not available.
Lower and upper explosive (flammable) limits : Lower: 0.9%
Upper: 9.5%
Vapor pressure : 101.3 kPa (760 mm Hg) [at 20°C]
Vapor density : 1 [Air = 1]
Relative density : 0.86
Solubility : Not available.
Partition coefficient: n-octanol/water : Not available.
Auto-ignition temperature : Not available.
Decomposition temperature : Not available.
Viscosity : Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
Molecular weight : Not applicable.

Aerosol product

Type of aerosol : Spray
Heat of combustion : 13.198 kJ/g

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : No specific data.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes	-
				100 milligrams	
	Eyes - Mild irritant	Rabbit	-	870 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Mild irritant	Rabbit	-	435 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Toluene	-	3	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Propane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Light Aliphatic Hydrocarbon	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Butane	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
Lt. Aliphatic Hydrocarbon Solvent	Category 3	Not applicable.	Respiratory tract

Section 11. Toxicological information

irritation and
Narcotic effects

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Toluene	Category 2	Not determined	Not determined
Propane	Category 2	Not determined	Not determined
Light Aliphatic Hydrocarbon	Category 2	Not determined	Not determined
Butane	Category 2	Not determined	Not determined
Lt. Aliphatic Hydrocarbon Solvent	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1
Propane	ASPIRATION HAZARD - Category 1
Light Aliphatic Hydrocarbon	ASPIRATION HAZARD - Category 1
Butane	ASPIRATION HAZARD - Category 1
Lt. Aliphatic Hydrocarbon Solvent	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
irritation
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Date of issue/Date of revision : 12/1/2017	Date of previous issue : 9/8/2017	Version : 7	10/14
A03405004 KRYLON® QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Pink			

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : Suspected of damaging the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	5002 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Toluene	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute LC50 >100000 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
Lt. Aliphatic Hydrocarbon Solvent			

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Toluene	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low
Lt. Aliphatic Hydrocarbon Solvent	-	10 to 2500	high

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Section 12. Ecological information

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1950	UN1950	UN1950	UN1950	UN1950
UN proper shipping name	AEROSOLS	AEROSOLS	AEROSOLS	AEROSOLS, flammable	AEROSOLS
Transport hazard class(es)	2.1 	2.1 	2.1 	2.1 	2.1 
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	- ERG No. 126	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2). ERG No. 126	- ERG No. 126	-	Emergency schedules F-D, S-U

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to Annex II of MARPOL and the IBC Code : Not available.

Proper shipping name : Not available.
Ship type : Not available.
Pollution category : Not available.

Section 15. Regulatory information

[SARA 313](#)

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

[California Prop. 65](#)

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

[Hazardous Material Information System \(U.S.A.\)](#)

Health	2
Flammability	2
Physical hazards	0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

[Procedure used to derive the classification](#)

Classification	Justification
FLAMMABLE AEROSOLS - Category 1	On basis of test data
GASES UNDER PRESSURE - Compressed gas	Calculation method
TOXIC TO REPRODUCTION (Unborn child) - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method

[History](#)

Date of printing : 12/1/2017

Date of issue/Date of revision : 12/1/2017

Date of previous issue : 9/8/2017

Version : 7

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
UN = United Nations

[Notice to reader](#)

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use

Date of issue/Date of revision	: 12/1/2017	Date of previous issue	: 9/8/2017	Version	: 7	13/14
A03405004	KRYLON® QUIK-MARK™ Water-Based Inverted Marking Paint (Fluorescent) Fluorescent Pink					

Section 16. Other information

or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Issue date 18-May-2018

Revision date 30-Apr-2018

Revision Number 1

1. IDENTIFICATION

Product identification

Product identifier	Lawson Expunge Graffiti And Vandal Mark Remover
Other means of identification	83570
Recommended use	Paint Remover
Restrictions on use	For industrial use only

Supplier

Corporate Headquarters:
Lawson Products, Inc.
8770 W. Bryn Mawr Ave., Suite 900
Chicago, IL 60631
(866) 837-9908

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Acute toxicity - Oral	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Symbol



Signal word DANGER

Hazard statements H222 - Extremely flammable aerosol

H280 - Contains gas under pressure; may explode if heated
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H373 - May cause damage to organs through prolonged or repeated exposure
H302 - Harmful if swallowed
H361 - Suspected of damaging fertility or the unborn child
H304 - May be fatal if swallowed and enters airways

Precautionary statements

General

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P103 - Read label before use.

Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P260 - Do not breathe dusts or mists
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing and eye/face protection
P281 - Use personal protective equipment as required

Response

General

P314 - Get medical advice/attention if you feel unwell.
P308 + P313 - IF exposed or concerned: Get medical advice/attention

Eyes

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention

Skin

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P362 - Take off contaminated clothing and wash before reuse
P332 + P313 - If skin irritation occurs: Get medical advice/attention

Inhalation

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P304 + P312 - IF INHALED: Call a POISON CENTER or doctor if you feel unwell

Ingestion

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Fire

P370 + P378 - In case of fire: Use appropriate method to extinguish

Spill

P391 - Collect spillage

Storage

P405 - Store locked up
P410 - Protect from sunlight
P412 - Do not expose to temperatures exceeding 50 °C/122 °F
P403 - Store in a well-ventilated place

Disposal

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Hazard(s) Not Otherwise Classified (HNOC) None known.

Physical Hazards Not Otherwise Classified (PHNOC) None known.

Unknown acute toxicity 17.2%

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition Mixture.

Chemical name	CAS-No	Weight %
Toluene	108-88-3	40.6
Propane	74-98-6	12.9
Diacetone alcohol	123-42-2	8.1
Butane	106-97-8	6.1
Isopropyl alcohol	67-63-0	4
Acetone	67-64-1	4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or environment and hence require reporting in this section

4. FIRST-AID MEASURES

Necessary first-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Ingestion

Seek medical attention immediately. Call a physician or Poison Control Center immediately. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Most important symptoms (acute)

Causes serious eye irritation. Can cause Central Nervous System depression. May cause respiratory irritation. May cause drowsiness or dizziness. Causes skin irritation. Harmful if swallowed. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Most important symptoms (over-exposure)	Adverse symptoms may include the following: eye pain, redness, and watering. Respiratory tract irritation. Coughing. Nausea or vomiting. Headache. Drowsiness/fatigue. Dizziness/vertigo. Unconsciousness. Skin irritation. Redness. Reduced fetal weight. Increased fetal deaths. Skeletal malformations.
Indication of any immediate medical attention and special treatment needed	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. No action shall be taken involving any personal risk or without suitable training. If it is suspected that vapors or fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	None known.
Specific hazards	Extremely Flammable Aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may cause fire or explosion hazard. Hazardous Thermal Decomposition Products: Carbon dioxide. Carbon monoxide.
Special protective equipment for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if you can do it without risk. Use water spray to keep fire-exposed containers cool. Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering the area. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in the hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information for 'non-emergency personnel'. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment and cleaning up	Small Spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor. Large Spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry in sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Use spark-proof tools and explosion proof equipment. See

section 1 for emergency contact information and section 13 for disposal information.

7. HANDLING AND STORAGE

Precautions for safe handling

Put on appropriate personal protective equipment (see section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid contact during pregnancy/while nursing. Do not handle until all safety precautions have been read and understood. Do not breathe vapors or spray mist. Do not take internally. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking, and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store away from direct sunlight in dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all sources of ignition. Use appropriate containment to avoid environmental contamination.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Toluene	300 ppm Ceiling 200 ppm TWA	20 ppm TWA	150 ppm STEL 560 mg/m ³ STEL 100 ppm TWA 375 mg/m ³ TWA
Propane	1000 ppm TWA 1800 mg/m ³ TWA	-	1000 ppm TWA 1800 mg/m ³ TWA
Diacetone alcohol	50 ppm TWA 240 mg/m ³ TWA	50 ppm TWA	50 ppm TWA 240 mg/m ³ TWA
Butane	-	1000 ppm STEL	800 ppm TWA 1900 mg/m ³ TWA
Isopropyl alcohol	400 ppm TWA 980 mg/m ³ TWA	400 ppm STEL 200 ppm TWA	500 ppm STEL 1225 mg/m ³ STEL 400 ppm TWA 980 mg/m ³ TWA
Acetone	1000 ppm TWA 2400 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	250 ppm TWA 590 mg/m ³ TWA

Appropriate engineering controls

Ensure adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures, such as personal protective equipment

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin and body protection

Chemical-resistant, impervious gloves (Nitrile or Viton) complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use the the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a properly fitted, air-purifying (Organic vapor) or supplied air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Toluene	50 ppm TWA 188 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA 188 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA 188 mg/m ³ TWA	60 ppm STEL 50 ppm TWA
Propane	1000 ppm TWA	1000 ppm TWA 1000 ppm TWA	-	-	-	-	-	-	1000 ppm TWA 1800 mg/m ³ TWA	1250 ppm STEL 1000 ppm TWA 1000 ppm TWA
Diacetone alcohol	50 ppm TWA 238 mg/m ³ TWA	50 ppm TWA	50 ppm TWA	50 ppm TWA 238 mg/m ³ TWA	50 ppm TWA	50 ppm TWA	50 ppm TWA	50 ppm TWA	50 ppm TWA 238 mg/m ³ TWA	60 ppm STEL 50 ppm TWA
Butane	1000 ppm TWA	750 ppm STEL 600 ppm TWA 1000 ppm TWA	1000 ppm STEL	800 ppm TWA 1900 mg/m ³ TWA	1000 ppm STEL	1000 ppm STEL	1000 ppm STEL	1000 ppm STEL	800 ppm TWA 1900 mg/m ³ TWA	1250 ppm STEL 1000 ppm TWA 1000 ppm TWA 1000 ppm TWA
Isopropyl alcohol	400 ppm STEL 984 mg/m ³ STEL 200 ppm TWA 492 mg/m ³ TWA	400 ppm STEL 200 ppm TWA	200 ppm TWA 400 ppm STEL	500 ppm STEL 1230 mg/m ³ STEL 400 ppm TWA 983 mg/m ³ TWA	400 ppm STEL 200 ppm TWA	400 ppm STEL 200 ppm TWA	400 ppm STEL 200 ppm TWA	400 ppm STEL 200 ppm TWA	500 ppm STEL 1230 mg/m ³ STEL 400 ppm TWA 985 mg/m ³ TWA	400 ppm STEL 200 ppm TWA

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Acetone	750 ppm STEL 1800 mg/m ³ STEL 500 ppm TWA 1200 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	250 ppm TWA 500 ppm STEL	750 ppm STEL 1782 mg/m ³ STEL 500 ppm TWA 1188 mg/m ³ TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	500 ppm STEL 250 ppm TWA	1000 ppm STEV 2380 mg/m ³ STEV 500 ppm TWA 1190 mg/m ³ TWA	750 ppm STEL 500 ppm TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Odor	Not available
Odor threshold	Not available
pH	7
Melting point/range °C	Not available
Melting point/range °F	Not available
Boiling point/range °C	Not available
Boiling point/range °F	Not available
Flash point °C	-29
Flash point °F	-20.2
Flash point method used	Pensky-Martens C.C.
Evaporation rate	5.6 (Butyl Acetate = 1)
Flammability (Solid, Gas)	Not available
Lower explosion limit	1 %
Upper explosion limit	12.8 %
Vapor pressure	13.5 kPa (101.325mm Hg) [at 20°C]
Vapor density	1(Air=1)
Relative density	0.8
Solubility	Not available
Partition coefficient (n-octanol/water)	Not available
Autoignition temperature °C	Not available
Autoignition temperature °F	Not available

Decomposition temperature °C Not available

Decomposition temperature °F Not available

Viscosity Kinematic (40°C (104°F)): <0.07cm²/s (<7 cSt)
Kinematic (room temperature): <0.07 cm²/s (<7 cSt)

10. STABILITY AND REACTIVITY

Reactivity No specific test data related to reactivity available for this product or its ingredients.

Chemical stability Stable.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Avoid heat, sparks, and other sources of ignition.

Incompatible materials No specific data.

Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure Dermal. Inhalation. Ingestion. Eyes.

Symptoms Causes serious eye irritation. Can cause Central Nervous System depression. Vapors may cause drowsiness and dizziness. May cause respiratory irritation. Causes skin irritation. Harmful if swallowed. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach. Adverse symptoms may include the following: eye pain, redness, and watering. May cause irritation of respiratory tract. Coughing. Nausea. Vomiting. Headache. Drowsiness. Dizziness/vertigo. Unconsciousness. Fatigue. Skin irritation. Redness. Reduced fetal weight. Increased fetal deaths. Skeletal malformations.

Delayed and immediate effects as well as chronic effects from short and long-term exposure May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Toluene	= 12.5 mg/L (Rat) 4 h	= 12000 mg/kg (Rabbit) Dermal LD50 Rabbit 12000 mg/kg (Source: JAPAN_GHS)	= 2600 mg/kg (Rat) Oral LD50 Rat 2600 mg/kg (Source: JAPAN_GHS)
Propane	> 800000 ppm (Rat) 15 min	-	-
Diacetone alcohol	> 7.23 g/m ³ (Rat) 8 h	= 13500 mg/kg (Rabbit) = 13630 mg/kg (Rabbit)	> 4 g/kg (Rat)
Butane	= 658 g/m ³ (Rat) 4 h	-	-
Isopropyl alcohol	= 72600 mg/m ³ (Rat) 4 h	= 4059 mg/kg (Rabbit)	= 1870 mg/kg (Rat)
Acetone	= 50100 mg/m ³ (Rat) 8 h	> 15700 mg/kg (Rabbit)	= 5800 mg/kg (Rat)

ATEmix (dermal) Not available

ATEmix (oral)	1220.4 mg/kg
ATEmix (inhalation-gas)	Not available
ATEmix (inhalation-vapor)	Not available
ATEmix (inhalation-dust/mist)	Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Toluene	A4	Group 3	-	-
Propane	-	-	-	-
Diacetone alcohol	-	-	-	-
Butane	-	-	-	-
Isopropyl alcohol	A4	Group 1 Group 3	Listed	-
Acetone	A4	-	-	-

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Toluene	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Propane	-	-	-	-	-	-
Diacetone alcohol	-	-	-	-	-	-
Butane	-	-	-	-	-	-
Isopropyl alcohol	-	-	ACGIH A4	-	ACGIH A4	-
Acetone	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Chemical name	Algae/aquatic plants	Fish
Toluene	433: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 12.5: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static	15.22 - 19.05: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 12.6: 96 h <i>Pimephales promelas</i> mg/L LC50 static 5.89 - 7.81: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 14.1 - 17.16: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 5.8: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 semi-static 11.0 - 15.0: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 54: 96 h <i>Oryzias latipes</i> mg/L LC50 static 28.2: 96 h <i>Poecilia reticulata</i> mg/L LC50 semi-static 50.87 - 70.34: 96 h <i>Poecilia reticulata</i> mg/L LC50 static
Propane	-	-
Diacetone alcohol	-	420: 96 h <i>Lepomis macrochirus</i> mg/L LC50 420: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static
Butane	-	-
Isopropyl alcohol	1000: 96 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	1400000: 96 h <i>Lepomis macrochirus</i> µg/L LC50 9640: 96 h <i>Pimephales promelas</i> mg/L LC50

Chemical name	Algae/aquatic plants	Fish
		flow-through 11130: 96 h Pimephales promelas mg/L LC50 static
Acetone	-	4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 8300: 96 h Lepomis macrochirus mg/L LC50

Persistence and degradability Not available.

Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)
Toluene 108-88-3	108-88-3	2.7
Propane 74-98-6	74-98-6	2.3 <=2.8
Diacetone alcohol 123-42-2	123-42-2	1.03
Butane 106-97-8	106-97-8	2.89 <=2.8
Isopropyl alcohol 67-63-0	67-63-0	0.05 25 °C
Acetone 67-64-1	67-64-1	-0.24

Mobility in soil Not available.

Other adverse effects No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

Disposal information

The generation of waste should be avoided or minimized whenever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Contaminated packaging

Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its containers must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No	UN1950
Proper shipping name	Aerosols
Hazard Class(es)	2.1
Packing group	
Special Provisions	LTD QTY

TDG

ID-No UN1950
Proper shipping name Aerosols
Hazard Class(es) 2.1
Packing group
Special Provisions LTD QTY

IATA

ID-No UN1950
Proper shipping name Aerosols, flammable
Hazard Class(es) 2.1
Subsidiary Risk
Packing group
Special Provisions LTD QTY

IMDG/IMO

ID-No UN1950
Proper shipping name Aerosols
Hazard Class(es) 2.1
Packing group
EmS No F-D, S-U
Special Provisions LTD QTY

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Toluene	108-88-3	-	-	-
Propane	74-98-6	-	-	-
Diacetone alcohol	123-42-2	-	-	-
Butane	106-97-8	-	-	-
Isopropyl alcohol	67-63-0	-	-	-
Acetone	67-64-1	-	-	-

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations
U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Toluene	108-88-3	X	X	X
Propane	74-98-6	X	X	X
Diacetone alcohol	123-42-2	X	X	X
Butane	106-97-8	X	X	X
Isopropyl alcohol	67-63-0	X	X	X
Acetone	67-64-1	X	X	X

California Prop. 65

Chemical name	CAS-No	California Prop. 65
Toluene	108-88-3	Developmental
Propane	74-98-6	-
Diacetone alcohol	123-42-2	-
Butane	106-97-8	-
Isopropyl alcohol	67-63-0	-
Acetone	67-64-1	-

U.S. Federal Regulations**US EPA SARA 313**

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Toluene	108-88-3	1000 lb 454 kg 1 lb 0.454 kg	1.0 %
Propane	74-98-6	-	-
Diacetone alcohol	123-42-2	-	-
Butane	106-97-8	-	-
Isopropyl alcohol	67-63-0	-	1.0 %
Acetone	67-64-1	5000 lb 2270 kg	-

**US EPA SARA 311/312
hazardous categorization**

Not available

International inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA 8(b)), Canada (DSL/NDSL) or are exempt.

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Toluene	X	X	-
Propane	X	X	-
Diacetone alcohol	X	X	-
Butane	X	X	-
Isopropyl alcohol	X	X	-
Acetone	X	X	-

Legend X - Listed

16. OTHER INFORMATION**NFPA****Health
Flammability**Not available
Not available

Instability	Not available

HMIS

Health	2 *
Flammability	3
Physical hazards	0
Personal protection	To be determined by customer.

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by	Regulatory Affairs

Issue date	18-May-2018

Revision date	30-Apr-2018

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
ATE (Average Toxicity Estimate)
DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
HMIS (Hazardous Materials Identification System)
IARC (International Agency for Research on Cancer)
IATA (International Air Transport Association)
IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
NFPA (National Fire Protection Association)
NTP (National Toxicology Program)
OEL (Occupational Exposure Level)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
TSCA (Toxic Substance Control Act)
USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet



Safety Data Sheet

Issue date 06-Jun-2018

Revision date 06-Jun-2018

Revision Number 1

1. IDENTIFICATION

Product identification

Product identifier	Lawson Ready Orange Wipes
Other means of identification	54334
Recommended use	hand wipes
Restrictions on use	Not available

Supplier

Corporate Headquarters:
Lawson Products, Inc.
8770 W. Bryn Mawr Ave., Suite 900
Chicago, IL 60631
(866) 837-9908

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

2. HAZARD(S) IDENTIFICATION

Hazard Classification While this material is not classified as hazardous under OSHA regulations, this SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

Symbol Not applicable

Signal word Not applicable

Hazard statements None known

Precautionary statements

Response Not applicable

Storage Not applicable

Disposal Not applicable

Hazard(s) Not Otherwise Classified (HNOC) Toxic to aquatic life with long lasting effects.

Physical Hazards Not None known.

**Otherwise Classified
(PHNOC)****Unknown acute toxicity** None known**3. COMPOSITION/INFORMATION ON INGREDIENTS****Composition** Mixture.

Chemical name	CAS-No	Weight %
Nonionic Surfactant	68131-39-5	1-5
Mineral Spirits	64742-47-8	1-5
Dimethyl Adipate	627-93-0	1-5
Diethylhexyl sodium sulfosuccinate	577-11-7	1-5
D-Limonene	5989-27-5	1-5
Propylene Glycol	57-55-6	<1
Myristic Acid Isopropyl Ester	110-27-0	<1
Iodopropynyl butylcarbamate	55406-53-6	<1
Glycerine	56-81-5	<1
Dimethyl Glutarate	1119-40-0	<1
2-Phenoxyethanol	122-99-6	<1
2,2-dimethyl-1,3-Propanediol	126-30-7	<1

The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST-AID MEASURES**Necessary first-aid measures**

Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Not a likely exposure route. If a large quantity of liquid is swallowed, do not induce vomiting, call a physician or poison control center immediately.
Skin contact	None usually required. Material is designed for skin cleansing. If symptoms develop seek medical attention.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. If symptoms persist, call a physician.

Most important symptoms (acute) Not expected to present a significant hazard under anticipated conditions of normal use.**Most important symptoms (over-exposure)** Not available.**Indication of any immediate medical attention and special treatment needed** Treat symptomatically.**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media** In case of fire, use water spray (fog), foam, dry chemical or carbon dioxide.**Unsuitable extinguishing media** None known.

Specific hazards No specific fire or explosion hazard. Hazardous Thermal Decomposition Products: Carbon dioxide. Carbon monoxide. Hydrocarbons. Sulfur dioxide. Soot. Hydrogen sulfide.

Special protective equipment for fire-fighters Use water spray or fog for cooling exposed containers.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protection recommended in Section 8. Prevent entry into waterways, sewers, basements, and confined areas. Avoid release to the environment. See Section 12: ECOLOGICAL INFORMATION. Dispose of contents/container to an approved waste disposal plant.

Methods and materials for containment and cleaning up Prevent further leakage or spillage if safe to do so. Small Spill: Wipe up with absorbent material (e.g. cloth, fleece). Large Spill: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

7. HANDLING AND STORAGE

Precautions for safe handling Avoid contact with eyes. Do not smoke while using. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities Keep container closed when not in use. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from food, beverages, and feed. Keep out of reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Nonionic Surfactant	-	-	-
Mineral Spirits	-	-	-
Dimethyl Adipate	-	-	-
Diethylhexyl sodium sulfosuccinate	-	-	-
D-Limonene	-	-	-
Propylene Glycol	-	-	-
Myristic Acid Isopropyl Ester	-	-	-
Iodopropynyl butylcarbamate	-	-	-
Glycerine	15 mg/m ³ TWA 5 mg/m ³ TWA	-	-
Dimethyl Glutarate	-	-	-
2-Phenoxyethanol	-	-	-
2,2-dimethyl-1,3-Propanediol	-	-	-

Appropriate engineering controls Eyewash stations.

Individual protection measures, such as personal protective equipment

Eye protection None necessary under normal use conditions.

Skin and body protection None necessary under normal conditions.

Respiratory protection None necessary under normal conditions. If exposure limits are exceeded or irritation is experienced, a NIOSH/MSHA approved respirator is recommended.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Nonionic Surfactant	-	-	-	-	-	-	-	-	-	-
Mineral Spirits	-	200 mg/m ³ TWA	-	-	-	-	-	-	-	-
Dimethyl Adipate	-	-	-	-	-	-	-	-	-	-
Diethylhexyl sodium sulfosuccinate	-	-	-	-	-	-	-	-	-	-
D-Limonene	-	-	-	-	-	-	-	-	-	-
Propylene Glycol	-	-	-	-	-	-	10 mg/m ³ TWA 50 ppm TWA 155 mg/m ³ TWA	-	-	-
Myristic Acid Isopropyl Ester	-	-	-	-	-	-	-	-	-	-
Iodopropynyl butylcarbamate	-	-	-	-	-	-	-	-	-	-
Glycerine	10 mg/m ³ TWA	10 mg/m ³ TWA 3 mg/m ³ TWA	-	10 mg/m ³ TWA	-	-	-	-	10 mg/m ³ TWA EV	20 mg/m ³ STEL 10 mg/m ³ TWA
Dimethyl Glutarate	-	-	-	-	-	-	-	-	-	-
2-Phenoxyethanol	-	-	-	-	-	-	25 ppm TWA 141 mg/m ³ TWA	-	-	-
2,2-dimethyl-1,3-Propanediol	-	-	-	-	-	-	-	-	-	-

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid
Color	Blue, White
Odor	Citrus
Odor threshold	No information available
pH	6
Melting point/range °C	Not available
Melting point/range °F	Not available
Boiling point/range °C	100 °C
Boiling point/range °F	212 °F
Flash point °C / °F	Not available
Evaporation rate	No data available

Flammability (Solid, Gas)	Not available
Lower explosion limit	Not available
Upper explosion limit	Not available
Vapor pressure	Not available
Vapor density	> 1
Relative density	0.995
Solubility	Miscible with water
Partition coefficient (n-octanol/water)	Not available
Autoignition temperature °C	No data available
Autoignition temperature °F	No data available
Decomposition temperature °C	Not available
Decomposition temperature °F	Not available
Viscosity	Not available

10. STABILITY AND REACTIVITY

Reactivity	No dangerous reactions under normal conditions of use.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Incompatible materials.
Incompatible materials	Strong oxidizing agents. Strong acids.
Hazardous decomposition products	Hazardous Thermal Decomposition Products: Carbon dioxide (CO ₂). Carbon monoxide. Hydrocarbons. Sulfur dioxide. Soot. Hydrogen sulfide.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure	Dermal. Eyes.
Symptoms	May cause eye irritation. May cause skin irritation.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	No known significant effects or critical hazards.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Nonionic Surfactant	-	= 2500 mg/kg (Rabbit)	= 1600 mg/kg (Rat) = 2 g/kg (Rat)
Mineral Spirits	> 5.2 mg/L (Rat) 4 h	> 2000 mg/kg (Rabbit)	> 5000 mg/kg (Rat)
Dimethyl Adipate	-	> 5000 mg/kg (Rabbit)	> 5000 mg/kg (Rat)
Diethylhexyl sodium sulfosuccinate	-	> 10000 mg/kg (Rabbit)	= 1900 mg/kg (Rat) = 3080 mg/kg (Rat)
D-Limonene	-	> 5 g/kg (Rabbit)	= 4400 mg/kg (Rat) = 5200 mg/kg (Rat) = 5300 mg/kg (Rat)
Propylene Glycol	-	= 20800 mg/kg (Rabbit)	= 20 g/kg (Rat)
Myristic Acid Isopropyl Ester	> 41 mg/L (Rat) 1 h	= 5 g/kg (Rabbit)	> 10000 mg/kg (Rat)
Iodopropynyl butylcarbamate	= 0.67 mg/L (Rat) 4 h = 0.63 mg/L (Rat) 4 h = 0.99 mg/L (Rat) 4 h	> 2000 mg/kg (Rat) Dermal LD50 Rat >2000 mg/kg (no deaths occurred, Source: EU_CLH)	= 1470 mg/kg (Rat) Oral LD50 Rat 1470 mg/kg (in corn oil, Source: EPA_HP)
Glycerine	> 570 mg/m ³ (Rat) 1 h	> 10 g/kg (Rabbit)	= 12600 mg/kg (Rat)
Dimethyl Glutarate	> 5.6 mg/L (Rat) 4 h	> 5000 mg/kg (Rabbit)	> 5000 mg/kg (Rat)
2-Phenoxyethanol	-	= 5 mL/kg (Rabbit) Dermal LD50 Rabbit 5 mL/kg (Source: NLM_CIP)	= 1260 mg/kg (Rat) Oral LD50 Rat 1260 mg/kg (Source: IUCLID)
2,2-dimethyl-1,3-Propanediol	-	-	= 3200 mg/kg (Rat) Oral LD50 Rat 3200 mg/kg (Source: NZ_CCID)

ATEmix (dermal) 329859 mg/kg

ATEmix (oral) 42888 mg/kg

ATEmix (inhalation-gas) Not available

ATEmix (inhalation-vapor) Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Nonionic Surfactant	-	-	-	-
Mineral Spirits	-	-	-	-
Dimethyl Adipate	-	-	-	-
Diethylhexyl sodium sulfosuccinate	-	-	-	-
D-Limonene	-	Group 2A Group 3	Listed	-
Propylene Glycol	-	-	-	-
Myristic Acid Isopropyl Ester	-	-	-	-
Iodopropynyl butylcarbamate	-	-	-	-
Glycerine	-	-	-	-
Dimethyl Glutarate	-	-	-	-
2-Phenoxyethanol	-	-	-	-
2,2-dimethyl-1,3-Propanediol	-	-	-	-

Canadian Province carcinogenicity limits

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Nonionic Surfactant	-	-	-	-	-	-
Mineral Spirits	-	-	-	-	-	-
Dimethyl Adipate	-	-	-	-	-	-
Diethylhexyl sodium sulfosuccinate	-	-	-	-	-	-
D-Limonene	-	-	-	-	-	-
Propylene Glycol	-	-	-	-	-	-
Myristic Acid Isopropyl Ester	-	-	-	-	-	-
Iodopropynyl butylcarbamate	-	-	-	-	-	-
Glycerine	-	-	-	-	-	-
Dimethyl Glutarate	-	-	-	-	-	-
2-Phenoxyethanol	-	-	-	-	-	-
2,2-dimethyl-1,3-Propanediol	-	-	-	-	-	-

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life Harmful to aquatic life with long lasting effects

Chemical name	Algae/aquatic plants	Fish
Nonionic Surfactant	-	-
Mineral Spirits	-	45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static
Dimethyl Adipate	-	-
Diethylhexyl sodium sulfosuccinate	-	24: 96 h Oncorhynchus mykiss mg/L LC50 static 37: 96 h Lepomis macrochirus mg/L LC50 static 20 - 40: 96 h Oncorhynchus mykiss mg/L LC50 semi-static
D-Limonene	-	0.619 - 0.796: 96 h Pimephales promelas mg/L LC50 flow-through 35: 96 h Oncorhynchus mykiss mg/L LC50
Propylene Glycol	19000: 96 h Pseudokirchneriella subcapitata mg/L EC50	41 - 47: 96 h Oncorhynchus mykiss mL/L LC50 static 51600: 96 h Oncorhynchus mykiss mg/L LC50 static 51400: 96 h Pimephales promelas mg/L LC50 static 710: 96 h Pimephales promelas mg/L LC50
Myristic Acid Isopropyl Ester	100: 72 h Desmodesmus subspicatus mg/L EC50	8400: 96 h Brachydanio rerio mg/L LC50 semi-static 8400: 96 h Brachydanio rerio mg/L LC50
Iodopropynyl butylcarbamate	-	0.14 - 0.32: 96 h Lepomis macrochirus mg/L LC50 flow-through 0.049 - 0.079: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.05 - 0.089: 96 h Oncorhynchus mykiss mg/L LC50 0.18 - 0.23: 96 h Pimephales promelas mg/L LC50 flow-through
Glycerine	-	51 - 57: 96 h Oncorhynchus mykiss mL/L LC50 static
Dimethyl Glutarate	-	19.6 - 26.2: 96 h Pimephales promelas mg/L LC50 static
2-Phenoxyethanol	500: 72 h Desmodesmus subspicatus mg/L EC50	337 - 352: 96 h Pimephales promelas mg/L LC50 flow-through 366: 96 h Pimephales promelas mg/L

Chemical name	Algae/aquatic plants	Fish
		LC50 static 220 - 460: 96 h <i>Leuciscus idus</i> mg/L LC50 static
2,2-dimethyl-1,3-Propanediol	500: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50 1000: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50	1000: 96 h <i>Oryzias latipes</i> mg/L LC50 semi-static

Persistence and degradability Not available.

Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)
Nonionic Surfactant 68131-39-5	68131-39-5	-
Mineral Spirits 64742-47-8	64742-47-8	-
Dimethyl Adipate 627-93-0	627-93-0	-
Diethylhexyl sodium sulfosuccinate 577-11-7	577-11-7	-
D-Limonene 5989-27-5	5989-27-5	-
Propylene Glycol 57-55-6	57-55-6	-
Myristic Acid Isopropyl Ester 110-27-0	110-27-0	>6
Iodopropynyl butylcarbamate 55406-53-6	55406-53-6	-
Glycerine 56-81-5	56-81-5	-1.76
Dimethyl Glutarate 1119-40-0	1119-40-0	-
2-Phenoxyethanol 122-99-6	122-99-6	1.13 25 °C
2,2-dimethyl-1,3-Propanediol 126-30-7	126-30-7	-0.15 25 °C

Mobility in soil Not available.

Other adverse effects Not available

13. DISPOSAL CONSIDERATIONS

Disposal information

This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4(b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult appropriate federal, state and local regulatory agencies to ascertain proper disposal procedures.

Contaminated packaging Do not re-use empty containers.

14. TRANSPORTATION INFORMATION

Shipping Descriptions**DOT**

Proper shipping name Not regulated

TDG

Proper shipping name Not regulated

IATA

Proper shipping name Not regulated

IMDG/IMO

Proper shipping name Not regulated

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Nonionic Surfactant	68131-39-5	-	-	-
Mineral Spirits	64742-47-8	-	-	-
Dimethyl Adipate	627-93-0	-	-	-
Diethylhexyl sodium sulfosuccinate	577-11-7	-	-	-
D-Limonene	5989-27-5	X	X	X
Propylene Glycol	57-55-6	-	-	-
Myristic Acid Isopropyl Ester	110-27-0	-	-	-
Iodopropynyl butylcarbamate	55406-53-6	-	-	-
Glycerine	56-81-5	-	-	-
Dimethyl Glutarate	1119-40-0	-	-	-
2-Phenoxyethanol	122-99-6	-	-	-
2,2-dimethyl-1,3-Propanediol	126-30-7	-	-	-

15. REGULATORY INFORMATION**State regulations****U.S. state Right-to-Know regulations**

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Nonionic Surfactant	68131-39-5	-	-	-
Mineral Spirits	64742-47-8	-	-	-
Dimethyl Adipate	627-93-0	-	-	-
Diethylhexyl sodium sulfosuccinate	577-11-7	-	-	-
D-Limonene	5989-27-5	-	X	-
Propylene Glycol	57-55-6	-	X	X
Myristic Acid Isopropyl Ester	110-27-0	-	-	-
Iodopropynyl butylcarbamate	55406-53-6	-	X	-
Glycerine	56-81-5	X	X	X
Dimethyl Glutarate	1119-40-0	-	-	-
2-Phenoxyethanol	122-99-6	-	X	X
2,2-dimethyl-1,3-Propanediol	126-30-7	-	-	-

California Prop. 65

Chemical name	CAS-No	California Prop. 65
Nonionic Surfactant	68131-39-5	-
Mineral Spirits	64742-47-8	-
Dimethyl Adipate	627-93-0	-
Diethylhexyl sodium sulfosuccinate	577-11-7	-
D-Limonene	5989-27-5	-
Propylene Glycol	57-55-6	-
Myristic Acid Isopropyl Ester	110-27-0	-
Iodopropynyl butylcarbamate	55406-53-6	-
Glycerine	56-81-5	-
Dimethyl Glutarate	1119-40-0	-
2-Phenoxyethanol	122-99-6	-
2,2-dimethyl-1,3-Propanediol	126-30-7	-

U.S. Federal Regulations

US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Nonionic Surfactant	68131-39-5	-	-
Mineral Spirits	64742-47-8	-	-
Dimethyl Adipate	627-93-0	-	-
Diethylhexyl sodium sulfosuccinate	577-11-7	-	-
D-Limonene	5989-27-5	-	-
Propylene Glycol	57-55-6	-	-
Myristic Acid Isopropyl Ester	110-27-0	-	-
Iodopropynyl butylcarbamate	55406-53-6	-	1.0 %
Glycerine	56-81-5	-	-
Dimethyl Glutarate	1119-40-0	-	-
2-Phenoxyethanol	122-99-6	-	1.0 %
2,2-dimethyl-1,3-Propanediol	126-30-7	-	-

US EPA SARA 311/312 hazardous categorization

Not applicable

International inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA 8(b)), Canada (DSL/NDSL) or are exempt.

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Nonionic Surfactant	X	X	-
Mineral Spirits	X	X	-
Dimethyl Adipate	X	X	-
Diethylhexyl sodium sulfosuccinate	X	X	-
D-Limonene	X	X	-
Propylene Glycol	X	X	-
Myristic Acid Isopropyl Ester	X	X	-
Iodopropynyl butylcarbamate	X	X	-
Glycerine	X	X	-
Dimethyl Glutarate	X	X	-

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
2-Phenoxyethanol	X	X	-
2,2-dimethyl-1,3-Propanediol	X	X	-

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health	1
Flammability	0
Instability	0

HMIS

Health	1
Flammability	0
Physical hazards	0
Personal protection	X

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 06-Jun-2018

Revision date 06-Jun-2018

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
 ATE (Average Toxicity Estimate)
 DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
 HMIS (Hazardous Materials Identification System)
 IARC (International Agency for Research on Cancer)
 IATA (International Air Transport Association)
 IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
 NFPA (National Fire Protection Association)
 NTP (National Toxicology Program)
 OEL (Occupational Exposure Level)
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 PEL (Permissible Exposure Limit)
 TSCA (Toxic Substance Control Act)
 USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet

DRUMMOND™

A LAWSON BRAND

SAFETY DATA SHEET

1. Identification

Product Identifier: DR8490 LIFEGUARD ONE STEP DISINFECTANT GERMICIDAL DETERGENT AND DEODORANT

Application or recommended use: Concentrated hard surface disinfectant cleaner

Restrictions on use: Do not use in any fashion not specified on the product label.

Manufacturer / supplier: Drummond, A Lawson Brand
Lawson Products, INC.
8770 W. Bryn Mawr Ave., Suite 900
Chicago, IL 60631

Telephone: 773-304-5050 **Emergency phone:** 888-426-4851

2. Hazards Identification

GHS Classification: Classification of this mixture in accordance with paragraph (d) of §1910.1200.
Skin Corrosion/Irritation - Category 2
Eye Damage/Irritation - Category 1

Label Elements:



Symbol:

Signal word:

DANGER

Hazard statements:

Causes skin irritation.

Causes serious eye damage.

Precautionary statements: Wash hands, face and any skin contact thoroughly after handling.

Wear protective gloves/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

See 4. First-Aid Measures for specific treatment.

Other Hazards: Harmful if swallowed.

3. Composition / Information on Ingredients

Chemical characterization: Concentrated mixture of water, detergents, germicides and auxiliary agents.

Hazardous ingredients: The exact percentage of composition has been withheld as a trade secret.

2.54% Didecyl dimethyl ammonium chlorides CAS 7173-51-5, EINECS/ELINCS 230-525-2

1.69% C₁₂₋₁₆ Alkyl dimethylbenzyl ammonium chlorides CAS 68424-85-1, EINECS/ELINCS 264-151-6

Other ingredients (> 1%):

> 92% Water CAS 7732-18-5, EINECS/ELINCS 231-791-2

4. First-Aid Measures

Symptoms: Burning or irritation of affected areas. Causes skin irritation. Causes serious eye damage.

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

Inhalation: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. Call a poison control center or doctor for treatment advice.

Skin Contact: Remove contaminated clothing and wash before reuse. Wash contaminated area with soap and water for 15-20 minutes. If skin irritation occurs, get medical advice/attention.

Eye Contact: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Ingestion: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to a person who is unconscious or convulsing. If vomiting occurs, keep head below hips to reduce risk of aspiration. Probable mucosal damage may contraindicate the use of gastric lavage.

Note to Physician: Treat exposed patients symptomatically.

5. Fire-Fighting Measures

Suitable Extinguishing Media: Not applicable. Product is not a fire hazard.

Unsuitable Extinguishing Media: High pressure water jet.

Specific hazards in case of fire: None known.

Special Fire Fighting Precautions: Prevent human exposure to fire, smoke, fumes or products of combustion. Fire fighters should wear appropriate protective equipment, including self-contained breathing apparatus and impervious clothing.

6. Accidental Release Measures

Emergency Procedures: Depending on the extent of release, consider the need for restriction to access of spill area.

Personal Precautions: Do not eat, drink or smoke during clean up. Wear protective clothing, eye protection and impervious gloves (e.g. neoprene). Wash thoroughly after clean up.

Environmental Precautions: Prevent spills from entering storm sewers/drains or contact with soil.

Clean up Methods: Small spills may be wiped up and rinsed with water. For larger spills, contain spill with inert material (sand, clay). Transfer material to labeled containers for recovery or proper disposal. After removal, flush area with water. Follow good industrial hygiene practices.

7. Handling and Storage

Precautions for Safe Handling: Read label before use. Avoid contact with skin or eyes. Avoid breathing vapor or spray mist. Wash hands, face and any skin contact thoroughly after handling. Wear protective gloves, eye protection, face protection. Use product only according to label directions. If unsure about safe use, contact your supervisor.

Conditions for Safe Storage: Keep out of reach of children. Do not contaminate water, food or feed by storage and disposal. Store in tightly closed, original container in a cool (10° - 30°C), dry area.

Incompatibility: Anionic detergents.

8. Exposure Controls / Personal Protection

Components with occupational exposure limits: None

Engineering Controls: Proper ventilation in accordance with good industrial hygiene should be provided.

Personal Protective Equipment

Respiratory: Respiratory protection is not necessary under normal conditions of use.

Gloves: Use water impervious gloves (latex or neoprene rubber). No breakthrough time has been established.

Eye Protection: Chemical resistant goggles or face protection.

Other: Protective clothing (long sleeves, pants), eyewash, safety shower are always advisable when working with chemicals.

9. Physical and Chemical Properties

Physical State - Liquid

Color - Green

Odor - Lemon

Odor Threshold - No data available

Boiling Point - 212°F

Decomposition temperature - No data available

Freezing Point - 32°F

pH (Conc.) - 6.0 - 8.0

pH (RTU) - 6.0 - 8.0

Relative Density - 1.000

Evaporation Rate - Similar to water

Auto-ignition temperature - Not applicable

Flash Point - None

Flammability - Not applicable

Flammability Limits - Not applicable

Partition coefficient - Not applicable

Solubility (Water) - Complete

Vapor Density - No data available

Vapor Pressure - No data available

Viscosity - Slightly viscous

% VOC - < 1 (Excluding exempt material)

10. Stability and Reactivity

Reactivity: No specific reactivity test data is available for this mixture. Under normal conditions of storage and use, hazardous reactions are not expected.

Incompatible materials: Oxidizers, anionic detergents.

Chemical stability: This product is stable at ambient temperatures and atmospheric pressures.

Conditions to avoid: Temperatures above 50°C or below 10°C.

Hazardous decomposition products: None known.

11. Toxicological Information

Acute Toxicity: Toxicity data is not available for this mixture. Data below are estimates based on summation methods.

Test	Results	Classification (A.0.4.1(c))	Basis (A.1.3.6.1)
Oral	> 2000mg/kg	Not applicable	Ingredient literature (Additive formula)
Dermal	> 2000mg/kg	Not applicable	Ingredient literature (Additive formula)
Inhalation	> 20 mg/L	Not applicable	Ingredient literature (Additive formula)
Eye Damage/Irritation	Corrosion	Category 1	Ingredient literature
Skin Damage/Irritation	Irritation	Category 2	Ingredient literature

Summary: Skin and eye contact are most likely routes of exposure. Exposure causes skin irritation and serious eye damage.

11. Toxicological Information (cont.)

Subchronic/Chronic Toxicity:

Test	Results	Classification	Basis
Skin Sensitization	Not a sensitizer	Not applicable	Ingredient literature.

Summary: Repeated or prolonged contact causes skin irritation and eye damage.

Carcinogens - Ingredients are not listed on the NTP Report on Carcinogens, IARC Monographs or by OSHA

Other data - No other toxicological information is available for this mixture.

12. Ecological Information

This material has not been tested for acute environmental effects.

Persistence and degradability: Material is not persistent. All organic components > 1% are inherently biodegradable.

Bio-accumulative potential: No evidence to suggest bio-accumulation will occur.

Mobility: Accidental spillage may lead to penetration of soil and groundwater.

13. Disposal Considerations

Do not contaminate water, food or feed by disposal. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray, or mixture of rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label directions, contact your State Pesticide or Environmental Control Agency, or the hazardous waste representative at the nearest EPA Regional Office for guidance. **Container Disposal:** Nonrefillable container. Do not reuse or refill this container. Clean container promptly after emptying. Triple rinse as follows: Fill container ¼ full with water and reclose the container. Agitate vigorously, and dispose of rinsate consistent with pesticide disposal instructions. Repeat two more times. Then offer for recycling if available or puncture and dispose in sanitary landfill or by other procedures approved by state and local authorities. Follow pesticide disposal instructions for rinsate. If not triple rinsed, these containers are acute hazardous wastes and must be disposed in accordance with local, state, and federal regulations.

14. Transport Information

Proper Shipping Name: Not regulated **RQ** - Not Applicable
Shipping emergency phone: 800-424-9300
Transport hazard class: Not Applicable **Hazard Label:** Not Applicable
Packing Group: Not Applicable **Emergency Guide No.:** Not Applicable **Marine Pollutant:** No

15. Regulatory Information

Inventory status: All components are listed on TSCA(US), EINECS/ELINCS(EU), DSL(Canada).

FIFRA: This product is a U.S. EPA Registered pesticide, EPA Reg. No. 47371-131-40208, and is subject to certain labeling requirements under Federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide products. The hazard information required on the pesticide label is reproduced here.

Danger: Corrosive. Causes irreversible eye damage. Do not get in eyes or on clothing. Wear protective eyewear (goggles, face shield, or safety glasses). Harmful if inhaled. Avoid breathing vapor or spray mist. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove contaminated clothing and wash clothing before reuse. The pesticide label also includes other important information, including directions for use.

OSHA Hazard Communication Standard: This product meets the §1910.1200 definition of a "Hazardous Chemical".

Superfund Amendments and Reauthorization Act of 1986 Title III (EPCRA) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes	Delayed (Chronic) Health Hazard	No
Fire Hazard	No	Reactive Hazard	No
Sudden Release of Pressure Hazard	No		

Superfund Amendments and Reauthorization Act of 1986 Title III (EPCRA) Section 313

*Chemicals marked with an asterisk in "**3. Composition/Information on Ingredients**" are subject to reporting requirements for Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40CFR Part 372.

Pennsylvania/New Jersey/Massachusetts Right to Know

See "**3. Composition/Information on Ingredients**" for hazardous and top five ingredients present in concentration greater than 1%.

California Proposition 65: This product does not contain a listed substance known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

16. Other information**Date issued:** 17. 09. 2014**F800-005 Revision:** N/A

Disclaimer: No representation or warranty, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, is made with respect to information concerning the product referred to in this document. The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, it is impossible to foresee every health effect or exposure risk incurred by the use of this product. All chemicals present some degree of hazard and should be used with caution. The information and recommendations contained herein are presented in good faith. The user should review this information in conjunction with their knowledge of the application intended to determine the suitability of this product for such purpose. In no event will the supplier be responsible for any damages of any nature whatsoever, resulting from the use, reliance upon, or the misuse of this information. Furthermore, it is the direct responsibility of the user to comply with all applicable regulations governing the use and disposal of this material. **Prepared by:** Regulatory Affairs Department

SAFETY DATA SHEET

Lysol® Brand Disinfectant Spray, All Scents (Aerosol)



HEALTH • HYGIENE • HOME

1. Product and company identification

Product name	: Lysol® Brand Disinfectant Spray, All Scents (Aerosol)
Supplier	: Reckitt Benckiser (Canada) Inc. 1680 Tech Avenue, Unit #2 Mississauga, Ontario L4W 5S9 CANADA Telephone: +1 905 283 7000
Material uses	: Multipurpose Cleaner
Product use	: Consumer
SDS #	: D0224478 v5.0
Formulation #:	: 1178-172 (0175917 v1.0 & 0242193 v2.0) Crisp Linen 1338-015 (0175918 v1.0 & 0258756 v1.0) Spring Waterfall 1338-018 (0175934 v1.0) Green Apple / Green Apple Breeze 1338-021 (0175938 v1.0) Crisp Berry 1338-019 (0175919 v1.0) Country 1338-026 (0175929 v1.0) Country Morning Breeze 1338-017 (0172927 v1.0) Lemon Breeze
DIN #	: 02395614
UPC Code / Sizes	: Tin plate steel cans Crisp Linen - 6 oz, 12.5 oz, 19 oz, 350g "To Go" Crisp Linen - 1 oz, 28 g Spring Waterfall - 12.5 oz, 19 oz, 350g Green Apple - 350g Crisp Berry - 12.5 oz, 19 oz, 350g Country - 350g Country Morning Breeze - 350g Lemon Breeze - 200g, 350g and 539g
Manufacturer	: Reckitt Benckiser LLC. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225 +1 973 404 2600
Validation date	: 23/04/2015.
Emergency telephone number	: 1-800-338-6167
Transport Emergency phone:	: 1-800-424-9300 (U.S. & Canada) CHEMTREC Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

D0224478 v5.0

2. Hazards identification

Emergency overview

- Physical state** : Liquid. [Aerosol.]
- Color** : Clear.
- Odor** : Characteristic.
- Signal word:** : DANGER
- Hazard statements** : EXTREMELY FLAMMABLE.
CONTAINER MAY EXPLODE IF HEATED
- Precautionary measures** : Keep out of reach of children. CONTENTS UNDER PRESSURE. Keep away from flames or sparks. Do not puncture, incinerate or store the container at temperatures above 120°F or in direct sunlight. Use only with adequate ventilation. Avoid contact with eyes and Food. Wash thoroughly after handling.
- OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential acute health effects

- Skin** : Slightly irritating to the skin.
- Eyes** : Moderately irritating to eyes.

Potential chronic health effects

- Chronic effects** : Contains material that may cause target organ damage, based on animal data.
- Carcinogenicity** : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.
- Target organs** : Contains material which may cause damage to the following organs: blood, lungs, the reproductive system, liver, heart, upper respiratory tract, skin, eyes, central nervous system (CNS).

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Eyes** : Adverse symptoms may include the following:
irritation
redness
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

Hazard statements :

3. Composition/information on ingredients

Name	CAS number	%
Ethanol	64-17-5	30 - 60
n-butane	106-97-8	5 - 10
Propane	74-98-6	1 - 2.5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

D0224478 v5.0

4. First aid measures

First aid

- Eye contact** : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : Use personal protective equipment as required.
- Notes to physician** : Contains denatured ethanol; ingestion may result in ethanol poisoning.

5. Fire-fighting measures

Flammability Remark : Not available.

Explosibility Remark : Not available.

Flammability of the product

Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable None known.

Special hazards arising from the substance or mixture

Special exposure hazards

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products

Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

NFPA (30B) aerosol Flammability

Level 1

Fire or projection hazard.

Aerosol cans may explode with extreme heat and become projectiles.

Advice for firefighters

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on explosion hazards

Sensitivity to mechanical impact

Not available.

Sensitivity to static discharge

Not available.

6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Empty containers retain product residue and can be hazardous.
- Do not puncture or incinerate CONTENTS UNDER PRESSURE
- Storage** : Do not store above the following temperature: 50°C (120°F). Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

D0224478 v5.0

7. Handling and storage

CONTAINERS SHOULD BE KEPT OUT OF REACH OF CHILDREN. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn after use. Keep away from all sources of ignition. Fires involving flammable aerosols are severe and can spread very quickly. Warehouses and stores containing aerosols should therefore be separated from other areas by a fire resistant construction of at least one half hour duration. Stores should be well ventilated, particularly at low levels. The natural ventilation in a large open warehouse building will normally be suitable. Avoid the storage of aerosols in basements where practicable.

EPA Product : It is a violation of federal law to use this product in a manner inconsistent with its labeling.

8. Exposure controls/personal protection

<u>Occupational exposure limits</u>		TWA (8 hours)			STEL (15 mins)			Ceiling (ACGIH TLV)			Notations
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	
butane	US ACGIH 6/2013	-	-	-	1000	-	-	-	-	-	
	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 7/2013	600	-	-	750	-	-	-	-	-	
	ON 1/2013	800	-	-	-	-	-	-	-	-	
	QC 12/2012	800	1900	-	-	-	-	-	-	-	
ethanol	US ACGIH 6/2013	-	-	-	1000	-	-	-	-	-	
	AB 4/2009	1000	1880	-	-	-	-	-	-	-	
	BC 7/2013	-	-	-	1000	-	-	-	-	-	
	ON 1/2013	-	-	-	1000	-	-	-	-	-	
	QC 12/2012	1000	1880	-	-	-	-	-	-	-	
propane	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 7/2013	1000	-	-	-	-	-	-	-	-	
	ON 1/2013	1000	-	-	-	-	-	-	-	-	
	QC 12/2012	1000	1800	-	-	-	-	-	-	-	

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Manufacturer: Exposure controls

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

D0224478 v5.0

8. Exposure controls/personal protection

Personal protection

Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Other protection	: Not available.

9. Physical and chemical properties

Physical state	: Liquid. [Aerosol.]
Flash point	: Closed cup: 25.6°C (78.1°F)
Burning time	: Not applicable.
Burning rate	: Not applicable.
Auto-ignition temperature	: Not available.
Flammable limits	: Not available.
Color	: Clear.
Odor	: Characteristic.
Taste	: Not available.
Molecular weight	: Not applicable.
Molecular formula	: Not applicable.
pH	: 10.8 to 11.8 [Conc. (% w/w): 100%]
Boiling/condensation point	: Not available.
Melting/freezing point	: Not available.
Critical temperature	: Not available.
Relative density (g/ml)	: 0.8667 to 0.8967 g/cm³ [20 to 25°C]
Bulk density	: 7.1 to 7.5 lbs/gal
Vapor pressure	: Not available.

D0224478 v5.0

9. Physical and chemical properties

Vapor density	: Not available.
Volatility	: Not available.
Odor threshold	: Not available.
Evaporation rate	: Not available.
SADT	: Not available.
Viscosity	: Not available.
Ionicity (in water)	: Not available.
Dispersibility properties	: Not available.
Solubility	: Easily soluble in the following materials: cold water and hot water.
Physical/chemical properties comments	: Not available.

Aerosol product

Type of aerosol	: Spray
Heat of combustion	: 21.41 kJ/g
Ignition distance	: <45.72 cm

10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Keep away from extreme heat. Protect from moisture. Keep from freezing. Do not store above 50°C
Incompatible materials	: Do not mix with household chemicals.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
butane	LC50 Inhalation Vapor	Rat	658000 mg/m ³	4 hours
ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Oral	Rat	7 g/kg	-
*Lysol® Brand Disinfectant Spray, All Scents (Aerosol)	LC50 Inhalation Vapor	Rat	>2.12 mg/l	4 hours Maximum attainable concentration

Conclusion/Summary : Not classified Harmful. *Information is based on toxicity test result of the concentrate of a similar product.

Chronic toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Conclusion/Summary : Not available.

D0224478 v5.0

11. Toxicological information

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-
*Lysol® Brand Disinfectant Spray, All Scents (Aerosol)	Eyes - Cornea opacity	Rabbit	< 1	72 hours	4 days
	Skin - Primary dermal irritation index (PDII)	Rabbit	0.3	4 hours	72 hours

Conclusion/Summary : Not available.

Skin : Slightly irritating to the skin. *Information is based on toxicity test result of the concentrate of a similar product.

Eyes : Moderately irritating to eyes. *Information is based on toxicity test result of the concentrate of a similar product.

Respiratory : Not available.

Sensitizer

Product/ingredient name	Route of exposure	Species	Result
Not available.			

Conclusion/Summary : Not available.

Skin : Not available.

Respiratory : Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Conclusion/Summary : Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
ethanol	A3	1	-	-	-	-

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Not available.			

Conclusion/Summary : Not available.

Teratogenicity

Product/ingredient name	Result	Species	Dose	Exposure
Not available.				

Conclusion/Summary : Not available.

D0224478 v5.0

11. Toxicological information

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
Not available.						

Conclusion/Summary : Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water Acute EC50 2000 µg/l Fresh water Acute LC50 25500 µg/l Marine water Acute LC50 42000 µg/l Fresh water Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 0.375 ul/L Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae Fish - Oncorhynchus mykiss Algae - Ulva pertusa Fish - Gambusia holbrooki - Larvae	96 hours 48 hours 48 hours 4 days 96 hours 12 weeks

Conclusion/Summary : Not available.

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Not available.				

Conclusion/Summary : Not available.

Partition coefficient: n-octanol/water : Not available.

Bioconcentration factor : Not available.

Mobility : Not available.

Toxicity of the products of biodegradation : Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations



Waste disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

D0224478 v5.0

14. Transport information

For long distance transport of bulk material or shrunk pallet take into consideration sections 7 and 10.

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
TDG Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
Mexico Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
IMDG Class	UN1950	Aerosols, flammable	2.1	-		Limited quantity
IATA-DGR Class	UN1950	Aerosols, flammable	2.1	-		See DG List

PG* : Packing group

15. Regulatory information

United States

U.S. Federal regulations : TSCA 8(a) PAIR: 2-methylpropan-2-ol
SARA 302/304: No products were found.
SARA 311/312 Hazards identification: Fire hazard, Delayed (chronic) health hazard
Clean Water Act (CWA) 311: ammonia
Clean Air Act (CAA) 112 regulated flammable substances: butane; propane

Clean Air Act Section 112 : Not listed

(b) Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 : Not listed
Class I Substances

Clean Air Act Section 602 : Not listed
Class II Substances

DEA List I Chemicals : Not listed
(Precursor Chemicals)

DEA List II Chemicals : Not listed
(Essential Chemicals)

SARA 311/312 HCS 1994

Classification : Fire hazard
Delayed (chronic) health hazard

Composition/information on ingredients

D0224478 v5.0

15. Regulatory information

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
butane	5 - 10	Yes.	Yes.	No.	No.	Yes.
ethanol	30 - 60	Yes.	No.	No.	Yes.	Yes.
propane	1 - 2.5	Yes.	Yes.	No.	No.	Yes.

State regulations

- Massachusetts** : The following components are listed: ETHYL ALCOHOL; BUTANE; PROPANE
- New York** : None of the components are listed.
- New Jersey** : The following components are listed: ETHYL ALCOHOL; ALCOHOL; BUTANE; PROPANE
- Pennsylvania** : The following components are listed: DENATURED ALCOHOL; BUTANE; PROPANE

Canada

- WHMIS (Canada)** : Class B-2: Flammable liquid
Class B-5: Flammable aerosol.

Canadian lists

- Canadian NPRI** : The following components are listed: Ethanol; Butane (all isomers); Propane
- CEPA Toxic substances** : None of the components are listed.
- Canada inventory** : Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

16. Other information

Hazardous Material Information System (U.S.A.) :

Health	1
Flammability	3
Physical hazards	0
Personal protection	B

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) :



NFPA (30B) aerosol Flammability Level 1

D0224478 v5.0

16. Other information

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of issue : 23/04/2015.
Date of previous issue : 22/04/2015.
Version : 5
Prepared by : Reckitt Benckiser LLC.
Product Safety Department
1 Philips Parkway
Montvale, New Jersey 07646-1810 USA.
FAX: 201-476-7770

Revision comments : Update & Revision of the SDS. Addition of formula #0175927.

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



MARVEL OIL CO., INC.
2250 W. Pinehurst Blvd., STE 150
Addison, IL 60101

SAFETY DATA SHEET

1. Product and Company Identification

1.1 Product Identifier

Product Name: Marvel Air Tool Oil
Product Code (SKU): MM85R1 (50100), MM080R (50093) - See Section 15 for discontinued SKU's

1.2 Relevant Identified Uses Of The Substance

Product Use: Engine Oil Additive – Fuel additive (EPA Registered)

1.3 Details of the Supplier of the SDS

Company Name: Marvel Oil Company, Inc.
Street Address: 2250 W. Pinehurst Blvd., Suite 150
City, State, Zip Code: Addison, IL 60101

1.4 Emergency Telephone Numbers

Phone Number: 1(630)455-3700
Fax Number: 1(630)455-3868
Transportation: 1(800)424-9300 (CHEMTREC)
Medical Assistance: Call your local Poison Control Center

2. Hazard Identification:

2.1 Classification of the Substance or Mixture

Hazard Classification: Flammable liquid 3
Skin irritation 2
Reproductive Toxicity 2
Aspiration toxicity 1

2.2 Label Elements



Pictogram:

Signal Word: Danger

Hazard Statement: Flammable liquid and vapor. Causes skin irritation.
Suspected of damaging fertility of the un-born child. May be fatal if swallowed and enters airways.

Precautionary Statement: Keep away from heat, sparks, open flames or hot surfaces. Do not smoke. Keep containers tightly closed. Ground all containers and receiving equipment. Use explosion proof electrical, ventilation, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static

discharge. Wear protective gloves, clothing, eye glasses and face shield. Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. If exposed, get medical attention. If on skin or hair, remove immediately all contaminated clothing and launder before re-use. Wash skin with soap and water. If skin irritation occurs, get medical attention. If swallowed, immediately call a poison control center or doctor. Do NOT induce vomiting. Store in a well ventilated place. Dispose of contents and container in accordance with all local, state, national and international regulations.

2.3 Other Hazards

Description of additional HNOC: None

3. Information on Ingredients:

3.1 Substance not applicable

3.2 Mixture

<u>Component</u>	<u>CAS Number</u>	<u>Concentration (wt%)</u>
Petroleum Distillates (Hydrotreated Heavy Naphthenic)	64742-52-5	60-100%
Petroleum Distillates (Stoddard Solvent)	8052-41-3	10-30%
Tricresyl Phosphate	1330-78-5	0.1-1.0%
Ortho Dichlorobenzene	95-50-1	0.1-1.0%
Para Dichlorobenzene	106-46-7	<0.1%

4. First Aid Measures:

4.1 Description of First Aid Measures

Inhalation: Remove to fresh air and promote deep breathing. Get medical attention if effects persist or you feel un-well.

Skin: In case of skin contact, wash thoroughly with soap and water. Remove contaminated clothing and footwear. Launder clothing before re-use. Call a physician if irritation develops or persists.

Eyes: In case of eye contact, immediately flush eyes with plenty of water. Remove contact lenses if worn. If irritation persists, get medical attention

Ingestion: If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a poison control center or physician.

4.2 Most important symptoms and effects – acute and chronic

Inhalation: May cause respiratory tract irritation. Vapors may cause drowsiness or dizziness.

Skin: Cause skin irritation. Symptoms may include redness, edema, drying, defatting, and cracking of skin.

Eyes: May cause temporary eye irritation. Symptoms may include discomfort or pain, excess blinking and tearing, with redness and swelling.

Ingestion: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea, and vomiting.

4.3 Indication of any immediate medical attention and special treatment

Symptoms may not appear immediately. Seek medical attention if effects develop or persist and you feel un-well.

5. Fire Fighting Measures:

5.1 Extinguishing media

Carbon dioxide, dry chemical, and alcohol foam

5.2 Special hazards arising from the substance or mixture

CO₂, CO, and hydrocarbons

5.3 Advice for Fire Fighters

Keep up wind of fire. Wear full firefighting turn out gear (full bunker gear) and respiratory protection (SCBA). Cool closed containers exposed to fire with water. See Section 8 for personal protection.

6. Accidental Release Measures:

6.1 Personal precautions, protective equipment, and emergency procedures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate all source of ignition.

6.2 Methods and materials for containment and clean up

For containment: Contain and absorb spill with inert material. Place in suitable container for disposal. Do not flush to sewer or allow to enter waterways. See section 8 for PPE.

For clean up: Take up material and place in a suitable container. Vapors may be heavier than air and may travel along the ground to a distant source of ignition. Provide adequate ventilation.

7. Handling and Storage

7.1 Precautions for safe handling

Keep away from source of ignition. Do not smoke. Take precaution to eliminate static discharge. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Do not swallow. Do not eat or drink while handling. Wash hands with soap and water after handling. Use only non-sparking tools.

7.2 Conditions for safe storage including incompatibilities

Keep out of reach of children. Store in a well ventilated place. Do not store above 49°C (120°F).

7.3 Specific end uses

Shelf Life: Shelf life is considered to be 7 – 10 years when properly stored.

8. Exposure Control/Personal Protection:

8.1 Control parameters

<u>Exposure Limits</u>	<u>8 hr TWA:</u>	<u>(OSHA PEL)</u>	<u>(ACGIH TWA)</u>
Petroleum Distillates (Hydrotreated Heavy Naphthenic)		not applicable	not applicable
Petroleum Distillates (Stoddard Solvent)		500 ppm	100 ppm
Tricresyl Phosphate		not applicable	not applicable
Ortho Dichlorobenzene		50 ppm	25 ppm
Para Dichlorobenzene		75 ppm	10 ppm

8.2 Exposure controls

Use adequate ventilation to keep exposure below recommended limits. Ensure that eye wash station and safety shower are close to work station.

Hand Protection Equipment: Wear chemical resistant gloves to prevent skin contact.

Eye Protection Equipment: Wear safety glasses or splash goggles to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiration/Ventilation Protection Requirements: Provide good ventilation.

Ingestion Protection Requirements: Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before re-use.

9. Physical And Chemical Properties:

9.1 Information of basic chemical and physical properties

Physical Form:	thin liquid
Color:	clear red
Odor:	typical oily
Odor Threshold:	not available
pH:	not applicable – oil based product
Melting Point/Freeze Point:	-51°C (-60°F)
Initial Boiling Point:	not available
Flash Point (Seta Closed Cup):	53°C (128°F)
Flammability Limits:	Explosive Limits: Upper: not available Lower: not available
Evaporation Rate:	not available
Flammability Solid/Gas:	not applicable
Vapor Pressure:	not available
Vapor Density:	not available
Specific Gravity:	0.876
Solubility in Water:	insoluble
Auto Ignition Temperature:	not available
Partition coefficient (n/octonol/water):	not available
Viscosity (Kinimatic @ 100°C):	2.0 – 3.0 cSt

9. 2 Other information

% NVM by Weight:	75.0%
% VOC Content (California):	24.92%

10. Stability and Reactivity:

10.1 Reactivity

Does not react under normal conditions

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Does not react under normal conditions

10.4 Conditions to avoid

Heat and incompatible materials

10.5 Incompatible materials

Strong oxidizers such as bleach and peroxides

10.6 Hazardous decomposition products

CO₂, CO and hydrocarbons

11. Toxicological Information:

11.1 Information on Toxicological effects

Marvel Mystery Oil

LD50 – Oral Rat	>2000 mg/Kg
LD50 – Dermal Rabbit	>2000 mg/Kg
LC50 – Inhalation Rat	>20 mg/L (4 hr)

Petroleum Distillates Hydrotreated Heavy Naphthenic (64742-52-5)

LD50 – Oral Rat	>5000 mg/Kg
LD50 – Dermal Rabbit	>5000 mg/Kg
LC50 – Inhalation Rat	>5 mg/L (4 hr)

Tricresyl Phosphate (1330-78-5)

LD50 – Oral Rat	3000 mg/Kg

o-Dichlorobenzene (95-50-1)

LD50 – Oral Rat	500 mg/Kg
LD50 – Dermal Rabbit	>10000 mg/Kg
LC50 – Inhalation Rat	8.15 mg/L (4 hr)

p-Dichlorobenzene (106-46-7)

LD50 – Oral Rat	>2000 mg/Kg
LD50 – Dermal Rabbit	>2000 mg/Kg

Skin corrosion/irritation

Causes skin irritation

Serious eye damage/irritation

Based on available data, classification data are not met

Respiratory or skin sensitization

Based on available data, classification data are not met

Germ cell mutagenicity

Based on available data, classification data are not met

Carcinogenicity

Based on available data, classification data are not met

o-Dichlorobenzene (95-50-1)

IARC Group 3 – Not Classified

p-dichlorobenzene (106-46-7)	IARC Group 2B – Possible carcinogen to humans. NTP 1-Evidence of Carcinogenicity 3, Reasonably anticipated to be a human Carcinogen
Reproductive toxicity	Suspected of damaging fertility of un-born child
Specific target organs – single exposure	Based on available data, classification data are not met
Specific target organs – repeated exposure	Based on available data, classification data are not met
Aspiration hazard	May be fatal if swallowed and enters air ways.
Symptoms/injuries after inhalation	May cause respiratory tract irritation. Vapors may cause drowsiness and dizziness.
Symptoms/injuries after skin contact	Cause skin irritation. Symptoms may include redness, edema, drying, defatting, and cracking of skin.
Symptoms/injuries after eye contact	May cause temporary eye irritation. Symptoms may include discomfort or pain, excess blinking and tearing, with redness and swelling.
Symptoms/injuries after ingestion	May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea, and vomiting.

12. Ecological Information:

12.1 Toxicity

Not recommended for release into aquatic systems without treatment

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential

Not established

12.4 Mobility in soil

Not established

12.5 Other adverse effects

None known

13. Disposal Considerations:

13.1 Waste treatment methods

RCRA Hazardous Waste:
Waste Disposal Method:

Regulated as a hazardous waste (D-001 Ignitable).
Dispose of in accordance with local, state and federal regulations

Waste Disposal Vessel:

Metal drums are recommended.

14. Transportation Information:

14.1 UN number

1268

14.2 UN Proper shipping name

Petroleum Distillate n.o.s.

14.3 Transport Hazard class

3

14.4 Packaging group

III

14.5 Marine Pollutant

No

14.6 Transportation in Bulk

Not applicable

14.7 Special precautions

Use limited quantities

15. Regulatory Information:**15.1 US Federal Regulations**

TSCA Status: All ingredients are commercially available and listed by the manufacturer under TSCA.

15.2 Foreign Regulations

Canadian Status: All materials contained in this product are listed on the Canadian Domestic Substance List (DSL). Consult Turtle Wax, Inc. regarding status of ingredients.

European Union: All materials contained in this product are listed on EINECS.

AICS: All materials are registered for AICS (Australia)

15.3 State Regulations**State Regulatory Information:**

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements, contact the appropriate agency in your state.

California Prop 65:

<u>CAS Number</u>	<u>Concentration</u>	<u>State Code</u>
p-Dichlorobenzene (106-46-7)	<0.1%	Cancer

15.4 HMIS & NFPA Classifications

HMIS Classification:	Health	2
	Flammability	2
	Reactivity	0
NFPA Classification:	Health	2
	Flammability	2

Reactivity 0

15.5 Discontinued SKU's All discontinued SKU's used this same formula.

MM080, MM085, MM85R, MM086, MM088R, MM089

16. Other Information:

Reason For Issue	Address Update
Prepared By	James Heidel
Preparer's Title	Technical Director, R&D
SDS Administrator	Jean Mayszak - Technical Compliance Manager, R&D
Approval Date	January 26, 2017
Supersedes Date	March 10, 2015
Revision Number	#12

This information is, to the best of Turtle Wax, Inc.'s knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitability and completeness of such information for their own particular use.

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : NAPA® MAC'S WINDSHIELD DEICER DEICER

Product code : 7000

Manufacturer or supplier's details

Company name of supplier : Niteo Products,LLC

Address : Dallas TX 19162

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable aerosols : Category 2

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 3

Acute toxicity (Dermal) : Category 3

Specific target organ toxicity - single exposure : Category 1 (Central nervous system, Eyes)

Specific target organ toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

GHS Label element

Hazard pictograms :

Signal word : Danger
DangerHazard statements : H223 Flammable aerosol.
H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

H370 Causes damage to organs (Central nervous system, Eyes).
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.
H223 Flammable aerosol.
H301 + H311 + H331 Toxic if swallowed, in contact with skin or if inhaled
H370 Causes damage to organs (Central nervous system, Eyes).
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary statements

: Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing.

Response:

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
P302 + P352 + P312 IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.
P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.
P362 Take off contaminated clothing and wash before reuse.
P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
P302 + P352 + P312 IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.
P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture
Substance name	: Blend used in aerosol is R0262703

Hazardous components

Chemical Name	CAS-No.	Concentration (% w/w)
METHANOL	67-56-1	>= 50 - < 70
ETHYLENE GLYCOL	107-21-1	>= 5 - < 10
CARBON DIOXIDE	124-38-9	>= 1 - < 5
MORPHOLINE	110-91-8	>= 0.1 - < 1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician. Move to fresh air. Keep patient warm and at rest.
In case of skin contact	: Wash off with warm water and soap. Wash contaminated clothing before re-use.

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing.
If swallowed	: Get medical attention immediately. Rinse mouth with water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Toxic if swallowed, in contact with skin or if inhaled Causes damage to organs. May cause damage to organs through prolonged or repeated exposure if swallowed. Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.
Notes to physician	: This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Water spray Carbon dioxide (CO ₂) Dry chemical Alcohol-resistant foam

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

-
Unsuitable extinguishing media	: High volume water jet
Specific hazards during fire-fighting	: Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: Carbon oxides Aldehydes
Specific extinguishing methods	: Product is compatible with standard fire-fighting agents.
Further information	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: In the event of fire, wear self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing dust. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Evacuate personnel to safe areas. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Comply with all applicable local, state and federal regulations.
Environmental precautions	: Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment. Do not spray on a naked

NAPA® MAC'S WINDSHIELD DEICER

Version 1.1 Revision Date: 07/21/2016 MSDS Number: 600000000431 Date of last issue: 05/23/2016
 Date of first issue: 05/23/2016

flame or any incandescent material.

- Advice on safe handling** : Open drum carefully as content may be under pressure.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Do not breathe vapours/dust.
 Do not smoke.
 Take precautionary measures against static discharges.
 Dispose of rinse water in accordance with local and national regulations.
 Container hazardous when empty.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
- Conditions for safe storage** : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
 Keep container tightly closed in a dry and well-ventilated place.
 Observe label precautions.
 No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
METHANOL	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m3	NIOSH REL
		ST	250 ppm 325 mg/m3	NIOSH REL
		TWA	200 ppm 260 mg/m3	OSHA Z-1
		STEL	250 ppm 325 mg/m3	OSHA P0
ETHYLENE GLYCOL	107-21-1	TWA	200 ppm 260 mg/m3	OSHA P0
		C (Aerosol only)	100 mg/m3	ACGIH
CARBON DIOXIDE	124-38-9	C	50 ppm 125 mg/m3	OSHA P0
		TWA	5,000 ppm	ACGIH
		STEL	30,000 ppm	ACGIH
		TWA	5,000 ppm 9,000 mg/m3	NIOSH REL
		ST	30,000 ppm 54,000 mg/m3	NIOSH REL
		TWA	5,000 ppm	OSHA Z-1

NAPA® MAC'S WINDSHIELD DEICER

Version 1.1 Revision Date: 07/21/2016 MSDS Number: 600000000431 Date of last issue: 05/23/2016
 Date of first issue: 05/23/2016

			9,000 mg/m3	
		TWA	10,000 ppm 18,000 mg/m3	OSHA P0
		STEL	30,000 ppm 54,000 mg/m3	OSHA P0
MORPHOLINE	110-91-8	TWA	20 ppm	ACGIH
		TWA	20 ppm 70 mg/m3	NIOSH REL
		ST	30 ppm 105 mg/m3	NIOSH REL
		TWA	20 ppm 70 mg/m3	OSHA Z-1
		TWA	20 ppm 70 mg/m3	OSHA P0
		STEL	30 ppm 105 mg/m3	OSHA P0

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis
METHANOL	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
 Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear as appropriate:

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

Impervious clothing
Flame-resistant clothing
Safety shoes
Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: aerosol
Odour	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 64.7 °C (1,013.25 hPa) Value for Component
Flash point	: 12 °C The value is calculated
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 36 %(V) The value is calculated
Lower explosion limit	: 3.2 %(V) The value is calculated
Vapour pressure	: 169.3164 hPa (25 °C) Value for Component
Density	: 0.7972 g/cm3 (15.56 °C)
Solubility(ies) Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Viscosity Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

Heat of combustion : estimated 15.35 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks. Exposure to sunlight.
Incompatible materials	: Aldehydes Alkali metals Alkaline earth metals Aluminium Lead Strong acids Strong bases Strong oxidizing agents Sulphur compounds Zinc Peroxides

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Eye contact
Skin contact

Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled

Product:

Acute oral toxicity	: Acute toxicity estimate: 159.13 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate: 0.8 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate: 479.17 mg/kg Method: Calculation method

Components:**METHANOL:**

Acute oral toxicity	: LDLo (Humans): 300 mg/kg

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

Assessment: The component/mixture is toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg
Assessment: The component/mixture is toxic after single contact with skin.

ETHYLENE GLYCOL:

Acute oral toxicity : LD50 (Rat): 6,140 mg/kg

LD50 (Humans): estimated 1.56 g/kg
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg

MORPHOLINE:

Acute oral toxicity : LD50 (Rat): ca. 1,900 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The component/mixture is toxic after short term inhalation.

Acute dermal toxicity : LD50 (Rabbit): ca. 500 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:**METHANOL:**

Species: Rabbit
Result: No skin irritation

ETHYLENE GLYCOL:

Result: Mild skin irritation

CARBON DIOXIDE:

Assessment: No skin irritation
Result: No skin irritation

MORPHOLINE:

Result: Corrosive after 3 minutes or less of exposure

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: No eye irritation

Remarks: Unlikely to cause eye irritation or injury.

Components:**METHANOL:**

Species: Rabbit

Result: Possibly irritating to eyes

ETHYLENE GLYCOL:

Result: Possibly irritating to eyes

CARBON DIOXIDE:

Result: No eye irritation

MORPHOLINE:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:**METHANOL:**

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:**MORPHOLINE:**

Genotoxicity in vitro

- : Test Type: unscheduled DNA synthesis assay
Species: rat hepatocytes
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 482
Result: negative
- : Test Type: In vitro mammalian cell gene mutation test
Species: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Causes damage to organs (Central nervous system, Eyes).

Components:**METHANOL:**

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

STOT - repeated exposure

May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Components:**ETHYLENE GLYCOL:**

Exposure routes: Ingestion

Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

Waste from residues	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION**International Regulation****IATA-DGR**

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Class	: 2.1
Subsidiary risk	: 6.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas, Toxic
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCES IN DIVISION 6.1, PACKING GROUP III
Class	: 2.1
Subsidiary risk	: 6.1
Packing group	: Not assigned by regulation
Labels	: 2.1 (6.1)
EmS Code	: F-D, S-U
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number	: UN 1950
Proper shipping name	: AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCES IN DIVISION 6.1, PACKING GROUP III
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Class 2 - Gases: Flammable (Division 2.1)
ERG Code	: 126
Marine pollutant	: no

NAPA® MAC'S WINDSHIELD DEICER

Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Component RQ (lbs)
METHANOL	67-56-1	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard
Chronic Health Hazard
Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

METHANOL	67-56-1	62.458 %
ETHYLENE GLYCOL	107-21-1	5.921 %

US State Regulations**Massachusetts Right To Know**

METHANOL	67-56-1	50 - 70 %
ETHYLENE GLYCOL	107-21-1	5 - 10 %
CARBON DIOXIDE	124-38-9	1 - 5 %

Pennsylvania Right To Know

METHANOL	67-56-1	50 - 70 %
WATER	7732-18-5	20 - 30 %
ETHYLENE GLYCOL	107-21-1	5 - 10 %
CARBON DIOXIDE	124-38-9	1 - 5 %

New Jersey Right To Know

METHANOL	67-56-1	50 - 70 %
WATER	7732-18-5	20 - 30 %
ETHYLENE GLYCOL	107-21-1	5 - 10 %
CARBON DIOXIDE	124-38-9	1 - 5 %

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive

NAPA® MAC'S WINDSHIELD DEICER


Version	Revision Date:	MSDS Number:	Date of last issue: 05/23/2016
1.1	07/21/2016	600000000431	Date of first issue: 05/23/2016

harm.

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:
ETHYLENE GLYCOL MONOMETHYL ETHER 109-86-4

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	2*
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 07/21/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

1. PRODUCT AND COMPANY IDENTIFICATION

Product information

Product name : OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Recommended use : Insect Repellent

Restrictions on use : Use only as directed on label

Manufacturer, importer, supplier : S.C. Johnson and Son, Limited
1 Webster Street
Brantford ON N3T 5R1

Telephone : +1-800-558-5566

Emergency telephone number : 24 Hour Transport & Medical Emergency Phone (866) 231-5406
24 Hour International Emergency Phone (952) 852-4647
24 Hour Canadian Transport Emergency Phone (CANUTEC) (613) 996-6666

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Globally Harmonized System (GHS) Classification

Hazard classification	Hazard category	Hazards identification
Aerosol	Category 1	Extremely flammable aerosol.
Eye irritation	Category 2A	Causes serious eye irritation.
Gases under pressure	Liquefied gas	Contains gas under pressure; may explode if heated.

Labelling

Hazard symbols

Flame
Gas cylinder
Exclamation mark

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Signal word

Danger

Hazard statements

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.

Precautionary statements

If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/ attention.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Store in a well-ventilated place.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Wear protective gloves/ protective clothing/ eye protection/ face protection.
Wash hands thoroughly after handling.

Other hazards

: Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous chemicals present at or above reportable levels as defined by Canadian Hazardous Products Regulation are listed in this table.

Chemical name	CAS-No.	Weight percent
Ethyl alcohol	64-17-5	40.00 - 60.00
N,N-Diethyl-m-toluamide	134-62-3	30.00 - 40.00

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Butane	106-97-8	3.00 - 5.00
Propane	74-98-6	1.50 - 3.00
Isobutane	75-28-5	1.50 - 3.00

The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

For additional information on product ingredients, see www.whatsinsidescjohnson.com.

4. FIRST AID MEASURES

Description of first aid measures

- Eye contact** : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention.
- Skin contact** : If you suspect a reaction to this product, discontinue use and remove contaminated clothing.
- Inhalation** : No special requirements.
- Ingestion** : No special requirements

Most important symptoms and effects, both acute and delayed

- Eyes** : Causes serious eye irritation.
- Skin effect** : No adverse effects expected when used as directed.
- Inhalation** : Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.
- Ingestion** : May cause irritation to mouth, throat and stomach.
May cause abdominal discomfort.
No adverse effects expected when used as directed.

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Indication of any immediate medical attention and special treatment needed

See Description of first aid measures unless otherwise stated.

5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Specific hazards during firefighting	: Aerosol Product - Containers may rocket or explode in heat of fire. Do not allow run-off from fire fighting to enter drains or water courses.
Further information	: Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers. Wear full protective clothing and positive pressure self-contained breathing apparatus. In case of fire and/or explosion do not breathe fumes.
NFPA Classification	: NFPA Level 2 Aerosol

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	: Remove all sources of ignition. Wear personal protective equipment. Wash thoroughly after handling.
Environmental precautions	: Do not flush into surface water or sanitary sewer system. Use appropriate containment to avoid environmental contamination. Outside of normal use, avoid release to the environment.
Methods and materials	: If damage occurs to aerosol can:

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Use only non-sparking equipment.
Dike large spills.
Clean residue from spill site.

7. HANDLING AND STORAGE

Handling

Precautions for safe handling

: Avoid contact with eyes and lips.
For personal protection see section 8.
Use only as directed.
KEEP OUT OF REACH OF CHILDREN AND PETS.
Pressurized container.
Do not pierce or burn, even after use.
Wash thoroughly after handling.

Advice on protection against fire and explosion

: Keep away from sources of ignition - No smoking.
Do not spray on an open flame or other ignition source.

Storage

Requirements for storage areas and containers

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Keep away from food, drink and animal feedingstuffs.
Keep in a dry, cool and well-ventilated place.

Other data

: Stable under recommended storage conditions.

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Components	CAS-No.	mg/m3	ppm	Non-standard units	Basis
Ethyl alcohol	64-17-5	-	1,000 ppm	-	ACGIH STEL
Butane	106-97-8	-	1,000 ppm	-	ACGIH STEL
Propane	74-98-6	-	-	-	ACGIH TWA
Isobutane	75-28-5	-	1,000 ppm	-	ACGIH STEL

Personal protective equipment

Respiratory protection : Do not spray in enclosed areas.

Hand protection : No special requirements.

Eye protection : Safety glasses with side-shields

Skin and body protection : No special requirements.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Form	: aerosol
Color	: clear
Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: Not applicable
Initial boiling point and boiling range	: No data available
Flash point	: < -7 °C < 19.4 °F Method: Tag Closed Cup (TCC) Propellant
Evaporation rate	: No data available
Flammability (solid, gas)	: Sustains combustion
Upper/lower flammability or explosive limits	: No data available
Vapour pressure	: No data available
Vapour density	: No data available

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Relative density : 0.84 g/cm³ at 21 °C

Solubility(ies) : slightly soluble

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity, dynamic :

Viscosity, kinematic : No data available

Oxidizing properties : No data available

Volatile Organic Compounds : 65 % - additional exemptions may apply
Total VOC (wt. %)* *as defined by US Federal and State Consumer Product Regulations

Other information : None identified :

10. STABILITY AND REACTIVITY

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : Stable under recommended storage conditions.

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Thermal decomposition can lead to release of irritating gases and vapours.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	: LD50 2,329 mg/kg
Acute inhalation toxicity	: LC50 > 10 mg/L
Acute dermal toxicity	: LD50 > 5,000 mg/kg

GHS Properties	Classification	Routes of entry
Acute toxicity	No classification proposed	Oral
Acute toxicity	No classification proposed	Dermal
Acute toxicity	No classification proposed	Inhalation - Dust and Mist
Acute toxicity	No classification proposed	Inhalation - Vapour
Acute toxicity	No classification proposed	Inhalation - Gas
Skin corrosion/irritation	No classification proposed	-
Eye irritation	Category 2A	-

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Skin sensitisation	No classification proposed	-
Respiratory sensitisation	No classification proposed	-
Germ cell mutagenicity	No classification proposed	-
Carcinogenicity	No classification proposed	-
Reproductive toxicity	No classification proposed	-
Specific target organ toxicity - single exposure	No classification proposed	-
Specific target organ toxicity - repeated exposure	No classification proposed	-
Aspiration hazard	No classification proposed	-

Aggravated Medical Condition : Do not apply to cuts or irritated skin.

12. ECOLOGICAL INFORMATION

Product : The product itself has not been tested.

Toxicity

The ingredients in this formula have been reviewed and no adverse impact to the environment is expected when used according to label directions.

Toxicity to fish

Components	End point	Species	Value	Exposure time
Ethyl alcohol	LC50	Fish	11,200 mg/l	96 h

Safety Data Sheet

classification according to Canadian Hazardous Products
Regulation

**OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT
(REG. NO. 23487 P.C.P. ACT)**

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

N,N-Diethyl-m-toluamide	static test LC50	Oncorhynchus mykiss (rainbow trout)	71.25 mg/l	96 h
Butane	LC50 QSAR	Fish	27.98 mg/l	96 h
Propane	LC50	Fish	27.98 mg/l	96 h
Isobutane	LC50 QSAR	Fish	27.98 mg/l	96 h

Toxicity to aquatic invertebrates

Components	End point	Species	Value	Exposure time
Ethyl alcohol	static test LC50	Ceriodaphnia dubia	5,012 mg/l	48 h
	NOEC	Daphnia magna	9.6 mg/l	9 d
N,N-Diethyl-m-toluamide	LC50	Daphnia magna (Water flea)	75 mg/l	51 h

Safety Data Sheet

classification according to Canadian Hazardous Products
Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

	semi-static test NOEC Measured OECD Guideline 211 (Daphnia magna Reproduction Test)	Daphnia magna	3.7 mg/l	21 d
Butane	No data available			
Propane	LC50	Daphnid	14.22 mg/l	48 h
Isobutane	LC50 QSAR	Daphnid	16.33 mg/l	48 h

Toxicity to aquatic plants

Components	End point	Species	Value	Exposure time
Ethyl alcohol	Static EC50	Chlorella vulgaris (Fresh water algae)	275 mg/l	72 h
N,N-Diethyl-m-toluamide	NOEC	Pseudokirchneriella subcapitata (green algae)	0.521 mg/l	96 h
Butane	EC50 QSAR	Green algae	7.71 mg/l	96 h
Propane	No data available			

Safety Data Sheet

classification according to Canadian Hazardous Products
Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Isobutane	EC50 QSAR	Green algae	8.57 mg/l	96 h

Persistence and degradability

Component	Biodegradation	Exposure time	Summary
Ethyl alcohol	97 %	28 d	Readily biodegradable.
N,N-Diethyl-m-toluamide	83.8 %	28 d	Readily biodegradable.
Butane	100 %	385.5 h	Readily biodegradable.
Propane	70 %	< 10 d	Readily biodegradable.
Isobutane	70 %	< 10 d	Readily biodegradable.

Bioaccumulative potential

Component	Bioconcentration factor (BCF)	Partition Coefficient n- Octanol/water (log)
Ethyl alcohol	3.2 estimated	-0.35 Measured
N,N-Diethyl-m-toluamide	21.9 estimated	2.4
Butane	No data available	2.89
Propane	No data available	2.36
Isobutane	1.57 - 1.97	2.8

Safety Data Sheet

classification according to Canadian Hazardous Products
Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

Mobility

Component	End point	Value
Ethyl alcohol	No data available	
N,N-Diethyl-m-toluamide	Koc	43.3
Butane	No data available	
Propane	No data available	
Isobutane	No data available	

PBT and vPvB assessment

Component	Results
Ethyl alcohol	Not fulfilling PBT and vPvB criteria
N,N-Diethyl-m-toluamide	Not fulfilling PBT and vPvB criteria
Butane	Not fulfilling PBT and vPvB criteria
Propane	Not fulfilling PBT and vPvB criteria
Isobutane	Not fulfilling PBT and vPvB criteria

Other adverse effects : None known.

13. DISPOSAL CONSIDERATIONS

PESTICIDAL WASTE:

For disposal information, please read and follow Disposal instructions on the pesticide label.
Consumer may discard empty container in trash, or recycle where facilities exist.

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/receiving documents for up-to-date shipping information.

	Land transport	Sea transport	Air transport
UN number	1950	1950	1950
UN proper shipping name	AEROSOLS, Flammable	AEROSOLS, Flammable	AEROSOLS, Flammable
Transport hazard class(es)	2.1	2	2.1
Packing group	-	-	-
Environmental hazards	-	-	-
Special precautions for user	Limited quantities derogation may be applicable to this product, please check transport documents.	Limited quantities derogation may be applicable to this product, please check transport documents.	Limited quantities derogation may be applicable to this product, please check transport documents.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Product not transported as bulk.	Product not transported as bulk.	Product not transported as bulk.

15. REGULATORY INFORMATION

PCPA Labeling

Read the approved PCPA label prior to using or handling the pest control product.

Safety Data Sheet

classification according to Canadian Hazardous Products Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

This chemical is a pest control product registered by Health Canada Pest Management Regulatory Agency and is subject to certain labelling requirements under the Pest Control Products Act. These requirements differ from the classification criteria and hazard information required for GHS-consistent safety data sheets. Following is the hazard information required on the pest control product label:

DANGER:

Explosive

PRESSURIZED SPRAY

EYE IRRITANT.

Severely irritating to eyes.

This product contains petroleum distillates.

Vomiting may cause aspiration pneumonia.

Extremely flammable.

- Notification status** : All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
- Notification status** : All ingredients of this product comply with the New Substances Notification requirements under the Canadian Environmental Protection Act (CEPA).
- California Prop. 65** : This product is not subject to the reporting requirements under California's Proposition 65.
- Canada Regulations** : This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Safety Data Sheet

classification according to Canadian Hazardous Products
Regulation



OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT (REG. NO. 23487 P.C.P. ACT)

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144

16. OTHER INFORMATION

HMIS Ratings

Health	2
Flammability	4
Reactivity	0

NFPA Ratings

Health	2
Fire	4
Reactivity	0
Special	-

This information is being provided in accordance with Canada's Workplace Hazard Material Information System. The information supplied is designed for workplaces where product use and frequency of exposure exceeds that established for the labeled consumer use.

Further information

This document has been prepared using data from sources considered to be technically reliable. It does not constitute a warranty, expressed or implied, as to the accuracy of the information contained herein. Actual conditions of use are beyond the seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Prepared by	SC Johnson Global Safety Assessment & Regulatory Affairs (GSARA)

Safety Data Sheet

classification according to Canadian Hazardous Products
Regulation



**OFF!® DEEP WOODS® FOR SPORTSMEN 1 INSECT REPELLENT
(REG. NO. 23487 P.C.P. ACT)**

Version 1.0

Print Date 09/07/2017

Revision Date 08/16/2017

SDS Number 350000004808GEN_SOF
Number 16144



PB Penetrating Catalyst

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Date of issue: 11/09/2016

Revision date: 06/26/2017

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product name : PB Penetrating Catalyst
Product code : 16-PB, 8-PB, 8-PBS, PB-TS, 20-PB, 26-PB

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Penetrant

1.3. Details of the supplier of the safety data sheet

Manufacturer

The Blaster Corporation
8500 Sweet Valley Drive
Valley View, Ohio 44125 - USA
T (216) 901-5800 - F (216) 901-5801
www.blastercorp.com

1.4. Emergency telephone number

Emergency number : ChemTel 800-255-3924

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 2
Dissolved gas
Asp. Tox. 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS02

GHS04

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways.

Precautionary statements (GHS-US) : Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

PB Penetrating Catalyst

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

3.2. Mixtures

Name	Product identifier	%
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	50 - 60
Solvent naphtha, petroleum, heavy aromatic	(CAS No) 64742-94-5	20 - 30
Distillates, petroleum, hydrotreated heavy naphthenic	(CAS No) 64742-52-5	20 - 30
Carbon dioxide	(CAS No) 124-38-9	1 - 4

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Direct contact with the eyes is likely to be irritating.
- First-aid measures after ingestion : IF SWALLOWED: immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide, dry chemical, halons or foam.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon and oxides of nitrogen.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : No dangerous reaction known under conditions of normal use.

5.3. Advice for firefighters

- Firefighting instructions : DO NOT fight fire when fire reaches explosives. Evacuate area. Exercise caution when fighting any chemical fire.
- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

PB Penetrating Catalyst

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Use non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharge. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas, fumes, vapour or spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Do not pierce or burn, even after use.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Keep in fireproof place.

Storage area : Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Petroleum distillates, hydrotreated light (64742-47-8)

Not applicable

Solvent naphtha, petroleum, heavy aromatic (64742-94-5)

Not applicable

Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)

Not applicable

Carbon dioxide (124-38-9)

ACGIH	ACGIH TWA (ppm)	5000 ppm

ACGIH	ACGIH STEL (ppm)	30000 ppm

OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m ³

OSHA	OSHA PEL (TWA) (ppm)	5000 ppm

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Safety glasses or goggles are recommended when using product.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

PB Penetrating Catalyst

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear. Aerosol.
Colour	: Orange
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 356 °F (180 °C)
Flash point	: > 141 °F (> 61 °C)
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Flammable aerosol.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.9
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

Heat of Combustion	: 45.8 kJ/g
Flame Projection	: 0 inches
Flashback	: None

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Sources of ignition. Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon and oxides of nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified.

PB Penetrating Catalyst

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

PB Penetrating Catalyst	
LD50 oral rat	> 2000 mg/kg (Calculated Acute Toxicity Estimate)
LD50 dermal rabbit	> 2000 mg/kg (Calculated Acute Toxicity Estimate)
LC50 inhalation rat	> 5 mg/l/4h (Calculated Acute Toxicity Estimate)
Petroleum distillates, hydrotreated light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2 ml/kg
LC50 inhalation rat	> 590 mg/m ³ (Exposure time: 4 h)

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Not classified.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified.
Specific target organ toxicity (single exposure)	: Not classified.
Specific target organ toxicity (repeated exposure)	: Not classified.
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.

Petroleum distillates, hydrotreated light (64742-47-8)	
LC50 fish 1	45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
LC50 fish 1	19 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	0.95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	2.34 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
Distillates, petroleum, hydrotreated heavy naphthenic (64742-52-5)	
LC50 fish 1	> 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

PB Penetrating Catalyst	
Persistence and degradability	Not established.

PB Penetrating Catalyst

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

12.3. Bioaccumulative potential

PB Penetrating Catalyst	
Bioaccumulative potential	Not established.
Petroleum distillates, hydrotreated light (64742-47-8)	
BCF fish 1	61 - 159
Solvent naphtha, petroleum, heavy aromatic (64742-94-5)	
BCF fish 1	61 - 159
Partition coefficient n-octanol/water	2.9 - 6.1
Carbon dioxide (124-38-9)	
BCF fish 1	(no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known effects from this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950

Proper Shipping Name (DOT) : Aerosols
flammable, (each not exceeding 1 L capacity)

Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

PB Penetrating Catalyst

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Naphthalene (91-20-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
Yes	No	No	No	5.8 µg/day

Carbon dioxide (124-38-9)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Date of issue : 11/09/2016
Revision date : 06/26/2017
Other information : None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200)

SECTION 1: Identification

Product Identifier Power Care Premium SAE 30 4-Cycle Engine Oil
SDS Number 829586
Additional identification AP20300A; AP30480A
Relevant identified uses Engine Oil
Uses advised against All others
24 Hour Emergency Phone Number CHEMTREC (800) 424-9300 after 5:00 CST or +17035273887

Manufacturer/Supplier Phillips 66 Spectrum Corporation 500 Industrial Park Drive Selmer, TN 38375-3276 United States of America	SDS Information Phone: 800-762-0942 Email: SDS@P66.com	Technical Information 1-800-264-6457 or +1-731-645-4972

SECTION 2: Hazard identification

Classified Hazards	Hazards Not Otherwise Classified (HNOC)

This material is not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200. PHNOC: None known

HHNOC: None known

Label Elements

No classified hazards

SECTION 3: Composition/information on ingredients

Chemical Name	CASRN	Concentration ¹
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	<65
Residual oils, petroleum, solvent-refined	64742-01-4	<35

¹ All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

Eye Contact: If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

Skin Contact: Remove contaminated shoes and clothing and cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops and persists, seek medical attention.

Inhalation: First aid is not normally required. If breathing difficulties develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. Seek immediate medical attention.

Ingestion: First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

Most important symptoms and effects, both acute and delayed: Prolonged or repeated contact may dry skin and cause irritation. Inhalation of oil mists or vapors generated at elevated temperatures may cause respiratory irritation. Accidental ingestion

829586 - Power Care Premium SAE 30 4-Cycle Engine Oil
Issue Date: 20-Sep-2016

Page 1/6
Status: FINAL

can result in minor irritation of the digestive tract, nausea and diarrhea.

Notes to Physician: Acute aspirations of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

SECTION 5: Firefighting measures

NFPA 704 Hazard Class

Health: 0 Flammability: 1 Instability: 0



0 (Minimal)
1 (Slight)
2 (Moderate)
3 (Serious)
4 (Severe)

Extinguishing Media: Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F / 100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Specific hazards arising from the chemical

Unusual Fire & Explosion Hazards: This material may burn, but will not ignite readily. If container is not properly cooled, it can rupture in the heat of a fire.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

Special protective actions for fire-fighters: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: This material may burn, but will not ignite readily. Keep all sources of ignition away from spill/release. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

Environmental Precautions: Stop and contain spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard.

Methods and material for containment and cleaning up: Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken. See Section 13 for information on appropriate disposal.

SECTION 7: Handling and storage

Precautions for safe handling: Keep away from flames and hot surfaces. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8). Spills will produce very slippery surfaces. Used motor oils have been shown to cause skin cancer in mice after repeated application to the skin without washing. Brief or intermittent skin contact with used motor oil is not expected to cause harm if the oil is thoroughly removed by washing with soap and water. Do not enter confined spaces such as tanks or pits without following proper entry procedures. Do not wear contaminated clothing or shoes.

Conditions for safe storage: Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated area away from heat and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to appropriate guidance pertaining to cleaning, repairing, welding, or other contemplated operations.

SECTION 8: Exposure controls/personal protection

Chemical Name	ACGIH	OSHA	Phillips 66
Distillates, petroleum, hydrotreated heavy paraffinic	TWA: 5mg/m ³ STEL: 10 mg/m ³ as Oil Mist, if Generated	---	---
Residual oils, petroleum, solvent-refined	TWA: 5mg/m ³ STEL: 10 mg/m ³ as Oil Mist, if Generated	---	---

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Engineering controls: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

Eye/Face Protection: The use of eye protection that meets or exceeds EN 166 is recommended to protect against potential eye contact, irritation, or injury. Depending on conditions of use, close fitting eye protection and a face shield may be necessary.

Skin/Hand Protection: The use of skin protection is not normally required; however, good industrial hygiene practice suggests the use of gloves or other appropriate skin protection whenever working with chemicals. Suggested protective materials: Nitrile

Respiratory Protection: Where there is potential for airborne exposure above the exposure limit a NIOSH certified air purifying respirator equipped with R or P95 filters may be used.

A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health (IDLH).

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

SECTION 9: Physical and chemical properties

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended to be specifications.

Appearance: dark brown

Physical Form: Liquid

Odor: Slight hydrocarbon

Odor Threshold: No data

pH: Not applicable

Vapor Density (air=1): >1

Upper Explosive Limits (vol % in air): No data

Lower Explosive Limits (vol % in air): No data

Evaporation Rate (nBuAc=1): No data

Flash Point: 425 °F / 218 °C

Test Method: Pensky-Martens Closed Cup (PMCC), ASTM D93, EPA 1010

Initial Boiling Point/Range: No data

Vapor Pressure: <1 mm Hg

Partition Coefficient (n-octanol/water) (Kow): No data

Melting/Freezing Point: No data

Auto-ignition Temperature: No data

Decomposition Temperature: No data

Specific Gravity (water=1): 0.888 @ 60°F (15.6°C)

Particle Size: Not applicable
Percent Volatile: No data
Flammability (solid, gas): Not applicable

Bulk Density: 7.4 lbs/gal
Viscosity: 10.5 cSt @ 100°C; 81 cSt @ 40°C
Solubility in Water: Negligible

SECTION 10: Stability and reactivity

Reactivity: Not chemically reactive.

Chemical stability: Stable under normal ambient and anticipated conditions of use.

Possibility of hazardous reactions: Hazardous reactions not anticipated.

Conditions to avoid: Extended exposure to high temperatures can cause decomposition. Avoid all possible sources of ignition.

Incompatible materials: Avoid contact with strong oxidizing agents and strong reducing agents.

Hazardous decomposition products: Not anticipated under normal conditions of use. During use in engines, contamination of oil with low levels of hazardous fuel combustion by-products (e.g. polycyclic aromatic hydrocarbons) may occur.

SECTION 11: Toxicological information

Information on Toxicological Effects

Substance / Mixture

Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Unlikely to be harmful		>5 mg/L (mist, estimated)
Dermal	Unlikely to be harmful		> 2 g/kg (estimated)
Oral	Unlikely to be harmful		> 5 g/kg (estimated)

Aspiration Hazard: Not expected to be an aspiration hazard.

Skin Corrosion/Irritation: Not expected to be irritating. Repeated exposure may cause skin dryness or cracking.

Serious Eye Damage/Irritation: Not expected to be irritating.

Skin Sensitization: No information available on the mixture, however none of the components have been classified for skin sensitization (or are below the concentration threshold for classification).

Respiratory Sensitization: No information available.

Specific Target Organ Toxicity (Single Exposure): No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

Specific Target Organ Toxicity (Repeated Exposure): No information available on the mixture, however none of the components have been classified for target organ toxicity (or are below the concentration threshold for classification).

Carcinogenicity: No information available on the mixture, however none of the components have been classified for carcinogenicity (or are below the concentration threshold for classification).

Germ Cell Mutagenicity: No information available on the mixture, however none of the components have been classified for germ cell mutagenicity (or are below the concentration threshold for classification).

Reproductive Toxicity: No information available on the mixture, however none of the components have been classified for reproductive toxicity (or are below the concentration threshold for classification).

Information on Toxicological Effects of Components

Lubricant Base Oil (Petroleum)

Carcinogenicity: The petroleum base oils contained in this product have been highly refined by a variety of processes including severe hydrocracking/hydroprocessing to reduce aromatics and improve performance characteristics. All of the oils meet the IP-346 criteria of less than 3 percent PAH's and are not considered carcinogens by NTP, IARC, or OSHA.

SECTION 12: Ecological information

GHS Classification: No classified hazards

Toxicity: All acute aquatic toxicity studies on samples of lubricant base oils show acute toxicity values greater than 100 mg/L for invertebrates, algae and fish. These tests were carried out on water accommodated fractions and the results are consistent with the predicted aquatic toxicity of these substances based on their hydrocarbon compositions.

Persistence and Degradability: The hydrocarbons in this material are not readily biodegradable, but since they can be degraded by microorganisms, they are regarded as inherently biodegradable.

Bioaccumulative Potential: Log Kow values measured for the hydrocarbon components of this material are greater than 5.3, and therefore regarded as having the potential to bioaccumulate. In practice, metabolic processes may reduce bioconcentration.

Mobility in Soil: Volatilization to air is not expected to be a significant fate process due to the low vapor pressure of this material. In water, base oils will float and spread over the surface at a rate dependent upon viscosity. There will be significant removal of hydrocarbons from the water by sediment adsorption. In soil and sediment, hydrocarbon components will show low mobility with adsorption to sediments being the predominant physical process. The main fate process is expected to be slow biodegradation of the hydrocarbon constituents in soil and sediment.

Other adverse effects: None anticipated.

SECTION 13: Disposal considerations

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations. This material, if discarded as produced, would not be a federally regulated RCRA "listed" hazardous waste and is not believed to exhibit characteristics of hazardous waste. See Sections 7 and 8 for information on handling, storage and personal protection and Section 9 for physical/chemical properties. It is possible that the material as produced contains constituents which are not required to be listed in the SDS but could affect the hazardous waste determination. Additionally, use which results in chemical or physical change of this material could subject it to regulation as a hazardous waste. This material under most intended uses would become "Used Oil" due to contamination by physical or chemical impurities. Whenever possible, Recycle used oil in accordance with applicable federal and state or local regulations. Container contents should be completely used and containers should be emptied prior to discard.

SECTION 14: Transport information

U.S. Department of Transportation (DOT)

UN Number: Not regulated

UN proper shipping name: None

Transport hazard class(es): None

Packing Group: None

Environmental Hazards: This product does not meet the DOT/UN/IMDG/IMO criteria of a marine pollutant

Special precautions for user: If shipped by land in a packaging having a capacity of 3,500 gallons or more, the provisions of 49 CFR, Part 130 apply. (Contains oil)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

SECTION 15: Regulatory information

CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds):

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

CERCLA/SARA - Section 311/312 (Title III Hazard Categories)

Acute Health Hazard:	No
Chronic Health Hazard:	No
Fire Hazard:	No
Pressure Hazard:	No
Reactive Hazard:	No

CERCLA/SARA - Section 313 and 40 CFR 372:

This material does not contain any chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372.

EPA (CERCLA) Reportable Quantity (in pounds):

This material does not contain any chemicals with CERCLA Reportable Quantities.

California Proposition 65:

This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm at concentrations that trigger the warning requirements of California Proposition 65.

International Hazard Classification

Canada:

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (SOR/2015-17) and the SDS contains all the information required by the Regulations.

International Inventories

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA.
All components are either on the DSL, or are exempt from DSL listing requirements.

U.S. Export Control Classification Number: EAR99

SECTION 16: Other information

Issue Date:	Previous Issue Date:	SDS Number	Status:
20-Sep-2016	01-Dec-2015	829586	FINAL

Revised Sections or Basis for Revision:

New SDS

Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.

Safety Data Sheet



SECTION 1: Identification

Product Identifier	Propane
Other means of identification	Commercial Propane(All); EGP; Export Grade Propane; HD5 Propane; LP-Gas; Liquefied Petroleum Gas; Odorized Propane; Propane (Unstented); Propane Commercial; Propane Motor Fuel; Propane for Process; Stented Propane; Unodorized Propane
Relevant identified uses	Fuel Chemical Chemical feedstock
Uses advised against	Other uses are not recommended unless an assessment demonstrates potential exposures will be controlled.
24 Hour Emergency Phone Number	CHEMTREC 1-800-424-9300 CHEMTREC México 01-800-681-9531

Manufacturer/Supplier

Ferrellgas (Blue Rhino)
One Liberty Plaza
Liberty, MO 64068

SDS Information

Phone: 855-738-9178
Email: Safety-fromFG.com@ferrellgas.com
URL: www.ferrellgas.com

SECTION 2: Hazard identification

Classified Hazards	Hazards Not Otherwise Classified (HNOC)
H220 - Flammable gases -- Category 1 H280 -- Gases under pressure -- Liquefied gas Simple asphyxiant	PHNOC: None known HHNOC: None known

Label Elements



DANGER

Extremely flammable gas
Contains gas under pressure. May explode if heated.
May displace oxygen and cause rapid suffocation



Keep away from heat/sparks/open flames/hot surfaces. - No smoking; Take precautionary measures against static discharge;
Leaking gas fire: Do not extinguish, unless leak can be stopped safely; Eliminate all ignition sources if safe to do so; Protect from sunlight. Store in a well-ventilated place

SECTION 3: Composition/information on ingredients

Chemical Name	CASRN	Concentration ¹
Propane	74-98-6	80-100
Propene	115-07-1	<20
Ethane	74-84-0	<6
Butane	106-97-8	<5
Isobutane	75-28-5	<2.5

¹ All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

HD-5 COMPOSITION: Propane >90%, Propylene <5%

Odorized products contain small quantities (<0.1%) ethyl mercaptan as an olfactory indicator.

SECTION 4: First aid measures

Eye Contact: For contact with the liquefied gas, remove contact lenses if present and easy to do, hold eyelids apart and gently flush the affected eye(s) with lukewarm water. Seek immediate medical attention.

Skin Contact: Liquefied gases may cause cryogenic burns or injury. Treat burned or frostbitten skin by flushing or immersing the affected area(s) in lukewarm water. Do not rub affected area. Do not remove clothing that adheres due to freezing. After sensation has returned to the frostbitten skin, keep skin warm, dry, and clean. If blistering occurs, apply a sterile dressing. Seek immediate medical attention.

Inhalation: If respiratory symptoms develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. If breathing is difficult, oxygen or artificial respiration should be administered by qualified personnel. If symptoms persist, seek medical attention.

Ingestion: This material is a gas under normal atmospheric conditions and ingestion is unlikely.

Most important symptoms and effects, both acute and delayed: Light hydrocarbon gases are simple asphyxiants and can cause anesthetic effects at high concentrations. Symptoms of overexposure, which are reversible if exposure is stopped, can include shortness of breath, drowsiness, headaches, confusion, decreased coordination, visual disturbances and vomiting. Continued exposure can lead to hypoxia (inadequate oxygen), rapid breathing, cyanosis (bluish discoloration of the skin), numbness of the extremities, unconsciousness and death.

Notes to Physician: Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to high concentrations of hydrocarbon solvents (e.g., in enclosed spaces or with deliberate abuse). The use of other drugs with less arrhythmogenic potential should be considered. If sympathomimetic drugs are administered, observe for the development of cardiac arrhythmias.

SECTION 5: Firefighting measures

NFPA 704 Hazard Class

Health: 2 Flammability: 4 Instability: 0



0 (Minimal)
1 (Slight)
2 (Moderate)
3 (Serious)
4 (Severe)

Extinguishing Media: Dry chemical or carbon dioxide is recommended. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces.

Specific hazards arising from the chemical

Unusual Fire & Explosion Hazards: Extremely flammable Contents under pressure This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe) Vapors may travel considerable distances to a source of ignition where they can ignite, flash back, or explode. May create vapor/air

explosion hazard indoors, in confined spaces, outdoors, or in sewers. If container is not properly cooled, it can rupture in the heat of a fire. Drains can be plugged and valves made inoperable by the formation of ice if rapid evaporation of large quantities of the liquefied gas occurs. Do not allow run-off from fire fighting to enter drains or water courses – may cause explosion hazard in drains and may reignite.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of nitrogen and sulfur may also be formed.

Special protective actions for fire-fighters: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. If this cannot be done, allow fire to burn. Move undamaged containers from immediate hazard area if it can be done safely. Stay away from ends of container. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: Extremely flammable Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep all sources of ignition and hot metal surfaces away from spill/release if safe to do so. The use of explosion-proof electrical equipment is recommended. Beware of accumulation of gas in low areas or contained areas, where explosive concentrations may occur. Prevent from entering drains or any place where accumulation may occur. Ventilate area and allow to evaporate. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

Environmental Precautions: Stop and contain spill/release if it can be done safely. Water spray may be useful in minimizing or dispersing vapors. If spill occurs on water notify appropriate authorities and advise shipping of any hazard.

Methods and material for containment and cleaning up: Notify relevant authorities in accordance with all applicable regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken.

SECTION 7: Handling and storage

Precautions for safe handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8). Extremely Flammable. Contents under pressure Gas can accumulate in confined spaces and limit oxygen available for breathing. Use only with adequate ventilation The use of explosion-proof electrical equipment is recommended and may be required (see appropriate fire codes). Refer to NFPA-70 and/or API RP 2003 for specific bonding/grounding requirements. Electrostatic charge may accumulate and create a hazardous condition when handling or processing this material. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. Cold burns may occur during filling operations. Containers and delivery lines may become cold enough to present cold burn hazard.

Propane and odorant are heavier than air and will collect and pool along the ground or floor. Odorant, therefore, may not be detectable above the location of propane storage or service (for example, odorant in propane released or leaked into the basement of a dwelling may not be detected above the basement).

WARNING - The intensity of the odorant may fade over prolonged storage or in the presence of rust, when placed initially in new or freshly-cleaned storage vessels, or when exposed to masonry.

Conditions for safe storage: Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Post area "No Smoking or Open Flame." Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Outdoor or detached storage is preferred. Indoor storage should meet OSHA standards and appropriate fire codes.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. Avoid exposing any part of a compressed-gas cylinder to temperatures above 125°F(51.6°C). Gas cylinders should be stored outdoors or in well ventilated storerooms at no lower than ground level and should be quickly removable in an emergency.

SECTION 8: Exposure controls/personal protection

Chemical Name	ACGIH	OSHA	Mexico	Phillips 66
Propane	---	TWA-8hr: 1000 ppm TWA-8hr: 1800 mg/m ³	---	---
Propene	TWA-8hr: 500 ppm	---	Carcinogen	---
Butane	STEL: 1000 ppm	---	TWA-8hr: 800 ppm (VLE-PPT) TWA-8hr: 1900 mg/m ³ (VLE-PPT)	---
Isobutane	STEL: 1000 ppm	---	---	---

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Engineering controls: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

Eye/Face Protection: The use of eye protection (such as splash goggles) that meets or exceeds ANSI Z.87.1 is recommended when there is potential liquid contact to the eye. Depending on conditions of use, a face shield may be necessary.

Skin/Hand Protection: Wear thermal insulating gloves and face shield or eye protection when working with materials that present thermal hazards (hot or cold).

Respiratory Protection: A NIOSH approved, self-contained breathing apparatus (SCBA) or equivalent operated in a pressure demand or other positive pressure mode should be used in situations of oxygen deficiency (oxygen content less than 19.5 percent), unknown exposure concentrations, or situations that are immediately dangerous to life or health (IDLH).

A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use.

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

SECTION 9: Physical and chemical properties

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended to be specifications.

Appearance: Colorless

Physical Form: Liquefied Gas

Odor: No distinct odor (or skunk, rotten egg or garlic if odorant added)

Odor Threshold: No data

pH: Not applicable

Vapor Density (air=1): >1

Upper Explosive Limits (vol % in air): 9.5

Lower Explosive Limits (vol % in air): 2.1

Evaporation Rate (nBuAc=1): >1

Particle Size: Not applicable

Percent Volatile: 100%

Flammability (solid, gas): Extremely Flammable

Flash Point: -156 °F / -104 °C

Test Method: Tag Closed Cup (TCC), ASTM D56

Initial Boiling Point/Range: -44 °F / -42 °C

Vapor Pressure: 208 psia (Reid VP) @ 100°F / 37.8°C

Partition Coefficient (n-octanol/water) (Kow): No data

Melting/Freezing Point: -309 °F / -189 °C

Auto-ignition Temperature: 842 °F / 450 °C

Decomposition Temperature: No data

Specific Gravity (water=1): 0.50-0.51 @ 60°F (15.6°C)

Bulk Density: No data

Viscosity: No data

Solubility in Water: Negligible

SECTION 10: Stability and reactivity

Issue Date: 02/12/2018

Reactivity: Not chemically reactive.

Chemical stability: Stable under normal ambient and anticipated conditions of use.

Possibility of hazardous reactions: Hazardous reactions not anticipated.

Conditions to avoid: Avoid all possible sources of ignition. Heat will increase pressure in the storage tank.

Incompatible materials: Avoid contact with acids, aluminum chloride, chlorine, chlorine dioxide, halogens and oxidizing agents.

Hazardous decomposition products: Not anticipated under normal conditions of use.

SECTION 11: Toxicological information

Information on Toxicological Effects

Substance / Mixture

Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Unlikely to be harmful	Simple Asphyxiant. May displace oxygen and cause rapid suffocation. See section 4 for more information.	>20,000 ppm (gas, estimated)
Dermal	Skin absorption is not anticipated		Not applicable
Oral	Ingestion is not anticipated		Not applicable

Aspiration Hazard: Not applicable

Skin Corrosion/Irritation: Not expected to be irritating. Contact with the liquefied or pressurized gas may cause frostbite ("cold" burn).

Serious Eye Damage/Irritation: Not expected to be irritating. Contact with the liquefied or pressurized gas may cause momentary freezing followed by swelling and eye damage.

Skin Sensitization: Skin contact is not anticipated.

Respiratory Sensitization: Not expected to be a respiratory sensitizer.

Specific Target Organ Toxicity (Single Exposure): Not expected to cause organ effects from single exposure.

Specific Target Organ Toxicity (Repeated Exposure): Not expected to cause organ effects from repeated exposure.

Carcinogenicity: Not expected to cause cancer.

Germ Cell Mutagenicity: Not expected to cause heritable genetic effects.

Reproductive Toxicity: Not expected to cause reproductive toxicity.

Other Comments: High concentrations may reduce the amount of oxygen available for breathing, especially in confined spaces. Hypoxia (inadequate oxygen) during pregnancy may have adverse effects on the developing fetus.

The odorant, ethyl mercaptan, can be irritating to the eyes, skin and respiratory tract. At high concentrations, a person can temporarily lose the ability to smell ethyl mercaptan. In addition, some individuals may have an impaired sense of smell, which inhibits the detection of the odorant.

Information on Toxicological Effects of Components

Propane

Reproductive Toxicity: No adverse reproductive or developmental effects were observed in rats exposed to propane; no observed adverse effect level = 12,000 ppm.

Target Organ(s): No systemic or neurotoxic effects were noted in rats exposed to concentrations of propane as high as 12,000 ppm for 28 days.

Butane

Reproductive Toxicity: No adverse reproductive or developmental effects were observed in rats exposed to butane; no observed adverse effect level = 12,000 ppm.

Target Organ(s): No systemic or neurotoxic effects were noted in rats exposed to concentrations of butane as high as 9,000 ppm for 28 days.

Isobutane

Reproductive Toxicity: No adverse developmental effects were observed in rats exposed to concentrations of isobutane as high as 9000 ppm. Fertility and mating indices may have been affected at 9000 ppm but no effects were observed at 3000 ppm (NOAEL).

Target Organ(s): No systemic or neurotoxic effects were noted in rats exposed to concentrations of isobutane as high as 9,000 ppm for 28 days.

SECTION 12: Ecological information

GHS Classification:

No classified hazards

Toxicity: Petroleum gases will readily evaporate from the surface and would not be expected to have significant adverse effects in the aquatic environment.

Persistence and Degradability: The hydrocarbons in this material are expected to be inherently biodegradable. In practice, hydrocarbon gases are not likely to remain in solution long enough for biodegradation to be a significant loss process. Hydrogen sulfide, if present in refinery gas streams, will be rapidly oxidized in water and insoluble sulfides precipitated from water when metallic radicals are present.

Bioaccumulative Potential: Since the log Kow values measured for refinery gas constituents are below 3, they are not regarded as having the potential to bioaccumulate.

Mobility in Soil: Due to the extreme volatility of petroleum gases, air is the only environmental compartment in which they will be found. In air, these hydrocarbons undergo photodegradation by reaction with hydroxyl radicals with half-lives ranging from 3.2 days for n-butane to 7 days for propane.

Other adverse effects: None anticipated.

SECTION 13: Disposal considerations

This material is a gas and would not typically be managed as a waste.

SECTION 14: Transport information

U.S. Department of Transportation (DOT)

UN Number: 1978 or 1075

UN proper shipping name: Propane,

Transport hazard class(es): 2.1

Packing Group: None

Environmental Hazards: This product does not meet the DOT/UN/IMDG/IMO criteria of a marine pollutant

Special precautions for user: *For domestic transportation only, UN1075 may be substituted for the UN number shown as long as the substitution is consistent on package markings, shipping papers, and emergency response information. See 49 CFR 172.102 Special Provision 19.*

Containers of NON-ODORIZED liquefied petroleum gas must be marked either NON-ODORIZED or NOT ODORIZED as of September 30, 2006. [49 CFR 172.301(f), 326(d), 330(c) and 338(e)]

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

SECTION 15: Regulatory information

CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds)

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

CERCLA/SARA - Section 311/312 (Title III Hazard Categories)

US EPA has published a final rule aligning hazardous chemical reporting under sections 311 and 312 of the Emergency Planning and Community Right-to-Know Act (EPCRA) with OSHA HCS. See Section 2 for hazard classifications under EPCRA.

CERCLA/SARA - Section 313 and 40 CFR 372

This material contains the following chemicals subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR 372:

Chemical Name	Concentration ¹	de minimis
Propene	<20	1.0%

EPA (CERCLA) Reportable Quantity (in pounds)

EPA's Petroleum Exclusion applies to this material - (CERCLA 101(14)).

California Proposition 65

 **WARNING:** Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm are created by the combustion of propane. For more information go to www.P65Warnings.ca.gov.

International Inventories

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA.
All components are either on the DSL, or are exempt from DSL listing requirements.

SECTION 16: Other information

Issue Date:	Previous Issue Date:
2/12/2018	03/20/2017

Revised Sections or Basis for Revision:

Intended Use (Section 1)

Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; HPR = Hazardous Products Regulations; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.

MATERIAL SAFETY DATA SHEET

EPA Reg. No. 10807-428-1658

EPA Est. No. 10807-GA-1

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION

NFPA Rating: Health-1; Flammability-2; Reactivity-0; Special-	HMIS Rating: Health-1; Flammability-2; Reactivity-0; Personal Protection-B
Manufactured For: Hillyard Industries, Inc. Address: 302 N. 4 th Street Address: St. Joseph, MO 64501	DOT Hazard Classification (post transition): LIMITED QUANTITY DOT Haz Classification(pretransition): Consumer Commodity ORM-D Identity (trade name as used on label): Quick & Clean Crawling Insect Killer II HIL0109454
Phone: (816)-233-1321 ext. 8285 or http://www.hillyard.com	MSDS Number: A00423 Revision- First Issue-a
EMERGENCY RESPONSE NUMBER: Chemtrec 1-800-424-9300	Review Date: 01/04/10 Last Issue Date: 12/11/08
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA	Replaced Original Date: 10/15/07 Prepared By: IB Information Calls: (770)422-2071

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
HYDROTREATED LIGHT PETROLEUM DISTILLATES	64742-47-8	No	5 mg/m3 (mist)	5 mg/m3 (mist)	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	NE	NE	d
	74-98-6	No	1000	1000	d
Insecticide Actives:					
PYRETHRIN (less than 1% by weight)	8003-34-7	No	5 mg/m3 TWA	5 mg/m3 TWA	d
DELTAMETHRIN (less than 1% by weight)	52918-63-5	No	NE	NE	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A	Specific Gravity (H2O=1): Concentrate Only = 0.96
Vapor Pressure: PSIG @ 70°F (Aerosols): Max. 60	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E	Evaporation Rate (water = 1): less than 1
Solubility in Water: Dispersible	Water Reactive: No
Appearance and Odor: White to off-white emulsion with bland odor. Dual spray valve: Sprays as pinpoint spray or coarse spray.	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY as per USA/CPSC FLAME PROJECTION TEST (aerosols): no projection: NOT CATEGORIZED AS FLAMMABLE	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E
FLASH POINT AND METHOD USED (non-aerosols): N/A	EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide, water fog.	
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus. Keep containers cool with a water stream.		
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.		

SECTION 4 - REACTIVITY HAZARD DATA

STABILITY [X] STABLE [] UNSTABLE	HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR
Incompatibility (Mat. to avoid): Strong oxidizers, strong acids.	Conditions to Avoid: Open flame, welding arcs, heat, sparks.
Hazardous Decomposition Products: CO, CO2 and various hydrocarbons.	

SECTION 5 - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: [X] INHALATION [X] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS	
ACUTE EFFECTS	
Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects, nausea.	
Eye Contact: May cause temporary irritation.	Skin Contact: Can cause irritation. Prolonged or repeated skin contact may cause allergic reaction in some individuals.
Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea, dizziness, loss of muscle coordination.	
CHRONIC EFFECTS: High concentration of vapors may cause eye and respiratory tract irritation, dizziness, headaches, drowsiness and central nervous system effects.	
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.	

EMERGENCY FIRST AID PROCEDURES

Eye Contact: Flush with large amounts of water for at least 15 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. Contact poison control center or doctor for treatment advice.
Skin Contact: Remove contaminated clothing. Rinse with water for 15-20 minutes. Contact poison control center or doctor for treatment advice.
Inhalation: Remove to fresh air. Resuscitate if necessary. Contact poison control center or doctor for treatment advice.
Ingestion: Immediately contact poison control center or doctor for treatment advice. DO NOT INDUCE VOMITING unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Get immediate medical attention.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH for organic vapor.	
Protective Gloves: Chemical resistant gloves recommended.	Eye Protection: Safety glasses recommended.
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.	
Other Protective Clothing & Equipment: None.	
Hygienic Work Practices: Wash with soap and water before handling food, eating, drinking, chewing gum or using tobacco.	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken If Material Is Spilled Or Released: Absorb spilled liquid with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid inhalation of spray mist. Avoid water contamination.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

THIS MSDS IS CURRENT AS OF January 4, 2010. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.

SAFETY DATA SHEET

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: RedGard® Waterproofing And Crack Prevention Membrane

Product Code: Not Available

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Product Use: Waterproofing Membrane

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEETS

Name/Address: Custom Building Products
Five Concourse Parkway, Suite 1900
Atlanta, GA 30328

Telephone Number: 1-(800)-272-8786

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: INFOTRAC 1-800-535-5053 (US and Canada)
INTERNATIONAL + 1-352-323-3500

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL IN ACCORDANCE WITH PARAGRAPH (d) OF 29 CFR 1910.1200 (OSHA HAZCOM2012)

Eye Irritation	Category 2B
Skin Irritation	Category 2
Carcinogenicity	Category 1A

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM2012

2.2a SIGNAL WORD:
DANGER!

2.2b HAZARD STATEMENTS
Causes eye irritation
Causes skin irritation
May cause cancer through inhalation of dust

2.2c HAZARD PICTOGRAMS



SAFETY DATA SHEET

2.2d PRECAUTIONARY STATEMENTS

i. PREVENTION	Wash hands thoroughly after handling. Do not breathe dust/fume/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear impervious gloves/protective clothing/eye protection/face protection.
ii. RESPONSE	If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor. If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.
iii. STORAGE	Store locked up. Store in a well-ventilated place. Keep container tightly closed.
iv. DISPOSAL	Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.

2.3 ADDITIONAL INFORMATION

2.3a HNOC – HAZARDS NOT OTHERWISE CLASSIFIED

Not Applicable

2.3b UNKNOWN ACUTE TOXICITY

31.7% of the mixture consists of ingredient(s) of unknown acute toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Chemical Name	CAS Number	Weight %
Calcium Carbonate	1317-65-3	15 – 40%*
Crystalline Silica, Quartz	14808-60-7	0.1 – 1.0%*

*Means that the component will fall into one the ranges specified due to batch-to-batch variability.

Section 4: FIRST-AID MEASURES

4.1 DESCRIPTION OF THE FIRST-AID MEASURES

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
Skin Contact:	In case of contact, immediately flush skin with plenty of water.

SAFETY DATA SHEET

Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

Inhalation: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS/EFFECTS, ACUTE AND DELAYED

ROUTES OF EXPOSURE	DESCRIPTION
Eye Contact:	Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Skin Contact:	May cause skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis.
Inhalation:	May cause respiratory tract irritation. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.
Ingestion:	May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

4.3 INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY

Flammability: Not Flammable/Not Combustible by WHMIS/OSHA HAZCOM2012 Criteria

5.2 EXTINGUISHING MEDIA

5.2a. Suitable Extinguishing Media:
Treat for surrounding material.

5.2b. Unsuitable Extinguishing Media:
Not Available

5.3 SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

5.3a. Products of Combustion:

SAFETY DATA SHEET

May include, and are not limited to: oxides of carbon

5.3b. Explosion Data

- i. **Sensitivity to Mechanical Impact:**
Not Available
- ii. **Sensitivity to Static Discharge:**
Not Available

5.4 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear(full bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

- Methods for Containment:** Prevent further leakage or spillage if safe to do so. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for Cleaning-Up:** Pick up and transfer to properly labeled containers. Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations.

Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

- Handling:** Use in well-ventilated areas. Wear impervious gloves, such as nitrile and eye protection. Do not mix with other chemical products, except as indicated by the manufacturers. Do not get in eyes. Do not get on skin or clothing. Do not breathe dust/fume/vapors/spray. Do not take internally. Good housekeeping is important to prevent accumulation of dust.
- General Hygiene Advice:** Use good industrial hygiene practices and wear recommended personal protection. Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

- Storage:** Keep out of the reach of children. Keep container tightly closed. Store locked up. Store at room temperature and keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Keep dry

SAFETY DATA SHEET

until use.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETER

Exposure Guidelines

Occupational Exposure Limits		
Chemical Name	OSHA-PEL	ACGIH-TLV
Calcium Carbonate	5 mg/m ³ (Resp.) 15 mg/m ³ (Total)	5 mg/m ³ (Resp.)
Crystalline Silica, Quartz	0.1 mg/m ³	0.025 mg/m ³

8.2 EXPOSURE CONTROLS

Engineering Controls:

Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTION MEASURES

8.3a. Personal Protective Equipment:

- i. **Eye/Face Protection:** Wear approved eye protection [properly fitted dust- or splash-proof chemical safety goggles/face (face shield)]
- ii. **Skin Protection:**
 1. **Hand Protection:** Wear impervious gloves, such as nitrile.
 2. **Body Protection:** Wear suitable protective clothing
- iii. **Respiratory Protection:** A NIOSH approved respirator or filtering face piece, such as N95, is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).
- iv. **General Health and Safety Measures:** Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.):	Red Liquid
Odor:	Not Available
Odor Threshold:	Not Available
pH:	8.5 – 9.5
Melting point/Freezing point:	Not Available
Initial boiling point and boiling range:	Not Available
Flash point:	Not Available
Evaporation rate (Water=1):	Not Available

SAFETY DATA SHEET

Flammability:	Not Flammable/Not Combustible
Upper Flammability/Explosive Limit:	Not Available
Lower Flammability/Explosive Limit:	Not Available
Vapor Pressure	Not Available
Vapor Density:	Not Available
Relative Density:	1.20 – 1.40 g/mL
Solubility in Water:	Slightly Soluble
Partition coefficient: n-octanol/water:	Not Available
Auto-ignition temperature:	Not Available
Decomposition Temperature:	Not Available
Viscosity (cps):	Not Available
VOC Content:	5 g/L

Section 10: STABILITY AND REACTIVITY

10.1. REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2. CHEMICAL STABILITY

Stable under normal storage conditions. Keep dry in storage.

10.3. POSSIBILITY OF HAZARDOUS REACTION

No dangerous reaction known under conditions of normal use.

10.4. CONDITIONS TO AVOID

Heat. Incompatible materials.

10.5. INCOMPATIBLE MATERIALS

Strong acids. Strong oxidizers.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS

Upon decomposition, this product may yield oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

11.1. LIKELY ROUTES OF EXPOSURE:

Skin contact, skin absorption, eye contact, inhalation, and ingestion.

11.2. SYMPTOMS RELATED TO PHYSICAL/CHEMICAL/TOXICOLOGICAL CHARACTERISTICS:

Eye Contact: Causes eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Skin Contact: Causes skin irritation. Handling can cause dry skin, discomfort, irritation, and dermatitis.

SAFETY DATA SHEET

Inhalation: May cause respiratory tract irritation. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica from this product can cause silicosis, a serious disabling and fatal lung disease.

Ingestion: May be harmful if swallowed. Ingestion may cause discomfort and/or distress, nausea or vomiting.

Acute Toxicity(ATE _{mix} = 10,523 mg/kg)		
Chemical Name	LC50	LD50
Calcium Carbonate	Not Available	Oral: >6,450 mg/kg, rat
Crystalline Silica, Quartz	Not Available	Oral: >10,000 mg/kg, rat

Carcinogenicity	
Chemical Name	Chemical Listed as Carcinogens or Potential Carcinogen (NTP,IARC,OSHA,ACGIH,CP65)
Calcium Carbonate	Not Listed
Crystalline Silica, Quartz	N-2, I-1, O-1, ACGIH-A2, CP65

11.3. DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT AND LONG-TERM EXPOSURE

SHORT-TERM	
Skin Corrosion/Irritation:	Causes skin irritation
Serious Eye Damage/Irritation:	Causes eye irritation
Respiratory Sensitization:	Not Classified
Skin Sensitization:	Not Classified
STOT-Single Exposure:	May cause respiratory irritation
Aspiration Hazard:	Not Classified
LONG-TERM	
Carcinogenicity:	May cause cancer through inhalation of dust
Germ Cell Mutagenicity:	Not Classified
Reproductive Toxicity:	Not Classified
STOT-Repeated Exposure:	Not Classified
Synergistic/Antagonistic Effects:	Not Classified

Section 12: ECOLOGICAL INFORMATION

12.1. ECOTOXICITY

May cause long-term adverse effects to the aquatic environment. Keep from entry into sewers and waterways.

Ecotoxicity		
Chemical Name	EC50/NOEC-48 Hours	LC50/NOEC-96 Hours
Calcium Carbonate	Not Available	Not Available
Crystalline Silica, Quartz	Not Available	Not Available

12.2. PERSISTENCE AND DEGRADABILITY

Not Available

12.3. BIOACCUMULATIVE POTENTIAL

Not Available

SAFETY DATA SHEET

12.4. MOBILITY IN SOIL

Not Available

12.5. OTHER ADVERSE EFFECTS

Not Available

Section 13: DISPOSAL CONSIDERATIONS

13.1. DISPOSAL METHOD

Dispose of contents/containers in accordance with all local, state, provincial, and federal regulations

13.2. OTHER DISPOSAL CONSIDERATIONS

Not Available

Section 14: TRANSPORT INFORMATION

DOT (U.S.)	TDG (CANADA)	IATA
UN NUMBER:	UN NUMBER:	UN NUMBER:
Not Regulated	Not Regulated	Not Regulated
UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:	UN PROPER SHIPPING NAME:
Not Regulated	Not Regulated	Not Regulated
TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):	TRANSPORT HAZARD CLASS (ES):
Not Regulated	Not Regulated	Not Regulated
PACKING GROUP (if applicable):	PACKING GROUP (if applicable):	PACKING GROUP (if applicable):
Not Regulated	Not Regulated	Not Regulated

SUMMARY: Product is NOT regulated under DOT/TDG and other transportation regulations.

14.1. ENVIRONMENTAL HAZARDS

Not Available

14.2. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not Available

14.3. SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATIONS SPECIFIC FOR THE CHEMICAL

Canada: This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the

SAFETY DATA SHEET

Hazardous Products Regulations.

US: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

15.2. US FEDERAL INFORMATION:

CHEMICAL NAME	SARA TITLE III			
	SECTION 302 (EHS) TPQ (LBS)	SECTION 304 EHS RQ (LBS)	CERCLA RQ (LBS)	SECTION 313 (TRI)
Calcium Carbonate	Not Listed	Not Listed	Not Listed	Not Listed
Crystalline Silica, Quartz	Not Listed	Not Listed	Not Listed	Not Listed

15.3. US STATE RIGHT TO KNOW LAWS:

California Proposition 65:	 WARNING: This product can expose you to chemicals including crystalline silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
Other U.S. States "Right to Know" Lists:	
New Jersey:	Calcium Carbonate: CAS#1317-65-3 Water: CAS#7732-18-5 Latex Dispersion: CAS#N/A Silica, Quartz: CAS#14808-60-7 Ammonium Hydroxide: CAS#1336-21-6
Pennsylvania:	Calcium Carbonate: CAS#1317-65-3 Water: CAS#7732-18-5 Latex Dispersion: CAS#N/A Silica, Quartz: CAS#14808-60-7 Ammonium Hydroxide: CAS#1336-21-6
Massachusetts:	Calcium Carbonate: CAS#1317-65-3 Water: CAS#7732-18-5 Latex Dispersion: CAS#N/A Silica, Quartz: CAS#14808-60-7 Ammonium Hydroxide: CAS#1336-21-6
Minnesota:	Calcium Carbonate: CAS#1317-65-3 Water: CAS#7732-18-5 Latex Dispersion: CAS#N/A Silica, Quartz: CAS#14808-60-7 Ammonium Hydroxide: CAS#1336-21-6
Florida:	Not Available
Michigan:	Not Available


15.4. GLOBAL INVENTORIES

Chemical Name	USA TSCA	Canada DSL/NDSL
Calcium Carbonate	Yes	NDSL(*)
Crystalline Silica, Quartz	Yes	DSL

SAFETY DATA SHEET

15.5. NFPA AND HMIS RATINGS:

HEALTH HAZARD 4 EXTREME - Highly toxic. May be fatal on short-term exposure. 3 SERIOUS - Toxic. Full protective suit and breathing apparatus should be worn. 2 MODERATE - Breathing apparatus and face mask must be worn. 1 SLIGHT - Breathing apparatus may be worn. 0 MINIMAL - No precautions necessary.	FLAMMABILITY HAZARD 4 EXTREME - Extremely flammable gas or liquid. Flash Point below 73°F. 3 SERIOUS - Flammable. Flash Point 73°F to 100°F. 2 MODERATE - Combustible. Requires moderate heating to ignite. Flash Point below 200°F. 1 SLIGHT - Slightly combustible. Requires strong heating to ignite. 0 MINIMAL - Will not burn under normal conditions.
SPECIFIC HAZARD OXIDIZER OXY ACID ACID ALKALI ALK CORROSIVE COR Use NO WATER W RADIATION 	INSTABILITY HAZARD 4 EXTREME - Explosive at room temperature. 3 SERIOUS - May detonate if shocked or heated under confinement or mixed with water. 2 MODERATE - Unstable. May react with water. 1 SLIGHT - May react if heated or mixed with water. 0 MINIMAL - Normally stable. Does not react with water.



Hazard Index	
4	Severe Hazard
3	Serious Hazard
2	Moderate Hazard
1	Slight Hazard

2 HEALTH	PROTECTIVE EQUIPMENT INDEX	
0 FLAMMABILITY	A 	G 
0 REACTIVITY	B 	H 
G PERSONAL PROTECTION	C 	I 
	D 	J 
	E 	K 
	F 	X Ask your supervisor for special handling instructions.

15.6. SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65	California Proposition 65
OSHA (O)	Occupational Safety and Health Administration
ACGIH (G)	American Conference of Governmental Industrial Hygienists - A1 – Confirmed human carcinogen - A2 – Suspected human carcinogen - A3 – Animal carcinogen - A4 – Not classifiable as a human carcinogen - A5 – Not suspected a human carcinogen
IARC (I)	International Agency for Research on Cancer 1 – The agent (mixture) is carcinogenic to humans 2A – The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals. 2B – The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of

SAFETY DATA SHEET

	sufficient evidence of carcinogenicity in experimental animals. • 3 – The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans. • 4 – The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.
NTP (N)	National Toxicology Program • 1 – Known to be carcinogens • 2 – Reasonably anticipated to be carcinogens

Section 16: OTHER INFORMATION

Date of Preparation: September 3, 2014

Version: 3.1

Revision Date: October 6, 2017

Disclaimer: The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to silica contained in our products.

Prepared by: Custom Building Products
 Phone: (562)-968-2980
www.custombuildingproducts.com

End of Safety Data Sheet



☒ Close this window

Common Name: ROHPER LSPR 6PK GLOSS CRYSTAL CLEAR, V2102838

Manufacturer: RUST-OLEUM

SDS Revision Date: 4/7/2016

SDS Format: GHS-US

Grainger Item Number(s): 4TH61

**Manufacturer Model
Number(s):**

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

- [1. IDENTIFICATION](#)
- [2. HAZARD IDENTIFICATION](#)
- [3. COMPOSITION/INFORMATION ON INGREDIENTS](#)
- [4. FIRST-AID MEASURES](#)
- [5. FIRE-FIGHTING MEASURES](#)
- [6. ACCIDENTAL RELEASE MEASURES](#)
- [7. HANDLING AND STORAGE](#)
- [8. EXPOSURE CONTROLS/PERSONAL PROTECTION](#)
- [9. PHYSICAL AND CHEMICAL PROPERTIES](#)
- [10. STABILITY AND REACTIVITY](#)
- [11. TOXICOLOGICAL INFORMATION](#)
- [12. ECOLOGICAL INFORMATION](#)
- [13. DISPOSAL INFORMATION](#)
- [14. TRANSPORT INFORMATION](#)
- [15. REGULATORY INFORMATION](#)
- [16. OTHER INFORMATION](#)

DATE PRINTED: 4/7/2016

SAFETY DATA SHEET

RUST-OLEUM CORPORATION

TRUSTED QUALITY SINCE 1921

WWW.RUSTOLEUM.COM

1. IDENTIFICATION

PRODUCT NAME: ROHPER LSPR 6PK GLOSS CRYSTAL CLEAR

PRODUCT IDENTIFIER: V2102838

PRODUCT USE/CLASS: CLEAR TOPCOAT/AEROSOLS

REVISION DATE: 4/7/2016

SUPERCEDES DATE: 8/13/2014

SUPPLIER:

RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

MANUFACTURER:

RUST-OLEUM CORPORATION
11 HAWTHORN PARKWAY
VERNON HILLS, IL 60061
USA

PREPARER: REGULATORY DEPARTMENT

EMERGENCY TELEPHONE:

24 HOUR HOTLINE: 847-367-7700

2. HAZARD IDENTIFICATION

CLASSIFICATION:

SYMBOL(S) OF PRODUCT:

FLAME
EXCLAMATION MARK
HEALTH HAZARD
GAS CYLINDER

SIGNAL WORD: DANGER

GHS HAZARD STATEMENTS:

FLAMMABLE AEROSOL, CATEGORY 1:
H222: EXTREMELY FLAMMABLE AEROSOL.

COMPRESSED GAS:
H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.

SKIN IRRITATION, CATEGORY 2:
H315: CAUSES SKIN IRRITATION.

EYE IRRITATION, CATEGORY 2:
H319: CAUSES SERIOUS EYE IRRITATION.

STOT, SINGLE EXPOSURE, CATEGORY 3, NE:
H336: MAY CAUSE DROWSINESS OR DIZZINESS.

GERM CELL MUTAGENICITY, CATEGORY 1B:
H340: MAY CAUSE GENETIC DEFECTS.

CARCINOGENICITY, CATEGORY 1B:
H350: MAY CAUSE CANCER.

REPRODUCTIVE TOXICITY, CATEGORY 2:
H361: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

STOT, REPEATED EXPOSURE, CATEGORY 2:
H373: MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

GHS LABEL PRECAUTIONARY STATEMENTS:
P201: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

P210:
KEEP AWAY FROM HEAT, HOT SURFACES, SPARKS, OPEN FLAMES AND OTHER IGNITION SOURCES. NO SMOKING.

P211: DO NOT SPRAY ON AN OPEN FLAME OR OTHER IGNITION SOURCE.

P251: DO NOT PIERCE OR BURN, EVEN AFTER USE.

P260: DO NOT BREATHE DUST, FUMES, GASES, MISTS, VAPORS, OR SPRAY.

P280:
WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.

P281: USE PERSONAL PROTECTIVE EQUIPMENT AS REQUIRED.

P302+P352:
IF ON SKIN: WASH WITH PLENTY OF SOAP AND WATER.

P305+P351+P338:
IF IN EYES:
RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.

P308+P313:
IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

P312: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL.

P337+P313:
IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

P362: TAKE OFF CONTAMINATED CLOTHING.

P403+P233: STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED.

P410+P403: PROTECT FROM SUNLIGHT. STORE IN A WELL-VENTILATED PLACE.

P410+P412:
PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C / 122 DEG. F.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS SUBSTANCES:

CHEMICAL NAME	CAS-NO.	WT.% RANGE

ACETONE	67-64-1	25-50
PROPANE	74-98-6	10-25
TOLUENE	108-88-3	10-25
N-BUTYL ACETATE	123-86-4	2.5-10
N-BUTANE	106-97-8	2.5-10
SOLVENT NAPHTHA, LIGHT AROMATIC	64742-95-6	1.0-2.5
1,2,4-TRIMETHYLBENZENE	95-63-6	1.0-2.5
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	64742-49-0	1.0-2.5

CHEMICAL NAME	GHS SYMBOLS	GHS STATEMENTS
ACETONE	GHS02-GHS07	H225-319-332-336
PROPANE	GHS04	H280
TOLUENE	GHS02-GHS07-GHS08	H225-304-315- 332-336-361-373
N-BUTYL ACETATE	GHS02-GHS07	H226-336
N-BUTANE	GHS04	H280
SOLVENT NAPHTHA, LIGHT AROMATIC	GHS07-GHS08	H304-332-340-350
1,2,4-TRIMETHYLBENZENE	GHS02-GHS07-GHS08	H226-304-315- 319-332-335
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	GHS08	H304-340-350

4. FIRST-AID MEASURES

FIRST AID - EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. DO NOT ALLOW RUBBING OF EYES OR KEEPING EYES CLOSED.

FIRST AID - SKIN CONTACT:

WASH SKIN WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:

REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. DO NOT USE MOUTH-TO-MOUTH RESUSCITATION. IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

FIRST AID - INGESTION:

ASPIRATION HAZARD:

DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION. IF SWALLOWED, GET MEDICAL ATTENTION.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA:

ALCOHOL FILM FORMING FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

FLASH POINT IS LESS THAN 20 DEG. F. EXTREMELY FLAMMABLE LIQUID AND VAPOR! WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT DUE TO BUILDUP OF STEAM. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME.

PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN. NO UNUSUAL FIRE OR EXPLOSION HAZARDS NOTED. SPECIAL FIREFIGHTING PROCEDURES: WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILDUP AND POSSIBLE AUTOIGNITION OR EXPLOSION. FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED. EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE. USE WATER SPRAY TO KEEP FIRE-EXPOSED CONTAINERS COOL. CONTAINERS MAY EXPLODE WHEN HEATED.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. ISOLATE THE HAZARD AREA AND DENY ENTRY TO UNNECESSARY AND UNPROTECTED PERSONNEL. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. VENTILATE AREA, ISOLATE SPILLED MATERIAL, AND REMOVE WITH INERT ABSORBENT. DISPOSE OF CONTAMINATED ABSORBENT, CONTAINER, AND UNUSED CONTENTS IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

7. HANDLING AND STORAGE

HANDLING:

WASH THOROUGHLY AFTER HANDLING. WASH HANDS BEFORE EATING. REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. USE ONLY WITH ADEQUATE VENTILATION. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING FUMES, VAPORS, OR MIST. AVOID CONTACT WITH EYES, SKIN AND CLOTHING.

STORAGE:

STORE IN A DRY, WELL VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. CONTENTS UNDER PRESSURE. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND

PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. KEEP AWAY FROM HEAT, SPARKS, FLAME AND SOURCES OF IGNITION. AVOID EXCESS HEAT. PRODUCT SHOULD BE STORED IN TIGHTLY SEALED CONTAINERS AND PROTECTED FROM HEAT, MOISTURE, AND FOREIGN MATERIALS.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CHEMICAL NAME	CAS-NO.	WEIGHT % LESS THAN
ACETONE	67-64-1	30.0
PROPANE	74-98-6	20.0
TOLUENE	108-88-3	20.0
N-BUTYL ACETATE	123-86-4	10.0
N-BUTANE	106-97-8	10.0
SOLVENT NAPHTHA, LIGHT AROMATIC	64742-95-6	5.0
1,2,4-TRIMETHYLBENZENE	95-63-6	5.0
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	64742-49-0	5.0

CHEMICAL NAME	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
ACETONE	250 PPM	500 PPM	1000 PPM	N.E.
PROPANE	N.E.	N.E.	1000 PPM	N.E.
TOLUENE	20 PPM	N.E.	200 PPM	300 PPM
N-BUTYL ACETATE	150 PPM	200 PPM	150 PPM	N.E.
N-BUTANE	N.E.	1000 PPM	N.E.	N.E.
SOLVENT NAPHTHA, LIGHT AROMATIC	N.E.	N.E.	N.E.	N.E.
1,2,4-TRIMETHYLBENZENE	N.E.	N.E.	N.E.	N.E.
NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	N.E.	N.E.	N.E.	N.E.

PERSONAL PROTECTION:

ENGINEERING CONTROLS:

USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT. PROVIDE GENERAL DILUTION OF LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP TLV OF HAZARDOUS INGREDIENTS BELOW ACCEPTABLE LIMITS. PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION.

RESPIRATORY PROTECTION:

A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2

REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

SKIN PROTECTION:

USE GLOVES TO PREVENT PROLONGED SKIN CONTACT. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION.

EYE PROTECTION:

USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:

REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER GUIDANCE REGARDING TYPES OF PERSONAL PROTECTIVE EQUIPMENT AND THEIR APPLICATIONS.

HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING. REMOVE CONTAMINATED CLOTHING IMMEDIATELY AND LAUNDER BEFORE REUSE.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: AEROSOLIZED MIST

PHYSICAL STATE: LIQUID

ODOR: SOLVENT LIKE

ODOR THRESHOLD: N.E.

RELATIVE DENSITY: 0.746

PH: N.A.

FREEZE POINT, DEG. C: ND

VISCOSITY: N.D.

SOLUBILITY IN WATER: SLIGHT

PARTITION COEFFICIENT, N-OCTANOL/WATER: N.D.

DECOMPOSITION TEMP., DEG. C: N.D.

BOILING RANGE, DEG. C: -37 - 375

EXPLOSIVE LIMITS, VOL%: 0.9 - 13.0

FLAMMABILITY: SUPPORTS COMBUSTION

FLASH POINT, DEG. C: -96

EVAPORATION RATE: FASTER THAN ETHER

AUTO-IGNITION TEMP., DEG. C: N.D.

VAPOR DENSITY: HEAVIER THAN AIR

VAPOR PRESSURE: N.D.

(SEE "OTHER INFORMATION" SECTION FOR ABBREVIATION LEGEND)

10. STABILITY AND REACTIVITY

CONDITIONS TO AVOID:

AVOID TEMPERATURES ABOVE 120 DEG. F (49 DEG. C). AVOID CONTACT WITH STRONG ACID AND STRONG BASES. AVOID ALL POSSIBLE SOURCES OF IGNITION.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIS.

HAZARDOUS DECOMPOSITION:

BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE. WHEN HEATED TO DECOMPOSITION, IT EMITS ACRID SMOKE AND IRRITATING FUMES. CONTAINS SOLVENTS WHICH MAY FORM CARBON MONOXIDE, CARBON DIOXIDE, AND FORMALDEHYDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

11. TOXICOLOGICAL INFORMATION

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES SERIOUS EYE IRRITATION

EFFECTS OF OVEREXPOSURE - SKIN CONTACT:

MAY BE ABSORBED THROUGH THE SKIN IN HARMFUL AMOUNTS. MAY CAUSE SKIN IRRITATION. ALLERGIC REACTIONS ARE POSSIBLE.

EFFECTS OF OVEREXPOSURE - INHALATION:

HARMFUL IF INHALED. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. AVOID BREATHING FUMES, SPRAY, VAPORS, OR MIST. HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS.

PROLONGED OR EXCESSIVE INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION.

EFFECTS OF OVEREXPOSURE - INGESTION: HARMFUL IF SWALLOWED.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:

MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. HIGH CONCENTRATIONS MAY LEAD TO CENTRAL NERVOUS SYSTEM EFFECTS (DROWSINESS, DIZZINESS, NAUSEA, HEADACHES, PARALYSIS, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

PRIMARY ROUTE(S) OF ENTRY:

EYE CONTACT, INGESTION, INHALATION, SKIN ABSORPTION, SKIN CONTACT

ACUTE TOXICITY VALUES:

THE ACUTE EFFECTS OF THIS PRODUCT HAVE NOT BEEN TESTED. DATA ON INDIVIDUAL COMPONENTS ARE TABULATED BELOW:

CAS-NO.	CHEMICAL NAME	ORAL LD50	DERMAL LD50	VAPOR LC50
67-64-1	ACETONE	5800 MG/KG RAT	N.I.	50.1 MG/L RAT
74-98-6	PROPANE	N.I.	N.I.	658 MG/L RAT
108-88-3	TOLUENE	2600 MG/KG RAT	12000 MG/KG RABBIT	12.5 MG/L RAT
123-86-4	N-BUTYL ACETATE	10768 MG/KG RAT	>17600 MG/KG RABBIT	>21 MG/L RAT
106-97-8	N-BUTANE	N.I.	N.I.	658 MG/L RAT
64742-95-6	SOLVENT NAPHTHA, LIGHT AROMATIC	8400 MG/KG RAT	>2000 MG/KG RABBIT	N.I.
95-63-6	1,2,4-TRIMETHYLBENZENE	3280 MG/KG RAT	>3160 MG/KG RABBIT	18 MG/L RAT
64742-49-0	NAPHTHA, PETROLEUM, HYDROTREATED LIGHT	>5000 MG/KG RAT	>3160 MG/KG RABBIT	>4951 MG/L RAT

N.I. - NO INFORMATION

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

13. DISPOSAL INFORMATION

DISPOSAL INFORMATION:

DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE, AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER WATERWAYS, WASTEWATER, SOIL, STORM DRAINS OR SEWER SYSTEMS.

14. TRANSPORT INFORMATION

	DOMESTIC (USDOT)	INTERNATIONAL (IMDG)	AIR (IATA)	TDG (CANADA)
UN NUMBER	N.A.	1950	1950	N.A.
PROPER SHIPPING NAME	PAINT PRODUCTS IN LIMITED QUANTITIES	AEROSOLS	AEROSOLS	PAINT PRODUCTS IN LIMITED QUANTITIES

HAZARD CLASS	N.A.	2.1	2.1	N.A.
PACKING GROUP	N.A.	N.A.	N.A.	N.A.
LIMITED QUANTITY	YES	YES	YES	YES

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES' PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:

FIRE HAZARD, PRESSURE HAZARD, ACUTE HEALTH HAZARD, CHRONIC HEALTH HAZARD

SARA SECTION 313:

THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND 40 CFR PART 372:

CHEMICAL NAME	CAS-NO.
TOLUENE	108-88-3
1,2,4-TRIMETHYLBENZENE	95-63-6

TOXIC SUBSTANCES CONTROL ACT:

THIS PRODUCT CONTAINS THE FOLLOWING CHEMICAL SUBSTANCES SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

NO TSCA 12(B) COMPONENTS EXIST IN THIS PRODUCT.

16. OTHER INFORMATION

HMIS RATINGS:

HEALTH	2*
FLAMMABILITY	4
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X

NFPA RATINGS:

HEALTH	2
FLAMMABILITY	4
INSTABILITY	0

VOLATILE ORGANIC COMPOUNDS, G/L: 586

SDS REVISION DATE: 4/7/2016

REASON FOR REVISION:

PRODUCT COMPOSITION CHANGED

SUBSTANCE AND/OR PRODUCT PROPERTIES CHANGED IN SECTION(S) :

01 - IDENTIFICATION

02 - HAZARD IDENTIFICATION

05 - FIRE-FIGHTING MEASURES

09 - PHYSICAL & CHEMICAL PROPERTIES

15 - REGULATORY INFORMATION

16 - OTHER INFORMATION

STATEMENT(S) CHANGED

LEGEND:

N.A. - NOT APPLICABLE

N.E. - NOT ESTABLISHED

N.D. - NOT DETERMINED

RUST-OLEUM CORPORATION BELIEVES, TO THE BEST OF ITS KNOWLEDGE, INFORMATION AND BELIEF, THE INFORMATION CONTAINED HEREIN TO BE ACCURATE AND RELIABLE AS OF THE DATE OF THIS SAFETY DATA SHEET. HOWEVER, BECAUSE THE CONDITIONS OF HANDLING, USE, AND STORAGE OF THESE MATERIALS ARE BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY OR LIABILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE INCURRED BY THE USE OF THESE MATERIALS. RUST-OLEUM CORPORATION MAKES NO WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OR RELIABILITY OF THE DATA OR RESULTS OBTAINED FROM THEIR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. THE INFORMATION AND RECOMMENDATIONS IN THIS MATERIAL SAFETY DATA SHEET ARE OFFERED FOR THE USERS' CONSIDERATION AND EXAMINATION. IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE FINAL SUITABILITY OF THIS INFORMATION AND TO COMPLY WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.



Sakrete Anchor Cement

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 01/20/2014

Revision date: 01/31/2018

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Sakrete Anchor Cement
Product code : 65450036 - 50lb pail, 60205003 - 10lb tub, 65450004 - 20lb tub

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Various

1.3. Details of the supplier of the safety data sheet

Sakrete of North America
625 Griffith Rd., Ste 100 Charlotte, NC 28217
T 800-334-0784 Tech Service: Monday - Friday; 8:00am - 5:00pm EST

1.4. Emergency telephone number

Emergency number : For Hazardous Materials [or Dangerous Goods] Incident
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
1-800-424-9300 [USA] / +1 703-527-3887 [CAN]

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity 4 (Oral)
Skin Irritation 2
Serious Eye Damage 1
Skin Sensitization 1
Carcinogenicity 1A
Reproductive Toxicity 1B
Specific Target Organ Toxicity After Single Exposure 3
Specific Target Organ Toxicity After Repeated Exposure 1

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS05



GHS07



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Harmful if swallowed. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause cancer. May damage fertility or the unborn child. May cause respiratory irritation. Causes damage to lungs through prolonged or repeated exposure.

Precautionary statements (GHS-US) : Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area. Do not breathe dust. If exposed or concerned: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Rinse mouth. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : Not applicable.

2.4. Unknown acute toxicity (GHS-US)

46 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Sakrete Anchor Cement

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Quartz	(CAS No) 14808-60-7	30 - 60	Acute Tox. 4 (Oral) Carc. 1A STOT RE 1
Cement, alumina, chemicals	(CAS No) 65997-16-2	10 - 30	Skin Irrit. 2 Eye Dam. 1
Cement, portland, chemicals	(CAS No) 65997-15-1	5 - 20	Skin Irrit. 2 Eye Dam. 1 Skin Sens. 1 STOT SE 3
Lithium carbonate	(CAS No) 554-13-2	0.1 - 1	Acute Tox. 4 (Oral) Skin Irrit. 2 Eye Dam. 1 Repr. 1B STOT SE 3 STOT RE 1

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.
- Symptoms/injuries after eye contact : Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : Harmful if swallowed. May cause stomach distress, nausea or vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.
- Unsuitable extinguishing media : Not available.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Sakrete Anchor Cement

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.1.2. For emergency responders

No additional information available

6.2. Methods and material for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Vacuum or sweep material and place in a disposal container.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid generating and breathing dust. Do not swallow. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep container tightly closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	(30)/(%SiO ₂ + 2) mg/m ³ TWA, total dust (250)/(%SiO ₂ + 5) mppcf TWA, respirable fraction (10)/(%SiO ₂ + 2) mg/m ³ TWA, respirable fraction
Cement, portland, chemicals (65997-15-1)		
USA ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear suitable waterproof gloves.

Eye protection : Wear approved eye protection (properly fitted dust- or splash-proof chemical safety goggles) and face protection (face shield).

Skin and body protection : Wear suitable waterproof protective clothing.

Respiratory protection : A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid.
Appearance	: Powder.
Colour	: Various.
Odour	: Characteristic.
Odour threshold	: No data available.
pH	: 10 – 12
Relative evaporation rate (butylacetate=1)	: No data available.

Sakrete Anchor Cement

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: No data available.
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: No data available.
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

VOC content : 0%, Not applicable; 0 wt, Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Keep dry in storage.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Incompatible materials. Moisture.

10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

Quartz (14808-60-7)	
LD50 oral rat	500 mg/kg

Lithium carbonate (554-13-2)	
LC50 inhalation rat (mg/l)	> 2.17 mg/l/4h

Sakrete Anchor Cement	
ATE (oral)	521 mg/kg, rat
ATE (dermal)	No data available
ATE (inhalation)	No data available

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: May cause cancer.

Quartz (14808-60-7)	
IARC group	1
National Toxicology Program (NTP) Status	2

Sakrete Anchor Cement

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Reproductive toxicity	: May damage fertility or the unborn child.
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Causes damage to lungs through prolonged or repeated exposure. (Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.)Based on available data, the classification criteria are not met.
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin. May cause sensitisation by skin contact.
Symptoms/injuries after eye contact	: Causes serious eye damage. May cause burns in the presence of moisture. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: Harmful if swallowed. May cause stomach distress, nausea or vomiting.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: No ecological consideration when used according to directions. Normal dilution of this product to drains, sewers, septic systems and treatment plants is not considered environmentally harmful.

12.2. Persistence and degradability

Sakrete Anchor Cement	
Persistence and degradability	No data available.

12.3. Bioaccumulative potential

Sakrete Anchor Cement	
Bioaccumulative potential	No data available.

12.4. Mobility in soil

Sakrete Anchor Cement	
Ecology - soil	No data available.

12.5. Other adverse effects

Other adverse effects	: No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Additional information

Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Sakrete Anchor Cement

Safety Data Sheet


according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Cement, alumina, chemicals (65997-16-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cement, portland, chemicals (65997-15-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Lithium carbonate (554-13-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting	1.0 %

15.2. US State regulations	
Sakrete Anchor Cement	
State or local regulations	This product contains Crystalline Silica, Quartz and may also contain other chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:	
IARC (I)	International Agency for Research on Cancer. 1 - Carcinogenic to humans; 2A - Probably carcinogenic to humans; 2B - Possibly carcinogenic to humans; 3 - Not classifiable; 4 - Probably not carcinogenic to humans.
NTP (N)	National Toxicology Program. 1 - Evidence of Carcinogenicity; 2 - Known Human Carcinogens; 3 - Reasonably anticipated to be Human Carcinogen; 4 - Substances delisted from report on Carcinogens; 5 - Twelfth Report - Items under consideration.

SECTION 16: Other information	
Indication of changes	: None.
Data sources	: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Other information	: None.
NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : SMOKE ODOR NEUTRALIZER CANADA

Material number : R01811

Manufacturer or supplier's details

Company : Zep Inc.

Address : 11627 - 178 Street
Edmonton, Alberta T5S 1N6
Canada

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation
Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.**Recommended use of the chemical and restrictions on use**

Recommended use : Air Care

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	opaque
Odour	pleasant

GHS ClassificationFlammable aerosols : Category 2
Gases under pressure : Liquefied gas
Skin sensitisation : Category 1**GHS label elements**

Hazard pictograms :



Signal word : Warning

Hazard statements : H223 Flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H317 May cause an allergic skin reaction.Precautionary statements : **Prevention:**

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
butane	106-97-8	>= 10 - < 20
propane	74-98-6	>= 1 - < 5
dodecyl methacrylate	142-90-5	>= 1 - < 5
benzyl salicylate	118-58-1	>= 0.1 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If skin irritation persists, call a physician.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

If swallowed	:	DO NOT induce vomiting unless directed to do so by a physician or poison control center. If a person vomits when lying on his back, place him in the recovery position. If conscious, drink plenty of water.
Most important symptoms and effects, both acute and delayed	:	Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. May cause an allergic skin reaction. Review section 2 of SDS to see all potential hazards.
Notes to physician	:	Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO ₂) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so.

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Observe label precautions.
Keep in a dry, cool and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	1,000 ppm	CA AB OEL
		TWA	600 ppm	CA BC OEL
		STEL	750 ppm	CA BC OEL
		TWAEV	800 ppm 1,900 mg/m ³	CA QC OEL
propane	74-98-6	TWA	1,000 ppm	CA AB OEL
		TWA	1,000 ppm	CA BC OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
		TWA	1,000 ppm	ACGIH

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

required.

Hand protection

Remarks

: Skin should be washed after contact.

Eye protection

: Always wear eye protection when the potential for inadvertent eye contact with the product cannot be excluded.

Skin and body protection

: No special protection is required.

Hygiene measures

: When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: Aerosol containing a liquefied gas

Colour

: opaque

Odour

: pleasant

pH

: Not applicable

Melting point/freezing point

: Not applicable

Boiling point

: not determined

Flash point

:

No data available

Evaporation rate

: < 1

Flammability (solid, gas)

: Flammable aerosol.

Vapour pressure

: No data available

Density

: 0.92 g/cm³

Solubility(ies)

Water solubility

: soluble in hot water, soluble in cold water

Solubility in other solvents

: slightly soluble

Partition coefficient: n-octanol/water

: No data available

Auto-ignition temperature

: not determined

Thermal decomposition

: No data available

Viscosity

Viscosity, kinematic

: No data available

Heat of combustion

: > 20 kJ/g

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects**

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash.

Carcinogenicity:**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Acute toxicity**Components:****benzyl salicylate:**

Acute oral toxicity	: LD50 Oral Rat: 2,227 mg/kg

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation**Product:**

Remarks: May irritate eyes.

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

Components:**butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation (TDG) / Règlement Pour Le Transport (TMD): (Canada): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IMDG (Vessel): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Cargo Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: IATA (Passenger Air): UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation / Règlement Pour Le Transport: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

The product as delivered to the customer conforms to packaging requirements for shipment by road under Transport Dangerous Goods (TDG) Canada regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

This product has been classified according to the hazard criteria of the HPR and the SDS contains all of the information required by the HPR.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory
DSL All components of this product are on the Canadian DSL

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

WHMIS - GHS Label Information:

Hazard pictograms :



Signal word :

Warning:

Hazard statements :

Flammable aerosol. Contains gas under pressure; may explode if heated. May cause an allergic skin reaction.

Precautionary statements :

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/ attention. Take off contaminated clothing and wash it before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	08/10/2017
Print Date:	03/27/2018

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®,

SMOKE ODOR NEUTRALIZER CANADA

Version 1.1

Revision Date 08/10/2017

Print Date 03/27/2018

Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.

Safety Data Sheet



1. Identification

Product Name:	STRUST +SSPR 6PK FLAT BLACK	Revision Date:	2/15/2018
Product Identifier:	7776830	Supersedes Date:	2/8/2018
Product Use/Class:	Topcoat/Aerosols		
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		
Emergency Telephone:	24 Hour Hotline: 847-367-7700		

2. Hazard Identification

Classification

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

42% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Carcinogenicity, category 1B	H350	May cause cancer.
Compressed Gas	H280	Contains gas under pressure; may explode if heated.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Flammable Aerosol, category 1	H222	Extremely flammable aerosol.
Germ Cell Mutagenicity, category 1B	H340	May cause genetic defects.

GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122°F.
P501	Dispose of contents/container in accordance with local, regional and national regulations.

3. Composition / Information On Ingredients

HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt.% Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Propane	74-98-6	10-25	GHS04	H280
Hydrotreated Light Distillate	64742-47-8	10-25	GHS08	H304
Acetone	67-64-1	10-25	GHS02-GHS07	H225-319-332-336
Hydrous Magnesium Silicate	14807-96-6	10-25	Not Available	Not Available
n-Butane	106-97-8	2.5-10	GHS04	H280
n-Butyl Acetate	123-86-4	2.5-10	GHS02-GHS07	H226-336
Xylenes (o-, m-, p- isomers)	1330-20-7	2.5-10	GHS02-GHS07	H226-315-319-332
Carbon Black	1333-86-4	0.1-1.0	Not Available	Not Available
Ethylbenzene	100-41-4	0.1-1.0	GHS02-GHS07-GHS08	H225-304-332-351-373
Stoddard Solvent	8052-41-3	0.1-1.0	GHS08	H304-372
Solvent Naphtha, Light Aromatic	64742-95-6	0.1-1.0	GHS07-GHS08	H304-332-340-350
Distillates (Petroleum), Hydrodesulfurized Middle	64742-80-9	0.1-1.0	GHS08	H350

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention. If swallowed, get medical attention.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: FLASH POINT IS LESS THAN 20°F. EXTREMELY FLAMMABLE LIQUID AND VAPOR! Water spray may be ineffective. Closed containers may explode when exposed to extreme heat due to buildup of steam. Closed containers may explode when exposed to extreme heat. Vapors may form explosive mixtures with air. Vapors can travel to a source of ignition and flash back. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Perforation of the pressurized container may cause bursting of the can. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Full protective equipment including self-contained breathing apparatus should be used. Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

Special Fire and Explosion Hazard (Combustible Dust): No Information

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Ventilate area, isolate spilled material, and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations.

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only in a well-ventilated area. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Contents under pressure. Do not store above 120 ° F. Store large quantities in buildings designed and protected for storage of flammable aerosols. Keep away from heat, sparks, flame and sources of ignition. Contents under pressure. Do not expose to heat or store above 120 ° F. Avoid excess heat. Product should be stored in tightly sealed containers and protected from heat, moisture, and foreign materials.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Propane	74-98-6	25.0	N.E.	N.E.	1000 ppm	N.E.
Hydrotreated Light Distillate	64742-47-8	20.0	N.E.	N.E.	N.E.	N.E.
Acetone	67-64-1	20.0	250 ppm	500 ppm	1000 ppm	N.E.
Hydrous Magnesium Silicate	14807-96-6	15.0	2 mg/m3	N.E.	N.E.	N.E.
n-Butane	106-97-8	10.0	N.E.	1000 ppm	N.E.	N.E.
n-Butyl Acetate	123-86-4	5.0	50 ppm	150 ppm	150 ppm	N.E.
Xylenes (o-, m-, p- isomers)	1330-20-7	5.0	100 ppm	150 ppm	100 ppm	N.E.
Carbon Black	1333-86-4	1.0	3 mg/m3	N.E.	3.5 mg/m3	N.E.

Ethylbenzene	100-41-4	1.0	20 ppm	N.E.	100 ppm	N.E.
Stoddard Solvent	8052-41-3	1.0	100 ppm	N.E.	500 ppm	N.E.
Solvent Naphtha, Light Aromatic	64742-95-6	1.0	N.E.	N.E.	N.E.	N.E.
Distillates (Petroleum), Hydrodesulfurized Middle	64742-80-9	1.0	N.E.	N.E.	N.E.	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof ventilation equipment. Provide general dilution of local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications. Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance:	Aerosolized Mist	Physical State:	Liquid
Odor:	Solvent Like	Odor Threshold:	N.E.
Relative Density:	0.774	pH:	N.A.
Freeze Point, °C:	N.D.	Viscosity:	N.D.
Solubility in Water:	Slight	Partition Coefficient, n-octanol/ water:	N.D.
Decomposition Temp., °C:	N.D.	Explosive Limits, vol%:	0.9 - 13.0
Boiling Range, °C:	-37 - 537	Flash Point, °C:	-96
Flammability:	Supports Combustion	Auto-ignition Temp., °C:	N.D.
Evaporation Rate:	Faster than Ether	Vapor Pressure:	N.D.
Vapor Density:	Heavier than Air		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid temperatures above 120°F (49°C). Avoid all possible sources of ignition.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes Serious Eye Irritation

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation. May cause skin irritation. Allergic reactions are possible. Prolonged or repeated contact may cause skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Harmful if swallowed. Aspiration hazard if swallowed; can enter lungs and cause damage.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: May cause central nervous system disorder (e.g., narcosis involving a

loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula. IARC lists Ethylbenzene as a possible human carcinogen (group 2B).

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
64742-47-8	Hydrotreated Light Distillate	>5000 mg/kg Rat	>2000 mg/kg Rabbit	>5000 mg/L Rat
67-64-1	Acetone	5800 mg/kg Rat	>15700 mg/kg Rabbit	50.1 mg/L Rat
14807-96-6	Hydrous Magnesium Silicate	6000	N.E.	30
106-97-8	n-Butane	N.E.	N.E.	658 mg/L Rat
123-86-4	n-Butyl Acetate	10768 mg/kg Rat	>17600 mg/kg Rabbit	> 21 mg/L Rat
1330-20-7	Xylenes (o-, m-, p- isomers)	3500 mg/kg Rat	>4350 mg/kg Rabbit	29.08 mg/L Rat
1333-86-4	Carbon Black	>15400 mg/kg Rat	N.E.	N.E.
100-41-4	Ethylbenzene	3500 mg/kg Rat	15400 mg/kg Rabbit	17.4 mg/L Rat
64742-95-6	Solvent Naphtha, Light Aromatic	8400 mg/kg Rat	>2000 mg/kg Rabbit	N.E.
64742-80-9	Distillates (Petroleum), Hydrodesulfurized Middle	>5000 mg/kg Rat	>2000 mg/kg Rabbit	N.E.

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components. Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Do not incinerate closed containers. Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems. This product as supplied is a USEPA defined ignitable hazardous waste. Dispose of unusable product as a hazardous waste (D001) in accordance with local, state, and federal regulation.

14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
UN Number:	N.A.	1950	1950	N.A.
Proper Shipping Name:	Paint Products in Limited Quantities	Aerosols	Aerosols	Paint Products in Limited Quantities
Hazard Class:	N.A.	2.1	2.1	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	Yes	Yes	Yes	Yes

15. Regulatory Information

U.S. Federal Regulations:**CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

No Information

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
Xylenes (o-, m-, p- isomers)	1330-20-7
Ethylbenzene	100-41-4

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Information**HMIS RATINGS**

Health: 2* Flammability: 4 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 4 Instability: 0

VOLATILE ORGANIC COMPOUNDS, g/L: 527

SDS REVISION DATE: 2/15/2018

REASON FOR REVISION: Product Composition Changed
Substance and/or Product Properties Changed in Section(s):
01 - Identification
02 - Hazard Identification
05 - Fire-fighting Measures
Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

SECTION 1	IDENTIFICATION

Product

Name: Type S Hydrated Lime

Other Names: Dolomitic Hydrate; Hydrated Dolomitic Lime; Calcium Magnesium Hydroxide; Double Hydrated Dolomitic Lime

Recommended Uses: Construction; pH adjustment; Water Treatment; FGT;

Company Identification:

US Operations:

Lhoist North America, Inc.
5600 Clearfork Main St, Ste. 300
Fort Worth, TX 76109
817-732-8164

Canadian Operations:

Lhoist North America of Canada, Inc.
20303-102B Ave.
Langley, BC V1M 3H1
604-888-4333

Emergency Phone Number:

Chemtrec 1-800-424-9300

SECTION 2	HAZARDS(S) IDENTIFICATION

Classification

Eye Damage – Category 1

Carcinogen – Category 1

Skin Irritation – Category 2

Specific Target Organ Toxicity Single Exposure – Category 3
(Respiratory System)

Specific Target Organ Toxicity Repeat Exposure – Category 1
(Respiratory System)

Labeling:

Pictograms:



Signal Word(s): Danger



Type S Hydrated Lime – February 2, 2018

Hazard Statements: Causes serious eye damage.

Causes skin irritation.

May cause respiratory irritation.

Causes damage to lungs through prolonged or repeated exposure when inhaled.

May cause cancer through inhalation.

Precautionary Statements:

Wear protective gloves and eye protection. Wash exposed skin thoroughly after handling. Do not breathe dust. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink or smoke when using this product.

If on skin: wash exposed skin with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Seek medical attention immediately. If inhaled: Remove person to fresh air and keep comfortable for breathing. Seek medical attention if you feel unwell.

If exposed or concerned: Get medical advice

Dispose of contents or containers in accordance with applicable regulations.

Other Hazards: None.

SECTION 3	COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical Name: Calcium Magnesium hydroxide

Common names and synonyms: Dolomitic Hydrate; Hydrated Dolomitic Lime; Calcium Magnesium Hydroxide; Double Hydrated Dolomitic Lime

Chemical Identity	CAS #	Concentration, % Wt.
Calcium Hydroxide	1305-62-0	> 50
Magnesium Hydroxide	1309-42-8	> 35
Crystalline Silica	14808-60-7	< 1

SECTION 4**FIRST AID MEASURES**

- Eye Contact:** Contact can cause severe irritation or burning of eyes, including permanent damage. Immediately flush eyes with generous amounts of water for several minutes. Pull back the eyelid to ensure that all lime dust has been washed out. Seek medical attention immediately. Do not rub eyes.
- Inhalation:** This product can cause severe irritation of the respiratory system. Move victim to fresh air. Seek medical attention if necessary. If breathing has stopped, give artificial respiration.
- Skin Contact:** Contact can cause severe irritation or burning of skin, especially in the presence of moisture. Wash exposed area with large amounts of water. Seek medical attention immediately.
- Ingestion:** This product can cause severe irritation or burning of gastrointestinal tract if swallowed. Do not induce vomiting. Seek medical attention immediately. Never give anything by mouth unless instructed to do so by medical personnel.
- Most important symptoms and effects, both acute and delayed:** Irritation of skin, eyes, gastrointestinal tract or respiratory tract. Long-term exposure by inhalation may cause permanent damage. This product contains crystalline silica, which has been classified by IARC as (Group I) carcinogenic to humans when inhaled. Inhalation of silica can also cause a chronic lung disorder, silicosis.

Note to Physician: Provide general supportive measures and treat symptomatically.

SECTION 5**FIREFIGHTING MEASURES****Extinguishing Media**

Appropriate Extinguishing Media: Use dry chemical fire extinguisher

Inappropriate Extinguishing Media: Do not use halogenated compounds.

Firefighting

Fire Hazards: Type S Hydrated Lime is not combustible or flammable. Type S Hydrated Lime is not considered to be an explosive hazard, although reaction with incompatible materials may rupture containers.

Hazardous Combustion Products: None

Special Protective Equipment and Fire Fighting Instructions: Keep personnel away from and upwind of fire. Wear full fire-fighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

SECTION 6	ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use proper protective equipment.

Environmental Precautions: For large spills, as much as possible, avoid the generation of dusts. Prevent release to sewers or waterways.

Methods and Materials for Containment and Cleaning Up:

Small Spills: Use dry methods to collect spilled materials. Avoid generating dust. Do not clean up with compressed air. Store collected materials in dry, sealed plastic or metal containers. Residue on surfaces may be washed with water or dilute vinegar.

Large Spills: Use dry methods to collect spilled materials. Evacuate area downwind of clean-up operations to minimize dust exposure. Store spilled materials in dry, sealed plastic or metal containers.

SECTION 7	HANDLING AND STORAGE

Precautions for Safe Handling: Keep in tightly closed containers. Protect containers from physical damage. Avoid direct skin contact with the material.

Conditions for Safe Storage, Including any Incompatibilities: Store in a cool, dry, and well-ventilated location. Do not store near incompatible materials (see Section 10 below). Keep away from moisture. Do not store or ship in aluminum containers.

SECTION 8	EXPOSURE CONTROLS/ PERSONAL PROTECTION

Control Parameters:

Component	CAS #	Exposure Limits
Calcium Hydroxide	1305-62-0	OSHA PEL: 15 mg/m ³ (total) 5 mg/m ³ (respirable) ACGIH TLV: 5 mg/m ³
Magnesium Hydroxide	1309-42-8	OSHA PEL: 15 mg/m ³ ACGIH TLV: 5 mg/m ³
Crystalline Silica	14808-60-7	OSHA PEL: 0.050 mg/m ³ as an 8 hr. TWA (respirable) ACGIH TLV: 0.025 mg/m ³ (respirable)

Appropriate Engineering Controls: Provide ventilation adequate to maintain PELs.

Personal Protection

Respiratory Protection: Use NIOSH approved respirators if airborne concentration exceeds PEL.

Eye Protection: Use safety glasses with side shields or safety goggles. Contact lenses should not be worn when working with lime products.

Skin Protection: Use appropriate gloves to prevent skin contact. Clothing should fully cover arms and legs.

Other: Eye wash fountain and emergency showers are recommended.

SECTION 9	PHYSICAL AND CHEMICAL PROPERTIES
Appearance	
Physical State:	Solid
Color:	White
Odor:	Odorless
Odor Threshold:	N/ A
pH:	12.44 @ 25° C
Melting Point:	N/ A
Initial Boiling Point:	N/ A
Freezing Point:	N/ A
Flash Point:	N/ A
Evaporation Rate:	N/ A
Flammability (solid, gas):	Non-flammable
Explosion Limits:	N/ A
Vapor Pressure:	N/ A
Vapor Density:	N/ A
Relative Density:	0.4 – 0.7 g/ cm ³ (apparent)
Solubility(ies):	Solubility is 1.6 g/L at 25° C
Partition coefficient:	Relatively insoluble
Auto-ignition Temperature:	N/ A
Decomposition Temperature:	580° C / 1076° F
Viscosity:	N/A

SECTION 10

STABILITY AND REACTIVITY

Reactivity:

Chemical Stability: Type S Hydrated Lime is chemically stable.

Possibility of Hazardous Reactions: See reactivity above

Conditions to Avoid: Do not allow Type S Hydrated Lime to come into contact with incompatible materials.

Incompatible Materials: Type S Hydrated Lime should not be mixed or stored with the following materials, due to the potential for violent reaction and release of heat:

Acids (unless in a controlled process)

Reactive Fluoridated Compounds

Reactive Brominated Compounds

Reactive Powdered Metals

Organic Acid Anhydrides

Nitro-Organic Compounds

Reactive Phosphorous Compounds

Interhalogenated Compounds

Hazardous Decomposition Products: None

SECTION 11

TOXICOLOGICAL INFORMATION

Health Effects: see First Aid discussion in Section 4

Routes of Exposure: see First Aid discussion in Section 4

Symptoms Related to Exposure: see First Aid discussion in Section 4

Carcinogen Listing: Type S Hydrated Lime is not listed by MSHA, OSHA, or IARC as a carcinogen, but this product contains crystalline silica, which has been classified by IARC as (Group I) carcinogenic to humans when inhaled.

SECTION 12

ECOLOGICAL INFORMATION

Ecotoxicity: Because of the high pH of this product, it would be expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems in high concentrations.

Persistence and Degradability: Reacts with atmospheric CO₂ over time to form calcium carbonate

Bioaccumulation Potential: This material shows no bioaccumulation effect or food chain concentration toxicity.



Type S Hydrated Lime – February 2, 2018

Mobility in Soil: Minimal mobility in soil. Reacts with clay portion of soil to form calcium silicates and calcium aluminates

Other Adverse Effects: This material is alkaline and if released into water or moist soil will cause an increase in pH

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal Recommendations: Dispose of in accordance with all applicable federal, state, and local environmental regulations.

Regulatory Disposal Information: If this product as supplied, and unmixed, becomes a waste, it will not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act.

SECTION 14

TRANSPORT INFORMATION

UN Number: Not Regulated

UN Proper Shipping Name: Not Regulated

Transport Hazard Class(es): Not Regulated

Packing Group: Not Regulated

Marine Pollutant (y/n): This material is alkaline and if released into water or moist soil will cause an increase in pH.

Special Precautions: None

SECTION 15

REGULATORY INFORMATION

National Chemical Inventory Listings:

All chemical ingredients are listed on the USEPA TSCA Inventory List.

US Regulations:

RCRA Hazardous Waste Number: not listed (40 CFR 261.33)

RCRA Hazardous Waste Classification (40 CFR 261): not classified

CERCLA Hazardous Substance (40 CFR 302.4) unlisted specific per RCRA, Sec. 3001;

CWA, Sec. 311 (b) (4); CWA, Sec. 307(a), CAA, Sec. 112

CERCLA Reportable Quantity (RQ) not listed.

SARA 311/312 Codes: not listed.

SARA Toxic Chemical (40 CFR 372.65): not listed.

SARA EHS (Extremely Hazardous Substance) (40 CFR 355): Not listed, Threshold Planning Quantity (TPQ): not listed

Specific State Regulations: **⚠️ WARNING:** This product can expose you to chemicals, including crystalline silica, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

These naturally occurring impurities may also be regulated by other States.

Canadian DSL: Listed

Canadian NPRI: None of the components are listed

CEPA Toxic Substances: None of the components are listed

SECTION 16	OTHER INFORMATION

Prepared By: Lhoist North America Technical Services

Date Prepared: February 2, 2015

Revision: 2018-1

Abbreviations:

N/A	Not Available or Not Applicable
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
ACGIH	ACGIH American Conference of Governmental Industrial Hygienists
TWA	Time Weighted Average
PEL	Permissible Exposure Limit
TLV	Threshold Limit Value
REL	Recommended Exposure Limit

Lhoist North America provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person. Individuals receiving this information must consult their own technical and legal advisors and/or exercise their own judgment in determining its appropriateness for a particular purpose. Lhoist North America makes no representations or warranties, either express or implied, including without limitation and warranties of merchantability or fitness for a particular purpose with respect to the Information set forth herein or the product(s) to which the information refers. Accordingly, Lhoist North America will not be responsible or liable for any claims, losses or damages resulting from the use of or reliance upon or failure to use this information.



Material Safety Data Sheet

Revision Date 08-Feb-2005

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product code 95789
Product name White Inverted Tip Marking Paint
Recommended Use Coating
Supplier Lawson Products, Inc.
1666 East Touhy Avenue
Des Plaines, IL 60018
(847)-827-9666

Emergency telephone number (888) 426-4851

2. HAZARDS IDENTIFICATION

Emergency Overview

Irritant. Extremely flammable.

Color White

Odor Solvent

Form Aerosol

Aggravated Medical Conditions Reports have associated prolonged overexposure to solvents with permanent brain and nervous system damage.

Principal Routes of Exposure Eyes. Inhalation.

Potential health effects

Eyes Irritation. Swelling.

Skin Skin Irritation.

Inhalation May cause irritation of the nose and throat. Central nervous system effects. Dizziness. Headaches. Fatigue. Exposure to hot fumes may cause nausea and damage to respiratory system. Misuse by deliberately concentrating vapors and inhaling contents can be harmful or fatal.

Ingestion No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Propane	74-98-6	10-30
Calcium Carbonate	1317-65-3	10-30
N-Butane	106-97-8	5-10
Light Aliphatic Naptha Solvent	64742-89-8	10-30
Titanium Dioxide	13463-67-7	5-10
Toluene	108-88-3	1-5
Xylene (mix)	1330-20-7	1-5
Hexane	110-54-3	1-5
Mineral Spirits	64742-47-8	1-5
Ethyl benzene	100-41-4	1-5

4. FIRST AID MEASURES

Eye contact	Remove to fresh air. Rinse thoroughly with plenty of water, also under the eyelids. Seek medical attention if irritation persists.
Skin contact	Wash area thoroughly with soap and water. Remove and wash contaminated clothing before re-use.
Ingestion	Call a physician or Poison Control Center immediately.
Inhalation	Move to fresh air. If symptoms persist, call a physician.

5. FIRE FIGHTING MEASURES

Flash point °C	-19
Flash point °F	-2
Method	No information available

Autoignition temperature °C	No data available
Autoignition temperature °F	

Flammability Limits (% in Air)	
Upper	10.9
Lower	0.9

Specific Information for Aerosol Products

Flame extension	15"
Flashback	None

Suitable extinguishing media

Carbon dioxide (CO₂). Water spray. alcohol-resistant foam. Sand.

Extinguishing media which must NOT be used for safety reasons

No information available.

Special Fire-Fighting Procedures

None known.

Fire and Explosion Hazards

Firefighters should wear NIOSH/MSHA approved (or equivalent) self-contained pressure-demand breathing apparatus and full protective clothing.

Sensitivity to shock

No information available.

Sensitivity to static discharge

No information available.

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up

Personnel should wear appropriate protective equipment. Follow all precautions for handling. Please refer to appropriate sections of MSDS for additional information. Evacuate area of unprotected and unnecessary personnel. Do not allow product to reach sewage system, soil, surface or ground water, or any water course. Notify proper authorities if entry occurs. Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up with inert absorbent material. Dispose of absorbent in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Handling

Protect against electrostatic charges. Do not smoke.

Storage

Small pressurized containers of flammable product may be stored in areas suitable for ordinary combustibles with respect to construction, drainage, control of ignition sources, and ventilation except that they should not be stored in basements. Keep away from heat. Keep away from direct sunlight. Do not freeze.

NFPA Storage Code

Store as Level 3 Aerosol (NFPA 30B)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Chemical Name	OSHA PEL (TWA)	OSHA PEL (Ceiling)	ACGIH OEL (TWA)	ACGIH OEL (STEL)
Propane	1000 ppm 1800 mg/m ³	-	1000 ppm listed under aliphatic hydrocarbon gases alkane C1-C4	-
Calcium Carbonate	15 mg/m ³ total dust 5 mg/m ³ respirable fraction	-	-	-
N-Butane	-	-	1000 ppm listed under aliphatic hydrocarbon gases alkane C1-C4	-
Light Aliphatic Naptha Solvent	-	-	-	-
Titanium Dioxide	15 mg/m ³ total dust	-	10 mg/m ³	-
Toluene	200 ppm	300 ppm	50 ppm	-
Xylene (mix)	100 ppm 435 mg/m ³	-	100 ppm	150 ppm
Hexane	1800 mg/m ³ 500 ppm	-	50 ppm 500 ppm	N/D
Mineral Spirits	-	-	-	-
Ethyl benzene	100 ppm 435 mg/m ³	-	100 ppm	125 ppm

Ventilation and Environmental Controls

Adequate ventilation should be provided to keep exposure levels below current acceptable exposure limits.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product.

Personal protective equipment**Respiratory protection**

None necessary under normal conditions. Use NIOSH approved respirator if TLV limit is exceeded.

Hand protection

Protective gloves. Impervious gloves.

Eye protection

Tightly fitting safety goggles.

Skin and body protection

No information available

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Aerosol	Color	White
Odor	Solvent	Odor Threshold	5 ppm
pH	No data available	Specific Gravity	0.77-0.90
Vapor pressure	No data available	Vapor density	No data available
Evaporation Rate	No data available	VOC Content	50.0 %
Water solubility	No data available	Partition Coefficient (n-octanol/water)	>1
Boiling point/range °F	-47	Boiling point/range °C	-44
Melting point/range °F	No data available	Melting point/range °C	No data available
Flash point °F	-2	Flash point °C	-19

10. STABILITY AND REACTIVITY**Stability**

Stable under normal conditions.

Conditions to avoid

Do not store in temperatures above 120 degrees F.

Materials to avoid

No information available

Hazardous decomposition products

None known.

Polymerization

No information available

Synergistic Products

No information available.

11. TOXICOLOGICAL INFORMATION**Component Information**

Chemical Name	LD50 (oral, rat)	LD50 (dermal, rat/rabbit)	LC50 (inhalation, rat)
<i>Propane</i> 74-98-6	-	-	-
<i>Calcium Carbonate</i> 1317-65-3	-	-	-
<i>N-Butane</i> 106-97-8	-	-	658 g/m ³ 680 g/m ³
<i>Light Aliphatic Naptha Solvent</i> 64742-89-8	-	-	-
<i>Titanium Dioxide</i> 13463-67-7	-	-	-
<i>Toluene</i> 108-88-3	636 mg/kg	14100 µL/kg	400 mg/kg 49 g/m ³
<i>Xylene (mix)</i> 1330-20-7	4300 mg/kg	1700 mg/kg	5000 ppm
<i>Hexane</i> 110-54-3	28710 mg/kg	-	48000 ppm
<i>Mineral Spirits</i> 64742-47-8	-	-	-
<i>Ethyl benzene</i> 100-41-4	3500 mg/kg	17800 µL/kg	-

Potential health effects**Sensitization**

No information available.

Mutagenic effects

No information available.

Reproductive toxicity

No information available

Carcinogenic effects

See table below

Chronic toxicity

No information available.

Teratogenic effects

No information available

Target Organ Effects

No information available

Chemical Name	ACGIH OEL - Carcinogens	IARC	NTP - Known Carcinogens	NTP - Suspected Human Carcinogens	OSHA RTK Carcinogens
Propane	-	-	-	-	-
Calcium Carbonate	-	-	-	-	-
N-Butane	-	-	-	-	-
Light Aliphatic Naptha Solvent	-	-	-	-	-
Titanium Dioxide	A4 - Not Classifiable as a Human Carcinogen	-	-	-	-
Toluene	A4 - Not Classifiable as a Human Carcinogen	-	-	-	-
Xylene (mix)	A4 - Not Classifiable as a Human Carcinogen	-	-	-	-
Hexane	-	-	-	-	-
Mineral Spirits	-	-	-	-	-
Ethyl benzene	A3 - Confirmed animal carcinogen with unknown relevance to humans	Group 2B	-	-	Listed

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Toluene

Microtox Data

Photobacterium phosphoreum EC50=19.7 mg/L (30 min)

Water Flea Data

water flea EC50=11.3 mg/L (48 h)

water flea EC50=310 mg/L (48 h)

Xylene (mix)

Microtox Data

Photobacterium phosphoreum EC50=0.0084 mg/L (24 h)

Water Flea Data

water flea EC50=3.82 mg/L (48 h)

Hexane

Water Flea Data

water flea LC50=3.87 mg/L (48 h)

Ethyl benzene

Microtox Data

Photobacterium phosphoreum EC50=9.68 mg/L (30 min)

Water Flea Data

water flea EC50=2.1 mg/L (48 h)

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products

Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate. Please recycle empty container whenever possible.

14. TRANSPORT INFORMATION

DOT

Consumer commodity (Toluene,Xylenes (isomers and mixture)),ORM-D,,RQ

TDG

AEROSOLS(Propane,N-Butane), Class 2.1,UN1950,PG

IMDG/IMO

Aerosols(Propane,N-Butane),UN1950,PG

IATA

Aerosols, flammable(Propane,N-Butane),UN1950
Hazard Class 2.1

MEX

UN1950 Aerosols(Propane,N-Butane),2.2,

15. REGULATORY INFORMATION

Chemical Name	US EPA SARA 313 Emission Reporting
Toluene	Listed
Xylene (mix)	Listed
Hexane	Listed
Ethyl benzene	Listed

State Regulations

Chemical Name	New Jersey - RTK	Pennsylvania - RTK	California Prop. 65
Propane	Listed	Listed	Not Listed
Calcium Carbonate	Not Listed	Listed	Not Listed
N-Butane	Not Listed	Listed	Not Listed
Light Aliphatic Naptha Solvent	Not Listed	Not Listed	Not Listed
Titanium Dioxide	Not Listed	Listed	Not Listed
Toluene	Listed	Listed	Developmental
Xylene (mix)	Not Listed	Listed	Not Listed
Hexane	Listed	Listed	Not Listed
Mineral Spirits	Not Listed	Not Listed	Not Listed
Ethyl benzene	Listed	Listed	Carcinogen

International Inventories

Chemical Name	EINECS	DSL	NDSL	TSCA
Propane	X	X	-	X
Calcium Carbonate	X	-	X	X
N-Butane	X	X	-	X
Light Aliphatic Naptha Solvent	X	X	-	X
Titanium Dioxide	X	X	-	X
	X			
	X			
Toluene	X	X	-	X
Xylene (mix)	X	X	-	X
Hexane	X	X	-	X
Mineral Spirits	X	X	-	X
Ethyl benzene	X	X	-	X

CPRC

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by the Controlled Product Regulations

16. OTHER INFORMATION

NFPA		HMIS	
Health	1	Health	1
Flammability	3	Flammability	3
Reactivity	3	Physical Hazard	3

Reason for revision

No information available.

Prepared By

T. Heidorn, MSDS Project Lead

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

1. Identification

Product identifier WINDOW CLEAN+

Other means of identification

SDS number 565N-26B

Product code HIL00138

Recommended use Window Cleaner

Recommended restrictions For Labeled Use Only

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HILLYARD INDUSTRIES

Address 302 North Fourth St.
St. Joseph, MO 64501

Contact person Regulatory Affairs

Telephone number (816) 233-1321 (Ext. 8285)

Fax (816) 383-8485

E-mail regulatoryaffairs@hillyard.com

Emergency telephone # (800) 424-9300

(Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3

Health hazards Acute toxicity, dermal Category 4

Acute toxicity, inhalation Category 4

Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. Harmful in contact with skin. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store in a well-ventilated place. Keep cool.
Disposal	Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law in compliance with applicable federal, state and local requirements. CONTAINER DISPOSAL: Triple rinse (or equivalent), then offer clean, dry container for recycling or reconditioning.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Ethylene glycol monobutyl ether		111-76-2	10 - < 20
Isopropyl Alcohol		67-63-0	5 - < 10
Propylene glycol monomethyl ether		107-98-2	5 - < 10
Other components below reportable levels			70 - < 80

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical advice/attention if you feel unwell.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ethylene glycol monobutyl ether (CAS 111-76-2)	PEL	240 mg/m3
Isopropyl Alcohol (CAS 67-63-0)	PEL	50 ppm 980 mg/m3 400 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA	20 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
Propylene glycol monomethyl ether (CAS 107-98-2)	TWA	200 ppm
	STEL	100 ppm
	TWA	50 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA	24 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Isopropyl Alcohol (CAS 67-63-0)	STEL	5 ppm 1225 mg/m3
	TWA	500 ppm 980 mg/m3
Propylene glycol monomethyl ether (CAS 107-98-2)	STEL	400 ppm 540 mg/m3
	TWA	150 ppm 360 mg/m3 100 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylene glycol monobutyl ether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.
Propylene glycol monomethyl ether (CAS 107-98-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Ethylene glycol monobutyl ether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene glycol monobutyl ether (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection For prolonged or repeated skin contact use suitable protective gloves.

Other None normally required. If unable to avoid prolonged or repeated contact with skin, wear impervious clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards None known.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear, dark purple liquid

Physical state Liquid.

Form Liquid.

Color Dark purple

Odor Mild solvent odor

Odor threshold	Not available
pH	6 - 8
Melting point/freezing point	Not available
Initial boiling point and boiling range	184 °F (84.44 °C) corr.
Flash point	> 101.0 °F (> 38.3 °C) Closed Cup
Evaporation rate	< 1 Ethyl ether = 1
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	17.5 mm Hg
Vapor density	1.5 Air=1
Relative density	0.98 at 77°F
Solubility(ies)	
Solubility (water)	100 % Complete
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Other information	
Density	8.15 lb/gal
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	> 97 %
VOC	30 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Isocyanates. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled.
Skin contact	Harmful in contact with skin. Causes skin irritation.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity	Harmful if inhaled. Harmful in contact with skin.

Product	Species	Test Results
WINDOW CLEAN+		
<u>Acute</u>		
Dermal		
LD50	Rabbit	2625 mg/kg estimated
Inhalation		
LC50	Mouse	6565 mg/l, 4 Hours estimated
		4667 ppm, 7 Hours estimated
	Rat	3000 ppm, 4 Hours estimated
		732 mg/l, 4 Hours estimated
Oral		
LD50	Guinea pig	7.9 g/kg estimated
	Mouse	7.6 g/kg estimated
	Rabbit	2 g/kg estimated
	Rat	3732 mg/kg estimated
Components	Species	Test Results
Ethylene glycol monobutyl ether (CAS 111-76-2)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	400 mg/kg
Inhalation		
LC50	Mouse	700 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	560 mg/kg
Isopropyl Alcohol (CAS 67-63-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12800 mg/kg
Oral		
LD50	Mouse	3600 mg/kg
	Rabbit	5.03 g/kg
	Rat	4.7 g/kg
Propylene glycol monomethyl ether (CAS 107-98-2)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	13 g/kg
Inhalation		
LC50	Guinea pig	15000 mg/l, 10 Hours
	Rat	54.6 mg/l, 4 Hours
Oral		
LD50	Dog	4.6 g/kg
	Mouse	10.8 g/kg
	Rabbit	5.3 g/kg
	Rat	5.71 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Ethylene glycol monobutyl ether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.	
US. National Toxicology Program (NTP) Report on Carcinogens	
Not listed.	
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	
Not regulated.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	May be harmful if absorbed through skin. Prolonged inhalation may be harmful.
	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species		Test Results
WINDOW CLEAN+			
Aquatic			
Crustacea	EC50	Daphnia	536.1516 mg/l, 48 hours estimated
Fish	LC50	Fish	896.8746 mg/l, 96 hours estimated
Components	Species		Test Results
Ethylene glycol monobutyl ether (CAS 111-76-2)			
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)			
Aquatic			
Fish	LC50	Western mosquitofish (Gambusia affinis)	> 1400 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethylene glycol monobutyl ether	0.83
Isopropyl Alcohol	0.05

Mobility in soil	No data available.

Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. Buyer assumes all risk and liability associated with disposal of this product (original concentration or dilution) in violation of applicable law.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Waste from normal product use may be sewered to a public owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Triple rinse (or equivalent). Then offer clean, dry container for recycling or reconditioning.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number	UN1993
UN proper shipping name	Flammable liquid, n.o.s. (Isopropyl Alcohol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	No.
ERG Code	128
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.
Cargo aircraft only	Allowed with restrictions.

IMDG

UN number	UN1993
UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (Isopropyl Alcohol)
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	III
Environmental hazards	
Marine pollutant	No.
EmS	F-E, S-E
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

No

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Safe Drinking Water Act (SDWA)

Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Isopropyl Alcohol (CAS 67-63-0)

Low priority

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylene glycol monobutyl ether (CAS 111-76-2)

Isopropyl Alcohol (CAS 67-63-0)

Propylene glycol monomethyl ether (CAS 107-98-2)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01-29-2015
Revision date 08-25-2016
Version # 02
HMIS® ratings Health: 2
Flammability: 3
Physical hazard: 0

Disclaimer No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose, or of any nature are made with respect to the product(s) or information contained in this material safety data sheet. The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate. The buyer or user assumes all risks associated with the use, misuse or disposal of this product. The buyer or user is responsible to comply with all federal, state or local regulations concerning the use, misuse or disposal of these products. HILLYARD cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information This document has undergone significant changes and should be reviewed in its entirety.