

Safety Data Sheets

Security Office



RSC, Sierra Vista

11/26/2019



Safety Data Sheet Index
Binder: RSC, Sierra Vista - Security Office

Product Name	CAS Number	Manufacturer	Version Date	Page
Germ-X Hand Sanitizer - Germ-X Hand Sanitizer		Vi-Jon Incorporated	04/23/2008	3
Safeway Disinfecting Wipes - Safeway Disinfecting Wipes		NICE-PAK PRODUCTS, INC.	01/01/2007	9
TRI - FLOW Superior Lubricant with PTFE - TRI-FLOW Superior Lubricant with PTFE		Sherwin-Williams Company - Consumer Group - Industrial	01/16/2014	11

Material Safety Data Sheet



Section 1: PRODUCT AND COMPANY IDENTIFICATION

Vi-Jon Incorporated
8515 Page Avenue
Saint Louis, MO 63114

Phone: 314-427-1000
In Case of Spill Emergency Contact:
Chemtrec: 1-800-424-9300

Product Name: Germ-X Hand Sanitizer

Product Code: 028

Product Use: Hand Sanitizer

Issue Date: 04/23/2008

Supersedes Date: July 2007

Section 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Keep out of reach of children.

Appearance/Odor: Clear gel with alcohol/citrus odor.

WARNING:

Flammable (ethyl alcohol and isopropyl alcohol)

Target (ethyl alcohol and isopropyl alcohol) respiratory system, skin, eyes, CNS, liver, blood and reproductive system.

Potential Health Effects: See Section 11 for more information.

Symptoms of Exposure:

Inhalation: May cause irritation of the respiratory tract.

Ingestion: May cause nausea, vomiting and diarrhea.

Eyes: May cause irritation to the eyes.

Skin: None expected.

This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.

This material contains components that are considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential Environmental Effects: See Section 12 for more information.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS#	% by Wt.
Ethyl Alcohol	64-17-5	59%
Isopropyl Alcohol	67-64-0	3%

Section 4: FIRST AID MEASURES

Emergency first aid procedures by route of exposure:

- Inhalation:** If symptoms are experienced, remove source of contamination or move victim to fresh air. If affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- Ingestion:** Do not induce vomiting. If the material is swallowed, get medical attention or advice.
- Skin:** If irritation is experienced, flush with water. If irritation persists, get medical attention.
- Eyes:** Immediately flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms persist, get medical attention.

Section 5: FIRE FIGHTING MEASURES

Flash Point: 71°F (21.6°C)

Method Used: ASTM D-93

Lower Flammable Limit: 3.3 (Volume % in air)

Upper Flammable Limit: 19.0 (Volume % in air)

Auto Ignition: (Ethyl Alcohol) 363°C

Flammability Classification: Flammable Liquid IB

Extinguishing Media: Use methods appropriate for the surrounding fire. Consider water spray or fog, carbon dioxide, dry chemical powder, or alcohol resistant foam.

Products of Combustion: Upon decomposition this product may emit carbon dioxide, carbon monoxide and/or low molecular weight hydrocarbons.

Fire Fighting Equipment/Instructions: Wear protective clothing and equipment suitable for the surrounding fire, including helmet, facemask, and self contained breathing apparatus.

NFPA Rating: Health:2 Fire: 3 Reactivity:0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: For large spills wear gloves, safety glasses and when levels exceed OSHA PEL use appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

Environmental Precautions: Prevent discharge to open waters.

Method for Containment: Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth.

Methods for Clean-Up: Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container. Wash spill area with water.

Section 7: HANDLING AND STORAGE

Handling: Keep away from heat, sparks and flame. Prevent contact with eyes. Avoid inhalation.

Storage: Keep the container tightly closed and in a cool, well ventilated place.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Ethyl Alcohol (64-17-5)

ACGIH: 1,000 ppm TWA

OSHA: 1,000 ppm TWA; 1,900 mg/m³ TWA

Isopropyl Alcohol (67-63-0)

ACGIH: 200 ppm TWA

OSHA: 400 ppm TWA; 980 mg/m³ TWA

Engineering Controls: Normal room ventilation is usually adequate under normal use.

Personal Protective Equipment (PPE)

Eye/Face Protection: None needed under normal use.

Skin Protection: None needed under normal use.

Respiratory Protection: None needed under normal use.

General Hygiene Considerations: None needed under normal use.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Color: Clear Translucent

Odor: Alcohol/Citrus

Physical State: Gel

pH: Not Available.

Vapor Density: (Ethyl Alcohol) 1.6

Boiling Point: (Ethyl Alcohol) 78.5°C

Vapor Pressure: (Ethyl Alcohol) 57.3 hPa at 20°C

Melting Point: (Ethyl Alcohol) -114.1°C

Freezing Point: Not Available

Flash Point (see section 5)

Flammability Properties (see section 5)

Solubility (in water): Soluble

Specific Gravity @ 25°C: 0.88-0.92

Evaporation Rate: Not Available

Octanol/Water partition coefficient (K_{ow}): (Ethyl Alcohol): - 0.32

Auto-ignition temperature: (Ethyl Alcohol) 363°C

Decomposition temperature: Not Available

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal ambient temperatures 70°C (21°C)

Condition to Avoid: Avoid excessive heat or sources of ignition.

Incompatible Materials: This product reacts with strong acid, strong bases, and oxidizing agents.

Hazardous Decomposition: upon decomposition, this product evolves carbon monoxide, carbon dioxide, and/or low weight hydrocarbons.

Hazardous Reactions: Hazardous polymerization will not occur.

Section 11: TOXICOLOGY INFORMATION

ACUTE EFFECTS:

A: General Product information

Product contains ethyl alcohol and isopropyl alcohol.

B: Component Analysis LD50

Ethyl Alcohol (64-17-5)

Oral LD50 Rat: 7060 mg/kg

Isopropyl Alcohol (67-63-0)

Inhalation LC50 Rat: 72.6 mg/L/4H

Oral LD50 Rat: 4396 mg/kg

Dermal LD50 Rat: 12800 mg/kg

Dermal LD50 Rabbit: 12870 mg/kg

CHRONIC EFFECTS:

Component

Ethyl Alcohol (64-17-5)

Carcinogenicity: ACGIH A4 – Not Classifiable as a Human Carcinogen

Neurotoxicity: This product contains ethyl alcohol, a central nervous system target.

Mutagenicity: No information available for product.

Reproductive: No information available for product.

Developmental: Ethyl alcohol is a developmental toxin when consumed during pregnancy.

Target Organs: When consumed, ethyl alcohol can target the respiratory system, skin, eyes, CNS, liver, blood and reproductive system.

Isopropyl Alcohol (67-63-0)

Carcinogenicity: ACGIH A4 – Not Classifiable as a Human Carcinogen

Neurotoxicity: This product contains isopropyl alcohol, a central nervous system target.

Mutagenicity: No information available for product.

Reproductive: No information available for product.

Developmental: No information available for product.

Target Organs: skin, eyes, CNS, Kidney, Developmental and respiratory system.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: Ethyl Alcohol (64-17-5)

96 hour LC50 Oncorhynchus mykiss: 12,900 mg/L (flow-through) (30days old)
96 hour LC50 Pimephales promelas 14.2 mg/L
5 min EC50 Photobacterium phosphoreum: 35,470 mg/L
30 min EC50 Photobacterium phosphoreum: 34,634 mg/L
48 hour EC50 Daphnia magna: 9,268 mg/L
24 hour EC50 Daphnia magna: 10,800 mg/L

Ecotoxicity: Isopropyl Alcohol (67-63-0)

96 Hr EC50 Scenedesmus Subspicatus: >1000 mg/L
72 Hr EC50 Scenedesmus subspicatus:>1000 mg/L
96 Hr LC50 Pimephales promelas: 9640 mg/L [flow through]
96 Hr LC50 Pimephales promelas: 94900 mg/L [flow through] (29 days old)
96 Hr LC50 Pimephales promelas: 61200 mg/L [flow through] (31 days old)
5 min EC50 Photobacterium phosphoreum: 35390 mg/L
48 Hr EC50 Daphnia magna: 13299 mg/L

Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state, and local regulations.

Section 14: TRANSPORTATION INFORMATION

Shipping Name: Consumer Commodity ORM-D

Proper Shipping Name for Non-Consumer Commodity: Ethyl Alcohol Solutions, 3, UN1170, PGIII.

IMDG: UN1170, Ethanol Solutions (Ethyl Alcohol Solution), Class 3, PG II (21.6C cc) EmS # F-E
S-D, Limited Quantity

Section 15: REGULATORY INFORMATION

Ethyl alcohol and isopropyl alcohol, components of this product, are on the TSCA inventory.

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65)

This material contains ethyl alcohol a developmental toxicity when in alcoholic beverages.

The following components appear on one or more of the following state hazardous substance lists:

Component	CAS#	CA	MA	MN	NJ	PA
Isopropyl Alcohol	67-63-0	YES	YES	YES	YES	YES
Ethyl alcohol	64-17-5	YES	YES	YES	YES	YES

Section 16: Other Information

Prepared by: Vi-Jon Inc.

Disclaimer:

The information and recommendations contained in the Material Safety Data Sheet (MSDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

Vi-Jon, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will Vi-Jon be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY VI-JON HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance which is the subject matter of this MSDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.

MATERIAL SAFETY DATA SHEET



NICE-PAK PRODUCTS, INC.
TWO NICE-PAK PARK
ORANGEBURG NY 10962-1376
845-365-1700

REVISION DATE: 1/07

I. PRODUCT IDENTIFICATION

PRODUCT TRADE NAME: EXCHANGE SELECT DISINFECTING SURFACE WIPES

HAZARD RATING (NFPA)

HEALTH: 0

FLAMMABILITY: 2

REACTIVITY: 0

SPECIFIC: NONE

EMERGENCY OR INFORMATION TELEPHONE NO: 845-365-1700 (M-F DAYTIME) AT OTHER TIMES, CONTACT THE LOCAL POISON CONTROL CENTER

CHEMICAL NAME: PROPRIETARY MIXTURE

II HAZARDOUS INGREDIENTS PER 29 CFR 1910.1200

Hazardous Ingredients	%	ACGIH TLV	CAS NUMBER
ISOPROPYL ALCOHOL	8	400 ppm	67-63-0
QUATERNARY AMMONIUM CMPD	<1	N/A	27479-28-3

III-PHYSICAL/CHEMICAL CHARACTERISTICS

COLOR/ODOR/APPEARANCE: TOWELETTE SATURATED WITH CLEAR LIQUID WITH CITRUS ODOR

BOILING POINT: 181⁰ F

FLASH POINT: 103⁰ F

VAPOR DENSITY N/A

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: COMPLETE

SPECIFIC GRAVITY (H₂O = 1): .983

IV FIRE & EXPLOSION HAZARD DATA

FLASH POINT(Method Used): 103⁰ F TAG CLOSED CUP : LEL: N/A UEL: N/A

EXTINGUISHING MEDIA: WATER, FOAM

SPECIAL FIRE FIGHTING PROCEDURES: TREAT PRODUCT AS COMBUSTIBLE

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

EXCHANGE SELECT DISINFECTING SURFACE WIPES

V-REACTIVITY DATA

STABILITY: STABLE

INCOMPATIBILITY: ANIONIC SURFACTANT, SOAPS

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: NONE KNOWN

POLYMERIZATION: WILL NOT OCCUR

CONDITIONS TO AVOID: NONE KNOWN

PRODUCT DOES NOT REACT WITH FORMALDEHYDE

VI-HEALTH HAZARD DATA

EFFECTS OF OVER EXPOSURE:SKIN : MAY CAUSE SKIN IRRITATION

EYES : MAY CAUSE IRRITATION

INHALATION: NOT NORMAL ROUTE OF ENTRY

INGESTION: NOT NORMAL ROUTE OF ENTRY

EMERGENCY AND FIRST AID PROCEDURES:

SKIN CONTACT: IF RASH OR IRRITATION DEVELOPS, DISCONTINUE USE

EYE CONTACT: FLUSH WITH COOL WATER FOR 15 MINUTES

INHALATION: REMOVE TO FRESH AIR

INGESTION: CONSULT PHYSICIAN

TARGET ORGANS; NONE KNOWN

KNOWN CARCINOGEN: NONE KNOWN

VII-SPILL AND DISPOSAL PROCEDURE

SPILL CONTROL: PICK UP WITH ABSORBENT

WASTE DISPOSAL METHOD: TREAT AS FLAMMABLE LIQUID. OBEY LOCAL, STATE AND FEDERAL REGULATIONS

HANDLING AND STORAGE: AVOID HIGH HEAT AND SOURCES OF IGNITION

VIII-CONTROL MEASURES/PROTECTION

RESPIRATION: USE NIOSH APPROVED RESPIRATOR WHEN HANDLING BULK LIQUID IF EXPOSURE LEVEL IS EXCEEDED

VENTILATION: RECOMMENDED

PROTECTIVE GLOVES: RECOMMENDED

EYE PROTECTION: IF SPLASHING MAY OCCUR

HYGIENIC PRACTICES: FOLLOW GOOD HOUSEKEEPING PRACTICES

OTHER: NONE

IX TRANSPORT/SHIPPING

DOT SHIPPING NAME:

TECHNICAL SHIPPING NAME:

DOT SHIPPING CLASSIFICATION: DOT NOT REGULATED

DOT ID NO.:

DOT ;LABEL; REQUIREMENTS:

UN/NA NUMBER REGULATIONS:

REPORTABLE QUANTITY:

X DISCLAIMER

THE INFORMATION FURNISHED HEREIN IS BELIEVED TO BE ACCURATE AND REPRESENTS THE BEST DATA CURRENTLY AVAILABLE TO US. NO WARRANTY, EXPRESSED OR IMPLIED IS MADE AND NICE-PAK PRODUCTS, INC. ASSUMES NO LEGAL RESPONSIBILITY OR LIABILITY RESULTING FROM ITS USE.

MATERIAL SAFETY DATA SHEET

20000
01 00

DATE OF PREPARATION
Jan 16, 2014

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

20000

PRODUCT NAME

TRI-FLOW® Superior Lubricant with PTFE

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
Consumer Group - Industrial
Cleveland, OH 44115

Telephone Numbers and Websites

Product Information	www.triflowlubricants.com
Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)	

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
10	74-98-6	Propane		
		ACGIH TLV	1000 PPM	760 mm
		OSHA PEL	1000 PPM	
10	106-97-8	Butane		
		ACGIH TLV	1000 PPM	760 mm
		OSHA PEL	800 PPM	
24	64742-47-8	Aliphatic Solvent		
		ACGIH TLV	Not Available	0.00787 mm
		OSHA PEL	Not Available	
2	64741-97-5	Naphthenic Oil		
		ACGIH TLV	5 mg/m3 as Mist	
		OSHA PEL	Not Available	
39	64742-52-5	Heavy Naphthenic Petroleum Oil		
		ACGIH TLV	Not Available	
		OSHA PEL	Not Available	
3	64742-65-0	Heavy Paraffinic Oil		
		ACGIH TLV	5 mg/m3 as Mist	
		OSHA PEL	5 mg/m3 as Mist	
2	628-63-7	Amyl Acetate		
		ACGIH TLV	100 PPM	4 mm
		OSHA PEL	100 PPM	

SECTION 3 — HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

HMIS Codes

Health	2
Flammability	4
Reactivity	0

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

SECTION 4 — FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and laundry before re-use.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

SECTION 5 — FIRE FIGHTING MEASURES**FLASH POINT**

Propellant < 0 °F

LEL

0.7

UEL

9.5

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION 6 — ACCIDENTAL RELEASE MEASURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

SECTION 7 — HANDLING AND STORAGE**STORAGE CATEGORY**

Not Available

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Contents under pressure. Do not puncture, incinerate, or expose to temperature above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst. Do not take internally. Keep out of the reach of children.

SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION**PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

PROTECTIVE GLOVES

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemical resistant gloves.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT	6.48 lb/gal	776 g/l
SPECIFIC GRAVITY	0.78	
BOILING POINT	<0 - 460 °F	<-18 - 237 °C
MELTING POINT	Not Available	
VOLATILE VOLUME	55%	
EVAPORATION RATE	Faster than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	Not Available	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)		
	Volatile Weight 46.26%	Less Water and Federally Exempt Solvents

SECTION 10 — STABILITY AND REACTIVITY

STABILITY — Stable

CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

SECTION 11 — TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

TOXICOLOGY DATA

CAS No.	Ingredient Name			
74-98-6	Propane	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
106-97-8	Butane	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
64742-47-8	Aliphatic Solvent	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
64741-97-5	Naphthenic Oil	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
64742-52-5	Heavy Naphthenic Petroleum Oil	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
64742-65-0	Heavy Paraffinic Oil	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
628-63-7	Amyl Acetate	LC50 RAT	4HR	Not Available
		LD50 RAT		6500 mg/kg

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

SECTION 13 — DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

US Ground (DOT)

May be classed as LTD. QTY. OR ORM-D
UN1950, AEROSOLS, 2.1, LIMITED QUANTITY, (ERG#126)

Canada (TDG)

May be classed as LTD. QTY. OR ORM-D
UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, (ERG#126)

IMO

May be shipped as Limited Quantity
UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, Ems F-D, S-U

IATA/ICAO

UN1950, AEROSOLS, FLAMMABLE, 2.1, LIMITED QUANTITY

SECTION 15 — REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
	Barium Compound	2	0.06

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.